

DOE/EIA-M059(2005)  
Part 2

**EIA Model Documentation**

**PETROLEUM MARKET MODEL  
OF THE  
NATIONAL ENERGY MODELING SYSTEM**

**Part 2 - Appendices B thru J**

**May 2005**

Oil and Gas Division  
Office of Integrated Analysis and Forecasting  
Energy Information Administration

## **For Further Information...**

The Petroleum Market Model (PMM) of the National Energy Modeling System is developed and maintained by the Energy Information Administration (EIA), Office of Integrated Analysis and Forecasting. General questions about the use of the model can be addressed to James Kendell (202) 586-9646, Director of the Oil and Gas Division. Specific questions concerning the PMM may be addressed to:

William Brown  
Mail Code: EI-83  
U.S. Department of Energy  
1000 Independence Avenue, S.W.  
Washington, D.C. 20585  
(202) 586-8181  
[william.brown@eia.doe.gov](mailto:william.brown@eia.doe.gov)

This report documents the archived version of the PMM that was used to produce the petroleum forecasts presented in the *Annual Energy Outlook 2005*, (DOE/EIA-0383(2005)). The purpose of this report is to provide a reference document for model analysts, users, and the public that defines the objectives of the model, describes its basic approach, and provides detail on the methodology employed. The model documentation is updated annually to reflect significant model methodology and software changes that take place as the model develops. The next version of the documentation is planned to be released in the first quarter of 2006.

## TABLE OF CONTENTS

	<u>Section Page number</u>
Acronyms and Abbreviations .....	vii
1. Introduction .....	1-1
1.1 Purpose of this Report .....	1-1
1.2 Model Summary .....	1-1
1.3 Model Archival Citation .....	1-1
1.4 Report Organization .....	1-1
2. Model Purpose .....	2-1
2.1 Model Objectives .....	2-1
2.2 Relationship to Other Models .....	2-2
3. Model Overview and Rationale .....	3-1
3.1 Theoretical Approach .....	3-1
3.2 Comparison with Oil Market Module .....	3-1
3.3 Fundamental Assumptions .....	3-2
4. Model Structure .....	4-1
4.1 Main Subroutines .....	4-8
4.2 Matrix Preprocessing Subroutines .....	4-25
4.3 Matrix Postprocessing Subroutines .....	4-41
4.4 Capacity Expansion Subroutine .....	4-50
4.5 OML Specific Subroutines .....	4-52
APPENDIX A PMM Data and Outputs .....	A-1
A.1 PMM Variables and Definitions .....	A-1
A.1.1 PMM LP and NEMS Variable Names Cross References .....	A-1
A.1.2 PMM Output Variables .....	A-6
A.1.3 PMM Input Variables .....	A-10
A.1.4 Other PMM Variables .....	A-13
A.2 Data Sources .....	A-29
A.2.1 Process Technology and Cost Data .....	A-29
A.2.2 Refinery Capacity Construction and Utilization Data .....	A-29
A.2.3 Crude Supply and Product Demand Data .....	A-30
A.2.4 Product Specification/Grade Split Data .....	A-31
A.2.5 Transportation Data .....	A-31
A.2.6 Product Yield and Quality Blending Data .....	A-31
A.2.7 Units of Measurement .....	A-32

A.3	PMM Model Data Tables.....	A-34
A.3.1	Matrix Control.....	A-35
A.3.2	Crude Oil Availability.....	A-41
A.3.3	Other Raw Materials Availability.....	A-43
A.3.4	Product Imports.....	A-45
A.3.5	Product Demands.....	A-46
A.3.6	Crude and Product Transportation.....	A-48
A.3.7	Refinery Capacities and Operations.....	A-51
A.3.8	Product Blending and Specifications.....	A-64
A.3.9	Refining Technology.....	A-70
APPENDIX B	Mathematical Description of Model.....	B-1
B.1	Mathematical Formulation.....	B-1
B.2	Matrix Indices.....	B-3
B.3	Column Definitions.....	B-4
B.4	Objective Function.....	B-8
B.5	Row Constraints.....	B-10
B.6	Row and Column Cross References.....	B-32
APPENDIX C	Bibliography.....	C-1
APPENDIX D	Model Abstract.....	D-1
D.1	Model Name.....	D-1
D.2	Model Acronym.....	D-1
D.3	Description.....	D-1
D.4	Purpose of the Model.....	D-1
D.5	Most Recent Model Update.....	D-2
D.6	Part of Another Model?.....	D-2
D.7	Model Interfaces.....	D-2
D.8	Official Model Representative.....	D-2
D.9	Documentation.....	D-2
D.10	Archive Media and Installation Manual.....	D-3
D.11	Energy System Described.....	D-3
D.12	Coverage.....	D-3
D.13	Modeling Features.....	D-4
D.14	Non-DOE Input Sources.....	D-4
D.15	DOE Input Sources.....	D-4
D.16	Independent Expert Reviews Conducted.....	D-5
D.17	Status of Evaluation Efforts by Sponsor.....	D-5
APPENDIX E	Data Quality.....	E-1
E.1	Quality of Distribution Cost Data.....	E-1
E.2	Quality of Tax Data.....	E-3
E.3	PMM Critical Variables.....	E-4

APPENDIX F	Estimation Methodologies.....	F-1
F.1	Refinery Investment Recovery Thresholds.....	F-1
F.2	Gas Plant Models .....	F-13
F.3	Chemical Industry Demand for Methanol .....	F-15
F.4	Estimation of Distribution Costs .....	F-16
F.5	Estimation of Taxes.....	F-20
F.6	Gasoline Specifications .....	F-21
F.7	Estimation of Gasoline Market Shares .....	F-28
F.8	Diesel Specifications .....	F-30
F.9	Estimation of Diesel Market Shares .....	F-31
F.10	Estimation of Regional Conversion Coefficients .....	F-33
F.11	Unfinished Oil Imports Methodology .....	F-36
F.12	Product Pipeline Capacities and Tariffs .....	F-37
F.13	Cogeneration Methodology.....	F-39
F.14	Natural Gas Plant Fuel Consumption.....	F-41
F.15	Crude Oil Exports/Total and Alaskan .....	F-42
F.16	Technology Improvement Option .....	F-42
F.17	GTL Representation in PMM.....	F-45
F.18	CTL Representation in PMM.....	F-52
F.19	Petroleum Coke Gasification Representation in PMM.....	F-61
APPENDIX G	Matrix Generator Documentation.....	G-1
G.1	Introduction.....	G-1
G.2	Code.....	G-1
G.3	Data.....	G-31
G.4	Submission of a Run .....	G-41
G-A	Example of An mrmparam File.....	G-44
G-B	Example of A Path File .....	G-45
G-C	Makefile .....	G-46
G-D	Common Blocks.....	G-49
G-E	MRM Data Conversion .....	G-69
G-F	Refinery Processes .....	G-72
APPENDIX H	Historical Data Processing .....	H-1
H.1	Processing Dada for PMM History File .....	H-1
H.2	Processing Other Historical Data .....	H-7
APPENDIX I	Ethanol Supply Model.....	I-1
I.1	Model Purpose .....	I-1
I.2	Corn-Based Ethanol .....	I-1
I.3	Cellulose-Based Ethanol .....	I-8
I.4	Ethanol Transportation Costs .....	I-12
APPENDIX J	Biodiesel Supply Model .....	J-1
J.1	Model Purpose .....	J-1
J.2	Fundamental Assumptions.....	J-1
J.3	Key Components and Equations .....	J-3
J.4	Inventory of Variables, Data, and Parameters .....	J-3

## LIST OF FIGURES

		<u>Section</u>	<u>Page number</u>
Figure 2.1	PMM Input - Output Flow Diagram.....	2-4	
Figure 4.1	PMM Flow Diagram .....	4-3	
Figure 4.2	Matrix Preprocessing Subroutines (PMMLP) .....	4-4	
Figure 4.3	Matrix Postprocessing Subroutines .....	4-5	
Figure 4.4	Capacity Expansion Subroutines (XPMMLP) .....	4-6	
Figure 4.5	Report Subroutines.....	4-7	
Figure H.1	Database Linkages .....	H-1	
Figure H.2	Sample Database Queries.....	H-4	

## LIST OF TABLES

		<u>Section</u>	<u>Page number</u>
Table A1.	PMM/NEMS Cross References .....	A-1	
Table A2.	Aggregate Crude Oil Categories for PMM/NEMS .....	A-30	
Table A3.	Atmospheric Residual Oil Qualities .....	A-71	
Table A4.	Oxygenate Products .....	A-88	
Table B1.	PMM Linear Program Structure.....	B-2	
Table B2.	Index Definitions.....	B-3	
Table B3.	Column Definitions.....	B-4	
Table B4.	Column Cross References .....	B-32	
Table B5.	Row Cross References .....	B-35	
Table E1.	Sources of Markup Inputs .....	E-2	
Table F1.	Location Multipliers for Refinery Construction .....	F-3	
Table F2.	State and Federal Corporate Income Tax Rate .....	F-6	
Table F3.	Location Multiplier for Refinery Operating Labor .....	F-11	
Table F4.	Capital-Related Fixed Operating Cost Multipliers .....	F-12	
Table F5.	Total Dry Gas Multiplier .....	F-14	
Table F6.	Gas Plant Model Liquid Component Yields .....	F-14	
Table F7.	Chemical Industry Demand for Methanol .....	F-15	
Table F8.	Estimated Annual Reid Vapor Pressure .....	F-24	
Table F9.	Complex Model Standards.....	F-25	
Table F10.	Directional Emission Effects of Gasoline Property Changes .....	F-26	
Table F11.	PMM Reformulated Gasoline Specifications .....	F-27	
Table F12.	Source of PMM Natural Gas Prices .....	F-33	
Table F13.	Source of PMM Electricity Prices.....	F-34	
Table F14.	PAD District to Census Division Conversion Factors .....	F-34	
Table F15.	NACOD Regions and NEMS/PMM Census Regions.....	F-37	
Table F16.	Petroleum Product Pipeline Capacities and Tariffs .....	F-38	
Table F17.	LPG/NGL Pipelines Capacities and Tariffs .....	F-39	
Table H1.	Park List Sample .....	H-2	
Table H2.	Components of PMM Variables.....	H-5	
Table I1.	DAI Regions and NEMS Regions.....	I-12	
Table I2.	2004 New Ethanol Shipments and Freight Costs by Census Divisions.....	I-13	
Table I3.	2007 New Ethanol Shipments and Freight Costs by Census Divisions.....	I-14	
Table I4.	2012 New Ethanol Shipments and Freight Costs by Census Divisions.....	I-15	

## Acronyms and Abbreviations

AEO	EIA Annual Energy Outlook
API	American Petroleum Institute
ASTM	American Society of Testing Materials
BAU	Business As Usual
bbl	Barrel
bbl/cd	Barrels Per Calendar Day
Bcf	Billion cubic feet
Btu	British thermal unit
BTX	Benzene, Toluene, and Xylene Aromatics
BPSD	Barrels Per Stream Day
CAAA	Clean Air Act Amendments
CARB	California Air Resources Board
CD	Census Division
CG	Conventional Gasoline (referred to as TRG in the PMM code)
CHP	Combined Heat and Power
C <sub>n</sub>	Represents a hydrocarbon stream containing n atoms of carbon, i.e. C <sub>1</sub> is methane, C <sub>2</sub> is ethane, C <sub>3</sub> is propane, C <sub>4</sub> is butane, etc.
CTL	Coal-To-Liquids (converting coal through syngas to diesel-grade blending streams)
COE	Crude Oil Equivalent
DOE	Department of Energy
E85	Gasoline blend of 85 percent ethanol and 15 percent conventional gasoline (annual average of ethanol content in E85 is lower when factoring in cold start need in winter)
EIA	Energy Information Administration
EOR	Enhanced Oil Recovery
EPA	Environmental Protection Agency
ETBE	Ethyl Tertiary Butyl Ether
FCC	Fluid Catalytic Cracker
FOE	Fuel Oil Equivalent
GWh	Gigawatthour
GTL	Gas-To-Liquids (converting natural gas through syngas to diesel-grade blending streams)
IEA	International Energy Agency
IEO	EIA International Energy Outlook
ISBL	Inside the battery limit
KWh	Kilowatthour
LP	Linear Programming
LPG	Liquefied Petroleum Gas
M85	Gasoline blend of 85 percent methanol and 15 percent conventional gasoline
M-B	Mansfield-Blackman methodology for new technology market penetration
Mbbl/cd	Thousand Barrels Per Calendar Day
Mbtu	Thousand British Thermal Units
Mcf	Thousand cubic feet
MG	Motor gasoline
MMbbl/cd	Million Barrels Per Calendar Day
MMbtu	Million British Thermal Units

MTBE	Methyl Tertiary Butyl Ether
MRM	Multi-Refining Model
MW	Megawatts, electric generation capacity
N2H	No. 2 Heating Oil
NACOD	North American Crude Oil Distribution
NEMS	National Energy Modeling System
NES	National Energy Strategy
NETL	National Energy Technology Laboratory
NGL	Natural Gas Liquid
NIPER	National Institute for Petroleum and Energy Research
NOx	Nitrogen Oxide
NPC	National Petroleum Council
NPRA	National Petrochemical and Refiners Association
OB1	Optimization with Barriers 1
OGSM	Oil and Gas Supply Module
OML	Optimization and Modeling Libraries
ORNL	Oak Ridge National Laboratory
OVC	Other Variable Costs
PADD	Petroleum Administration for Defense District
PCF	Petrochemical Feed
Petcoke	Petroleum Coke
PMM	Petroleum Market Model
ppm	Parts per million
PSA	Petroleum Supply Annual
RFG	Reformulated Gasoline
RFS	Renewable Fuels Standard (optional for regulatory analysis purposes)
RHS	Right-hand side
RVP	Reid Vapor Pressure
RYM	Refinery Yield Model (EIA)
SCF	Standard Cubic Feet
SIC	Standard Industrial Classification
SPR	Strategic Petroleum Reserve
STEO	Short Term Energy Outlook
Syngas	Gaseous products from hydrocarbons (e.g., natural gas, petroleum coke, or coal) reacting with steam/O <sub>2</sub> , mostly consisting of CO and H <sub>2</sub>
TAME	Tertiary amyl methyl ether
TAP	Toxic Air Pollutant
TAPS	Trans-Alaska Pipeline System
TRG	Conventional gasoline (replacing old nomenclature for traditional gasoline)
ULSD	Ultra-Low Sulfur Diesel
VOC	Volatile Organic Compound
WOP	World Oil Price
WORLD	World Oil Refining Logistics Demand (model)

## **APPENDIX B**

### **Mathematical Description of Model**

## APPENDIX B. Mathematical Description of Model



Each refiner is trying to minimize the cost of meeting demands. Therefore, the market moves toward lower-cost refiners who have access to crude oil and markets. A key premise is that the selection of crude oils, refinery process utilization, and logistics will adjust to minimize the overall cost of supplying the market with petroleum products.

In order to generate refined product prices, the PMM contains a static linear programming (LP) model of the U.S. petroleum refining and marketing system that meets demand for refined products while minimizing costs. The PMM, like the other NEMS models, is written in FORTRAN90. The software includes the Optimization Modeling Library or OML, a set of FORTRAN callable subroutines. The LP portion of the PMM is a complete problem matrix prepared prior to NEMS processing. The LP remains in fast memory throughout the NEMS run, thereby avoiding many disk I/O operations.

It is necessary to view the PMM in the context of the NEMS program to understand its function. For each cycle, the main NEMS model calls the demand models to calculate energy demands. Each supply model is then called to calculate energy prices. When the prices and demands converge to within the specified tolerance, the NEMS iteration is complete and the next yearly NEMS cycle begins. If the computed prices have not converged, new demand quantities are computed, passed to the supply models, and the cycle is repeated. In the case of the PMM, a supply model, the refined product prices are obtained from the marginal prices of an optimal solution to the PMM LP, with transportation costs and taxes added. These product prices are sent to the NEMS demand models. The LP matrix is updated with the new demands for refined products and the cycle continues until convergence is reached. The demand level modifications to the PMM LP and the re-optimization of the LP matrix, which remains in core memory, are accomplished by executing FORTRAN callable subroutines.

For *AEO2005* the original generation of the PMM matrix is performed using OML<sup>1</sup> and FORTRAN. OML (Optimization Modeling Library) is a library of FORTRAN callable subroutines for data table manipulation, matrix generation, and solution retrieval programs for report writing. The matrix is solved with the optimizer, C-WHIZ.<sup>2</sup>

### B.1 Mathematical Formulation

---

<sup>1</sup>Ketron Management Science, Inc., *Optimization Modeling Library, OML User Manual*, (November 1994).

<sup>2</sup>Ketron Management Science, Inc., *C-WHIZ Linear Programming Optimizer, User Manual*, (July 1994).

**Table B1. PMM Linear Program Structure**

PMM Linear Program Overview											
	Crude Trans.	Purchases Crude Oil, Other Inputs	Crude Distillation	Other Process Unit Operations	Capacity Expansion	Stream Transfers	Blending	Product Sales	Product Trans.	Row Type	RHS
Objective	-ct	-c	-o	-o	-i			+p	-pt	NC	Max
Crude Oil Balance	+1 +1 -1	+1 +1 +1	-1 -1							GE	0
Intermediate Stream Balance			+y +y	-1 -1 +y +y		-1 +1 -1 +1	-1 -1			GE	0
Utilities		+1	-u	-u +1						GE	0
Policy Constraints				+z -z				+z -z		GE LE	0
Environmental Constraints			+q	+q						GE LE	E
Unit Capacities			+1	+1	-1					LE	K
Quality Specifications							+q +q -Q			GE LE	0
Product Sales							-1	-1	-1 +1 +1 -1	GE	0
Pipeline/Marine Capacities	+1 +1								+1 +1	LE	C
Bounds	Up/Lo/Fix	Up/Lo/Fix						Up/Lo/Fix			
Legend:	c = crude cost      p = price      Q = product specifications      z = policy ratio y = yield      q = stream quality      C = pipeline/marine capacity      E = environmental quality limit u = utility consumption      K = unit capacity      o = operating cost      ct = crude transportation cost      pt = product transportation cost      i = investment cost										



## B.2 Matrix Indices

Several indices are used in the column and row definitions presented below. The definition of these indices is shown in Table B2.

**Table B2. Index Definitions**

<b><u>Index Symbol</u></b>	<b><u>Description</u></b>
(a)	Alcohol and renewable fuel
(b)	Domestic crude oil production region
(c)	Crude oil type
(col)	Coal type
(d)	Marketing region (demand)
(e)	Emissions source
(f)	Fuel type consumed at US refineries
(g)	Dry gas (CC1)
(h)	Product recipe
(i)	Intermediate stream
(l)	Utility type
(m)	Processing mode or shipping mode
(p)	Refined product
(pc)	Shipping class
(q)	Pricing level (step on curve)
(r)	Refinery region
(s)	Refinery stream
(u)	Processing unit type
(v)	Crude oil source (foreign(F), domestic(D), Alaska(A))
(y)	Product specification quality

## B.3 Column Definitions

Table B3. Column Definitions

<u>Column Notation</u>	<u>Description</u>
$B_{a,d,q}$	Volume of alcohol or renewable fuel (a) purchased in demand region (d) at price level (q). At present, this column exists for ethanol and biodiesel.
$D_{p,d}$	Sales volume of product (p) in demand region (d).
$E_{u,r}$	Stream day capacity added during this simulated period for processing unit type (u) in refinery region (r).
$G_{i,p,r}$	Volume of intermediate stream (i) blended into spec blended product (p) at refinery region (r).
$H_{p,h,r}$	Volume of product (p) produced in refinery region (r) using recipe (h).
$H_{p,h,d}, H_{RFN,h,d}$	Volume of product (p) made by recipe (h) in demand region (d) by splash blending; volume of intermediate stream (i) from gas plant to refinery (RFN) in region (r)
$H_{p,i,r}$	Volume of product (p) from gas plant stream (i) in refinery region (r).
$H_{g,i,r}$	Volume of dry gas (g) from gas plant stream (i) in refinery region (r).
$HKWHMCH_r$	Electricity usage at merchant plant in refinery region (r).
$HCTL_{i,r}$	Volume of CTL stream (i) transferred from facility to refinery region (r).
$HMP_{FR,TO,i,r}$	Merchant plant stream transfers from plant (FR) to plant (TO): Volume of GTL liquid stream (i) transferred from Alaska (merchant plant) to refinery region (r); volume of CTL liq stream (i) transferred from facility to refinery region (r); volume of misc. stream (i) from merchant plant to refinery region (r); volume of misc. stream (i) from refinery to merchant plant in region (r) ; volume of misc. stream (i) from gas plant to merchant plant in region (r); volume of misc. stream (i) from merchant plant to gas plant in region (r).
$Iz_{p,d}$	Volume of distress import of product (p) into demand region (d) where d = 2,3,7,8,9.
$I_{p,r,q}$	Volume of refined product (p) imported into refinery region (r) at price level (q).

<b><u>Column Notation</u></b>	<b><u>Description</u></b>
$K_{u,r}$	Base processing capacity in processing unit (u) at refinery region (r) in Mbbbl/cd. This column is upper bounded.
$L_{u,r}$	Cumulative stream day capacity added for processing unit (u) at refinery region (r) during the previous simulated periods. This column is fixed.
$M_r$	Volume of methanol consumed by the chemical industry in refinery region (r).
$Mr_r$	Volume of methanol transferred from refinery or imported to meet U.S. methanol consumption by the chemical industry in refinery region (r).
$Mt$	Total volume of U.S. methanol consumption by the chemical industry, an input.
$NCL_{r,q,col}$	Coal supply curve (steps (q)), type (col), used to generate CTLs for transport to refinery region (r).
$NGA_{r,q}$	Alaska natural gas supply curve (steps (q)) used to generate GTLs for transport to refinery region (r).
$NZAMHN_q$	Volume at price discount q of Alaskan Crude (AMH) exports.
$NZAMHP_q$	Volume at price increment q of Alaskan Crude (AMH) exports.
$N_rNGRFN_q$	Volume at price discount (q) of natural gas in refinery region (r).
$N_rNGRFP_q$	Volume at price increment (q) of natural gas in refinery region (r).
$O_{c,v,b}$	Export volume of crude oil (c) with source code (v) produced in domestic region (b). At present, only Alaska exports are allowed.
$P_b$	Volume of domestic crude oil produced at producing region (b).
$Pi_{c,r,q}$	Volume of imported crude oil type (c) imported by refinery region (r) at price level (q).
$PNGL$	Alaska production of NGLs.
$Q_{p,r}$	Volume of spec product (p) manufactured in refinery region (r).
$Ra_{c,v,r}$	Crude oil volume distilled in refinery region (r) from source (v) of crude oil type (c).
$Rc_r$	Manufacturing activity level for cogeneration in refinery region (r).

<b><u>Column Notation</u></b>	<b><u>Description</u></b>
Rchp <sub>r,m</sub>	Manufacturing activity level for combined heat/power burning syngas (from coke gasifier) in operating mode (m) in refinery region (r).
R <sub>u,r,m</sub>	Manufacturing activity level in mode (m) operation in processing unit (u) at refinery region (r).
Tu	Total volume of imported unfinished oil over all refinery regions.
T <sub>i,r</sub>	Volume of unfinished oil component (i) processed in refinery region (r).
TAAMHXZ	Volume of AMH crude transported from Alaska to Valdez.
TATOT <sub>c</sub>	Volume of crude type (c) produced in Alaska.
TAGTL	Volume of GTL transported from Alaska to Valdez.
TANSO	Volume of North Slope oil transported from Alaska to Valdez.
TCBN <sub>r</sub>	Total tax levied on total carbon emissions resulting from refinery operations in refinery region (r).
TX <sub>s,p,r</sub>	Volume of stream (s) transferred into product (p) in refinery region (r).
TX <sub>p,p',r</sub>	Volume of product (p) transferred into product (p') storage in refinery region (r).
TX <sub>s,s',r</sub>	Volume of stream (s) transferred to stream (s') at refinery region (r).
U <sub>l,r</sub>	Quantity of utility (l) that is purchased in refinery region (r): (l) = KWH, STM, and NGF (power, steam, and natural gas fuel) with units in thousands of kWh, Mlbs., and MMcf respectively.
V <sub>cj</sub>	Total dead weight ton capacity of Jones Act crude oil tankers. This column is constrained to some maximum.
V <sub>pc</sub>	Total dead weight tons of Jones Act product tanker of shipping class (pc). This column is constrained to some maximum.
V <sub>cts</sub>	Total crude oil transshipped from PADD III to PADD II. This column is constrained to some maximum.
V <sub>cpb,r</sub>	Total crude oil shipped by pipeline from domestic producing region (b) to refinery region (r). This column is constrained to some maximum.

<b><u>Column Notation</u></b>	<b><u>Description</u></b>
$V_{pp,r,d,m}$	Total volume of light products (p) shipped via pipeline mode (m) from refining region (r) to demand region (d). This column is constrained to some maximum.
$V_{tpl,r,d,m}$	Total volume of LPG products (p) shipped via pipeline mode (m) from refining region (r) to demand region (d). This column is constrained to some maximum.
$W_{a,d,r,m}, W_{a,d,d',m}$	Volume of alcohol or renewable fuel (a) shipped from demand region (d) to refinery region (r) <or demand region d'> via transfer mode (m).
$W_{a,r,d,m}$	Volume of alcohol or renewable fuel (a) shipped from refinery region (r) to demand region (d) via transfer mode (m).
$W_{p,r,d,m}$	Volume of product (p) shipped from refinery region (r) to demand region (d) via transfer mode (m).
$W_{p,d,d',m}$	Volume of product (p) transshipped from demand region (d) to demand region (d') via transfer mode (m).
$WGTL_{m,r}$	Volume of GTL shipped via transfer mode (m) to refinery region (r).
$X_{p,d}$	Volume of product (p) exported from demand region (d).
$Xz_{p,d}$	Distress volume of product (p) exported from demand region (d).
$Y_{c,v,b,r,m}$	Volume of crude oil type (c) with source code (v) shipped from domestic region (b) to refinery region (r) via transfer mode (m).
$Z_t$	Total volume of crude oil processed over all refinery regions.
$ZET_d$	Total volume of ethanol (from corn and cellulose) supplied from demand region (d).
$Z_rFLO_u$	Sum of the base, build, and expanded capacity in processing unit (u) at refinery region (r).
$ZOX_r$	Total quantity of percent oxygen-barrels in reformulated gasoline produced in refinery region (r).
$ZZAMHTOT$	Export volume of Alaskan Crude Oil.

## B.4 Objective Function

The objective function has been established based on the premise that costs associated with product imports, non-crude oil inputs, and crude oil supplies are based on a given world oil price. With this in mind, the following objective function has been defined for the PMM.

Given:

$PR_{p,d}$	is the unit price of product (p) sold in demand region (d). It is the price associated with the demand volume for that product in the specified demand region, i.e. it is associated with $D_{p,d}$ . Similarly, each of the other 'PR' coefficients represents the unit price of the activity it is associated with.
$PRAMH$	is the target price for Alaskan crude exports.
$PRAMHP_q$	is the premium added to the Alaskan crude target price.
$C_rNGRFN_q$	is the discount from target natural gas fuel price in refinery region (r), to differentiate steps on the supply curve.
$TE_d$	is the sum of Federal and State tax credits for use of ethanol in gasoline.
$C_{u,r,m}$	is the variable cost per unit of column $R_{u,r,m}$ , i.e. the cost of one unit of manufacturing activity R in mode (m) operation in processing unit (u) at refinery region (r). Similarly, each of the other 'C' coefficients represents the unit cost of the activity it is associated with in the objective function as stated below.
$CAMHXZ$	is the cost of transferring Alaskan exports to Valdez.
$CAMHN_q$	is the discount from Alaskan crude target price.
$C_rNGRFP_q$	is the premium added to the target natural gas fuel price in refinery region (r) to differentiate steps on the supply curve.

Maximize the difference between the following sum of product revenues and costs. Thus the objective function is represented as the maximization of a quantity defined by the following revenue terms:

$$\begin{aligned}
 & \sum_p \sum_d D_{p,d} * PR_{p,d} + \sum_p \sum_h \sum_r H_{p,h,r} * PR_{p,h,r} + \sum_g \sum_i \sum_r H_{g,i,r} * PR_{g,i,r} \\
 & + \sum_p \sum_d X_{p,d} * PR_{p,d} + \sum_p \sum_d X_{z,p,d} * PR_{p,d} + \sum_d ZET_d * TE_d + ZZAMHTOT * PRAMH \\
 & + \sum_q NZAMHP_q * PRAMHP_q + \sum_r \sum_q N_rNGRFN_q * C_rNGRFN_q + \sum_r Rc_r * PR_r \\
 & + \sum_r \sum_m Rchp_{r,m} * PR_{r,m}
 \end{aligned}$$

minus the following cost terms:

$$\begin{aligned}
& \sum_a \sum_d \sum_q B_{a,d,q} * C_{a,d,q} + \sum_p \sum_r \sum_q I_{p,r,q} * C_{p,r,q} + \sum_p \sum_d IZ_{p,d} * C_{p,d} + \sum_b P_b * C_b \\
& + \sum_c \sum_r \sum_q Pi_{c,r,q} * C_{c,r,q} + \sum_i \sum_r Ti_{i,r} * C_{i,r} + \sum_l \sum_r Ul_{l,r} * C_{l,r} + \sum_u \sum_r \sum_m Ru_{r,m} * C_{u,r,m} \\
& + \sum_u \sum_r Eu_{u,r} * C_{u,r} + \sum_u \sum_r Lu_{u,r} * C_{u,r} + \sum_s \sum_i \sum_r \sum_l Wa_{d,r,m} * C_{a,d,r,m} \\
& + \sum_p \sum_r \sum_d \sum_m W_{p,r,d,m} * C_{p,r,d,m} + \sum_p \sum_d \sum_d' \sum_m W_{p,d,d',m} * C_{p,d,d',m} \\
& + \sum_c \sum_v \sum_b \sum_r \sum_m Y_{c,v,b,r,m} * C_{c,v,b,r,m} + \sum_r TCBN_r + \sum_r \sum_q N_r NGRFP_q * C_r NGRFP_q \\
& + \sum_q NZAMHN_q * CAMHN_q + TAAMHXZ * CAMHXZ \\
& + \sum_r Mr * Cr + \sum_p \sum_i \sum_r Hp_{i,r} * Cp_{i,r} + \sum_i \sum_r HMP_{FR,TO,i,r} * C_{FR,TO,i,r} \\
& + \sum_r HKWHMCH_r * Cr + \sum_r \sum_q NGA_{r,q} * C_{r,q} + PNGL * C + TAGTL * C + TANSO * C \\
& + \sum_m \sum_r WGTL_{m,r} * C_{m,r} + \sum_r \sum_q NCL_{r,q,col} * C_{r,q,col} + \sum_p \sum_h \sum_d Hp_{h,d} * C_{p,h,d}
\end{aligned}$$

- 
- Note: (1)  $\sum_u \sum_r \sum_m Ru_{r,m} * C_{u,r,m}$  term is represented in the matrix as T(r)OVCOBJ + T(r)GPLOVC + T(r)MCHOVC as represented by rows P(r)OVC, G(r)OVC, H(r)OVC, respectively.  
(2) ZZAMHTOT=TAAMHXZ as defined by row CZAMH.  
(3) Row P(r)CBNTAX is used to set TCBN<sub>r</sub> regional totals for tax on carbon emissions.

## B.5 Row Constraints

1. The implicit world oil price, WOP (the refiner's acquisition cost of imported crude oil), must be at least some fraction of premised WOP:

$$\sum_c \sum_r \sum_q P_{i_{c,r,q}} * C_{c,r,q} - WOP * Nwop * Zt \geq 0$$

where:

$P_{i_{c,r,q}}$  the volume of imported crude oil acquired by refinery region (r) of crude type (c) at price level (q). The volume of each crude type (c) is upper bounded by each step of the supply curve.

$C_{c,r,q}$  is crude oil cost applicable to  $P_{i_{c,r,q}}$ . \$/bbl

WOP is the premised World Oil Price. \$/bbl

Nwop is minimum fraction of the WOP by which refiners must acquire crude oils by volume weighted average; and  $Nwop \leq 1$ .

Zt is total processed foreign crude oil over all refinery regions.

I.e., the average refiner acquisition cost of crude oil will be at least some input fraction of WOP.

Note: The index (v) denoting crude oil source is always "F" for imported crude. Therefore, no summation on (v) occurs for  $P_{i_{c,r,q}}$ .

2. The implicit world oil price, WOP (the refiner's acquisition cost of imported crude oil), must not be greater than some fraction of premised WOP:

$$\sum_c \sum_r \sum_q P_{i_{c,r,q}} * C_{c,r,q} - WOP * Xwop * Zt \leq 0$$

where:

Xwop is the maximum fraction of the WOP by which refiners must acquire crude oils by volume weighted average, and  $Xwop \geq 1$ .

I.e., the average refinery acquisition cost of crude oil must not exceed some input fraction of WOP.

Note: This constraint in conjunction with the previous constraint confines the imported crude oil volumes so that their composite unit cost is close to the WOP.

Since the costs of the five types of imported crude oil bracket the WOP, there is a continuum of import possibilities. The crude oils vary in cost according to crude quality and transportation cost. However, to avoid infeasibilities due to an overly restrictive constraint, it is presently the practice to allow a variation of 50

cents per barrel. This is also made necessary when maximum import restrictions are placed on all but a "swing" crude oil. Clearly, if the tolerance is sufficiently relaxed, a single crude type could be imported rather than a reasonably balanced mix.

3. Calculate total foreign crude oil processed by summing all crude oil volumes processed over all refinery regions:

$$\sum_c \sum_v \sum_r Ra_{c,F,r} - Zt = 0$$

where:

$Ra_{c,F,r}$  is the crude oil volume distilled in refinery region (r) from foreign source (F) of crude oil type (c).

I.e. the total U.S. refined foreign crude oil volume equals the sum of all foreign crude oils refined over all regions.

4. Place an upper bound on product import volume:

$$\sum_p \sum_r \sum_q I_{p,r,q} \leq IPmax$$

where:

$I_{p,r,q}$  is the volume of product (p) imported into refinery region (r) at cost level (q).

$IPmax$  is the maximum assumed volume of imported products allowed into the United States, an input value.

I.e., the sum of product volumes imported at all price levels over all refinery regions must not exceed some maximum.

5. Assure that the volumes of methanol consumed in each refinery region sum to the assumed total volume.

$$\sum_r M_r - Mt = 0$$

where:

$M_r$  is methanol consumed by the chemical industry in refinery region (r).

$Mt$  is total U.S. methanol consumption by the chemical industry, an input.

I.e., methanol consumed by the chemical industry in each refinery region must sum to the projected chemical industry total.

Note: The PMM models domestic methanol production aggregated to the refinery region level as though the plants were processing units integral to the refinery.

The methanol production is allocated to two demands: chemical industry demand and transportation sector demand.

6. Limit capital investment for refinery expansion in each refinery region:

$$\sum_u E_{r,u} * A_{r,u} \leq E_{max_r} \quad \text{for all } r$$

where:

$E_{r,u}$  is a capacity addition for this operating year for processing unit type (u) in refinery region (r).

$A_{r,u}$  is the capital investment required per unit of capacity for processing unit type (u) in refinery region (r), million dollars per Mbb/d.

$E_{max_r}$  is the upper limit on capital expenditures per year in refinery region (r), an input. \$MM per year

I.e., total capital expenditures are limited for each refinery region. This limit allows the user to place limits on expansion for a given scenario. The limits set for PADD's I and II phase down to \$500 million per year by 2025. This value is based on analyst judgment to reflect the low expectation of refinery expansion in these regions. The assumption has been that the lack of environmental waivers and permits will preclude capacity additions in these regions. PADD's III, IV, and V investments have been limited to 12,000, 2,000, and 19,000 million dollars, respectively (generally non-constraining).

7. Limit total U.S. refinery capital investment:

$$\sum_r \sum_u E_{r,u} * A_{r,u} \leq E_{max}$$

where:

$E_{max}$  is the upper limit on capital investment over all refinery regions, an input. \$MM

I.e., total capital expenditures are constrained to some maximum. This limit allows the user to place limits on expansion for all regions in the United States. The default value is \$50 billion and is not constraining.

Note: This constraint has been used to determine maximum product import needs by setting  $E_{max}$  to zero. It has not been operative in any production runs thus far. However, like the previous row, it is a potential policy exploration handle. For instance, one could hypothesize that in a capital-short domestic environment, total industry investment is limited.

8. Limit the volume of unfinished oil processed in U.S. refineries:

$$\sum_c \sum_v \sum_r Ra_{c,v,r} - B1 * Tu \geq B0$$

where:

$Ra_{c,v,r}$  is the crude oil volume distilled in refinery region (r) from source (v) of crude oil type (c).

Tu is total processed unfinished oil over all refinery regions.

B0,B1 are regression equation coefficients (see Appendix A). B0 = 11,674.3, B1 = 4.087.

I.e., the maximum allowable unfinished oil processed is a linear function of total crude oil processed.

9. Limit the volume of each unfinished oil component processed in each refinery region:

$$A_{i,r} * Tu - T_{i,r} \geq 0 \quad \text{for all } r, i$$

where:

$T_{i,r}$  is the volume of unfinished oil component (i) processed in refinery region (r).

$A_{i,r}$  is the fraction of component (i) of total unfinished oil that is processed in refinery region (r), an input ( $\sum_i \sum_r A_{i,r} = 1.0$ ).

I.e., the volume distribution of each type of unfinished oil processed at each refinery region is constrained to the historical pattern.

Note: No unfinished oil processing in PADD's II and IV.

10. Balance by volume, at the demand regions, each alcohol/renewable fuel purchased by the petroleum industry and domestic methanol shipped in from the refinery regions against alcohol/renewable fuel blended by recipe in the demand region and alcohol/renewable fuel shipped out of the demand region:

$$\sum_q B_{a,d,q} + \sum_r \sum_m W_{a,r,d,m} + \sum_{d'} \sum_m W_{a,d',d,m} - \sum_p H_{p,a,d} * A_{p,a} - \sum_r \sum_m W_{a,d,r,m} - \sum_{d'} \sum_m W_{a,d,d',m} = 0 \quad \text{for all } a, d$$

where:

$a \in h$  so that a is a subset of all recipe blends (h) and in fact,  $a = \text{ETH, BIM, BIN, and MET}$ .

$B_{a,d,q}$  is the volume of alcohol (a) purchased in demand region (d) at price level (q). At present, this column exists only for ethanol.

$W_{a,r,d,m}$	is the volume of alcohol (a) received in demand region (d) from refinery region (r) via shipping mode (m). This column exists only for methanol.
$W_{a,d',d,m}$	is the volume of alcohol (a) received in demand region (d) from demand region (d') via shipping mode (m). This column exists only for ethanol.
$H_{p,a,d}$	is the volume of recipe product (p) manufactured by alcohol blend recipe (a) consumed in demand region (d).
$A_{p,a}$	is the volume fraction of recipe product (p) represented by alcohol (a), an input.
$W_{a,d,r,m}$	is the volume of alcohol (a) shipped from demand region (d) to refinery region (r) via mode (m). This column is valid only for ethanol.
$W_{a,d,d',m}$	is the volume of alcohol (a) shipped from demand region (d) to demand region (d') via mode (m). This column is valid only for ethanol.

I.e., in each demand region, all alcohol/renewable that is purchased or produced and shipped in from the refinery regions must be either splash blended into or shipped to a refining center.

Note: It is assumed that all ethanol/renewables purchases are made in the demand regions. Thus, ethanol/renewables needed by the refinery for processing or blending must be shipped from the demand regions.

11. For those products which are not blended by recipe at the demand regions, for each demand region, and for each product: imports plus what is received via domestic shipment must equal the volume blended into recipes plus regular sales volume (local and exports):

$$I_{p,d} + \sum_r \sum_m W_{p,r,d,m} + \sum_h H_{p,h,d} - \sum_{p'} \sum_h H_{p',h,d} * A_{p',h} - D_{p,d} - X_{p,d} - XZ_{p,d} = 0 \quad \text{for all } d, p$$

where:

$I_{p,d}$	is volume of product (p) imported into demand region (d).
$W_{p,r,d,m}$	is product (p) received in demand region (d) from refinery region (r) via transfer mode (m).
$X_{p,d}$	is volume of product (p) exported from demand region (d).
$XZ_{p,d}$	is distress volume of product (p) exported from demand region (d).
$H_{p,h,d}$	is volume of product (p) manufactured by recipe (h) at demand region (d).
$H_{p',h,d}$	is volume of product (p') manufactured by recipe (h) at demand region (d). This column exists only when product (p) is consumed to produce product (p') by a recipe blended at the demand region, i.e. splash blended at the terminals.

$A_{p,h}$  is the volume fraction of product (p') represented by product (p), consumed by recipe (h), an input.

$D_{p,d}$  is a sales volume of product (p) in demand region (d), this activity is fixed at the last NEMS iterative demand value; i.e., it does not influence the cost decision in the solution.

I.e., in each demand region, for each product, a balance is made whereby the volume imported and the volume shipped in from the refinery regions must equal the volume splash blended at the terminal plus straight sales volume.

12. Balance, at each demand region, the volumes for each of the recipe products M85 and E85 - the products which are blended at the demand terminals - so that manufactured volume plus imports equals the recipe sales volume for these terminal splash blended recipes:

$$\sum_h H_{p',h,d} + I_{p',d} - D_{p',d} = 0 \quad \text{for all } p', d$$

where:

$p' \in p$  so that  $p'$  is a subset of all products and in fact,  $p' = E85$  and  $M85$ .

$H_{p',h,d}$  is volume of recipe product (p') made by recipe (h), produced at demand region (d) by splash blending.

$I_{p',d}$  is volume of product (p') imported into demand region (d).

$D_{p',d}$  is the sales volume of product (p') in demand region (d).

I.e., for each demand region, all M85 and E85 blended at the terminals plus M85 and E85 imported into the demand region must equal sales of the corresponding products.

13. For Census Divisions (demand regions) 5 and 6, balance the volume of each product that is shipped into the demand region with volume shipped out of the demand region:

$$\sum_r \sum_m W_{p,r,d',m} + \sum_d \sum_m W_{p,d,d',m} - \sum_d \sum_m W_{p,d',d,m} = 0 \quad \text{for all } d', p$$

where:

$d' \in d$  and in fact,  $d' = \text{Census Divisions 5 (South Atlantic) and 6 (South Central)}$ .

$W_{p,r,d',m}$  is volume of product (p) received by demand region (d') from refinery region (r) via pipeline (P/L) mode (m). These columns are generated only for the pipeline shipping mode when (d') is CD 6.

$W_{p,d,d',m}$  is volume of product (p) received in demand region (d') via transshipment from demand region (d) by mode (m), e.g. from 6 to 5 or from 5 to 2. For these columns,  $d' = d$  is not allowed.

$W_{p,d',d,m}$  is volume of product (p) transshipped from demand region (d') to demand region (d) by mode (m). However, for these columns, d' = d is allowed; in this case the activity represents P/L sales

I.e., pipeline product received in CD 5 or CD 6 must balance P/L product sales and transshipments.

Note: CD 5 and CD 2 (Mid Atlantic) receive much of their product volumes via pipeline (P/L) originating in PAD District III. Thus PAD District II production which is transported via P/L is split into one activity representing P/L product which is sold in CD 6 and another activity which is product transshipped through CD 6 into CD 5. Similarly, this latter component is split into two column activities, one which represents P/L product sales in CD 5, and another which represents product transhipped through CD 5 to CD 2.

14. Balance the domestic production of each crude type at each producing region (b) against shipments to domestic refineries (r) and exports:

Lower 48 regions (all crude types) and Alaska crude type ALL :

$$P_b * A_{c,v,b} - \sum_r \sum_m Y_{c,v,b,r,m} - O_{c,v,b} = 0 \quad \text{for all } b, c, v \quad (\text{currently, } O_{c,v,b} = 0)$$

Alaska crude type AMH only (takes into account gain due to mixing of GTLs during transport from N. Slope; exports from AK = 0 for 2005 and beyond.) :

$$P_b * A_{c,v,b} + \text{GTLLOS} * \text{TAGTLTOT} - \sum_r \sum_m Y_{c,v,b,r,m} - \text{TAAMHXZ} = 0 \quad \text{for all } b, c, v$$

where:

$P_b$  is total volume of domestic crude oil produced at producing region (b).  
NOTE: for Alaska,  $P_b * A_{c,v,b} = \text{TATOT}_c$

$A_{c,v,b}$  is the fraction by volume of  $P_b$  that is crude type (c) with source code (v), an input.

$Y_{c,v,b,r,m}$  is volume of crude oil type (c) with source code (v) produced in domestic region (b) that is shipped to refinery region (r) via mode (m).

$\text{TAGTLTOT}$  is total volume of GTL transported in Alaska to Valdez.

$\text{GTLLOS}$  percent of GTL lost due to mixing with AK oil during transport in Alaska to Valdez.

$\text{TAAMHXZ}$  is total volume of AMH crude transferred from Alaska to Valdez. Only used with Alaska production region (A) row constraint.  
(Note:  $\text{TAAMHXZ} = \text{ZZAMHTOT}$  as defined by row constraint CZAMH.)

NOTE: for Alaska,  $P_b * A_{c,v,b} = TATOT_c$

I.e., for each production region and crude oil type, domestic production must be balanced against exports and shipments to refinery regions.

15. Set minimum renewables required in total US gasoline and diesel production (special study ONLY):

$$\sum_a \sum_d \sum_q B_{a,d,q} * A_a \geq \text{MinRen}$$

where:

a = ETH, ETC, BIM (not BIN)

$A_a$  = 1.0 for ETH, BIM; = 1.5 for ETC (special study requirement)

$B_{a,d,q}$  Volume of ethanol produced in demand region d at price q (where a= ETH, ETC)

MinRen Minimum renewables content in US production of gasoline and diesel.

NOTE: For AEO runs, MinRen requirement is zero (non-constraining).

16. Limit shipments of crude oil on Jones Act (with U.S. flag) marine tankers:

$$\sum_c \sum_v \sum_b \sum_r \sum_{m'} Y_{c,v,b,r,m'} * A_c - V_{cj} = 0$$

where:

$m' \in m$   $m'$  is the set of shipping modes that correspond to Jones Act crude oil tankers.

$Y_{c,v,b,r,m'}$  is volume of crude oil type (c) with source code (v) produced in domestic region (b) that is shipped to refinery region (r) via mode (m').

$A_c$  is dead weight tons per barrel of crude oil of type (c), about 0.1344.

$V_{cj}$  is total dead weight tons of Jones Act crude oil. This column is constrained to some maximum.

I.e., total Jones act crude oil shipments are limited by the existing fleet.

Note: This constraint is stated in the form 'X - MAX = 0' with bounds on MAX rather than in the form 'X # MAX' (which is more straight forward from a mathematical standpoint) because this allows the analyst to add a minimum constraint or change over to a fixed constraint within the FORTRAN code without a regeneration of the MPS file. Thus it is an artifice of convenience.

17. Limit shipments of refined product (and GTL) on Jones Act marine tankers by product class (clean, dirty...):

$$\sum_p \sum_r \sum_d \sum_{m'} W_{p',r,d,m'} * A_{p'} + \sum_p \sum_r \sum_d \sum_{m'} W_{GTL,A,r,m'} * A_{GTL} - V_{pc} = 0 \quad \text{for all product class (pc)}$$

where:

$m' \in m$   $m'$  is the set of shipping modes that correspond to Jones Act product tankers carrying product class (pc).

$p' \in p$   $p'$  is the set of products which correspond to the product class (pc) of the particular constraint row.

$W_{p',r,d,m'}$  is volume of product ( $p'$ ) shipped from refinery region (r) to demand region (d) via mode ( $m'$ ).

$A_{p'}$  is dead weight tons per barrel of product ( $p'$ ), an input.

$W_{GTL,A,r,m'}$  is volume of product GTL shipped from Alaska to refinery region (r) via mode ( $m'$ ).

$A_{GTL}$  is dead weight tons per barrel of GTL, an input.

$V_{pc}$  is total dead weight tons of Jones Act product of a shipping class (pc). This column is constrained to some maximum.

I.e., Jones Act product shipment volume is limited by tanker availability.

18. For each domestic crude oil producing region and refinery region (r) allowable combination, allow and limit pipeline shipments of crude oil:

$$\sum_c \sum_v \sum_m Y_{c,v,b,r,m} - V_{cp_{b,r}} = 0 \quad \text{for all } b, r$$

where:

$Y_{c,v,b,r,m}$  is volume of crude oil type (c) that is shipped from domestic producing region (b) to refinery region (r) via pipeline mode (m).

$V_{cp_{b,r}}$  is total crude oil shipped by pipeline from domestic producing region (b) to refinery region (r). This column is constrained to some maximum.

I.e., limit the crude oil volume shipped by pipeline from each applicable producing region//refinery region pair.

19. For each refinery/demand region applicable combination, limit pipeline shipments of light products to available capacity:

$$\sum_{p'} \sum_r \sum_d \sum_m W_{p',r,d,m} - V_{pp_{r,d,m}} = 0 \quad \text{for all } r, d, m$$

where:

$p' \in p$   $p'$  is the set of light products which can be shipped from refinery region (r) to demand region (d) via pipeline mode (m).

$W_{p',r,d,m}$  is volume of product (p') shipped from refinery region (r) to demand region (d) via pipeline mode (m).

$V_{ppr,d,m}$  is total volume of light products (p') shipped via pipeline mode (m) from refining region (r) to demand region (d). This column is constrained to some maximum.

I.e., the volume of light products that can be shipped by pipeline from each refinery region to each demand region is limited by the available pipeline capacity.

Note: Special cases exist for transfer from CD 6 to CD 5, from CD 5 to CD 2, from CD 6 to CD 6 (P/L sales), and from CD 5 to CD 5 (P/L sales).

20. For each refinery/demand region applicable combination, limit pipeline shipments of liquid petroleum gas and PCF volumes to available LPG pipeline capacity:

$$\sum_{p'} \sum_r \sum_d \sum_m W_{p',r,d,m} - V_{tpl,d,m} = 0 \quad \text{for all } r, d, m$$

where:

$p' \in p$   $p'$  is the set of LPG and PCF products which can be shipped from refinery region (r) to demand region (d) via pipeline mode (m).

$W_{p',r,d,m}$  is volume of LPG and PCF product (p') shipped from refinery region (r) to demand region (d) via pipeline mode (m).

$V_{tpl,d,m}$  is total volume of LPG and PCF products (p') shipped via pipeline mode (m) from refining region (r) to demand region (d). This column is constrained to some maximum.

I.e., the volume of LPG products that can be shipped by pipeline from each refinery region to each demand region is limited by the available pipeline capacity.

Note: Special case exists for transfer from CD 6 to CD 5.

21. Refinery 'policy' table entries are adhered to:

$$\sum_u \sum_m R_{u,r,m} * A_{e,u,r,m} - A_{e,r} * Z_r FLO_u \leq, \geq, = 0 \quad \text{for all } e, r$$

where:

$R_{u,r,m}$  is the manufacturing activity level in mode (m) operation in processing unit (u) at refinery region (r).

$A_{e,u,r,m}$  is the coefficient entered into the processing unit (u) table for refinery region (r) in the operating mode (m) column at policy row (e), an input.

$A_{e,r}$  is the fractional amount of total capacity value entered in the policy table in row (e) for refinery region (r), an input, i.e., constraints may be introduced by the analyst via the "policy" rows.

Note: The type of row (#,\$,=) is determined by the entry in column heading TYPE of the policy table (r)POL where  $A_{e,r}$ , appears. It may also be a non-constraining row, in which case the row is free. The total processing unit throughput is the base for the policy limits in each refinery region:

$$Z_r FLO_u - K_{u,r} - A_{u,r} * (L_{u,r} + E_{u,r}) = 0 \quad \text{for all } r, u$$

where:

$Z_r FLO_u$  is the sum of the base, build, and expanded capacity in processing unit (u) at refinery region (r).

$K_{u,r}$  is the base processing capacity in processing unit (u) at refinery region (r) in Mbbbl/cd. This column is upper bounded rather than fixed.

$A_{u,r}$  is the stream factor for processing unit (u) at refinery region (r) defined as the ratio of calendar day capacity to stream day capacity.

$L_{u,r}$  is the cumulative stream day capacity added for processing unit (u) at refinery region (r) during the previous simulated periods. This column is fixed.

$E_{u,r}$  is the stream day capacity added during this simulated period for processing unit (u) at refinery region (r). This column is generally upper bounded.

22. For each applicable combination of domestic crude oil and refinery region, balance shipments received directly from the producing region plus transshipments received from other refinery regions against crude oil consumed at the refinery and crude that is transshipped to other refinery regions:

$$\sum_b \sum_m Y_{c,v,b,r,m} + \sum_{r'} \sum_m Y_{c,v,r',r,m} - \sum_{r'} \sum_m Y_{c,v,r,r',m} - Ra_{c,v,r} = 0 \quad \text{for all } c, v, r$$

where:

$Y_{c,v,b,r,m}$  is volume of crude oil type (c) with source code (v) produced in domestic region (b) that is shipped to refinery region (r) via mode (m).

$Y_{c,v,r',r,m}$  is volume of domestic crude oil type (c) with source code (v) that is received at refinery region (r) by transshipment through refinery region (r') via mode (m).

$Y_{c,v,r,r',m}$  is volume of domestic crude oil type (c) with source code (v) that is transshipped through refinery region (r) to refinery region (r') via mode (m).

$Ra_{c,v,r}$  is volume of domestic crude oil type (c) with source code (v) that is processed through the atmospheric tower at refinery region (r).

I.e., for each domestic crude oil at each refinery region, the volume consumed at the refinery plus what is shipped out of the refinery region must equal what is shipped into the refinery region.

23. For each applicable combination of imported crude oil and refinery region, balance imports received directly plus imports transshipments received from other refinery regions against crude oil consumed at the refinery and crude that is transshipped to other refinery regions:

$$\sum_q P_{i_{c,r,q}} + \sum_{r'} \sum_m Y_{c,F,r',r,m} - \sum_{r'} \sum_m Y_{c,F,r,r',m} - Ra_{c,F,r} - O_{SPR} = 0 \quad \text{for all } c, r$$

where:

$P_{i_{c,r,q}}$  is the quantity of imported crude oil acquired by refinery region (r) of crude type (c) at price level (q).

$Y_{c,F,r',r,m}$  is volume of imported crude oil type (c) that is received at refinery region (r) by transshipment from refinery region (r') via mode (m).

$Y_{c,F,r,r',m}$  is volume of imported crude oil type (c) that is transshipped from refinery region (r) to refinery region (r') via mode (m).

$Ra_{c,F,r}$  is volume of imported crude oil type (c) that is processed through the atmospheric tower at refinery region (r).

$O_{SPR}$  volume of imported oil moved to the Strategic Petroleum Reserve in PADD III

I.e., each imported crude oil must be balanced at each refinery by matching imports and what is received through transshipment against refinery consumption and what is transshipped to other refineries or to the SPR.

24. Balance each product at each refinery region:

$$Q_{p,r} + \sum_i H_{p,i,r} + \sum_q I_{p,r,q} + \sum_{p'} TX_{s,p,r} - \sum_u \sum_m R_{u,r,m} * A_{p,u,r,m} - \sum_m \sum_d W_{p,r,d,m} = 0 \quad \text{for all } p, r$$

where:

$Q_{p,r}$  is volume of spec product (p) manufactured in refinery region (r). When product (p) is a spec product, column  $H_{p,h,r}$  does not exist.

$H_{p,i,r}$  is volume of product (p) generated from gas plant stream (i) in refinery region (r). (Also includes  $H_{p,h,r}$ .) When this column is active for product (p), column  $Q_{p,r}$  does not exist.

$I_{p,r,q}$  is volume of refined product (p) imported into refinery region (r) at price level (q).

$T_{x,s,p,r}$	is the volume of stream (s) transferred into product (p) in refinery region (r).
$R_{u,r,m}$	is the manufacturing activity level in mode (m) operation in processing unit (u) at refinery region (r). (Applicable to product N6I and N6B only.)
$A_{p,u,r,m}$	is the volume fraction of manufacturing activity level in mode (m) operation in processing unit (u) which defines the volume of product (p) produced (or consumed if the sign is negative) per unit of manufacturing activity level in refinery region (r).
$W_{p,r,d,m}$	is the volume of product (p) shipped from refinery region (r) to demand region (d) via mode (m).

I.e., for each product at each refinery, the volume manufactured plus volume imported plus volume transferred from another higher quality product must equal to the volume transferred to other lower quality products plus the amount consumed by recipe plus the volume shipped to market.

25. Balance each utility at each refinery region:

$$U_{l,r} + \sum_u \sum_m R_{u,r,m} * A_{l,u,r,m} - \sum_p Q_{p,r} * A_{l,p,r} - \sum_p \sum_h H_{p,h,r} * A_{l,h,r} = 0 \quad \text{for all } r, l$$

where:

$U_{l,r}$	is the quantity of utility (l) that is purchased in refinery region (r). (l) = KWH, STM, and NGF (power, steam, and natural gas fuel) with units in thousands of kWh, lbs., and Mcf respectively.
$R_{u,r,m}$	is the manufacturing activity level in mode (m) operation in processing unit (u) at refinery region (r).
$A_{l,u,r,m}$	is the quantity of utility (l) consumed (-) or manufactured (+) per unit of operation of processing unit (u) in mode (m) in refinery region (r). The (u) index includes the utility manufacturing units.
$Q_{p,r}$	is the volume of spec product (p) manufactured at refinery region (r). This column exists only when product (p) is a spec blend.
$A_{l,p,r}$	is the quantity of utility (l) consumed per unit of spec product (p) manufactured at refinery region (r).
$H_{p,h,r}$	is the volume of product (p) manufactured by recipe blend (h) at refinery region (r). This column exists only when product (p) is a spec blend.
$A_{l,h,r}$	is the quantity of utility (l) consumed per unit of recipe product (h) manufactured at refinery region (r).

I.e., for each utility at each refinery region, the quantity purchased plus the amount manufactured must equal the consumption.

26. Constrain each processing unit throughput to maximum capacity at each refinery region:

$$\sum_m R_{u,r,m} - K_{u,r} - A_{u,r} * (L_{u,r} + E_{u,r}) = 0 \quad \text{for all } r, u$$

where:

$R_{u,r,m}$  is the manufacturing activity level in mode (m) operation in processing unit (u) at refinery region (r).

$K_{u,r}$  is the base processing capacity in processing unit (u) at refinery region (r) in Mbbbl/cd. This column is upper bounded rather than fixed. See note below.

$A_{u,r}$  is the stream factor for processing unit (u) at refinery region (r) defined as the ratio of calendar day capacity to stream day capacity.

$L_{u,r}$  is the cumulative stream day capacity added for processing unit (u) at refinery region (r) during the previous simulated periods. This column is fixed.

$E_{u,r}$  is the stream day capacity added during this simulated period for processing unit (u) at refinery region (r). This column is generally upper bounded.

I.e., the activity of a particular processing unit must be limited to the maximum operating capacity.

Note: By making this row fixed with the base capacity upper bounded, the processing throughput is calculated as  $K_{u,r} + A_{u,r} * (L_{u,r} + E_{u,r})$ . In a model lacking capacity expansion capability, the capacity constraint row is commonly constructed as throughput and is equal to or less than a right-hand-side capacity value so that the throughput is merely the row activity.

27. Balance each intermediate refinery stream at each refinery region:

$$\sum_u \sum_m R_{u,r,m} * A_{i,u,r,m} + \sum_s (Tx_{s,i,r} - Tx_{i,s,r}) - \sum_p G_{i,p,r} - \sum_p \sum_h H_{p,i,r} * A_{i,h} - Mr_r = 0 \quad \text{for all } i, r$$

where:

$i \in s$  i.e., the intermediate streams are a subset of all refinery streams.

$R_{u,r,m}$  is the manufacturing activity level in mode (m) operation in processing unit (u) at refinery region (r).

$A_{i,u,r,m}$  is the volume fraction of intermediate stream (i) created (or consumed if the sign is negative) per unit of manufacturing activity level in mode (m) operation for processing unit (u) at refinery region (r).

$T_{x_{s,i},r}$	is the volume of stream (s) transferred to intermediate stream (i) at refinery region (r).
$T_{x_{i,s},r}$	is the volume of intermediate stream (i) transferred to stream (s) at refinery region (r).
$G_{i,p,r}$	is the volume of intermediate stream (i) blended into spec blended product (p) at refinery region (r).
$H_{p,i,r}$	is volume of product (p) generated from gas plant stream (i) in refinery region (r). (Also includes $H_{p,h,r}$ and $H_{RFN,i,r}$ )
$A_{i,h}$	is the volume fraction of product (p) for which intermediate stream (i) is consumed (per unit volume of product manufactured) according to recipe (h) at refinery region (r).
$Mr_r$	Volume of methanol transferred from refinery or imported to meet U.S. methanol consumption by the chemical industry in refinery region (r). (only used with methanol balance $B(r)MET$ , $G(r)MET$ )

I.e., at each refinery region, each intermediate stream must be volume balanced so that the amount manufactured plus the amount transferred from higher quality streams must equal the volumes consumed by manufacturing processes, the amount that may be transferred to other lower quality streams plus the volumes blended into spec and recipe products.

#### 28. Constrain qualities of spec blended products:

$$\sum_i G_{i,p,r} * A_{y,i,p} - Q_{p,r} * A_{y,p,r} \leq, \geq, = 0 \quad \text{for all } y, p, r$$

where:

$G_{i,p,r}$	is the volume of intermediate stream (i) blended into spec-blended product (p) at refinery region (r).
$A_{y,i,p}$	is the blend value of spec blend property (y) for spec product (p) of stream (i).
$Q_{p,r}$	is the total volume of spec-blended product (p) manufactured at refinery region (r).
$A_{y,p,r}$	is the constraining value of property (y) that spec product (p) must adhere to; e.g., an octane number, at refinery region (r).

Note: The row type varies depending upon whether the blend specification quality is a maximum, minimum, or fixed value.

i.e., for each spec for each product at each refinery region, the aggregate spec value of the product determined by volume weighting the spec properties of the consumed blending stocks must not violate the specification limit.

29. Balance blending rows with specific blended products:

$$\sum_i G_{i,p,r} - \sum_{p'} Q_{p',r} = 0 \quad \text{for all } p, r$$

where:

$p$  is only TRG, RFG, N6I, N6B, DSL, DSU, N2H, and JTA.

$p' \in p$  for  $p=TRG$ ,  $p'=TRG, TRH, SST, SSE$ ;  
for  $p=RFG$ ,  $p'=RFG, RFH, SSR$ ;  
for remaining products ( $p$ ),  $p'=p$  only (i.e., for JTA,  $p'=JTA$  only).

$G_{i,p,r}$  is the volume of intermediate stream (i) blended into spec-blended product (p) at refinery region (r).

$Q_{p',r}$  is the total volume of spec-blended product (p) manufactured at refinery region (r).

30. Sum oxygen percentage contribution by oxygenates blended to reformulated gasoline

$$\sum_{OX} G_{OX,RFG,r} * PO_{OX} + \sum_{d \in r} H_{ETH,RFG,d} * PO_{ETH} * F_{ETHRFG} + \sum_{d \in r} H_{ETH,RFH,d} * PO_{ETH} * F_{ETHRFH} - ZOX_r = 0 \quad \text{for all } r$$

where:

$G_{OX,RFG,r}$  is the volume of oxygenate stream (OX) blended to RFG in region (r).

$PO_{OX}$  is the percentage oxygen in oxygenate stream (OX). This group includes MTBE, TAM, and THM from methanol and ETBE, TAE, and THE from ethanol. Also included is the ethanol splash blended.

$H_{ETH,RFG,d}$  is the volume of RFG splash blended with ethanol in demand region d (within region r).

$PO_{ETH}$  is the percentage oxygen in ethanol

$F_{ETHRFG}$  is the fraction of ethanol in RFG for 2.0 percent min oxygen (= 5.8 percent).

$H_{ETH,RFH,d}$  is the volume of RFH splash blended with ethanol in demand region d (within region r).

$F_{ETHRFH}$  is the fraction of ethanol in RFH for 2.7 percent min oxygen (= 7.8 percent).

$ZOX_r$  is the total volume in units of percent oxygen-barrels of RFG.

31. Sum oxygen percentage contribution by *renewable oxygenates* blended to RFG.

$$\sum_{OE} G_{OE,RFG,r} * PO_{OE} + \sum_{d \in r} H_{ETH,RFG,d} * PO_{ETH} * F_{ETHRFG} + \sum_{d \in r} H_{ETH,RFH,d} * PO_{ETH} * F_{ETHRFH} - L * ZOX_r \geq 0 \quad \text{for all } r$$

where, in addition to the terms defined in equation 29:

$G_{OE,RFG,r}$  is the volume of renewable oxygenate stream (OE) blended to RFG in region (r).

$PO_{OE}$  is the percentage oxygen in oxygenate stream (OE). This group includes ETB, TAE, and THE from ethanol. Also included is the ethanol splash blended.

$L$  is the volume fraction of the oxygen that must come from *renewable oxygenates*, i.e., ethanol, ethylbenzene (ETB) and ethyl ethers (TAE and THE).

32. Calculate refinery consumption of natural gas supply by summing volumes processed for each refinery region:

$$\sum_q N_r NGRFN_q + \sum_q N_r NGRFP_q - U_r NGF = 0$$

where:

$N_r NGRFN/P_q$  is the volume of natural gas consumed in refinery region (r) at supply price delta (q).

$U_r NGF$  is the total volume of natural gas consumed in refinery region r.

33. Place an upper bound on each natural gas supply step volume:

$$N_r NGRFN/P_q \leq NG_q \text{ max}$$

where:

$N_r NGRFN/P_q$  is the volume of natural gas allowed on step q in region (r) at cost a cost delta.

$NG_q \text{ max}$  is the maximum volume of natural gas supply allowed, based on an input value. Note that step N1 has a minimum lower bound volume.

34. Calculate Alaskan crude export volumes:

$$\sum_q NZAMHP_q + \sum_q NZAMHN_q - ZZAMHTOT = 0$$

where:

$\sum_q NZAMHP_q$  Volume at price increment q of Alaskan Crude (AMH) exports.

$\sum_q \text{NZAMHN}_q$  Volume at price discount  $q$  of Alaskan Crude (AMH) exports.

35. Place an upper bound on each Alaskan crude supply step volume:

$$\text{NZAMHX}_q \geq \text{NZAMHX}_q \text{ max}$$

where:

$\text{NZAMHX}_q$  Volume at price increment/discount  $q$  of Alaskan Crude (AMH) exports.

$\text{NZAMHX}_q \text{ max}$  is the maximum volume of crude export allowed, based on an input value.

36. Calculate taxable carbon emissions:

$$\text{TCBN}_r - \sum_m \text{R}_{\text{FUM},r,m} = 0 \quad \text{for all } r$$

where:

$\text{TCBN}_r$  Total carbon emissions resulting from refinery operations in refinery region  $r$  for which tax is levied.

$\text{R}_{\text{FUM},r,m}$  is the manufacturing activity level in mode ( $m$ ) operation in processing unit FUM at refinery region ( $r$ ).

37. Calculate ethanol available for tax subsidy:

$$\sum_q \text{B}_{a,d,q} - \text{ZET}_d = 0 \quad \text{for all } d, a = \text{ETH, ETC}$$

where:

$\text{ZET}_d$  Total ethanol production in demand region  $d$  for which tax subsidy is allowed.

$\text{B}_{a,d,q}$  Volume of ethanol produced in demand region  $d$  at price  $q$  (where  $a = \text{ETH, ETC}$ )

38. Calculate volume of GTL movement from Alaska to refining regions:

$$\sum_m \text{W}_{\text{GTL},A,r,m} - \sum_i \text{HMP}_{i,r} = 0 \quad \text{for all } r$$

where:

$\text{W}_{\text{GTL},A,r,m}$  Total GTL transferred from Alaska to region  $r$  via transportation mode  $m$

39. Limit volume percent of undesirable oxygenate in RFG (and TRG) - related motor gasoline (mogas) produced at refinery  $r$  for sale or splash blending:

$$\sum_{\text{ox}} \text{G}_{\text{ox},\text{RFG},r} - \sum_{\text{mg} \in \text{RFG}} \text{Q}_{\text{mg},r} * \text{PO}_{\text{mg}} \leq 0 \quad \text{for all } r$$

and

$$\sum_{\text{ox}} \text{G}_{\text{ox},\text{TRG},r} - \sum_{\text{mg} \in \text{TRG}} \text{Q}_{\text{mg},r} * \text{PO}_{\text{mg}} \leq 0 \quad \text{for all } r$$

where:

$G_{ox,TRG,r}$	Volume of oxygenate ox (MTBE, ETBE, TAE, TAM for TRG component) blended or splash blended in the manufacture of TRG mogas components.
$G_{ox,RFG,r}$	Volume of oxygenate ox (MTBE, ETBE, TAE, TAM, THE, THM for RFG component) blended or splash blended in the manufacture of RFG mogas components.
$Q_{mg,r}$	Volume of spec product mg (SST, SSE, TRG, TRH for TRG component, and SSR, RFG, RFH for RFG component) manufactured in refinery region r.
$PO_{mg}$	Percentage oxygen required in mogas component mg.

40. Maximum and minimum flow requirements along TAPS in Alaska:

$$\text{TANSOTOT} + \text{TAGTLTOT} > \text{NSOmin}$$

and

$$\text{TANSOTOT} + \text{TAGTLTOT} < \text{NSOmax}$$

where:

$\text{TANSOTOT}$  Total oil transported from Alaska North Slope to Valdez along TAPS.

$\text{TAGTLTOT}$  Total GTL transported from Alaska North Slope to Valdez along TAPS.

$\text{NSO}$  Min and Maximum (capacity) flow allowed on TAPS in Alaska.

41. Maximum natural gas available for processing to GTL in Alaska:

$$\sum_r \sum_q \text{NGA}_{r,q} \leq \text{NGmax}$$

$\text{NGA}_{r,q}$  Natural gas used at price q to generate GTL for transport to refinery region r

$\text{NSO}$  Maximum quantity of natural gas allowed to be consumed for GTL production in Alaska.

42. Place an upper or lower bound on selected refinery fuels used in all US refining regions:

$$\sum_r \sum_m R_{u,r,m} \# \text{ or } \$ \text{MFuel}_f \quad \text{for all } m \in \text{refinery fuel}_f$$

where:

$u$  = FUM only

$f$  includes refinery fuel types LPG, RES, STG, and OTH only.

$R_{u,r,m}$  is the manufacturing activity level in mode (m) operation in processing unit (u=FUM) at refinery region (r);  $m \in \text{refinery fuel}_f$  (ie,  $m=N6I, N6B, N6A$  for  $f=RES$ ).

$\text{MFuel}_f$  is the maximum (or minimum) volume of fuel (f) allowed to be consumed as fuel at US refineries. This is based on historical levels, with analyst judgment used to

allow for growth. Currently, the growth rate per year for the LPG upper bound is 10% for the base AEO run, with side case runs at 12% for LWOP, 6% for HWOP, 8% for LMAC, and 11% for HMAc. The minimum bound for STG grows at 0.3% per year for all cases.

43. For each applicable combination of imported crude oil and refinery region, total imports received directly to the U.S. must be greater than a minimum:

$$\sum_c \sum_r \sum_q P_{i,c,r,q} \geq \text{rhs} \quad \text{for all } c \in \text{foreign crude}$$

where:

$P_{i,c,r,q}$  is the quantity of imported crude oil acquired by refinery region (r) of crude type (c) at price level (q).

rhs lower limit on total imports of foreign crude (currently set to 10.045 MM bbl/cd, and zero for LWOP)

44. For each applicable combination of imported crude oil and refinery region, total imports received directly to refining region r must be less than a maximum:

$$\sum_c \sum_q P_{i,c,r,q} \leq \text{rhs} \quad \begin{array}{l} \text{for all } c \in \text{foreign crude} \\ \text{only for } r=\text{PADD II or PADD IV} \end{array}$$

where:

$P_{i,c,r,q}$  is the quantity of imported crude oil acquired by refinery region (r) of crude type (c) at price level (q).

rhs upper limit on total imports of foreign crude into PADD II or IV only (limit on Canadian imports).

$$\text{PADD II: } \text{rhs} = 1212 * \text{cangrw}^{**}(\text{curiyr}-16)$$

$$\text{PADD IV: } \text{rhs} = 266 * \text{cangrw}^{**}(\text{curiyr}-16)$$

where, cangrw = 1.008 for all, except HWOP  
= 1.011 for HWOP

45. For PADD II and PADD IV only, total product imports received directly to refining region r must be less than a maximum:

$$\sum_p \sum_q I_{p,r,q} \leq \text{rhs} \quad \text{only for } r = \text{PADD II, IV only}$$

where:

$I_{p,r,q}$  is volume of refined product (p) imported into refinery region (r=PADD II or IV) at price level (q).

rhs upper limit on total imports of refinery product into PADD II or IV only (limit on Canadian imports).

$$\text{PADD II: } \text{rhs} = 108 * \text{cangrw}^{**}(\text{curiyr}-16)$$

$$\text{PADD IV: } \text{rhs} = 15.6 * \text{cangrw}^{**}(\text{curiyr}-16)$$

where, cangrw = 1.03 for all, except HWOP

= 1.04 for HWOP

46. For all Census Division exporting refinery products, total exports of coke must be greater than a minimum:

$$\sum_d X_{p,d} \geq \text{rhs} \quad \text{only for } p = \text{coke}$$

where:

$X_{p,d}$  is volume of product (p=coke) exported from demand region (d).

47. For PADD I only, imports of SSR for blend with ethanol must be greater than a minimum (to account for localized attainment areas and MTBE ban requirements):

$$\sum_q I_{p,r,q} \geq \text{rhs} \quad \text{only for } r = \text{PADD I}, p = \text{SSR}$$

where:

$I_{p,r,q}$  is volume of refined product (p=SSR) imported into refinery region (r=PADD I) at price level (q).

48. For each refining region, the ethane transferred to LPG must not exceed the amount extracted as liquids from the gas plant (should not include ethane transferred to gas plant):

$$\sum_q H_{p,i,r} - \sum_m A_{i,u,r,m} * R_{u,r,m} \leq 0.0 \quad \text{only for } i = \text{PGS}, p = \text{LPG}, \text{CC1}, u = \text{gas plant}$$

where:

$A_{i,u,r,m}$  is the volume fraction of intermediate stream (i) created (or consumed if the sign is negative) per unit of manufacturing activity level in mode (m) operation for processing unit (u) at refinery region (r). (special case: u=gas plant, i=pgs)

$R_{u,r,m}$  is the manufacturing activity level in mode (m) operation in processing unit (u= gas plant) at refinery region (r).

$H_{p,i,r}$  Volume of product (p) from gas plant stream (i) in refinery region (r).

49. Limit total ACU capacity addition in a single year:

$$\sum_r E_{r,u} \leq \text{ACU}_{\text{max}} \quad \text{for } u = \text{ACU only}$$

where:

$E_{r,u}$  is a capacity addition for this operating year for processing unit type (u=ACU) in refinery region (r).

$\text{ACU}_{\text{max}}$  is the maximum total ACU build allowed in one decision year (= 1000000 bbl/cd)

50. In addition to the above, several non-constraining rows exist merely as a convenience to sum over certain columns via the row activity parameter, including rows CAALLTOT, CAAMHTOT, CAGTLTOT, CANSOTOT, A(r)DSLCTI, A(r)DSUCTI, A(r)RFGM00, A(r)RFGR00, A(r)TRGM00, A(r)TRGR00.

## B.6 Row and Column Cross References

The PMM LP matrix is generated from a program written in the FORTRAN language using callable subroutines from OML. The correspondence between the rows and the column symbols in the preceding matrix description and the generated matrix names of PMM are shown in Table B4.

**Table B4. Column Cross References**

<u>Column Notation</u>	<u>Matrix Name</u>
$B_{a,d,q}$	C(d)(a)R(q)
$D_{p,d}$	D(d)(p)S1 & D(d)(p)SX
$E_{u,r}$	E(r)(u)INV
$G_{i,p,r}$	B(r)(p)(i) & F(r)(p)(i)
$H_{p,h,r}$	X(r)(h)(p)
$H_{p,h,d}$	X(d)(h)(p)
$H_{p,i,r}, H_{RFN,i,r}$	G(r)(i)(p)
$H_{g,i,r}$	G(r)(i)(g)
$HKWHMCH_r$	H(r)KWHMCH
$HMP_{i,r}$	H(r)MPRF(i), H(r)MPGP(i), H(r)RFMP(i), H(r)GPMP(i)
$I_{p,r,q}$	I(r)(p)R(q)
$Iz_{p,d}$	I(d)(p)Z9
$K_{u,r}$	K(r)(u)CAP
$L_{u,r}$	L(r)(u)BLD
$M_r$	G(r)METDEM
$Mr_r$	G(r)RFNMET
$Mt$	D@METS1
$NCL_{r,q,col}$	N(r)(col)N(q)
$NGA_{r,q}$	N(r)NGKN(q)
$N_rNGRFN_q$	N(r)NGRFN(q)

**Column Notation****Matrix Name**

$N_r$ NGRFP <sub>q</sub>	N(r)NGRFP(q)
NZAMHN <sub>q</sub>	NZAMHN(q)
NZAMHP <sub>q</sub>	NZAMHP(q)
O <sub>c,v,b</sub>	O@CRDEXP
O <sub>SPR</sub>	O@CRDSPR
P <sub>b</sub>	P(b)DCRQ1
P <sub>i,c,r,q</sub>	P(r)F(c)Q(q)
PNGL	PANGLQ1
Q <sub>p,r</sub>	Q(r)(p)
R <sub>a,c,v,r</sub>	R(r)ACU(v)(c)
R <sub>c,r</sub>	R(r)CGNCGN, R(r)CGXCGN
Rchp <sub>r,m</sub>	R(r)CHP(mod)
R <sub>u,r,m</sub>	R(r)(u)(m) & H(r)(u)(m)
Tu	T@UNFTOT
T <sub>i,r</sub>	T(r)UNF(i)
TAAMHXZ	TAAMHXZ
TATOT <sub>c</sub>	TAA(c)TOT
TAGTL	TAGTLTOT
TANSO	TANSOTOT
TCBN <sub>r</sub>	T(r)CBNTAX
Tx <sub>s,p,r</sub>	T(r)(s)(p)
Tx <sub>p,p',r</sub>	T(r)(p)(p')
Tx <sub>s,s',r</sub>	T(r)(s)(s')
U <sub>l,r</sub>	U(r)(l)
U <sub>r</sub> NGF	U(r)NGF
V <sub>cj</sub>	VTVC(m)CP

<u>Column Notation</u>	<u>Matrix Name</u>
$V_{pc}$	VTVP(m)CP
Vcts	VTPCGAC (not used)
$V_{cp_{b,r}}$	VTPC(b)(m)(r)
$V_{pp_{r,d,m}}$	VTPP(r)(m)(d)
$V_{tp_{l,r,d,m}}$	VTPL(r)(m)(d)
$WGTL_{m,r}$	WAGTL(m)(r)
$W_{a,r,d,m}$	W(r)(a)(m)(d)
$W_{a,d,r,m}, W_{a,d,d',m}$	W(d)(a)(m)(r), W(d)(a)(m)(d')
$W_{p,r,d,m}$	W(r)(p)(m)(d)
$W_{p,d,d',m}$	W(d)(p)(m)(d')
$X_{p,d}$	D(d)(p)SX
$XZ_{p,d}$	D(d)(p)Z9
$Y_{c,v,b,r,m}$	Y(b)(v)(c)(m)(r)
Zt	Z@TOTCRD
ZET <sub>d</sub>	Z(d)ETHTAX Z(d)ETCTAX
$Z_rFLO_u$	Z(r)FLO(u)
ZOX <sub>r</sub>	Z(r)RFGOXY
ZZAMHTOT	ZZAMHTOT

**Table B5. Row Cross References**

<u>Row Number</u>	<u>Matrix Name</u>
1	Z@IRACN
2	Z@IRACX
3	Z@CRDTOT
4	A@PRDIMP
5	D@MET
6	A(r) INVST
7	A@INVST
8	F@TOTCRD
9	F(r)UNF(i)
10	D(d)(a)
11	D(d)(p)
12	D(d)(p')
13	M(d)(p)
14	C(b)(v)(c), (CZAMH)
15	C@ETHBIO
16	TVC(m)CP
17	TVP(m)CP
18	TPC(b)(m)(r)
19	TPP(r)(m)(d)
20	TPL(r)(m)(d)
21	P(r)(e), Z(r)CAP(u), H(r)(e), G(r)(e)
22	C(r)(v)(c)
23	C(r)F(c)
24	M(r)(p)
25	U(r)(l)
26	L(r)(u)CAP, H(r)FUMCAP
27	B(r)(i), G(r)(i), H(r)(i)
28	Q(r)(p)(y)
29	S(r)(p)E
30	S(r)RFGOXY
31	Q(r)RFGREN
32	Z(r)NGFSUM
33*	N(r)NGRFN/P(q)
34	ZZAMHSUM
35*	NZAMHN/P(q)
36	P(r)CBNTAX
37	A(d)ETHTAX, A(d)ETCTAX
38	C(r)GTL
39	M(r)MTBREFG, M(r)MTBTRG
40	TAOILGTN, TAOILGTX
41	TANGKGTX
42	A@(f)FU
43	A@CRDIMP
44	A(r)CRDIMP
45	A(r)PRDIMP
46	A@COKEXP
47	A(r)SSRIMP
48	G(r)PGSLGX, G(r)SC2C1X
49	A@1YRBLD
50	(misc)

---

\* Bound on column variable.

## **APPENDIX C**

### **Bibliography**

## APPENDIX C Bibliography

1. Abt Associates Inc. 1991. *A Methodology for Evaluating the Costs and Global Warming Implications of Ethanol*. Report prepared for Office of Policy Analysis, U.S. Environmental Protection Agency, April 2, 1991.
2. F. Gerard Adams and James M. Griffin, "An Economic-Linear Programming Model of the U.S. Petroleum Refining Industry," *Journal of the American Statistical Association* (September 1972), 67:339, pp. 542-551.
3. ASM Consulting Services, *Petroleum Market Module Review*, prepared for the Office of Statistical Standards, EIA/DOE, (July 1992).
4. American Petroleum Institute, *How Much We Pay For Gasoline: 1996 Annual Review*, (Washington, DC, May 1997).
5. ASM Consulting Services, *Petroleum Market Module Review*, prepared for the Office of Statistical Standards, EIA/DOE, (September 1992).
6. C.E. Bodington, "A History of Mathematical Programming in the Petroleum Industry," *Interfaces* (July-August 1990), 20:4, pp. 117-127.
7. Bureau of the Census, 1989 Annual Survey of Manufacturers, Statistics for Industry Groups and Industries (M89AS1).
8. *Chemical Market Reporter*, Methanol Capacity Data By Company, December 16, 2002.
9. Chowdhury, A., E.O. Heady, and S. Bhide. 1981. Optimum Crop Production and Resource Use Under Alternative Energy Prices and Agricultural Exports: A Separable and Change-Constrained Programming Analysis. Report 103. The Center for Agricultural and Rural Development, Ames, IA.
10. Christensen, D.A., R.J. Schatzer, E.O. Heady, and B.C. English. 1981. *The Effects of Increased Energy Prices on U.S. Agriculture: An Econometric Approach*. Report 104. The Center for Agricultural and Rural Development, Ames, IA.
11. CMAI, Houston, TX, *United States Methanol Chemicals Demand Forecast*, January 2004.
12. ConocoPhillips, *S Zorb Process Overview*, [http://www/fuelstechnology.com/szorb\\_processover.htm](http://www/fuelstechnology.com/szorb_processover.htm)
13. Decision Analysis Corporation of Virginia, *The Oil Trade Model (OTM) Draft Documentation, User's Manual [and] Data Base*, (Vienna, VA, October 31, 1989).

14. Decision Analysis Corporation of Virginia, Transportation and Refining of International Petroleum (TRIP) Model Documentation, Volume I (Vienna, VA, December 1988).
15. Decision Analysis Corporation of Virginia, Transportation and Refining of International Petroleum (TRIP) Model Documentation, Volume II (Vienna, VA, December 1988).
16. Defense Energy Support Center, *Compilation of United States Fuel Taxes, Inspection Fees and Environmental Taxes and Fees*, Edition: 2004-14, August 9, 2004.
17. DiPardo, Joseph. April 2000. *Outlook for Biomass Ethanol Production and Demand*. Energy Information Administration, U.S. Department of Energy.
18. Dvoskin, D., E.O. Heady, and B.C. English. 1978. *Energy Use in U.S. Agriculture: An Evaluation of National and Regional Impacts from Alternative Energy Policies*. The Center for Agricultural and Rural Development. Report 78. Ames, IA.
19. *E85 Blending, Tax Incentives, and Pump Pricing*, National Ethanol Vehicles Coalition, A copy of the report may be obtained by calling (877) 485-8595
20. Energy Information Administration, *Annual Energy Review*, DOE/EIA-0384(2001)(Washington, DC, November 2002).
21. Energy Information Administration, *Component Design Report: The Integrating Module*, (Washington, DC, May 1992).
22. Energy Information Administration, Component Design Report: The Macroeconomic Activity Module of the National Energy Modeling System, (Washington, DC, March 1992).
23. Energy Information Administration, *Fuel Oil and Kerosene Sales 2001*, DOE/EIA-0535(2001)(Washington, DC, November 2002).
24. Energy Information Administration, *International Energy Annual 2000*, DOE/EIA-0219(2000)(Washington, DC, May 2002).
25. Energy Information Administration, *Modeling Environmental Costs*, memorandum prepared by S.R. MacIntyre (Washington, DC, February 1993).
26. Energy Information Administration, *Historical Natural Gas Annual 1930 Through 2000*, DOE/EIA-0110(00), (Washington, DC, December 2001).
27. Energy Information Administration, *NEMS Crude Oil Categories*, memorandum prepared by Xavier Szebrat (Washington, DC, July 1992).
28. Energy Information Administration, *The Transition to Ultra-Low-Sulfur Diesel Fuel: Effects on Prices and Supply*, SR/OIAF/2001-01 (Washington DC, May 2001).

29. Energy Information Administration, Impact of Renewable Fuels Standard/MTBE Provisions of S. 1766 Requested by the Senate Energy Committee (Washington DC, March 2002).
30. Energy Information Administration, Impact of Renewable Fuels Standard/MTBE Provisions of S. 517 Requested by Senators Daschle and Murkowski (Washington DC, April 2002).
31. Energy Information Administration, Summary – Analysis of Selected Transportation Fuel Issues Associated with Proposed Energy Legislation, by Joanne Shore (Washington DC, September 2002).
32. Energy Information Administration, *Outstanding Issues of Refinery Plant Expansion*, memorandum prepared by G.R. Harp (Washington, DC, May 1993).
33. Energy Information Administration, *Petroleum Marketing Annual 2001*, DOE/EIA-0487(2001) (Washington, DC, September 2002).
34. Energy Information Administration, *Petroleum Supply Annual 2003, Volume 1*, DOE/EIA-0340(2003/1)(Washington, DC, June 2004).
35. Energy Information Administration, *Petroleum Supply Monthly, DOE/EIA Washington, DC, July 2004*.
36. Energy Information Administration, PMM Procedure to Calculate Investment Recovery and Fixed Cost Charges on Existing U.S. Refinery Plant, memorandum prepared by G.R. Harp (Washington, DC, August 1993).
37. Energy Information Administration, *Preliminary Design for the PMM and Detailed Refinery Model*, memorandum prepared by S.R. MacIntyre (Washington, DC, February 1992).
38. Energy Information Administration, *Proceedings of the National Energy Modeling System Conference*, (Washington, DC, May 1993).
39. Energy Information Administration, NEMS Component Design Report for Biofuels (Ethanol) Supply Submodule - Renewable Fuels Model - National Energy Modeling System. Draft 3/12/93.
40. English, Smith, Atwood, Johnson, and Oamek. 1989. *Resource Conservation Act Analysis; An Overview of the CARD Agricultural Resource Interregional Modeling System*. The Center for Agricultural and Rural Development, Iowa State University, Ames, IA, Technical Report 89-TR11.
41. Energy Information Administration, *Requirements Analysis for a National Energy Modeling System* (Washington, DC, 18 May 1992).
42. Energy Information Administration, *Test Plan for the Petroleum Market Module (PMM)*, memorandum prepared by G.R. Harp (Washington, DC, May 1993).

43. Energy Information Administration, *The Treatment of Foresight and Expectation*, Decision Memorandum, Mary J. Hutzler and Mark E. Rodekohr, (Washington, DC, March 12, 1992).
44. Ensys Energy & Systems, Inc., *WORLD Reference Manual*, prepared for the Department of Energy, Contract No. DE-AC01-87FE-61299, September 1992.
45. Farmer, Richard D., "Problems and Lessons in Estimating Supply Curves for Refined Petroleum Products," *The Journal of Energy and Development*, Autumn, 1986, Vol. XII, No. 1, pp. 27-42.
46. J.H. Gary and G.E. Handwerk, *Petroleum Refining: Technology and Economics* (New York: Marcel Dekker, 1975), Chapters 13 and 14.
47. Giovando, CarolAnn June 1998. "1998 Powerplant Awards Sweeny Cogeneration Facility", *Power*.
48. Haverly Systems, Inc., *OMNI Linear Programming System, User Reference Manual*, (Denville, NJ, January 1987).
49. ICF Resources, North American Crude Oil Demand Model, July 1992.
50. Independent Reviews of Energy Information Administration's *The Transition to Ultra-Low-Sulfur Diesel Fuel: Effects on Prices and Supply*, by Ray Ory and Kevin Waguespack, April 2001.
51. Kane, S.M., and J.M. Reilly. 1989. *Economics of Ethanol Production in the United States*. Agricultural Economic Report 607. USDA/ERS, Washington, DC.
52. Ketron Management Science, Inc., *MPS III Mathematical Programming System, User Manual*, (Arlington, VA, August 1988).
53. Ketron Management Science, Inc., *Optimization and Modeling Subroutine Library, User Manual*, Draft, (Arlington, VA, 1994).
54. LeBlanc, M. and J. Reilly. 1988. *Ethanol: Economic and Policy Tradeoffs*. Agricultural Economic Report No. 585. Resources and Technology Division, Economic Research Service, U.S. Department of Agriculture, Washington, DC.
55. Lee, Hyunok. June 1993. "Ethanol's Evolving Role in the U.S. Automobile Fuel Market." *Industrial Uses of Agricultural Materials*, Situation and Outlook Report. United States Department of Agriculture, Washington, DC.
56. Lee, R., S.M. Cohn, and R.D. Perlack. 1991. *Prototype of an Integrated Model for Projecting Biofuels Consumption*. Draft report prepared for Energy Information Administration, U.S. Department of Energy. Oak Ridge National Laboratory, Oak Ridge, TN.

57. Linear Programming, Inc., *PAL/REMS Integration Methodology Study*, final report prepared for the Office of Statistical Standards, EIA/DOE, Contract No. DE-AC01-84EI-19633 (April 1987).
58. MacIntyre, Stacy, "Motor Fuels Tax Trends and Assumptions", *Issues in Midterm Forecasting 1998*, DOE/EIA-0607(98), (Washington DC, July 1998).
59. Macro International, Inc., *EIA-888 and EIA-878 Data Comparisons and Performance Measures*, Third Quarter 1997 (Washington, DC, December 15, 1997).
60. Marano, John J., Ph.D., *Refinery Technology Profiles: IsoOctane/IsoOctene and Related Technologies*, prepared for the National Energy Technology Laboratory, Energy Information Administration, DOE, January 2003.
61. Marano, John J., Ph.D., *Refinery Technology Profiles: Gasification and Supporting Technologies*, prepared for the National Energy Technology Laboratory, Energy Information Administration, June 2003.
62. Marland, G. and A.F. Turhollow. 1991. "CO<sub>2</sub> Emissions From the Production and Combustion of Fuel Ethanol from Corn". *Energy*, 16(11/12):1307-1316.
63. Mitretech Technical Report, *Coproduction: A Green Coal Technology*, by David Gray and Glen Tomlinsong, March 2001.
64. National Petroleum Council, *Petroleum Storage and Transportation*, (Washington, DC, April 1989).
65. National Petroleum Council, *U.S. Petroleum Refining* (Washington, DC, June 2000).
66. National Renewable Energy Laboratory 1999. *Bioethanol Multi-Year Technical Plan*.
67. National Research Council, *The National Energy Modeling System* (Washington, DC, January 1992).
68. Oak Ridge National Laboratory, *Review of the Component Design Report for the Petroleum Market Module*, letter prepared by Jerry Hadder (Oak Ridge, TN, July 1992).
69. The Pace Consultants, Inc., *Pace Petrochemical Service: Annual Issue*, (Houston, TX, October 1990).
70. Solar Energy Research Institute. March 1990. *The Potential of Renewable Energy: An Interlaboratory White Paper*, SERI/TP-260-3674, Golden, CO, prepared for the Office of Policy, Planning, and Analysis, U.S. Department of Energy, in support of the National Energy Strategy.

71. Trumble, David A. 1994. *Estimation of Supply Curve for Ethanol with Corn as the Feedstock*. Draft report prepared for Energy Information Administration, U.S. Department of Energy. Oak Ridge National Laboratory, Oak Ridge, TN.
72. Turhollow, A.F. 1991. *Economic Consideration for the Production of Wood for Energy*. Presentation at Trees for Energy, First National Fuelwood Conference, November 11-13, 1991, Lincoln, NE.
73. Turhollow, A.F., D.A. Christensen, and E.O. Heady. 1984. The Potential Impacts of Large-Scale Fuel Alcohol Production from Corn, Grain Sorghum, and Crop Residues Under Varying Technologies and Crop Expert Levels. Report 126. The Center for Agricultural and Rural Development, Ames, IA.
74. Turhollow, A.F., C. Short, and E.O. Heady. 1983. *Potential Impacts of Future Energy Price Increases on U.S. Agricultural Production*. Report 116. The Center for Agricultural and Rural Development, Ames, IA.
75. Tyson, K.S. 1990. *Biomass Resource Potential of the United States*. Report prepared for Office of Transportation Technologies, U.S. Department of Energy, October 1990. Solar Energy Research Institute, Golden, CO.
76. The University of Oklahoma, *Review of the Component Design Report for the Petroleum Market Module*, letter prepared by D.J. O'Neil (Norman, OK, July 1992).
77. U.S. Department of Agriculture, *USDA Agricultural Baseline Projections to 2009*, Staff Report WAOB-00-1 (Washington, DC, September 2000).
78. U.S. Department of Energy, Integrated Analysis Supporting the National Energy Strategy: Methodology, Assumptions, and Results, Technical Annex 2, First Addition, 1991/1992, DOE/S-0086P, p.148.
79. U.S. Department of Energy, *National Energy Strategy* (Washington, DC, February 1991).
80. U.S. Department of Energy, *Review of the Component Design Report for the Petroleum Market Module*, memorandum prepared by A.E. Haspel (Washington, DC, June 1992).
81. U.S. Department of Energy, *Review of the Component Design Report for the Petroleum Market Module*, memorandum prepared by J.D. Pearson (Washington, DC, June 1992).
82. U.S. Environmental Protection Agency, *Control of Emissions of Air Pollution From Nonroad Diesel Engines and Fuel*; Final Rule, 40 CFR, Parts 9, 69, et al.
83. U.S. Environmental Protection Agency, Heavy-Duty Engines and Vehicle Standards and Highway Diesel Sulfur Control Requirements, January 18, 2001.

84. U.S. Department of Energy, *Review of the Component Design Report for the Petroleum Market Module*, memorandum prepared by J.L. Petersen (Washington, DC, June 1992).
85. U.S. Department of Energy, *Review of the Component Design Report for the Petroleum Market Module*, memorandum prepared by C.P. Shirkey (Washington, DC, June 1992).
86. Urbanchuk, J.M. 1998. Review of Alternative Ethanol Supply Curves Used in the Energy Information Administration's National Energy Modeling System.
87. Walsh, M. et al June 1997. Evolution of the Fuel Ethanol Industry: Feedstock Availability and Price. Oak Ridge National Laboratory.
88. Wang, M. et al 1997. Fuel-Cycle Fossil Energy Use and Greenhouse Gas Emissions of Fuel Ethanol Produced from U.S. Midwest Corn.
89. Also see citations in Appendix A.

## **APPENDIX D**

### **Model Abstract**

# APPENDIX D Model Abstract

## D.1 Model Name:

Petroleum Market Model

## D.2 Model Acronym:

PMM

## D.3 Description:

The Petroleum Market Model is a simulation of the U.S. petroleum industry. It includes 12 domestic crude oil production regions, five refining centers with full processing representations and capacity expansion capability and gas plant liquid production, and nine marketing regions. The heart of the model is a linear programming optimization which ensures a rational economic simulation of decisions of petroleum sourcing, resource allocation, and the calculation of a marginal price basis for the products. Nineteen refined products are manufactured, imported, and marketed. Ten of these products are specification blended, while the remaining nine are recipe blended. Capacity limited transportation systems are included to represent existing intra-U.S. crude oil and product shipments (LPG, clean, dirty) via pipeline, marine tanker, barge, and truck/rail tankers. The export and import of crude oil and refined products is also simulated. All imports are purchased in accordance with import supply curves. Domestic manufacture of methanol is represented as though the processing plants are part of a refinery complex. Ethanol sources are treated as merchant plants. Transportation is allowed for ethanol shipments to the demand region terminals for splash blending.

The program is written in FORTRAN which includes callable subroutines allowing full communication with the LP portion of the model which is in the form of an MPS resident file.

## D.4 Purpose of the Model:

The PMM models domestic petroleum refining activities, the marketing of petroleum products to consumption regions, the production of natural gas liquids in gas processing plants, and domestic methanol and MTBE production. The purpose of the PMM is to project petroleum product prices, refining activities, and movements of petroleum across United States' borders and among domestic regions. In addition, the model contains adequate structure and is sufficiently flexible to examine the

impact of a wide variety of petroleum-related issues and policy options. These capabilities allow for understanding of the petroleum refining and marketing industry as well as determine the effects of certain policies and regulations.

The PMM projects sources of supply for meeting petroleum product demand. The sources of supply include crude oil, both domestic and imported; other inputs including alcohols and ethers; natural gas plant liquids production; petroleum product imports; and refinery processing gain. In addition, the PMM estimates domestic refinery capacity expansion and fuel consumption. Product prices are estimated at the Census Division (CD) level and much of the refining activity information is at the Petroleum Administration for Defense District (PADD) level.

### **D.5 Most Recent Model Update:**

October 2004

### **D.6 Part of Another Model?**

The PMM is a component of the National Energy Modeling System (NEMS)

### **D.7 Model Interfaces:**

The PMM receives information from the International, Natural Gas Transmission and Distribution, Oil and Gas Supply, Renewable Fuels, Electricity Market, Residential, Commercial, Industrial, and Transportation Models and delivers information to each of the models listed above plus the Macroeconomic Model.

### **D.8 Official Model Representative:**

William Brown  
Office of Integrated Analysis and Forecasting  
Oil and Gas Division  
(202) 586-8181

### **D.9 Documentation:**

*EIA Model Documentation: Petroleum Market Model of the National Energy Modeling System (NEMS), April 2005. (DOE/EIA-M059).*

## **D.10 Archive Media and Installation Manual**

Archived as part of the NEMS *AEO2005* production runs.

### **D.11 Energy System Described:**

Petroleum refining industry and refined products market.

### **D.12 Coverage:**

Geographic: Twelve domestic crude oil production regions (East Coast, Gulf Coast, Mid-Continent, Permian Basin, Rocky Mountain, West Coast, Atlantic Offshore, Gulf Offshore, Pacific Offshore, Alaska South, Alaska North, Alaska Offshore); five refining regions (PADDs I-V); nine market regions, the Census divisions (New England, Mid Atlantic, East North Central, West North Central, South Atlantic, East South Central, West South Central, Mountain, Pacific)

Time Unit/Frequency: Annual, 1995 through 2025

Products: LPG, conventional motor gasoline, conventional high oxygen motor gasoline, reformulated motor gasoline, reformulated high oxygen motor gasoline, M85, E85, jet fuel, distillate fuel oil, low-sulfur highway diesel, ultra-low sulfur diesel, low-sulfur residual fuel oil, high-sulfur residual fuel oil, petrochemical feedstocks, asphalt/road oil, marketable coke, still gas, “other” petroleum products, ethanol and biodiesel.

Refinery Processes: crude distillation, vacuum distillation, delayed coker, fluid coker, visbreaker, fluid catalytic cracker, thermal cracker, hydrocracker-dist, hydrocracker-resid, solvent deasphalter, resid desulfurizer, FCC feed hydrofiner, distillate HDS, naphtha hydrotreater, catalytic reformer-450 psi, catalytic reformer-200 psi, alkylation plant, catalytic polymerization, pen/hex isomerization, butane isomerization, etherification, butanes splitter, dimersol, butylene isomerization, total recycle isomerization, naphtha splitter, C2-C5 dehydrogenator, cyclar unit, hydrogen plant, sulfur plant, aromatics recovery plant, lube + wax plants, FCC gasoline splitter, gas/H<sub>2</sub> splitter, stream transfers, fuel system, steam production, power generation, and petroleum coke gasification.

Crude Oil: Alaska low-sulfur light, Alaska mid-sulfur heavy, domestic low-sulfur light, domestic mid-sulfur heavy, domestic high-sulfur light, domestic high-sulfur heavy, domestic high-sulfur very heavy, imported low-sulfur light, imported mid-sulfur heavy, imported high-sulfur light, imported high-sulfur heavy, imported high-sulfur very heavy.

Transportation Modes: Jones Act dirty marine tanker, Jones Act clean marine tanker, LPG marine tanker, import tankers, clean barge, dirty barge, LPG pipeline, clean pipelines, dirty pipelines, rail/truck tankers. These cover all significant U.S. links.

### **D.13 Modeling Features:**

Model Structure: FORTRAN callable subroutines which update the linear programming matrix, re-optimize, extract and post-process the solution results, update system variables, and produce reports.

Model Technique: Optimization of linear programming representation of refinery processing and transportation which relates the various economic parameters and structural capabilities with resource constraints to produce the required product at minimum cost, thereby producing the marginal product prices in a manner that accounts for the major factors applicable in a market economy.

Special Features: Choice of imports or domestic production of products is modeled, capacity expansion is determined endogenously, product prices include fixed and environmental costs, oxygenated and reformulated gasolines, and low-sulfur and ultra-low sulfur diesel fuels are explicitly modeled.

### **D.14 Non-DOE Input Sources:**

Information Resources Inc. (IRI), WORLD model data, National Petroleum Council, ICF Resources, Oil and Gas Journal, U.S. EPA gasoline properties survey.

### **D.15 DOE Input Sources:**

Forms:

EIA-14	Refiners' Monthly Cost Report
EIA-182	Domestic Crude Oil First Purchase
EIA-782A	Monthly Petroleum Product Sales
EIA-782B	Reseller/Retailer's Monthly Petroleum Product Sales
EIA-782C	Monthly Petroleum Products Sold into States for Consumption
EIA-759	Monthly Power Plant Report
EIA-810	Monthly Refinery Report
EIA-811	Monthly Bulk Terminal Report
EIA-812	Monthly Product Pipeline Report
EIA-813	Monthly Crude Oil Report
EIA-814	Monthly Imports
EIA-817	Monthly Tanker and Barge Movement

EIA-820	Annual Refinery Report
EIA-826	Monthly Electric Utility Sales
EIA-856	Monthly Foreign Crude Oil Acquisition
EIA-860B	Annual Nonutility Power Producer Report
FERC-423	Monthly Report of Cost and Quality of Fuels for Electric Plants

In addition to the above, information is obtained from several Energy Information Administration formal publications: *Petroleum Supply Annual*, *Petroleum Supply Monthly*, *Petroleum Marketing Annual*, *Petroleum Marketing Monthly*, *Fuel Oil and Kerosene Sales*, *Natural Gas Annual*, *Natural Gas Monthly*, *Annual Energy Review*, *Monthly Energy Review*, *State Energy Data Report*, *State Energy Price and Expenditure Report*.

## **D.16 Independent Expert Reviews Conducted:**

Independent reviews of the PMM were conducted by:

A.S. Manne, ASM Consulting Services, July 1992  
A.S. Manne, ASM Consulting Services, September 1992  
N. Yamaguchi, Trans-Energy Research Associates, Inc., November 1997.  
J. Urbanchuk, AUS Consultants, May 1998.  
Ray Ory, independent consultant, June 2003  
Terry Higgins, International Fuel Quality Center, June 2003  
Fred Joutz and Inderjit Kundra, George Washington University and Statistics and Methods Group of EIA, December 2003

## **D.17 Status of Evaluation Efforts by Sponsor:**

None.

# **APPENDIX E**

## **Data Quality**

# APPENDIX E. Data Quality

## E.1 Quality of Distribution Cost Data

Costs relating to distributing petroleum products to end-users are incorporated by adding fixed transportation markups to the wholesale prices which include the variable and fixed refinery costs. Transportation markups for petroleum products are estimated as the average annual difference between retail and wholesale prices over the years 1990 through 2000.<sup>1</sup> The differences are based on **wholesale prices** in the producing Census Division and **end-use prices** (which do not include taxes) in the consuming Census Division. See Appendix F for a discussion of programs and input files used in estimating these markups.

Annual **wholesale prices** for all petroleum products are aggregated from state-level prices from the EIA-782A. The estimation and reliability of the EIA-782A data is discussed in the *Petroleum Marketing Annual 2003* ([http://www.eia.doe.gov/pub/oil\\_gas/petroleum/data\\_publications/petroleum\\_marketing\\_annual/current/pdf/enote.pdf](http://www.eia.doe.gov/pub/oil_gas/petroleum/data_publications/petroleum_marketing_annual/current/pdf/enote.pdf)). See Explanatory Notes for inputs and sources.

With the exception of gasoline, non-utility distillate fuel, and jet fuel, **sectoral end-user prices** through 2000 are aggregated from prices from *State Energy Data 2000: Prices (SEDP)* ([http://www.eia.doe.gov/emeu/states/price\\_multistate.html](http://www.eia.doe.gov/emeu/states/price_multistate.html)). The methodology behind these state-level sectoral prices is discussed in the Technical notes section ([http://www.eia.doe.gov/emeu/states/sep\\_prices/notes/pr\\_petrol.pdf](http://www.eia.doe.gov/emeu/states/sep_prices/notes/pr_petrol.pdf)).

Gasoline, jet fuel, and non-utility distillate prices are estimated as weighted averages using end-user prices from EIA-782A and sectoral consumption from the *State Energy Data 2000: Consumption (SEDC)* ([http://www.eia.doe.gov/emeu/states/use\\_multistate.html](http://www.eia.doe.gov/emeu/states/use_multistate.html)).

Due to a lag in the publication of the *SEDP* data, end-use price estimates for 2001-2003 are calculated using the same data series and methodology described in *SEDP*. The *SEDP* methodology uses prices from EIA-782A, FERC-423, EIA-759, and weights them with most recent consumption volumes from *SEDC*. Refer to *SEDC* for a discussion of the reliability of consumption data (<http://eia.doe.gov/pub/state.data/pdf/petrol.pdf>, May 2001). Years 2004 and 2005 are estimated by applying the percent change of national product prices as reported in the September 2004 Short Term Energy Outlook (STEO) to each 2000 sectoral price.

---

<sup>1</sup>Transportation markups for kerosene are based on the difference between end-user kerosene prices and wholesale distillate prices.

**Table E1. Sources of Markup Inputs**

<b>Products</b>	<b>Sectors</b>	<b>Data Series Inputs</b>
Distillate	CM, IN, RS	EIA-782A, SEDC
Jet Fuel	TR	EIA-782A, SEDC
Low Sulfur Diesel Fuel	TR	EIA-782A, SEDC
Motor Gasoline	CM, IN, TR	EIA-782A, SEDC
Asphalt and Road Oil	IN	SEDP, EIA-782A, SEDC
Kerosene	CM, IN, RS	SEDP, EIA-782A, SEDC
Liquified Petroleum Gases	CM, IN, RS, TR	SEDP, EIA-782A, SEDC
Low Sulfur Residual Fuel	CM, IN	SEDP, EIA-782A, SEDC
High Sulfur Residual Fuel	TR	SEDP, EIA-782A, SEDC
Distillate	EU	SEDP, EIA-759, FERC-423
Low Sulfur Residual Fuel	EU	SEDP, EIA-759, FERC-423
High Sulfur Residual Fuel	EU	SEDP, EIA-759, FERC-423

## E.2 Quality of Tax Data

In the PMM, State and Federal taxes are added to the prices of gasoline, distillate fuel, liquefied petroleum gas (LPG), jet fuel, ethanol, and methanol in the transportation sector. State taxes are assumed to keep pace with inflation (held constant in real terms) while Federal taxes are held at current nominal levels (deflated in each forecast year).<sup>2</sup> The Federal tax assumption reflects the overall forecast assumption of current laws and legislation. The assumption that State taxes will increase at the rate of inflation reflects an implied need for additional highway revenues as driving increases. An additional 1 percent per gallon of gasoline price is added to the State gasoline taxes to approximate local taxes.

The State taxes are added as Census Division weighted averages which are based on the most recently-available State taxes. State taxes for jet fuel are derived from unpublished data collected by the Petroleum Marketing Division of EIA, while state taxes for ethanol are taken from average prices reported in *Oxy Fuel News* (published by Hart Energy Publishing, LP). State and Federal taxes for gasoline, transportation distillate, and LPGs are based on data from the Federal Highway Administration, but are modified to include other known changes to State taxes. The quality of the State level tax data is unknown but deemed reliable. The local tax estimate of 1 percent per gallon of gasoline price is reasonable given that a comparison of two EIA data series, one including local taxes and one not, revealed a gasoline price difference of 1.6 cents-per-gallon.<sup>3</sup> Federal taxes, which were adjusted in January of 2001, are widely published and deemed highly reliable.

See Appendix F for a description of programs and input files used in the calculation of historical taxes and the estimation of taxes used in the price projections.

---

<sup>2</sup>Refer to Stacy MacIntyre, *Motor Fuels Tax Trends and Assumptions*, Issues in Midterm Analysis and Forecasting 1998, DOE/EIA-0607(98), (Washington, D.C., July 1998).

<sup>3</sup>Macro International, Inc., *EIA-888 and EIA-878 Data Comparisons and Performance Measures*, Third Quarter 1997 (Washington, D.C., December 15, 1997).

## **E.3 PMM Critical Variables**

The PMM contains numerous variables and parameters. Some variables have greater impact on model results than others. The following is a list of variables that we believe has a high degree of influence on PMM results. It is provided to help users understand the critical factors affecting the PMM.

- World oil price
- Product demands
- Imported crude supply curves
- Imported product supply curves
- Domestic crude production
- Prices and available supplies of methanol, ethanol, MTBE, and other ethers
- Investment cost for capacity expansion
- Market shares for gasoline and distillate types
- NGL supply volumes

Most of these variables are provided by other models in the NEMS system. Ethanol supply and prices are provided by the Ethanol Supply Model, a sub-module of the PMM, documented in Appendix I. The investment cost and market share data are developed offline and read in to the PMM.

## APPENDIX F. Estimation Methodologies

### F.1 Refinery Investment Recovery Thresholds

The threshold for expansion investment decisions is represented by the process plant cost function (PCF). The PCF considers actual cash flows associated with the operation of the individual process plants within the refinery, as well as cash flows associated with capital for the construction of new plants. It includes terms for capital-related financial charges (CFC), fixed operating costs (FOC), and other variable operating costs (OVC):

$$PCF = \sum_i ( CFC_i + FOC_i + OVC_i ) \quad (1)$$

where

$i =$  individual process plants that make up the petroleum refinery, such as the atmospheric crude distillation unit, fluid catalytic cracking unit, etc.

However, since the  $OVC_i$  for each processing unit are represented as a separate term in the PMM LP objective function, only the sum of the  $FOC_i$  and  $CFC_i$  is included as the coefficient in the objective function row corresponding to the unit expansion vectors (E(r)(uns)INV and L(r)(uns)BLD, respectively) in the PMM. The methodologies used to calculate the capital-related financial charges and the fixed operating costs are presented below.

#### Capital-Related Financial Charges (CFC)

The CFC equation includes an annual capital recovery charge (ACR) minus a depreciation tax credit (DTC):

$$CFC_i = ACR_i - DTC_i \quad (2)$$

A discounted cash flow calculation is generally used to determine the annual capital charge for any given plant investment. The annual capital recovery charge assumes a discount rate equal to the cost of capital (COC), which includes equity (cost of equity, COE) and interest payments on any loans or other debt instruments used as part of capital project financing (cost of debt, COD). The depreciation of capital equipment is used for the purpose of determining the depreciation tax credit (DTC). Both the ACR and DTC are estimated on an after-tax basis.

Since the PMM and other energy forecasting models employ “notional” representations of U.S. petroleum refineries involving aggregation of data for many individual refineries, the cost estimating algorithm has been simplified while still capturing all the factors and costs refiners must consider when adding a new processing unit. The methodology draws upon the National Petroleum Council (NPC) study<sup>1</sup>, and other

---

<sup>1</sup> National Petroleum Council, *U.S. Petroleum refining – Meeting Requirements for Cleaner Fuels and Refineries*, Washington D.C., August 1993.

sources<sup>2</sup>. Some of the steps for the cost estimate are conducted exogenous to the NEMS (Step 0 below), either by the analyst in preparing the input data or during input data preprocessing, such as the estimate for the inside battery-limit (ISBL) field cost of the process unit. The individual steps in the plant capital cost estimation algorithm are:

- 0) Estimation of the ISBL field cost
- 1) Estimation of the ISBL field cost for different refinery locations
- 2) Estimation of the outside battery-limit (OSBL) field cost and the total field cost
- 3) Estimation of total project cost
- 4) Estimation of capital-related financial charges
- 5) Convert capital-related charges to a “per-day,” “per-capacity” basis

Step 0 may involve several adjustments which must be made prior to input into the PMM. The remaining steps 1-4 are performed within the PMM.

### ***Step 0 - Estimation of ISBL Field Cost***

The inside battery limits (ISBL) field costs include the direct cost such as major equipment, bulk materials, direct labor costs for installation, construction subcontracts, and indirect costs such as distributables. The ISBL investment cost and labor costs for most of the processing unit types modeled were initially obtained from a study by Bonner and Moore Associates (BMA),<sup>3</sup> and updated annually with revised estimates from EnSys Energy and Systems, Inc. (EnSys). The data for typical unit sizes and stream factors, as well as supplementary investment and labor, were obtained from the World Oil Refining, Logistics, and Distribution (WORLD) model<sup>4</sup>. The data used by the PMM currently represent process plants sited at a generic U.S. Gulf Coast (PADD III) location, and are in year 2000 dollars. (The latest EnSys data were expressed in year 2000 dollars.)

### ***Step 1 - Year-Dollar and Location Adjustment to ISBL Field Costs***

Before the PMM can utilize the ISBL investment cost data, it must convert the raw information via the following steps:

- a) Adjust the ISBL field costs and labor costs for each processing unit (j) from 2000 dollars, first to the year-dollar (rptyr) reported by NEMS for *AEO2005*, which is in 2003 dollars, using the Nelson-Farrar refining-industry cost-inflation indices. Then the GDP chain-type price indices provided by the NEMS Macroeconomic Activity Model are used to convert

---

<sup>2</sup>J.H. Gary and G.E. Handwerk, *Petroleum Refining: Technology and Economics*, 4<sup>th</sup> edition (New York: Marcel Dekker, 2001), Chapters 17 and 18.

<sup>3</sup>Bonner & Moore Associates, Inc., *A Capital Expansion Methodology Review of the Department of Energy's Petroleum Market Model*, prepared for the United States Department of Energy, Contract No. EI-94-25066 (Houston, TX, July 1994).

<sup>4</sup>EnSys Energy & Systems, Inc., *WORLD Reference Manual*, a reference for use by the analyst and management prepared for the United States Department of Energy, Contract No. DE-AC-01-87FE-61299 (Washington, D.C., September 1992).

from report-year dollars to 1987 year dollars used internally by the NEMS.

- b) Convert the ISBL field costs in 1987 dollars for each processing unit (j) from a PADD III (Gulf Coast) basis ( $BM\_ISBL_j$ ) to costs of the same processing unit for other PADD regions ( $RISBL_j$ ) via location multipliers ( $INVLOC_l$ ). The location multipliers represent differences in material costs between the various PADD regions.

$$RISBL_j = BM\_ISBL_j * INVLOC_l / 1000 \quad (3)$$

where

$RISBL_j$  = ISBL costs for processing unit j in refining region (PADD) l, in million 1987 dollars (MM 87\$)

$BM\_ISBL_j$  = ISBL costs for processing unit j in PADD III, in thousand 1987 dollars (M 87\$)

$INVLOC_l$  = Location multiplier for refining region l

Location multipliers for refinery construction were developed on a PADD basis using the most recent data available from the U.S. Bureau of Labor Statistics (BLS)<sup>5</sup> and the EIA<sup>6</sup>. The development of these multipliers and assumed values for other factors is described elsewhere<sup>7</sup>. The recommended location multipliers for refinery construction are given below:

**Table F1. Location Multipliers for Refinery Construction**

<u>Location</u>	<u>Construction Location Multiplier</u>
PADD I – U.S. East coast	1.50
PADD II – U.S. Midwest	1.29
PADD III – U.S. Gulf Coast	1.00
PADD IV – U.S. Rocky Mountain	1.40
PADD V – U.S. West Coast	1.48

### ***Step 2 - Estimation of OSBL Cost and Total Field Cost***

The outside battery-limit (OSBL) costs include the cost of cooling water, steam and electric power generation and distribution, fuel oil and fuel gas facilities, water supply, etc. The total field cost (FDC) is the sum of the ISBL and OSBL field costs. The OSBL field cost is estimated as a fraction (OSBLFAC) of the ISBL costs. Thus, the resulting FDC equation is:

$$RFDC_j = (1. + OSBLFAC) * RISBL_j \quad (\text{MM } 87\$) \quad (4)$$

<sup>5</sup> Wages Data, U.S. Department of Labor, Bureau of Labor Statistics, available on the web at [www.bls.gov/bls/blswage.htm](http://www.bls.gov/bls/blswage.htm).

<sup>6</sup> Refinery Capacity Data, U.S. Department of Energy, Energy Information Administration, available on the web at [www.eia.doe.gov/oil\\_gas/petroleum/data\\_publications/refinery\\_capacity\\_data/refcapacity.html](http://www.eia.doe.gov/oil_gas/petroleum/data_publications/refinery_capacity_data/refcapacity.html).

<sup>7</sup> *A General Cost Estimating Methodology for New Petroleum Refinery Process Capacity*, Appendix D, prepared for the U.S. Department of Energy, National Energy Technology Laboratory, and Energy Information Administration by John Marano, Ph.D., September 2004.

A default value of 0.45 is assumed by the PMM for the OSBL cost factor.

### **Step 3 – Estimation of Total Project Cost**

The total project investment (TPI) is the sum of the total field cost (Eq. 4) and other one-time costs (OTC):

$$RTPI_j = RFDC_j + ROTC_j \quad (\text{MM87\$}) \quad (5)$$

Other one-time costs include the contractor’s cost (such as home office costs), the contractor’s fee and a contractor’s contingency, the owner’s cost (such as pre-startup and startup costs), and the owner’s contingency and working capital (WC). The OTC’s are estimated as a function of total field costs (FDC), using cost factors (OTCFAC). The corresponding equations are presented below.

$$OTCFAC = PCTENV + PCTCNTG + PCTLND + PCTSPECL + PCTWC \quad (6)$$

where

PCTENV	= 0.10	Home, office, contractor fee
PCTCNTG	= 0.05	Contractor & owner contingency
PCTLND	= 0.00	Land (assuming expansion only at existing refinery)
PCTSPECL	= 0.05	Prepaid royalties, license, start-up costs
PCTWC	= 0.10	Working capital
thus, OTCFAC = 0.30		

and

$$ROTC_j = OTCFAC * RFDC_j \quad (\text{MM 87\$}) \quad (7)$$

The TPI given above represents the total project cost for “overnight construction.”. The TPI at project completion and startup will be discussed in Step 4 below.

Closely related to the total project investment are the fixed capital investment (FCI) and total depreciable investment (TDI). The fixed capital investment is equal to the total project investment less working capital. It is used to estimate capital-related fixed operating costs (discussed later). A default value of 0.10 is assumed for the WC factor:

$$WRKCAP = PCTWC * RFDC_j \quad (\text{MM 87\$}) \quad (8)$$

thus,

$$RFCI_j = RTPI_j - WRKCAP \quad (\text{MM 87\$}) \quad (9)$$

The total depreciable investment is equal to the total project investment less the cost of land, interest during construction and working capital (as discussed in Step 4 below). For construction at an existing refinery site through expansion, as most likely the case in the United States, the cost of land can be assumed to be zero, and interests during construction are considered implicitly in the calculation of the capital charge factor (Step 4); thus, total depreciable investment is assumed to be approximately equal to fixed capital investment:

$$RTDI_j = RFCI_j \quad (\text{MM } 87\$) \quad (10)$$

#### ***Step 4 - Estimation of Capital-Related Financial Charges***

For the purpose of determining the economic viability of expanding refinery processing capacity, capital-related financial charges (CFC), which consist of an annual capital recovery charge (ACR) and a depreciation tax credit (DTC), must be estimated from the total project investment (TPI). The ACR is based on the cost of capital (COC) for the corporation that owns the refinery where the project is located. It is assumed that projects will be financed by both debt and equity and will return the expected interest payments to creditors and the expected dividends to shareholders. Therefore, the after-tax weighted average cost of capital is an appropriate discount rate for evaluating investment opportunities.

##### a) Cost of Capital

The cost of capital (COC) is the weighted average of the cost of equity (COE) and cost of debt (COD). The COE represents an implied opportunity of financial return to the corporation's stockholders in the form of dividend payments and stock price appreciation. The COD is the after-tax interest rate which a company would pay for new, long-term borrowing. In general, the required rate of return for equity investors is much higher than the required rate of return for debt investors (creditors) since the holder of common stock (equity investors) accepts all the risks involved in business ownership. The COC is related to COE and COD as follows:

$$COC = x_{eq} \times COE + x_{debt} \times COD(at) \quad (11)$$

and,

$$COD(at) = (1 - T_{eff,l}) \times COD(bt) \quad (12)$$

where

$x_{eq}$ ,  $x_{debt}$  = Fractions of equity and debt financing, respectively ( $x_{debt} = 1 - x_{eq}$ )  
 $T_{eff,l}$  = Effective corporate income tax rate; "l" is for refining region index where all state taxes in that region are averaged to represent a single value.  
at, bt = Indices for after- and before-taxes, respectively

Based on a review of annual financial reports of refining companies or their parent companies, the relative fraction of equity and debt used in the model is set to the capacity-weighted average determined for 2002 ( $x_{eq} = 0.60$  and  $x_{debt} = 0.40$ ). Also,  $T_{eff}$  is related to the federal tax rate  $T_{fed}$  (FTAXRAT in the PMM) and state tax rate  $T_{state}$  (STAXRAT in the PMM, which is location dependent) as follows:

$$\begin{aligned}
T_{eff,l} &= T_{state,l} + T_{fed} \times (1 - T_{state,l}) \\
&= T_{fed} + T_{state,l} - T_{fed} \times T_{state,l}
\end{aligned}
\tag{13}$$

Average state and federal income tax rates were developed on a PADD basis using the most recent tax information available as of Jan. 1, 2004<sup>8</sup>. PADD averages were weighted based on the crude oil processing capacity within the states making up each PADD. The resulting state and federal tax rates used in the model are:

**Table F2. State and Federal Corporate Income Tax Rates**

<b>Location</b>	<b>State</b>	<b>Federal</b>
PADD I – U.S. East coast	9.32%	35%
PADD II – U.S. Midwest	7.38%	35%
PADD III – U.S. Gulf Coast	3.32%	35%
PADD IV – U.S. Rocky Mountain	4.21%	35%
PADD V – U.S. West Coast	6.76%	35%

The pre-tax cost of debt (COD(bt)) will vary based on the proportions of short-term loans and bonds. A Baa average corporate bond rate (MC\_RMCORPBAA from the NEMS Macroeconomic Activity Model) is used for COD(bt).

The expected opportunity cost, or cost of equity (COE), for stockholders should be comparable to what could be realized from alternative investments of similar risk. The Capital Asset Pricing Model (CAPM) is used to compute a cost of equity<sup>9</sup>, which is an implied investor’s opportunity cost or the required rate of return of any risky investment. The model is:

$$COE = RFR + \beta \times EMRP
\tag{14}$$

The model requires three variables be specified: RFR, a “risk-free” rate; EMRP, an expected market risk premium; and  $\beta$ , a systematic risk coefficient relative to the stock market (referred to as the “equity beta”). In the model, the risk-free rate is based on 10-year Treasury note rates (MC\_RMTCM10Y, provided by the NEMS Macroeconomic Activity Model). The EMRP and  $\beta$  (BEQ, in model) are assumed to be constant. Thus, the EMRP is assumed at 7 percent based on the expected return on market over the rate of a 10-year Treasury note (risk-free rate); and, the  $\beta$  is set based on the risk level of the processing unit investment (for average risk,  $\beta = 1.0$ ; for high risk,  $\beta = 1.25$ ).

<sup>8</sup> State Corporate Income Tax Rates, available on the web at: [www.taxfoundation.org/corporateincometaxrates.html](http://www.taxfoundation.org/corporateincometaxrates.html), and at [www.taxadmin.org/fta/rate/corp\\_inc.html](http://www.taxadmin.org/fta/rate/corp_inc.html).

<sup>9</sup> The **capital asset pricing model** (CAPM) was introduced by Treynor (1961), Sharpe (1964) and Lintner (1965). It extended portfolio theory to introduce the notions of systematic and specific risk. More description of the model can be found at: [http://www.riskglossary.com/articles/capital\\_asset\\_pricing\\_model.htm](http://www.riskglossary.com/articles/capital_asset_pricing_model.htm)

b) Annual Capital Recovery

The annual capital recovery (ACR) is the difference between the total project investment (TPI) and the recoverable investment (RCI), all in terms of present value (e.g., at startup). The TPI estimated in Step 3 is for overnight construction (ONC). In reality, the TPI is spread out through the construction period. Land costs (LC) will occur as a lump-sum payment at the beginning of the project, construction expenses (TPI – WC – LC = FCI - LC) will be distributed during construction, and working capital (WC) expenses will occur as a lump-sum payment at startup. Thus, the TPI at startup (present value) is determined by discounting the construction expenses (assumed as discrete annual disbursements) and adding working capital (WC):

$$TPI(startup) = F_v(COC, N_{con}) \times LC + F_{v,n}(COC, N_{con}) \times (TPI(ONC) - LC - WC) + WC \quad (15)$$

where

$F_v =$  Future-value compounding factor for an instantaneous payment made n years before the startup year

$F_{v,n} =$  Future-value compounding factor for discrete uniform payments made at the beginning of each year starting n years before the startup year.

The future-value factors are a function of the number of compounding periods (n), and the interest rate (r) assumed for compounding. In this case, (n) equals the construction time in years before startup ( $N_{con}$  years), and the compounding rate used is the cost of capital (COC). The formulae for computing each of the discrete compounding factors are:

$$F_v(COC, N_{con}) = (1 + COC)^{N_{con}} \quad (16)$$

$$F_{v,n}(COC, N_{con}) = \left( \sum_{k=1, N_{con}} (1 + COC)^{k} \right) / N_{con} \quad (17)$$

The recoverable investment (RCI) includes the value of the land and the working capital (assumed not to depreciate over the life of the project), as well as the salvage value (SV) of the used equipment:

$$RCI = LC + WC + SV \quad (\text{MM87\$}) \quad (18)$$

The present value of RCI is subtracted from the TPI at startup to determine the present value of the project investment (PVI):

$$PVI(startup) = TPI(startup) - P_v(COC, N_{asset}) \times RCI \quad (\text{MM87\$}) \quad (19)$$

Where

$P_v =$  Present-value discounting factor for an instantaneous payment made n years (project life) in the future. The present-value factor is a function of the number of discounting periods (n), and the interest rate (r) used for discounting. In this case, (n) equals the asset's economic life in years  $N_{asset}$ , and the discounting rate is the

cost of capital COC:

$$P_v(COC, N_{asset}) = 1. / ((1. + COC)^{**} N_{asset}) \quad (\text{MM87\$}) \quad (20)$$

If the cost of land is assumed to be zero, and the salvage value is equal to dismantling costs, then the PVI(startup) can be reduced to:

$$PVI(startup) = F_{v,n}(COC, N_{con}) \times FCI + (1 - P_v(COC, N_{asset}) \times WC) \quad (21)$$

Thus, the annual capital recovery (ACR) is given by:

$$ACR(at) = A_v(COC, N_{asset}) \times PVI(startup) \quad (\text{MM87\$/yr}) \quad (22)$$

where

$A_v$  = uniform-value leveling factor for a periodic payment (annuity) made at the end of each year for (n) years in the future, and (at) signifies that the required annual capital recovery is on an after-tax basis. The uniform-value factor is a function of the number of periods (n), and the interest rate (r), where (n) equals the asset's economic life in years  $N_{asset}$ , and the discounting rate is the cost of capital COC, as defined by:

$$A_v(COC, N_{asset}) = (COC * ((1. + COC)^{**} N_{asset})) / (((1. + COC)^{**} N_{asset}) - 1.) \quad (23)$$

A construction period of 2 years and asset life of 15 years are assumed for construction of a new plant within an existing refinery.

### c) Depreciation Tax Credit & Capital-Related Financial Charges

The depreciation tax credit (DTC) is based on the depreciation schedule for the investment and the total depreciable investment (TDI). The simplest method used for depreciation calculations (and used in the PMM) is the straight-line method, where the total depreciable investment is depreciated by a uniform annual amount over the tax life of the investment. Generic equations representing the present value and the levelized value of the annual depreciation charge are:

$$PVD_{DPM}(startup) = P_{v,DPM}(COC, N_{tax}) \times TDI \quad (\text{MM87\$}) \quad (24)$$

$$DTC(at) = A_v(COC, N_{asset}) \times T_{eff} \times PVD_{DPM}(startup) \quad (\text{MM87\$/yr}) \quad (25)$$

where

$P_{v,DPM}$  = Present-value discounting factor for depreciation, which is a function of the number of discounting periods (n), and the interest rate (r)

$A_v$  = is the uniform-value leveling factor

$T_{eff}$  = Effective combined income tax rate

at = Signifies the depreciation tax credit on an after-tax basis.

In this case, (n) equals the tax life in years  $N_{tax}$ , and (r) equals the cost of capital COC. The subscript DPM signifies the depreciation method used (i.e., straight-line method). If the tax life  $N_{tax}$  is assumed to be equal to the asset life  $N_{asset}$ , then the leveled depreciation tax credit (DTC) can be represented as follows:

$$DTC(at) = T_{eff} \times TDI / N_{asset} \quad (\text{MM87\$/yr, DPM} = \text{SRL, } N_{tax} = N_{asset}) \quad (26)$$

Finally, the capital-related financial charges (CFC) are set equal to the ACR less the DTC, after taxes (at) and before taxes (bt):

$$CFC(at) = ACR(at) - DTC(at) \quad (\text{MM87\$/yr}) \quad (27)$$

and,

$$CFC(bt) = CFC(at) / (1 - T_{eff}) \quad (\text{MM87\$/yr}) \quad (28)$$

### ***Step 5 - Convert Fixed Operating Costs to a “per-day,” “per-capacity” Basis***

The annualized capital-related financial charge is converted to a daily charge, and then converted to a “per-capacity” basis by dividing the result by the operating capacity of the unit being evaluated. The result is a fixed operation cost on a per-barrel basis. It is the before-tax CFC that is included in the process plant cost function (PCF) presented in equation (1) above.

## **Refinery Unit Fixed Operating Costs**

Fixed operating costs (FOC), a component of total product cost, are costs incurred at the plant that do not vary with plant throughput, and any other costs which cannot be controlled at the plant level. These include such items as wages, salaries and benefits; the cost of maintenance, supplies and repairs; laboratory charges; insurance, property taxes and rent; and other refinery overhead. These components can be factored from either the operating labor requirement or the capital cost. The accuracy of this type of estimate should be within  $\pm 50$  percent.

Like capital cost estimations, operating cost estimations, involve a number of distinct steps. Some of the steps associated with the FOC estimate are conducted exogenous to NEMS (Step 0 below), either by the analyst in preparing the input data or during input data preprocessing. The individual steps in the plant fixed operating cost estimation algorithm are:

- 0) Estimation of the annual cost of direct operating labor
- 1) Year-dollar and location adjustment for operating labor costs (OLC)
- 2) Estimation of total labor-related operating costs (LRC)
- 3) Estimation of capital-related operating costs (CRC)
- 4) Convert fixed operating costs to a “per-barrel” basis

Step 0 involves several adjustments which must be made prior to input into the PMM; steps 1-4 are performed within the PMM.

### ***Step 0 – Estimation of Direct Labor Costs***

Direct labor costs are reported based on a given processing unit size. The operating labor cost data for most of the processing unit types modeled in the PMM were initially obtained from a study by Bonner and Moore Associates (BMA), and updated annually with revised estimates from EnSys. The actual data were obtained from the World Oil Refining, Logistics, and Distribution (WORLD) model.<sup>10</sup> The data used by the PMM currently represent process plants sited at a generic U.S. Gulf Coast (PADD III) location, and are in year 2000 dollars.

### ***Step 1 – Year-Dollar and Location Adjustment for Operating Labor Costs***

Before the PMM can utilize the labor cost data, it must convert the raw information via the following steps:

- a) Adjust the labor costs for each processing unit (j) from 2000 dollars, first to the year-dollar (rptyr) reported by NEMS for *AEO2005*, which is in 2003 dollars, using the Nelson-Farrar refining-industry cost-inflation indices. Then the GDP chain-type price indices provided by the NEMS Macroeconomic Activity Model are used to convert from report-year dollars to 1987 year dollars used internally by the NEMS.
- b) Convert the 1987 operating labor costs for each processing unit (j) from a PADD III (Gulf Coast) basis into regional (other U.S. PADDs) costs using regional (l) location factors. The location multiplier (LABORLOC) represents differences in labor costs between the various locations and includes adjustments for construction labor productivity.

$$RLABOR_{j,i} = BM\_LABOR_j * LABORLOC_i \quad (87\$/calendar \text{ day}) \quad (29)$$

Location multipliers for refinery operating labor were developed on a PADD basis using the most recent data available from the U.S. Bureau of Labor Statistics (BLS)<sup>11</sup> and the EIA.<sup>12</sup> The recommended location multipliers for refinery construction are given below:

---

<sup>10</sup>EnSys Energy & Systems, Inc., *WORLD Reference Manual*, a reference for use by the analyst and management prepared for the United States Department of Energy, Contract No. DE-AC-01-87FE-61299 (Washington, D.C., September 1992).

<sup>11</sup> Wages Data, U.S. Department of Labor, Bureau of Labor Statistics, available on the web at [www.bls.gov/bls/blswage.htm](http://www.bls.gov/bls/blswage.htm).

<sup>12</sup> Refinery Capacity Data, U.S. Department of Energy, Energy Information Administration, available on the web at [www.eia.doe.gov/oil\\_gas/petroleum/data\\_publications/refinery\\_capacity\\_data/refcapacity.html](http://www.eia.doe.gov/oil_gas/petroleum/data_publications/refinery_capacity_data/refcapacity.html).

**Table F3. Location Multipliers for Refinery Operating Labor**

<u>Location</u>	<u>Operating Labor Multiplier</u>
PADD I – U.S. East coast	1.11
PADD II – U.S. Midwest	0.98
PADD III – U.S. Gulf Coast	1.00
PADD IV – U.S. Rocky Mountain	1.07
PADD V – U.S. West Coast	1.06

***Step 2 - Estimation of Labor-Related Fixed Operating Costs***

Fixed operating costs related to the cost of labor include the salaries and wages of supervisory and other staffing at the refinery, charges for laboratory services, and payroll benefits and other plant overhead. These labor-related fixed operating costs (LRC) can be factored from the direct operating labor cost (OLC). This relationship is expressed by:

$$LRC = M_{LRC} * OLC \quad (\text{M87\$/yr}) \quad (30)$$

where

$M_{LRC}$  = Sum of LRC cost multipliers relating the LRC to the cost of direct operating labor cost. A default value of 2.15 is assumed for the direct labor, with two additional multipliers for supervisory/staff salaries and other/overhead costs at 0.55 and 0.39, respectively. Thus, fixed operating costs (FXOC\_LABOR) related to the cost of labor is thus the following:

$$\begin{aligned} LRC &= (2.15 + 0.55 + 0.39) * OLC \\ &= 2.99 * OLC \end{aligned} \quad (\text{M87\$/yr}) \quad (31)$$

***Step 3 - Estimation of Capital-Related Fixed Operating Costs***

Capital-related fixed operating costs (CRC) include insurance, local taxes, maintenance, supplies, non-labor related plant overhead, and environmental operating costs. These costs can be factored from the fixed capital investment (FCI). This relationship is expressed by:

$$CRC = M_{CRC} * FCI \quad (\text{MM87\$/yr}) \quad (32)$$

where

$M_{CRC}$  = Sum of CRC cost multipliers.

The multipliers used in the PMM are defined in the table below:

**Table F4. Capital-Related Fixed Operating Cost Multipliers**

Yearly Insurance	0.005
Local Tax Rate	0.01
Yearly Maintenance	0.03
Yearly Supplies, Overhead, Etc.	0.005

***Step 4 - Convert Fixed Operating Costs to a “per-capacity” Basis***

On a “per-capacity” basis, the FOC is the sum of capital-related operating costs and labor-related operating costs, divided by the operating capacity of the unit being evaluated

## F.2 Gas Plant Models

The gas plant models for each PADD are recorded on a spreadsheet maintained within EIA by the Oil and Gas Division. These models require gas plant wet gas volumes as input. In order to accommodate the information available and permit gas plant activity to be driven by dry natural gas demand, factors are applied to dry gas production volumes to calculate imputed volumes of processed wet gas. In PADD V, the PMM uses California gas processing plants as a proxy for PADD V. Although Alaska produces and processes a considerable volume of natural gas, it is nearly all re-injected with some NGL dumped into the crude pipeline with the exception of modest volumes of southern Alaska production. The southern Alaska production has a local NGL market with much of the dry gas shipped to Japan as LNG. In any case, the PADD V refinery industry is virtually unaffected by Alaska NGL production and California serves as a proxy for the district. Thus, the PMM aggregate gas plant for PADD V includes California only.

Gas residue volumes are not available to the PMM but total dry gas volumes by PADD are. . For *AEO2005*, wet gas volumes arising from Coal Bed Methane (CBM) and shale gas are excluded from the wet gas estimate calculation since these gas types contain little or no liquids content and there is no economic incentive to process them in a gas plant. This information is contained in the NEMS common block region. Specifically, the total dry gas volumes are available in:

Common block:	NGTDMOUT
Variable matrix:	PRNG_PADD(PADD, YEAR), BCF
Description:	Total dry gas produced including plant fuel and lease fuel (P&L) for PADD 'PADD' in year 'YEAR' excluding Alaska.

Each dry gas PADD volume is multiplied by a factor to obtain an estimate of the corresponding wet gas that is processed by the gas plants; i.e. the total dry gas volumes are multiplied by the ratio of processed wet gas to total dry gas production. The conversion ratios are derived from the average of the most recent five years of data<sup>13</sup> with the analysis maintained offline. The five factors (Table GASCAP) are contained in file nrfplant.dat as shown in Table F5.

---

<sup>13</sup>Energy Information Administration, *Natural Gas Annual* for years 1992-2002, DOE/EIA,

**Table F5. Total Dry Gas Multiplier**

<b><u>PADD</u></b>	<b><u>Factor</u></b>
I	0.3343
II	0.6807
III	0.7397
IV	0.7708
V (CA)	0.7209

The multiplier for PADD I is relatively low because little of the modest PADD I gas production is processed for liquids extraction beyond field decontamination.

The NGL extraction is allowed to occur at an average level. Complete ethane rejection is allowed with a processing credit for each barrel rejected. Propane rejection occurs in U.S. gas plants but to an unknown extent. The model allows propane rejection up to one fourth of the propane volume. The basic model structure was originally devised from the Pace Consultants annual petrochemical report<sup>14</sup> and has been modified over the years as gas markets have evolved.

Liquids extraction data have been calculated by averaging actual liquid extraction volumes from the 5-year period 1998 - 2002<sup>15</sup>. The data are contained in Table GASPLT in file nrfplant as shown in Table F6 for illustrative purposes.

**Table F6. Gas Plant Model Liquid Component Yields  
(M Bbls per MMcf)**

	<b>PADD I</b>	<b>PADD II</b>	<b>PADD III</b>	<b>PADD IV</b>	<b>PADD V</b>
<b>Ethane</b>	23.40	20.77	18.12	20.80	.19
<b>Propane</b>	32.61	20.38	13.01	17.22	14.59
<b>Iso Butane</b>	4.06	3.89	5.25	3.45	6.10
<b>Normal Butane</b>	11.50	6.62	2.85	6.71	7.15
<b>Natural Gasoline</b>	9.33	8.02	7.12	8.99	14.20

---

<sup>14</sup>Pace Petrochemical Service, *Annual Issue*, (Houston, TX, September 1989).

<sup>15</sup>Energy Information Administration, *Petroleum Supply Annual 1992-2002*, DOE/EIA, and similarly, the *Natural Gas Annual* for years 1992-2002.

Propane rejection is controlled via column limit in the LP rather than as a row limit and the operating costs are merely entered into the objective function row rather than occupying two rows as the above depiction suggests. Of course these things are shown in the above form for the sake of clarity. The major difference is that the wet gas balance row is an equal zero row in the LP representation. There is a column representing pseudo purchases of wet gas with a plus one in the wet gas balance row and minus the forecasted gas price in the objective function row. Of course, this column is fixed at the determined level of processed wet gas.

### F.3 Chemical Industry Demand for Methanol

The PMM incorporates methanol plant models in each PADD representing all U.S. operating methanol capacity. Given the diverse and competing uses for methanol in both the refining and petrochemical industries, U.S. chemical industry demand (demand other than for MTBE/TAME feedstock and neat fuel) is a required input to gauge market supply pressures. The chemical industry demand requirement (Tables DEMMET and PRDDMDME) is entered in files demand.dat and qdcrdcf.txt, respectively. Chemical Market Associates, Inc. (CMAI) makes long range forecasts of demand for methanol <sup>16</sup> by the chemical industry. This forecast is outlined in Table F7.

**Table F7. Chemical Industry Demand for Methanol**

<u>Year</u>	<u>Demand (Mbbbl/d)</u>	<u>Year</u>	<u>Demand (Mbbbl/d)</u>
1990	77.7	2008	131.2
1991	73.1	2009	134.4
1992	80.0	2010	137.3
1993	83.9	2011	140.7
1994	87.7	2012	143.7
1995	90.2	2013	146.3
1996	94.6	2014	149.1
1997	100.2	2015	151.9
1998	108.8	2016	155.7
1999	111.0	2017	158.9
2000	118.3	2018	162.4
2001	110.6	2019	165.7
2002	112.7	2020	169.4
2003	114.1	2021	173.0
2004	117.3	2022	176.9
2005	120.8	2023	180.7
2006	124.1	2024	184.9
2007	127.7	2025	189.0

<sup>16</sup>CMAI, (Houston, TX), United States Methanol Chemicals Demand, (January 2004).

The methanol plant model in each PADD is represented by a single column activity that consumes natural gas and produces methanol. Two additional transportation activities allow the methanol produced to be transported to the refining region for production of MTBE/TAME and/or splash blending in gasoline or sent to meet the national demand for methanol by chemical plants. Given the mounting phase-out of MTBE as a gasoline blending component, methanol is becoming a less-sensitive refinery driver component within the PMM modeling structure.

Methanol plant capacity (Table MOHCAP) is updated periodically for the five PADDs in file nrfplant.dat using *Chemical Market Reporter* and other industry trade references for establishing current operating capacity. The model allows capacity expansion of methanol plants if ever needed. However, from a practical standpoint, an abundance of mothballed plants would likely be reopened rather than implementing new construction since nearly half U.S. methanol production capacity has been closed down since the late 1990s.

## F.4 Estimation of Distribution Costs

Costs related to distributing petroleum products to end-users are incorporated by adding fixed transportation markups to the wholesale prices which include the variable and fixed refinery costs. Transportation markups for petroleum products except gasoline are estimated as the average annual difference between retail and wholesale prices. Due to an observable market shift before and after 1990 (due to the CAAA of 1990), the transportation markups for all products except gasoline are estimated based on data between 1990 and 2001. Due to the requirement for oxygenated gasoline beginning in October of 1992, gasoline markups are estimated with data beginning in 1993. The differences are based on wholesale prices in the producing Census division and end-use prices (which do not include taxes) in the consuming Census division. Wholesale prices are aggregated from State-level prices from the EIA-782A. Sectoral end-user prices are aggregated from State-level prices from the [State Energy Data 2000: Prices \(SEDP\)](#) Report. End-use prices after 2000 are estimated according to the SEPER's methodology. Computer programs and data files used to estimate transportation markups are discussed below.

### Data-Reading Programs

**Database:** SEDS\_SEPERS.mdb

Input Files : pr\_pet\_all\_price.csv  
use\_pet\_all\_btu.csv

This database reads State-level prices by sector from SEPER data query provided by EIA’s Julia Hutchins of Office of Energy Markets and End-Use (EMEUE). To import new data use the Access import utility with the Specification SEDS BTU Data Import Specification for the Volume file and SEPER Price Import Specification for the Price file. These files include the following data series from 1960-2001:

ARICB	ARICD	ARICV	AVACB	AVACD
AVACV	DFACB	DFACD	DFACV	DFCCB
DFCCD	DFCCV	DFEUB	DFEUD	DFEUV
DFICD	DFICV	DFISB	DFRCB	DFRCD
DFRCV	FNICB	FNICD	FNICV	FOICB
FOICD	FOICV	FSICB	FSICD	FSICV
JFACB	JFACD	JFACV	JFEUB	JFEUD
JFEUV	KSCCB	KSCCD	KSCCD	KSICB
KSICD	KSICV	KSRCB	KSRCD	KSRCV
LGACB	LGACD	LGACV	LGCCB	LGCCD
LGCCV	LGICD	LGICV	LGISB	LGRCB
LGRCD	LGRCV	LUACB	LUACD	LUACV
LUICB	LUICD	LUICV	MGACB	MGACD
MGACV	MGCCB	MGCCD	MGCCV	MGICB
MGICD	MGICV	MSICB	MSICD	MSICV
PCEUB	PCEUD	PCEUV	PCICD	PCICV
PCISB	RFACB	RFACD	RFACV	RFCCB
RFCCD	RFCCV	RFEUB	RFEUD	RFEUV
RFICD	RFICV	RFISB	SNICB	SNICD
SNICV	WXICB	WXICD	WXICV	

The Five letter code corresponds to the following information.

<b>Data Identification Codes</b>	
<b>Characters</b>	<b>Identity</b>
<a href="#">1 and 2</a>	represent an Energy Source (Fuel)
<a href="#">3 and 4</a>	represent an Energy Consumption End-Use Sector (Sector)
<a href="#">5</a>	represents a Type of Data (Type)

<b>Energy Source (Characters 1 and 2)</b>	
<b>Code</b>	<b>Name</b>
AR	asphalt and road oil
AV	aviation gasoline
DF	distillate fuel
FN	petrochemical feedstocks naphtha less than 401 degrees F.
FO	petrochemical feedstocks other oils equal to or greater than 401 degrees F.
JF	jet fuel
KS	kerosene
LG	liquefied petroleum gases
LU	lubricants
MG	motor gasoline
MS	miscellaneous petroleum products
PC	petroleum coke
RF	residual fuel
WX	waxes

<b>Energy End-Use Sectors (Characters 3 and 4)</b>	
<b>Code</b>	<b>Name</b>
AC	transportation sector estimates
CC	commercial sector estimates
EI	electric power sector estimates
EU	electric utility sector estimates
IC	industrial sector estimates
RC	residential sector estimates
TC	total energy sector estimates

<b>Type of Data (Character 5)</b>	
<b>Code</b>	<b>Name</b>
B	consumption in Btu. Data are in billion Btu
D	current price per Btu. Data are in dollars per million Btu
P	consumption in various physical units
V	expenditures in current dollars. Data are in millions of dollars

The following other tables should be updated as well: BTU to Barrels (conversion factors), GDP87 (Macroeconomic inflators)

This database compiles state and sector level Retail prices to provide Census District retail prices by sector

### **Markup Estimating Program**

The database New Markups.mdb is used to compute the differences in wholesale product prices and retail product prices. For year 2001 prices detailed markups are created for all products by sector by comparing the retail prices computed in SEDS\_SEPERS.mdb to the wholesale rack prices published in the Petroleum Marketing Annual. For years 2001 to 2003; Transportation fuels, Heating Oil, and Propane markups are updated by calculating by difference between End-use and “Sales for resale” prices reported in the *Petroleum Marketing Annual, 2003*.

## **F.5 Estimation of Taxes**

In the PMM, taxes are added to the prices of gasoline, transportation distillate fuel (diesel), transportation liquefied petroleum gases (LPG), and jet fuel. Taxes are also estimated for E85 (transportation ethanol) and a placeholder is used for M85 (transportation methanol) because M85 prices are no longer projected by PMM. Weighted averages of the most recently available State and Federal taxes are developed for each Census Division (CD) using periodic State survey data collected by the Defense Energy Support Center (DESC)<sup>17</sup>. The DESC data is then aggregated to the CD level in an analyst’s spreadsheet using State annual product volumes obtained from the Petroleum Marketing Annual to calculate a volume-weighted CD average. The spreadsheets utilized for each product are as follows:

Gasoline- gasoline tax CD volumes.xls  
Diesel- diesel tax CD volumes.xls  
Jet- jet tax CD volumes.xls

. The State taxes are fixed in real terms; the Federal taxes decline at the rate of inflation (i.e., Federal taxes are fixed in nominal terms). An additional 2 percent of the retail product CD value is added to the gasoline and diesel taxes to approximate local taxes. Historical values are also calculated for gasoline, transportation distillate, jet fuel and LPG, which are then added to historical end-use prices excluding taxes in order to develop a series with taxes included. The CD taxes, including both historical and projected series by sector, product, and year, are contained in following file, which resides in the default input directory:

### **MU2PRDS**

The Federal taxes are read into the PMM from file:

### **QDCRDCF**

---

<sup>17</sup> Defense Energy Support Center, “Compilation of United States Fuel Taxes, Inspection Fees and Environmental Taxes and Fees,” August 9, 2004, Edition: 2004-14.

and are updated each forecast year by deflating the current value by the rate of inflation for that forecast year.

The following section traces the development of the taxes and lists the files used to produce both historical and forecast values. The historical data are developed on a monthly basis by State, and then aggregated to volume-weighted annual averages by Census division. The outputs specified are members of the following MSAccess database unless otherwise stated:

### **SEDS\_SEPERS.MDB**

**Tables:** Taxes-MG & Taxes- Diesel

**Inputs:** Tax information from the Defense Energy Support Center

**Sources:** Gasoline/Diesel “Compilation of United States Fuel Taxes, Inspection Fees and Environmental Taxes and Fees,” August 9, 2004, Edition: 2004-14.

**Table:** Taxes- LPG & Jet

**Inputs:** State-level LPG & Jet collected once each year

**Sources:** Jet fuel “Compilation of United States Fuel Taxes, Inspection Fees and Environmental Taxes and Fees,” August 9, 2004, Edition: 2004-14.  
LPG Federal Highway Administration, Table MF-121T

After compilation each product was then arranged for placement into MU2PRDS.txt. Data for forecast years was then copied from the latest tax information into the future thus preserving the real value of the state taxes as described above.

## **F.6 Gasoline Specifications**

The PMM models the production and distribution of four different types of gasoline: conventional, oxygenated, reformulated, and CARB gasoline. The following specifications are included in PMM to differentiate between conventional and reformulated gasoline blends: octane, oxygen content, Reid vapor pressure (RVP), benzene content, aromatic content, sulfur content, olefin content, and the percent evaporated at 200 and 300 degrees Fahrenheit (E200 and E300).

The sulfur specification for gasoline is reduced to reflect recent regulations requiring the average annual sulfur content of all gasoline used in the United States to be phased-down to 30 ppm between the years 2004 and 2007. PMM assumes that RFG has an average annual sulfur content of 135 ppm in 2000 and will meet the 30 ppm requirement in 2004. The reduction in sulfur content between now and 2004 is assumed to reflect incentives for “early reduction.” The regional assumptions for phasing-down the sulfur in conventional gasoline account for less stringent sulfur requirements for small refineries and refineries in the Rocky Mountain region. The 30 ppm annual average standard is not fully realized in conventional gasoline until 2008 due to allowances for small refineries.

Starting in 1998 the specifications for conventional gasoline reflect the Environmental Protection Agency's (EPA) "1990 baseline." These specifications prevent the quality of conventional gasoline from eroding over time, which is the intent of the EPA's "antidumping" requirements.

Oxygenated gasoline, which has been required during winter in many U.S. cities since October of 1992, requires an oxygen content of 2.7 percent by weight. Oxygenated gasoline is assumed to have specifications identical to conventional gasoline with the exception of a higher oxygen requirement. Some areas that require oxygenated gasoline will also require reformulated gasoline. For the sake of simplicity, the areas of overlap are assumed to require gasoline meeting the reformulated specifications.

Reformulated gasoline has been required in many areas of the United States since January 1995. Beginning in 1998, the EPA has certified reformulated gasoline using the "Complex Model," which allows refiners to specify reformulated gasoline based on emissions reductions either from their companies' 1990 baseline or from the EPA's 1990 baseline. In 2000 the Complex Model was tightened to require further emissions reductions. The PMM has used a set of specifications that meet these “Phase 2” Complex Model requirements, but it does not attempt to determine the optimal specifications that meet the Complex Model. Actually, gasoline currently sold in the United States slightly exceeds the quality implied in the Complex Model 2 specifications (i.e., over-compliance). Thus, in addition to assuming Complex Model 2 compliance for the RFG, *AEO2004* also reflects the “over-compliance” nature of gasoline in general (including conventional gasoline) by adopting the EPA survey of RFG properties in 2002.<sup>18</sup>

The State of California currently uses its own set of performance based gasoline standards instead of the Federal Complex Model standards. The PMM assumes that all West Coast refiners must meet the current California Air Resources Board “CARB 2” requirements until 2003 when a new set of “CARB 3” requirements will take their place. The CARB 3 standards reflect the removal of the oxygen requirement designed to compliment the State’s plans to ban the oxygenate, methyl tertiary butyl ether (MTBE) by the end of 2003. The U.S. 9<sup>th</sup> Circuit Court of Appeals recently ruled that EPA must reconsider a request by

---

<sup>18</sup>. Information on Reformulated Gasoline (RFG) Properties and Emissions Performance by Area and Season, U.S. EPA Office of Transportation and Air Quality, <http://www.epa.gov/otaq/regs/fuels/rfg/proper/rfgperf.htm>

California to waive the Federal oxygen requirement in Federal non-attainment areas, including Los Angeles, San Diego, Sacramento, and San Joaquin Valley. Because those areas contain about 80 percent of California's population and EPA is appealing the Court's ruling, *AEO2004* assumes that 80 percent of RFG in the State will continue to require 2.0 percent oxygen by weight after MTBE is banned.

Other areas of California, do not have an oxygen requirement but use oxygenates because of their octane boosting, and volume extending properties. RFG in the areas with the Federal oxygen requirement is classified in the PMM as "RFG" while CARB gasoline in other areas is classified as "RFH." *AEO2004* reflects legislation which bans or limits the use of MTBE in 17 States: California, Colorado, Connecticut, Illinois, Indiana, Iowa, Kansas, Kentucky, Michigan, Minnesota, Missouri, Nebraska, New York, Ohio, South Dakota, Washington, and Wisconsin.<sup>19</sup> Since the oxygen requirement on RFG is assumed to continue in these States, the MTBE ban is modeled as a requirement to produce ethanol blended gasoline in the CHGDMDS subroutine.

Arizona also has a reformulated gasoline program for the Phoenix area which is mandated by State law. Phoenix had previously been part of the Federal RFG program but opted out when State requirements were adopted. Phoenix is required to use CARB in the winter but may use either CARB or Federal RFG in the summer. Arizona is in a different model region than California and, for the sake of simplicity, is assumed to use RFG meeting Federal specifications.

## Annual Average RVP Methodology

The annual average RVP limits are derived based on the latest EPA survey of summertime gasoline and estimated wintertime levels.<sup>20</sup> The assumed summer and winter RVP specifications had been annualized by simple averaging using summer and winter weights provided by the EPA.<sup>21</sup> The RVP specifications used in the PMM are shown in Table F8. The lower RVP specifications in PADD V reflect more stringent California limits that are imposed statewide.

---

<sup>19</sup>Maine has passed legislation that provides a "goal" of phasing-out MTBE. Since the legislation is not binding, Maine is not included in *AEO2004* assumptions.

<sup>20</sup> *Information on Reformulated Gasoline (RFG) Properties and Emissions Performance by Area and Season*, U.S. EPA Office of Transportation and Air Quality, <http://www.epa.gov/otag/regs/fuels/rfg/properf/rfgperf.htm>

<sup>21</sup>The summer weight of 0.396 and winter weight of 0.604 were provided by Dave Korrotney of EPA (313-668-5507).

**Table F8. Estimated Annual Reid Vapor Pressure**

Gasoline Market/Type	Annual RVP in PMM				
	PADD I	PADD II	PADD III	PADD IV	PADD V
Conventional	9.6	10.2	9.9	10.8	9.2
Reformulated	8.5	9.5	8.6	8.6	7.9

## Complex Model Standards for Motor Gasoline

The U.S. EPA has promulgated regulations for reformulated motor gasoline that are designed to lower vehicle emission pollutants as required by the amended Clean Air Act of 1990.<sup>22</sup> The reformulated gasolines are designed to reduce vehicle emissions of toxic and ozone-forming compounds. Reformulated gasoline must be sold in certain regions where there are severe ozone problems as well as in areas with less severe ozone problems which opt into the program. Conventional gasoline may be sold elsewhere but it must not be more polluting than it was in 1990. These areas are discussed elsewhere in the documentation.

Although the EPA has established some conventionally treated specifications, namely minimum oxygen content and maximum benzene content, the conceptual aspect of the emission standards is that the reformulated gasoline must be blended in such a way that it meets maximum allowable emissions of volatile organic compounds (VOCs), nitrous oxides (NO<sub>x</sub>), and toxics. These motor gasoline standards are calculated by complex formulae based upon key properties of the gasoline blend. The regulations cover Phase I (1 January 1995 through 31 December 1999) and Phase II (1 January 2000 and afterwards). The model uses a set of specifications that meet or exceed emissions requirements for Phase II of the Complex Model. Also, the refiner may meet the requirements for VOCs and NO<sub>x</sub> on either a per gallon basis or on an average basis although some per gallon constraints still apply. The average basis has been incorporated into the model.

The NO<sub>x</sub> and toxics emission standards for reformulated gasoline apply year-round whereas the VOC standards apply only in the summer. The NO<sub>x</sub> standard varies depending upon whether the VOC standards apply, i.e. depending upon whether it is summer or winter. The VOC standard for the north<sup>23</sup> is different from the VOC standard applying to the south, greater volatility is allowed in the north. The Complex Model Averaged Standards are shown below in Table F9.

<sup>22</sup>Federal Register, Environmental Protection Agency, Regulation of Fuels and Fuel Additives; Standards for Reformulated and Conventional Gasoline; Final Rule, Part II, 40 CFR Part 80, (Washington, DC, 16 February 1994)

<sup>23</sup>For the sake of simplicity, we use the terms south and north to refer to EPA regions 1 and 2 respectively. Region 1 is covered by ASTM Class B while Region 2 is covered by Class C.

**Table F9. Complex Model Standards**

	<b>Phase I 1995 - 1999</b>	<b>Phase II 2000+</b>
VOC Reduction, %		
South	≥ 36.6	≥ 29.0
North	≥ 17.1	≥ 27.4
NO <sub>x</sub> Reduction, %		
Summer	≥ 1.5	≥ 6.8
Winter	≥ 1.5	≥ 1.5
Toxics Reduction, %	≥ 16.5	≥ 21.5
Oxygen, wt%	≥ 2.1	≥ 2.1
Benzene, %	≤ 0.95	≤ 0.95

**Source:** U. S. Environmental Protection Agency 40 CFR Part 80, *Regulation of Fuels and Fuel Additives: Modifications to Standards and Requirements for Reformulated and Conventional Gasoline.*

These standards were translated into conventionally configured specifications for blending motor gasoline. First, two winter specifications were developed, one for Phase I and one for Phase II. Of course, the VOC standard was excluded from consideration. Then four summer specifications were created, a south set and a north set for Phase I and similarly for Phase II. Specifications for Phase I were used in prior forecasts for years up to 1999. PMM currently uses only the Phase II specifications as 2005 is the initial forecast year. The sulfur specification is adjusted to reflect the regulations requiring the reduction of sulfur in gasoline. RFG is assumed to reach the target of 30 ppm sulfur by 2004.

These sets were developed by use of a spreadsheet, developed by EPA, which calculates the VOCs, NO<sub>x</sub>, and Toxics of a reformulated gasoline as a function of the 'conventional' properties of the gasoline, i.e. as a function of RVP, sulfur content, oxygen content, aromatics content, olefins content, benzene content, percent evaporation at 200 degrees Fahrenheit (E200), and percent evaporated at 300 degrees Fahrenheit (E300). The approach was to start with 'best informed guess' properties and use trial and error to gradually expand the allowable property limits. The blend properties cited as typical fuels in an EPA presentation<sup>24</sup>

<sup>24</sup>C.L. Gray, "Reformulated Gasoline Final Rulemaking and Renewable Oxygenate Proposal," Proceedings of The World

served as the starting values for both Phases I and II. The same starting point was used for both winter and summer. Table F11, following a chart developed by the EPA,<sup>25</sup> indicates the directional sensitivities of the properties on the standards. Of course, a more rigorous approach is possible in establishing the specification sets. For instance, one might perform incremental changes over the reformulated gasoline properties followed by computer runs to establish minimum cost specifications. However, this approach was not implemented due to resource constraints.

**Table F10. Directional Emission Effects of Gasoline Property Changes**

<b>Property</b>	<b>VOC</b>	<b>NO<sub>x</sub></b>	<b>Air Toxics</b>
RVP ↓	↓↓↓	,	↓
Sulfur ↓	↓	↓↓↓	↓↓
Aromatics ↓	↓	↓	↓↓
Olefins ↓	–	↓	–
E200 ↑	↓	↑	↓
E300 ↑	↓	–	,
Oxygen ↑	–	,	↓↓
Benzene ↓	,	–	↓↓↓

The PMM is an annual model, i.e. it does not have seasonality. A decision was made to develop, for PADDs I-IV, a single reformulated gasoline specification for Phase I simulation and a single specification for Phase II. This required several actions. The two summer sets for Phase I were linearly blended by combining the projected gasoline sales-weighted south specifications to the appropriately weighted specifications of the north. The resulting two sets of specifications for Phase I, one for summer and one for winter, were then combined after weighting them according to summer sales and winter sales respectively. The Phase II specifications were collapsed to a single set in the same manner. The composites were calculated in a spreadsheet maintained by the Oil and Gas Division. This specification was adapted from the presentation made by Charles L. Gray at the conference cited above. The resulting reformulated gasoline specifications are shown in Table F12. It is, of course, a simple matter to convert the PMM blending stock distillation temperature values as needed.

---

Conference on Refinery Processing and Reformulated Gasoline, March 22-24, 1994, Information Resources, Inc.

<sup>25</sup>Ibid.

**Table F11. PMM Reformulated Gasoline Specifications**

	<b>Phase I PADDs I-IV</b>	<b>Phase II PADDs I-IV</b>	<b>Phase II with Reduced Sulfur PADDs I-IV</b>
Max RVP, psia	8.7	8.6	8.6
Max S, ppm	305	108.75	30
Max Aro, %	25.0	25.0	25.0
Max Ole, %	12.0	12.0	12.0
Min E200, %	49.0	49.0	49.0
Min E300, %	87.0	87.0	87.0
Min Oxy, wt%	2.1	2.0	2.0
Max Ben, %	0.95	0.66	0.66

Data represent 2001 specifications to meet Complex Model standards. PMM adopted specifications in each forecast year based on the regulations in effect at the time. Therefore, in 2004 when the Tier 2 regulation kicks in, the maximum sulfur content is reduced to 30 ppm. The sulfur specification on the Complex Model is adjusted to meet Tier 2 gasoline requirements.

## F.7 Estimation of Gasoline Market Shares

Within the PMM, total gasoline demand is disaggregated into demand for conventional, oxygenated, reformulated and CARB gasolines by applying assumptions about the annual market shares for each type. Annual assumptions for each region account for the seasonal and city-by-city nature of the regulations. The market shares are assumed to remain constant at the actual 2003 level. Due to the on going litigation surrounding the addition of Baton Rouge, LA, and Atlanta, GA to the RFG program the gasoline shares for these metropolitan areas was not included in AEO2005.

In 2003, the Census Division 9 market share for RFG is separated into two different categories which represent CARB3 gasoline without an oxygen requirement (RFH) and CARB3 gasoline with the Federal oxygen requirement (RFG). This breakout into another product is needed to represent the planned MTBE ban in California in the absence of a waiver to the Federal RFG oxygen requirement. PMM assumes the Federal oxygen requirement remained intact in the four areas of California bound by the Federal requirement; Los Angeles, Sacramento, San Diego, and the recently added San Joaquin Valley. In effect, these areas must use ethanol to meet the oxygen requirement. The market shares assume that 60 percent of the gasoline in Census Division 9 will continue to meet the Federal 2.0 percent (by weight) oxygen requirement, and 15 percent will meet California specifications with no oxygen requirement.

Although the shares are assumed to remain constant after 2004, the PMM structure allows for them to change over time based on alternative assumptions about the market penetration of new fuels. This allows for flexibility to analyze the impact of differing market share assumptions and to adjust the assumptions over time based on updated information about announced participation in the oxygenated and reformulated gasoline programs.

### Limitation on MTBE Blended into Gasoline

MTBE is a gasoline blending component used primarily to meet the oxygen requirement of reformulated gasoline specified by the Clean Air Act Amendments of 1990. In the past few years, the use of MTBE has become a source of debate, because it has made its way from leaking pipelines and storage tanks into water supplies. Legislation to ban/limit the use of MTBE in California and 16 other States is modeled as a requirement to produce ethanol blended gasoline in the CHGDMDS subroutine. Ethanol blends are assumed to account for the following market percentages:

- 29.0 percent of RFG in Census Division 1
- 36.5 percent of RFG in Census Division 2
- 99.0 percent of RFG in Census Division 8
- 100.0 percent of RFG (with 2.0 percent oxygen requirement) in Census Division 9
- 100.0 percent of oxygenated gasoline in Census Division 4
- 100.0 percent of oxygenated gasoline in Census Division 8
- 100.0 percent of oxygenated gasoline in Census Division 9

Concerns for water quality have also prompted a number of congressional proposals that would ban MTBE and similar ethers in all States. The PMM can model future MTBE limits or bans in gasoline produced at the U.S. refineries. The MTBE limits are defined for conventional and reformulated gasolines (separately) on a national level, and can be activated in any forecast year. In the qdcrdcf.txt input file, the user can define the allowed volume percent of MTBE (combined with other undesirable ethers) for either or both conventional and reformulated gasolines, and the year the restrictions will go into effect. The constraints are defined mathematically below.

For reformulated gasoline (RFG):

$$\sum_{\text{ethers}} B(r)\text{RFG}(\text{ethers}) \leq \text{pct} * Q(r)\text{RFG} + \text{pct} * Q(r)\text{RFH} + \text{pct} * Q(r)\text{SSR}$$

and for conventional gasoline (TRG):

$$\sum_{\text{ethers}} B(r)\text{TRG}(\text{ethers}) \leq \text{pct} * Q(r)\text{TRG} + \text{pct} * Q(r)\text{TRH} + \text{pct} * Q(r)\text{SST} + \text{pct} * Q(r)\text{SSE}$$

where ethers include all or some of the following:

MTBE, ETBE, TAME, TAEE, THME, THEE (all oxygen-containing hydrocarbon compounds)

## F.8 Diesel Specifications

PMM models three types of distillate fuel oil: heating oil (N2H), low-sulfur diesel (DSL), and ultra-low-sulfur-diesel (DSU). Both types of the diesel fuel reflect specifications for sulfur, aromatics content, and API gravity. DSL reflects current highway diesel fuel requirements while DSU reflects the tighter “ultra-low-sulfur-diesel”(ULSD) requirement that will begin to be phased-in in 2006. ULSD also covers growing volumes of nonroad, locomotive and marine (NRLM) applications beginning after 2010. DSL in Census Divisions 1 through 8 is assumed to meet Federal specifications including a maximum sulfur content of 500 parts per million (ppm) and a maximum aromatic content of 35 percent by volume.<sup>26</sup> DSL in Census Division 9 is assumed to meet California Air Resources Board (CARB) standards that limit sulfur content to 500 ppm and aromatics to 10 percent by volume.<sup>27</sup>

According to the “ultra-low-sulfur diesel”(ULSD) regulation finalized in December 2000, ULSD is highway diesel that contains no more than 15 ppm sulfur at the pump. In PMM this new product is assumed to contain 7 ppm sulfur at the refinery gate, reflecting the general consensus that refiners will need to produce diesel with a sulfur content below 10 ppm to allow for contamination during the distribution process.

During mid-2004, the U. S. Environmental Protection Agency (EPA) finalized its new nonroad diesel rules which effectively parallel the highway standards but lag by several years in implementation. The specifications and timing of each quality type by refiner class are summarized below.

---

<sup>16</sup> Federal regulations require either a maximum 35 percent (volume) aromatics or a cetane index of 40.

<sup>17</sup><http://arbis.arb.ca.gov/diesel/diesregs.pdf>

## Final U.S. EPA Diesel Fuel Sulfur Limits

<u>Refiner Class</u>	6/1/2006	6/1/2007	6/1/2010	6/1/2012	6/1/2014 +
<i><u>HIGHWAY DIESEL</u></i>					
Non-“small” refineries	> 80% 15 ppm		15 ppm		
“Small” refineries (< 155,000 bbl/day; < 1,500 employees)	-		15 ppm		
<i><u>NONROAD AND LOCOMOTIVE/MARINE (NRLM) DIESEL</u></i>					
Non-“small” refineries nonroad (NR) diesel	-	500 ppm	15 ppm		
Non-“small” refineries locomotive/marine (LM) diesel	-	500 ppm		15 ppm	
“Small” refineries (< 155,000 bbl/day; < 1,500 employees)	-	<sup>a</sup>	500 ppm		15 ppm <sup>b</sup>

a. Northeast/Mid-Atlantic requires 500 ppm for all NRLM diesel starting mid-2007.

b. LM diesel downgrade to 500 ppm is allowed indefinitely. Fifteen ppm sulfur is required at refinery gate only.

In late November 2004, after *AEO2005* model runs had been frozen, CARB announced that 15-ppm diesel would be required in harbor-craft in the South Coast Air Quality Management District (SCAQMD, metro Los Angeles) by January 1, 2006.<sup>28</sup> The state ULSD mandate would spread statewide for harbor-craft and intrastate locomotives by January 1, 2007. Given the relatively short lead time (13 months) of the CARB rule, it is uncertain whether this accelerated timetable (versus the Federal nonroad rule) is achievable and whether legal challenges will be mounted in the meantime by affected parties. An abundance of available ULSD arising from the highway program is the rationale for CARB’s decision. Since locomotive and marine fuels represent only a very small percentage of California diesel markets, modeling impacts would have been inconsequential in *AEO2005*.

## F.9 Estimation of Diesel Market Shares

When fully implemented after 2014, there will be three (3) distillate fuels in the marketplace: (a) 15 ppm highway, (b) Nonroad Locomotive & Marine (NRLM) diesel; (c) high-sulfur heating oil. The PMM has been revised to reflect this new rule and at the same time has been re-calibrated regarding market shares of highway and NRLM diesels, as well as other distillate (mostly heating oil, but excluding jet fuel and kerosene).

Historically, highway-grade diesel supplied has nearly matched total transportation distillate sales, although some highway-grade diesel has gone to non-transportation uses such as agriculture and construction. An offline analysis was performed to re-aggregate diesel fuel by sector and by quality to

<sup>28</sup> “CARB to Mandate ULSD in Locomotives, Harborcraft Between 2006-2007,” *World Fuels Today* (November 22, 2004), page 3.

reflect individual uses for the PMM. The following table provides an overview of how the categories were regrouped between the former listings and the new labeled applications.

### Distillate Consumption

Fuel Oil & Kerosene Sales Total Distillate Consumption by Sector (adjusted sales)		In MMBCD				
NEMS (SIBS) Sectors	FO & Kero Sectors	1998	1999	2000	2001	2002
<b>U.S. Total</b>		<b>3,461</b>	<b>3,672</b>	<b>3,732</b>	<b>3,847</b>	<b>3,776</b>
<b>Residential</b>		<b>0.367</b>	<b>0.381</b>	<b>0.399</b>	<b>0.409</b>	<b>0.387</b>
<b>Commercial</b>		<b>0.199</b>	<b>0.196</b>	<b>0.217</b>	<b>0.229</b>	<b>0.200</b>
<b>Industrial</b>		<b>0.147</b>	<b>0.142</b>	<b>0.138</b>	<b>0.152</b>	<b>0.146</b>
	Oil Company	0.037	0.038	0.044	0.054	0.054
	Farm	0.198	0.189	0.204	0.224	0.207
	0.35	0.069	0.066	0.071	0.078	0.073
	0.65	0.129	0.123	0.132	0.146	0.135
	Off-Highway Diesel	0.142	0.140	0.150	0.164	0.145
	<b>Total Industrial</b>	<b>0.524</b>	<b>0.508</b>	<b>0.535</b>	<b>0.594</b>	<b>0.552</b>
<b>Transportation</b>		<b>1.967</b>	<b>2.091</b>	<b>2.161</b>	<b>2.167</b>	<b>2.238</b>
	On-Highway Diesel	0.185	0.182	0.197	0.193	0.201
	Railroad	0.139	0.135	0.133	0.137	0.135
	Vessel/Bunkering	0.018	0.019	0.015	0.023	0.022
	Military					
	<b>Total Transportation</b>	<b>2.308</b>	<b>2.427</b>	<b>2.507</b>	<b>2.519</b>	<b>2.596</b>
<b>Electric Power</b>		<b>0.063</b>	<b>0.060</b>	<b>0.074</b>	<b>0.095</b>	<b>0.041</b>
<b>Diesel used for highway diesel engines &amp; Military</b>		<b>1.985</b>	<b>2.110</b>	<b>2.176</b>	<b>2.189</b>	<b>2.260</b>
<b>Rail (locomotive) &amp; Vessel (marine)</b>		<b>0.323</b>	<b>0.317</b>	<b>0.321</b>	<b>0.330</b>	<b>0.336</b>
<b>(2002 data)</b>	<b>63% (1998-2002 avg)</b>	<b>0.335</b>	<b>0.320</b>	<b>0.340</b>	<b>0.378</b>	<b>0.350</b>
<b>Industrial</b>	<b>22%</b>	<b>0.106</b>	<b>0.108</b>	<b>0.124</b>	<b>0.134</b>	<b>0.124</b>
	<b>14%</b>	<b>0.083</b>	<b>0.090</b>	<b>0.073</b>	<b>0.082</b>	<b>0.078</b>
<b>Residential &amp; Electric HO</b>		<b>0.430</b>	<b>0.441</b>	<b>0.474</b>	<b>0.504</b>	<b>0.428</b>
<b>(2002 data)</b>	<b>33% (1998-2002 avg)</b>	<b>0.063</b>	<b>0.060</b>	<b>0.069</b>	<b>0.079</b>	<b>0.066</b>
<b>Commercial</b>	<b>16%</b>	<b>0.032</b>	<b>0.031</b>	<b>0.031</b>	<b>0.032</b>	<b>0.031</b>
	<b>51%</b>	<b>0.104</b>	<b>0.104</b>	<b>0.120</b>	<b>0.118</b>	<b>0.102</b>
<b>Highway (Road) Diesel</b>		<b>2.155</b>	<b>2.278</b>	<b>2.369</b>	<b>2.402</b>	<b>2.449</b>
<b>Non-Road (Off-Highway) Diesel</b>		<b>0.366</b>	<b>0.351</b>	<b>0.371</b>	<b>0.409</b>	<b>0.382</b>
<b>Locomotive/Marine (LM)</b>		<b>0.323</b>	<b>0.317</b>	<b>0.321</b>	<b>0.330</b>	<b>0.336</b>
<b>Heating Oil (HO)</b>		<b>0.617</b>	<b>0.626</b>	<b>0.667</b>	<b>0.705</b>	<b>0.609</b>

The ULSD regulation includes a phase-in period under the “80/20” rule, that requires the production of 80 percent ULSD and 20 percent 500 ppm highway diesel between June 2006 and June 2010, and a 100 percent requirement for ULSD thereafter. The phase-in path for ULSD is determined in the input file QDCRDCF.TXT. As NEMS is an annual average model, only a portion of the production of highway diesel in 2006 is subject to the 80/20 rule and the 100 percent requirement does not cover all highway diesel until 2011.

Heating oil is not subject to ULSD rules. Over two-thirds of all high sulfur distillate use after 2010 will be concentrated in the Northeast.

## F.10 Estimation of Regional Conversion Coefficients

Differing regional definitions necessitate the conversions of certain variables from one regional structure to another. Regional conversions are not extensive in the PMM, but are needed for five refinery input prices, refinery fuel consumption, and cogeneration information. The factors are used to convert prices consumption, or cogeneration from census districts to the PADD level since the PMM was originally constructed by PADD.

### Conversions for Prices of Refinery Inputs

PMM receives prices for refinery inputs of natural gas from the NGTDM by Census Division and must convert these into PADD level prices. Due to the proximity of refineries in PADDs II, III, and IV to the sources of natural gas supply, prices in these PADD's reflect wellhead natural gas prices in the corresponding Oil and Gas Production Regions. This is achieved by scaling the industrial price for natural gas by an appropriate factor (PNGADJ). Table F12 shows the source of PADD level natural gas prices:

**Table F12. Source of PMM Natural Gas Prices**

<b>Correlation of Prices</b>	
<b>PADD</b>	<b>Input Price</b>
I	Census Division 2 industrial price (PGIIN) * PNGADJ
II	Census Division 3 industrial price (PGIIN) * PNGADJ
III	Census Division 7 industrial price (PGIIN) * PNGADJ
IV	Census Division 8 industrial price (PGIIN) * PNGADJ
V	Census Division 9 industrial price (PGIIN) * PNGADJ

PMM receives prices for refinery inputs of electricity by Census division. PADD level prices are derived by assuming prices in intersecting Census divisions. Table F13 shows the correlation between PADD and Census division electricity input prices:

**Table F13. Source of PMM Electricity Prices**

<b>Correlation of Prices</b>	
<b>PADD</b>	<b>Input Price</b>
I	Census Division 2 industrial prices (PELIN)
II	Census Division 3 industrial prices (PELIN)
III	Census Division 7 industrial prices (PELIN)
IV	Census Division 8 industrial prices (PELIN)
V	Census Division 9 industrial prices (PELIN)

**Conversions for Refinery Fuel Consumption**

Refinery fuel consumption must be converted from the PADD to the Census division level. Each Census division consumption number will equal the consumption in the overlapping PADD's times a factor. The factors were developed using State-level refinery operating capacity and are shown in Table F14. The factors are interpreted as follows: The 0.8434 at the intersection of Census Division 2 and PADD I indicates that 84.3 percent of the PADD I refinery fuel consumption is estimated (using refinery operating capacity as estimator) to occur in Census Division 2. These values will change by small amounts as refinery capacities change, but the impact on model results will be small.

Example: Census Division 7 fuel consumption =  
(PADD II consumption \* .12) + (PADD III consumption \* .93)

**Table F14. PADD to Census Division Conversion Factors**

	<b>Census Division</b>									<b>SUM</b>
	<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>	<b>6</b>	<b>7</b>	<b>8</b>	<b>9</b>	
<b>PADD 1</b>		0.84			0.16					1.00
<b>PADD 2</b>			0.60	0.19		0.09	0.12			1.00
<b>PADD 3</b>						0.07	0.93			1.00
<b>PADD 4</b>								1.00		1.00
<b>PADD 5</b>									1.00	1.00

## **Conversions for Cogeneration**

Information including cogeneration levels (RFCGGEN(CD)), cogeneration capacity (RFCGCAP(CD)), refinery fuel consumption (RFCGFUEL(CD)), self-generation (RFCGSELF(CD)), and generation for grid (RFCGGRID(CD)) must also be converted from PADD level to Census divisions. The same factors and methodology developed for refinery fuel consumption (Table F16) are used to convert the cogeneration data.

Conversion coefficients for refinery fuel consumption and cogeneration information are estimated using &6007PRJ.PMM.CAPACITY.COEFS. Manual updates to the data file were made using data from Oil and Gas Journal survey and making some minor adjustments to the program that reads the data.

## F.11 Unfinished Oil Imports Methodology

PADDs I and III are the primary recipients of unfinished oil imports into the United States. In recent years, PADD V has started receiving increasing volumes of Resid and Heavy Gas Oils. Accordingly, for AEO2005, PADD V has been added and allocation factors have been revised.

The mix of unfinished imported oils flowing into the United States has changed considerably in recent years. An analysis<sup>1</sup> is conducted periodically and maintained offline to gauge the relative distribution of principal unfinished oils into the applicable PADDs. Of the four product import categories that EIA publishes, light gas oils are insignificant and not modeled in PMM. Naphtha, Heavy Gas Oil (HGO), and Resid are tracked and modeled. The corresponding product percentage allocation factors by PADD are shown below:

	<u>PADD III</u>	<u>PADD I</u>	<u>PADD V</u>
PADD Allocation Factor	.72	.18	.10
Naphtha	.10	.08	.01
HGO	.60	.77	.33
Resid	.30	.15	.65

Total unfinished oil imports are estimated as a function of crude oil input to refineries. A regression equation using annual data was developed to represent this relationship and has served over the years despite the erratic timing, magnitude, distribution, and volatility of the various unfinished oil imports into the PADDs. The most significant fundamental shift in unfinished oil imports in recent years has been the dramatic reduction in Resid imports approaching 50 percent. Consequently, the original equation has been modified proportionally to reflect this new circumstance:

$$\text{U.S. Unfinished Oil Imports} = -2856.7 + (0.1224 * \text{Crude Inputs})$$

Total U.S. unfinished oil imports are estimated from the equation; the PADD values are then allocated to PADDs I, III, and V using the values presented in the above table.

---

<sup>1</sup> Energy Information Administration, *Petroleum Supply Annual*, June 2004, Tables 3, 5, 9, and 20.

## F.12 Product Pipeline Capacities and Tariffs

Three sources were used to obtain the product pipeline data; (1) The NPC study <sup>29</sup>, (2) The North American Crude Oil Distribution (NACOD) model prepared by ICF for the Office of Strategic Petroleum Reserves (OSPR) during 1990-91. (3) Updates to these sources prepared by ICF in July 2003.

NACOD data for the year 2000 were used for the petroleum product pipeline capacities and tariffs (1991\$). The NPC study was used for LPG and NGL pipeline capacity data. The NACOD model defines 15 crude oil demand regions (including Canada and Puerto Rico/Virgin Islands) and the NPC study uses PADD regions. The links needed for PMM, as shown in Table F15, are based on PADD's for refining regions and Census Divisions for demands.

**Table F15. NACOD Regions and NEMS/PMM Census Regions**

NACOD Regions		NEMS/PMM Regions	
Code	Locations	Code	Locations
1	New England	1	NE, New England
2	Includes MD, DE	2	MA, excludes MD, DE
3	WV to FL	5	SA, includes MD, DE
4	KS, OK	7	WSC, includes OK, KS
5	PADD II	3, 4	WNC, ENC, and KY, TN from
6	Texas Gulf Coast	7	WSC
7	LA Gulf Coast	7	WSC
8	West Texas, NM	7	WSC, excludes NM
9	AR, No. LA, No. MS, AL	6, 7	ESC, AR, LA, MS, AL
10	PADD IV, North- ID, MT	8	MNT
11	PADD IV, South-	8	MNT
12	Alaska	9	PAC
13	Hawaii	9	PAC
14	PADD V	9	PAC, excludes NV, AZ

<sup>29</sup>National Petroleum Council, *Petroleum Storage and Distribution, Volume 5, Petroleum Liquids Transportation*, (April 1989).

Many of the links shown in Table F16 and Table F17 represent more than one pipeline. In some cases, we have retained more than one link from a source to a destination in order to have a better representation of product movements.

The product pipeline capacities, excluding LPG/NGL service, are shown in Table F16. The matrix formulation used in PMM allows for separate arcs for product movements. For example, to deliver a barrel of gasoline to Dorsey, Maryland (in Census Region 2) from PADD III, (Census Region 7), requires flow on the link from PADD III to Region 6 (capacity of 2,954 Mbbbl/cd) at a cost of \$0.38/bbl, flow on the link from Region 6 to Region 5 (capacity of 2,954 Mbbbl/cd) at a cost of \$0.40/bbl, and flow on the link from Region 5 to Region 2 (capacity of 1,400 Mbbbl/cd) at a cost of \$0.28/bbl. The total tariff is \$1.06/bbl or 2.52 cents/gallon.

**Table F16. Petroleum Product Pipeline Capacities and Tariffs**

Link from Refinery PADD* to Census District (CD)			
From PADD	To CD	Capacity (Mbbbl/cd)	Rate (Wt. avg \$2002/bbl)
PAD District II	2	136	1.32
PAD District II	6	120	1.32
PAD District II	7	124	0.80
PAD District II	8	136	0.41
PAD District III	3	1,006	1.31
PAD District III	4	40	2.05
PAD District III	8	55	0.82
PAD District III	6	2,954	0.38
PAD District IV	4	106	1.07
PAD District IV	9	73	0.62
CD 5	6	320	0.37
CD 5	2	1,400	0.28
CD 6	5	2,954	0.40

\*Some census district source areas are included to represent pipelines that have terminals in more than one CD

**Source:** July 2003 ICF update..

The LPG/NGL pipelines are shown in Table F17.

**Table F17. LPG/NGL Pipelines Capacities and Tariffs**

Link from Refinery PADD* to Census District (CD)		Capacity (Mbbbl/cd)	Rate (Wt. avg \$2002/bbl)
From PADD	To CD		
PAD District I	CD 6	5	2.00
PAD District III	CD 4	50	1.34
PAD District III	CD 3	290	1.17
PAD District III	CD 6	109	0.24
PAD District II	CD 2	56	0.45
PAD District II	CD 7	165	2.48
PAD District II	CD 5	5	0.53
PAD District II	CD 8	5	0.53
PAD District IV	CD 7	160	1.15
PAD District IV	CD 4	60	1.15

\*Some census district source areas are included to represent pipelines that have terminals in more than one CD

**Source:** July 2003 ICF update.

## F.13 Cogeneration Methodology

Electricity consumption in the refinery is a function of the throughput of each unit. Sources of electricity consist of refinery power generation, utility purchases, refinery cogeneration, and merchant cogeneration. Power generators and cogenerators are modeled in the PMM Linear Program (LP) as separate units which are allowed to compete along with purchased electricity.

### Refinery Cogeneration

The refinery cogeneration unit in the PMM LP was modeled using historical data as a guideline. Cogeneration activity for each refinery was aggregated to the PADD level for incorporation into the PMM LP. Cogeneration capacity, fuel consumption, and percent sales to the utility grid were estimated from the EIA-860B, Annual Non-utility Power Producer Report for 2002. The data covers all of SIC 29, not just SIC 2911. Cogeneration investment and operating costs were derived from the 1980 Office of Technology Assessment (OTA) report "Industrial Cogeneration."

Cogeneration capacity (including planned capacity) for each refining region was derived from the EIA-860B historical data base. The LP limits utilization to 90 percent of capacity. Cogeneration capacity is allowed to expand when the value received from the additional product exceeds the investment and operating costs of the new unit. The value of adding capacity includes revenues from sales to the utility grid and the displacement of purchases of electricity. Investment costs are derived from the OTA report. The capacity expansion methodology is described in detail in Chapter 4.

Forecasted Refinery cogeneration fuel consumption was derived from the NEMS Industrial Model for small cogeneration systems. A 1,000 kw capacity unit was assumed with an overall heat rate of 14,217 btu/kwh. Converted to fuel oil equivalent, consumption of 2.26 barrels of fuel oil produces approximately 1,000 kwh of electricity and 6,530 lbs of steam. Since the LP refinery consumes fuel in barrels of fuel oil equivalent, shares of individual fuels were determined from the historical data and computed post process. The shares are allocated as follows:

Oil	6.0%
Natural Gas	68.1%
Other Gaseous Fuels	25.2%
Other	0.7%.

In the past, shares of all petroleum based fuels were aggregated under Petroleum Products. This category has now been divided into Oil and Other Gaseous Fuels.

In general, refinery cogeneration units tend to be small, designed to supply the refinery's steam and electricity needs, with a small amount of leftover capacity sold to the grid. However, if it is profitable to sell cogeneration electricity, the LP will sell all of it. Likewise if it is not profitable, it will sell none of it. To model the situation more realistically, sales to the grid were modeled using percentages derived from the historical data base. The percentage of sales to the grid for each refining region (PADD) was calculated from the 2001 data as follows:

<u>REGION</u>	<u>PERCENT SOLD TO GRID</u>
1 (PADD I)	67
2 (PADD II)	1
3 (PADD III)	1
4 (PADD IV)	1
3 (PADD V)	45

The LP is forced to sell electricity back to the grid in these percentages at a price equal to the average price of electricity.

Fixed operating costs are calculated in the model as a function of cogeneration capacity while variable operating costs are determined as a function of electricity generated. The following rates were determined from the OTA report.

Annual Fixed Cost    \$7.32/kw  
 Variable Cost        \$0.00565/kwh

Data from the EIA-860B report obtained from an Access query by Alan Beamon. The resulting data were manipulated in New NUGS.MDB to obtain fuel use, capacity, and capacity factors for existing refinery co-gen units. Output tables become linked input tables for the PMM history file generator “Build ELGCPUR.MDB” described in Appendix H.

### **Merchant Cogeneration**

Merchant cogeneration is also modeled in the PMM. Merchant cogenerators are defined as non-refiner owned facilities located near refineries to provide energy to the open market and to the neighboring refinery. The PMM merchant cogeneration model parameters are based on the Central & South West Energy Inc. (CSWE) facility located adjacent to the Phillips Petroleum Company in Sweeny, Texas. CSWE supplies all of the refinery’s steam and electricity requirements and receives up to three quarters of their fuel from refinery waste gases.<sup>30</sup> Electricity not used by Phillips, about two-thirds of total capacity, is sold on the open market.

Fuel consumption parameters for the PMM merchant plant are based on the Sweeny facility. The PMM merchant cogeneration unit consumes 1.90 barrels of fuel oil equivalent to produce 1,000 kwh of electricity and 5,200 lbs. of steam.

Initial capacity in PMM PADDs II, III, and IV is 330 Mw (Sweeny plant). Base capacity in all other regions is zero. Capacity expansion methodology is the same as in the refinery cogeneration model. Investment cost for a new cogeneration facility is \$580 per kw of capacity. Annual fixed cost and variable operating cost are the same as for the refinery cogeneration model.

Unlike refinery cogeneration units, merchant facilities tend to be large units designed to sell a large portion of their electricity to the grid. The PMM merchant cogeneration model assumes 67 percent of electricity generated is sold to the grid in all regions, based on the Sweeny facility. The sale price is equal to the average of the generation price and the industrial price of electricity for each PMM region. Electricity prices are obtained from the Electricity Market Model.

## **F.14 Natural Gas Plant Fuel Consumption**

The consumption of natural gas by natural gas processing plants is modeled as a function of dry gas production. Natural gas consumed at gas processing plants is calculated as a percentage of dry gas production using data from the *Natural Gas Annual 1992*. The ratios are calculated by PADD, except for PADD V where Alaska is computed separately from the rest of PADD V.

---

<sup>30</sup>CarolAnn Giovando, June 1998. *1998 Powerplant Awards Sweeny Cogeneration Facility*, Power.

PADD I	1.36
PADD II	2.50
PADD III	2.43
PADD IV	2.61
PADD V	2.25
ALASKA	8.93

## F.15 Crude Oil Exports/Total and Alaskan

Exports of crude oil have historically been linked to the level of domestic production. A significant amount of crude oil exports used to be from Alaska. Since 2001, however, Alaska has not exported any crude oil due to increasing domestic demand and decreasing crude production in Alaska. This trend is expected to continue. As a result, crude oil exports are represented in the PMM as a percentage of the total lower 48-state crude oil production based on the latest available data

## F.16 Technology Improvement Option

A number of mechanisms for representing technological progress for key PMM refinery processing units have been implemented in the PMM. The first option allows the PMM to represent process technology improvements that will impact operating costs on any or all active processing units and/or processing modes. Thus, the user defines the processing unit(s), corresponding processing mode(s), and percentage change in variable operating cost (OVC) (positive or negative), along with a range of years over which these are phased in. The second option allows the user to define a set of processing units and corresponding output streams whose yields would change due to technology improvements. The year in which the technology will come on and the corresponding yields are also included in the input data. The third option allows the user to upgrade the properties of intermediate streams beginning in any user-specified year. The user defines the stream ID, the spec ID(s), and the new spec value(s), along with the activation year for this change. The design for each of these options is modular in that the control data are located in a file separate from the current PMM refinery technology database, and the user defines the information needed to drive the technology change. Each of these options are summarized below.

For the first option, the user has the option to change the OVC data for all processing units (global), for any number of user-defined processing units, for both (with the user-defined unit data over riding the global data), for any set of processing modes, or for nothing at all. The user defines the period over which the OVC change is phased in, as well as the total percentage change (- for a decrease and + for an increase) that is desired over the period. For the user-specified option, the user also includes the 3-digit processing unit ID(s). The last record of data in the user-specified option must begin with a # symbol to signal the end of the list. To turn off either or both options, the phase-in begin and end years must be set to 0. The

control data are located at the bottom of the PMM QDCRDCF data file. The format of this control data is as follows:

```

C Data for Global changes to reflect Technological Progress
C | Phase-in Period | Chng over period
C | BeginYR      EndYR | Percent Chng
@ |      Y1      Y2 | TPCT_CHNG
  |      0      0 | 0.0000

C Data for Process Unit changes to reflect Technological Progress
C | Phase-in Period | Chng over period | Name of ProcUnit/ Mode
C | BeginYR      EndYR | Percent Chng      | Three-letter ID
@ |      Y1      Y2 | TPCT_CHNG        | UNAMID      MNAMID
x |      0      0 | 0.0000           | FCC 75H
x |      0      0 | 0.0000           | ALK        C4A
# |      0      0 | 0.0              | ---        ---

```

To activate the option to *change stream yields* for a processing unit and mode of operation, the user is required to define the processing unit(s), mode(s) and stream(s) being affected, the corresponding new yield level(s), and an activation year (not phased in for this version). The number of processing units, modes, and streams must be included in the data file to act as controls for reading and processing the data. Up to ten modes and ten streams per mode can be changed for each processing unit defined. To deactivate this option, the number of processing units is set to zero. During the processing effort, the original yield and gain levels associated with the processing unit/mode combination are first retrieved from the LP matrix. Next, the yields corresponding to streams specified by the control data are updated based on the input data. Finally, the gain is recalculated and updated in the matrix. The data format representing an activated list of new yield levels is presented below:

```

C Data for Yield improvement to reflect Technological Progress
C | Num/Name | | | MAX MODES = 10
C | ProcUnit | Tech | # of | 1 new | 2 new | 3 new | 4 new
C | 3-let ID | Year | modes | mode, coeff | mode, coeff | mode, coeff | mode, coeff |
@ | ----- | ---- | ---- | ---- | ---- | ---- | ---- |
  | 1
  | FCC      | 2005 | 2    | 80S      | 75H
  |          |      |      | 4        | 8
  |          |      |      | RC8      | UC4      | .635 | .064
  |          |      |      | LC8      | UC3      | .099 | .050
  |          |      |      | UC4      | ZR8      | .089 | .286
  |          |      |      | COX      | ZR7      | .051 | .286
  |          |      |      | ---      | ZC7      | .000 | .040
  |          |      |      | ---      | ZC8      | .000 | .040
  |          |      |      | ---      | LC1      | .000 | .054
  |          |      |      | ---      | LC2      | .000 | .055

```

To activate the option to *change spec values* of intermediate streams, the user is required to define the stream(s), spec ID(s), new spec levels, and an activation year (not phased in for this version). The number of streams and spec IDs must also be included in the data file to act as controls for reading and processing the data. Up to ten spec types can be changed for each stream defined. To deactivate this option, the number of streams is set to zero. During the processing effort, the coefficients corresponding to the product



## F.17 GTL Representation in PMM

In the PMM, a gas-to-liquids (GTL) facility can be built on the North Slope in Alaska. A minimum build requirement is 50,000 bbl/d GTL production (gas: ~500MMCFD or 180 BCF a year). The investment and operating costs do not change over time (in constant 1987 dollars). The natural gas supply is represented as a three-step supply curve. A set of price/quantity pairs (AKNG\_SUPCURV) for North Slope natural gas is provided by the NGTDM (Natural Gas Transmission and Distribution Module) team. Quantities represent the maximum gas used by GTL's at current capacity. Prices are set using the function CUM\_AKNGCRV, which takes into account cumulative North Slope gas supply for both GTL and ANGTS, based on the following price groups.

If cumulative production of North Slope NG (including ANGTS and GTL) is:

<= 31,000 BCF/yr	Price = \$0.80 /mcf (2000\$'s)
<= 36,000 BCF/yr	Price = \$1.40 /mcf (2000\$'s)
<= 50,000 BCF/yr	Price = \$2.00 /mcf (2000\$'s)
> 50,000 BCF/yr	Price = \$3.00 /mcf (2000\$'s)

GTL output streams can be transported from the North Slope, through Valdez, to any of the five PMM regions. GTL mixing losses (PMM input) due to transport with the oil along the Trans-Alaska Pipeline System (TAPS) are accounted for and added to the Alaska oil total to be processed in a US refinery. A maximum flow (oil plus gas) is defined along the TAPS pipeline. [A minimum flow could also be defined, but would force the build of a GTL facility if the oil flow is below the minimum.] GTL transport costs from the North Slope to Valdez (along TAPS) are calculated within the PMM as a function of a variable cost, a fixed cost (converted to a unit cost based on t-1 GTL and oil flow), and a subsidy factor (based on value of oil if total flow is below a pipeline minimum). The fixed and variable costs are determined within the PMM based on input data. GTL transport costs from Valdez to California via vessel are also defined (PMM input).

The following LP variables and coefficients are related to Alaska GTL (and oil) production, transport, and accounting:

TAAMHXZ	Volume of AMH (Alaska medium sulfur - heavy) crude transported from Alaska to Valdez for export to Canada
O@CRDEXP	Other Alaskan crude exports (from South Alaska)
YAAMH5(r)	Volume of AMH crude transported from North Slope to Valdez + to region (r)
YAALL5(r)	Volume of ALL (Alaska low sulfur - light) crude transported from S. AK to region (r)
PADCRQ1	Total Alaskan crude production

TAALLTOT	Total ALL oil produced in Alaska
TAAMHTOT	Total AMH oil produced in Alaska
TAGTLTOT	Total GTLs transported from Alaska North Slope to Valdez along TAPS
TANSOTOT	Total oil transported from Alaska North Slope to Valdez along TAPS
WAGTLJ(r)	Total GTLs transported from Valdez to US refinery regions (r)
GTLLOSS	Percent of GTLs lost due to mixing with Alaska oil during transport along TAPS
H(r)SMD(mod)	Operating level for the SMD GTL processing unit
H(r)SOD(mod)	Operating level for the SOD GTL processing unit
N(r)NGKN1	Alaska NG supply curve, step 1
N(r)NGKN2	Alaska NG supply curve, step 2
N(r)NGKN3	Alaska NG supply curve, step 3
H(r)MPRFSL	Quantity of GTL stream SNL transferred from North Slope to Valdez
H(r)MPRFSP	Quantity of GTL stream SNP transferred from North Slope to Valdez
H(r)MPRFSE	Quantity of GTL stream SKE transferred from North Slope to Valdez
H(r)MPRFSX	Quantity of GTL stream SDX transferred from North Slope to Valdez

The following new and modified equations define the relationship between the variables defined above as related to GTL production in Alaska.

*Equation 1*

Total GTLs produced in Alaska and transported from the Alaska North Slope to Valdez equals the sum of the individual GTL stream types (produced by each GTL unit's mode of operation) going to each of the 5 PMM regions. The corresponding TAPS transport cost (minus GTL subsidy, if applicable) is applied to the TAGTLTOT variable. The PRICNS and GTLSUB are calculated in the refine.f, and presented in the "Changes to PMM" subsection below.

$$\text{CAGTLTOT: TAGTLTOT} = \sum_r \sum_{\text{gtl}} \text{H(r)MPRF(gtl)}$$

$$\text{OBJ:} \quad - (\text{PRICNS-GTLSUB}) * \text{TAGTLTOT}$$

*Equation 2*

Total GTLs being transported via a U.S. flag light product vessel from Valdez to PADD (r) equals the total GTLs produced in Alaska, minus the loss due to mixing with Alaskan oil during transport. The corresponding transport cost (cst) is applied to the WAGTLJ(r) variable, and currently set to 3.7, 3.2, 3.2, 3.2, and 0.8 for PADD's 1-5, respectively, in \$87/bbl.

$$\begin{aligned} \text{C(r)GTL:} \quad & \text{WAGTLJ(r)} = (1. - \text{GTLLOSS}) * \sum_{\text{gtl}} \text{H(r)MPRF(gtl)} \\ \text{OBJ:} \quad & - \text{cst} * \text{WAGTLJ(r)} \end{aligned}$$

*Equation 3*

The mass balance equation for AMH Alaskan crude was modified to include a gain due to mixing of GTLs during transport. This gain is accounted for in the Alaska North Slope oil stream [YAAMH5(r)].

$$\begin{aligned} \text{CAAMH:} \quad & \text{TAAMHTOT} + \text{GLTLOSS} * \text{TAGTLTOT} = \\ & \text{TAAMHXZ} + \text{O@CRDEXP} + \sum_r \text{YAAMH5(r)} \end{aligned}$$

*Equation 4*

Since total North Slope Alaska crude does not consist totally of AMH crude, a new variable (TANSOTOT) is created to represent total North Slope Alaska crude, as defined within a new balance row (CANSOTOT). The corresponding TAPS transportation cost for North Slope crude is applied to the TANSOTOT variable. [Note: The OBJ row coefficient on the Y variables now represents other transportation costs from Valdez to the PMM regions.]

$$\begin{aligned} \text{CANSOTOT:} \quad & \text{TANSOTOT} = \text{TAAMHXZ} + \\ & \sum_r \text{YAAMH5(r)} - \text{GLTLOSS} * \text{TAGTLTOT} \\ \text{OBJ:} \quad & - \text{PRICNS} * \text{TANSOTOT} \\ \text{OBJ:} \quad & - \text{coef(r)} * \text{YAAMH5(r)} \end{aligned}$$

*Equations 5,6,7*

Two new row constraints are added to account for maximum and minimum flow requirements on TAPS; and, 1 new row constraint to account for maximum NG production in Alaska for GTL use.

$$\begin{aligned} \text{TAOILGTX:} \quad & \text{TANSOTOT} + \text{TAGTLTOT} \leq \text{TAPSUL} \\ \text{TAOILGTN:} \quad & \text{TANSOTOT} + \text{TAGTLTOT} \geq \text{TAPSL} \\ \text{TANGKGTX:} \quad & \sum_r \sum_s \text{N(r)NGKN(s)} \leq \text{NGKUL} \end{aligned}$$

*Equations 8,9*

New balance rows were defined for AMH and ALL Alaska crude.

$$\begin{aligned} \text{CAAMHTOT:} \quad & \text{TAAMHTOT} = .9844 * \text{PADCRQ1} \\ \text{CAALLTOT:} \quad & \text{TAALLTOT} = .0156 * \text{PADCRQ1} \end{aligned}$$

*Equations 10-13*

Other mass balance additions and changes include mass balance for the GTL stream at the refinery [B(r)(gtl)], mass balance for the GTL stream generated in Alaska [H(r)(gtl)], mass balance for the Alaskan natural gas stream [H(r)NGK], and a capacity limit on the transportation mode (J) [TVPJCP]:

$$\mathbf{B(r)(gtl):} \quad (1. - \text{GTLLOSS}) * \mathbf{H(r)MPRF(gtl)} = \sum_{\text{unt}} \sum_{\text{mod}} \mathbf{R(r)(unt)(mod)} + \sum_{\text{prd}} \mathbf{F(r)(prd)(gtl)} + \sum_{\text{prd}} \mathbf{B(r)(prd)(gtl)} + \mathbf{T(r)(gtl)(str)}$$

$$\mathbf{H(r)(gtl):} \quad \sum_{\text{gtl}} \mathbf{H(r)MPRF(gtl)} = \text{coef}_{\text{gtl}} * \sum_{\text{unt}} \sum_{\text{mod}} \mathbf{H(r)(unt)(mod)}$$

$$\mathbf{H(r)NGK:} \quad \sum_{\text{s}} \mathbf{N(r)NGKN(s)} = \text{coef}_{\text{ngk}} * \sum_{\text{unt}} \sum_{\text{mod}} \mathbf{H(r)(unt)(mod)}$$

$$\text{TVPJCP:} \quad \dots + .002 * \sum_{\text{r}} \mathbf{WAGTL(r)}$$

where,

R(r)(unt)(mod)	Refinery unit (unt) operating level for mode (mod) in region (r)
B(r)(prd)(gtl)	Quantity of GTL (gtl) blended into mogas product (prd) in region (r)
F(r)(prd)(gtl)	Quantity of GTL (gtl) blended into distillate product (prd) in region (r)
T(r)(gtl)(str)	Quantity of GTL (gtl) transferred into blend component (str) in region (r)

### Changes to the PMM

Four subroutines (CHGAKTRN, RFGTLCAP, RPTAKGTL CHGTRANS) and a function (CUM\_AKNGCRV) in the refine.f code define the new GTL capability in Alaska. In addition, subroutines ADDCAP and CHGBLDLIM handle the PMM ability to specify which processing units are allowed to build. A set of data at the bottom of the rinvest.txt data file define GTL parameters and control flags. The data are included below, followed by a list of the GTL variables defined.

In equations 1 and 4 above, the transport price along TAPS (PRICNS) is based on the fixed costs (TAP\_FIXCST) and variable costs (TAP\_VARCHG). The GTL subsidy (GTLSUB) is positive only when the flow along the TAPS is lower than an economic minimum level (TAPMIN). It is a function of the Alaskan NG wellhead price and an oil lift cost times an adjustment factor. These equations are presented below:

$$\begin{aligned} \text{PRICNS} &= ( \text{TAP\_FIXCST} / (\text{PIPOILNS} + \text{PIPGTLNS} ) ) \\ &\quad + \text{TAP\_VARCHG} \\ \text{GTLSUB} &= 1000. * \text{PIPOILNS} * \\ &\quad (\text{AKWHP} - \text{TAP\_OILIFT} * (1. + \text{TAP\_OILADJ} ) ) \\ &\quad / (\text{PIPGTLNS} * 1000.) \end{aligned}$$

## GTL Data

=====

PMM input data related to GTL

=====

Data: Parameters related to GTL process  
Variables: GTL\_INCBLD -- incremental GTL output levels for building (Mbb/d)  
GTL\_FSTYR -- first possible start year for facility to come on-line  
GTL\_DCLCAPCST -- annual decline rate for capital recovery costs  
GTL\_DCLOPRCST -- annual decline rate for fixed operating costs  
Source: Analyst's judgement  
Notes:

-----

DOCUMENTATION UPDATES: DATE--AUTHOR--COMMENT

-----

NOTES:

-----

@

50.0 GTL\_INCBLD  
2010 GTL\_FSTYR  
0.000 GTL\_DCLCAPCST  
0.000 GTL\_DCLOPRCST

=====

Data: Parameters related to TAPS volumes  
Variables: TAP\_MAXCAP -- maximum capacity on TAPS (Mbb/d)  
TAP\_MINTHRU -- minimum economic throughput on TAPS (Mbb/d)  
TAP\_MINSTVOL -- minimum incremental volume above min when subsidy  
nonzero (Mbb/d)  
TAP\_PGTLOIL -- fraction of GTL volume transferred to oil in TAPS (fraction)  
Source: TAP\_MAXCAP -- analyst's judgment  
TAP\_MINTHRU -- analyst's judgment  
TAP\_MINSTVOL -- analyst's judgment  
TAP\_PGTLOIL -- analyst's judgment

-----

DOCUMENTATION UPDATES: DATE--AUTHOR--COMMENT

-----

NOTES:

-----

@

3000.00 TAP\_MAXCAP  
300.00 TAP\_MINTHRU  
100.00 TAP\_MINSTVOL  
0.10 TAP\_PGTLOIL

```

Data:      Parameters related to TAPS costs/prices
Variables: TAP_FIXCST  -- fixed transportation cost on TAPS (1000 $/day)
           TAP_VARCHG -- variable transportation cost on TAPS ($/bbl)
           TAP_OILIFT -- assumed oil lifting cost in Alaska ($/bbl)
           TAP_OILADJ -- minimum upward adjustment of lift cost to set total costs (e.g.,
                        including profit) (fraction)
Source:    TAP_FIXCST  -- judgment based on Alaska Department of Natural Resources
                        graph of tariff rates and volumes
           TAP_VARCHG-- judgment based on Alaska Department of Natural Resources
                        graph of tariff rates and volumes
           TAP_OILIFT -- lifting cost for oil production in Alaska
           TAP_OILADJ -- analyst's judgment

```

-----  
DOCUMENTATION UPDATES: DATE--AUTHOR--COMMENT  
-----

NOTES:

TAPS transportation costs (PMM sets oceanic shipping costs elsewhere)

TAPS tariff = (fixed cost / throughput) + variable charge

throughput = oil prod + GTL prod (mbbl/d)

for build decision:

GTL prod = current CAPgtlms + GTL\_INCBLD

Oil prod = PCTAKAMH \* 1000\* ( XRFQTDCRD<sub>10</sub> +  
XRFQTDCRD<sub>11</sub> +XRFQTDCRD<sub>12</sub> ) - QEXCRDIN

Oil prod = oil\_prod(t) \* ( oil\_prod(t) / oil\_prod(t-1) )\*\*3.

in general

GTL prod = current CAPGTLNS

Oil prod = oil\_prod(t) = PCTAKAMH\*RFQTDCRD\*1000 - QEXCRDIN

Parameters for calculating GTL subsidy from oil production

if (oil\_prod(t) .le. (TAP\_MINTHRU + TAP\_MINSTVOL))

then subsidy = [(oil prod \* oil price) - (lift cost \* oil prod \* (1.+min add))] /GTL prod

```

-----
@  year $  value
    1995  2055.  TAP_FIXCST
    1995   0.90  TAP_VARCHG
    1999  10.00  TAP_OILIFT
           0.20  TAP_OILADJ

```

## GTL Variables

! PUT INTO PMMCOM1 INCLUDE

CAPGTLNS(MNUMYR) ! TOTAL GTL CAPACITY (bbl/d)  
TAP\_FIXCST ! FIXED TRANS CST ON TAPS, 1987 dollars  
TAP\_VARCHG ! VAR TRANS CST ON TAPS, 1987 dollars/BBL  
TAP\_OILIFT ! ASSUMED OIL LIFTING CST IN AK, 1987 dollars/BBL  
TAP\_OILADJ ! MIN UPWARD ADJ OF LIFT CST, 1987 dollars/bbl  
TAP\_MAXCAP ! MAX CAP ON TAPS, MMBBL/D  
TAP\_MINTHRU ! MIN ECONOMIC THROUGHPUT ON TAPS, MMBBL/D  
TAP\_MINSTVOL ! MIN INCR VOL ABOVE MINTHRU, MMBBL/D  
GTL\_INCBLD ! INCR GTL OUTPUT BLD LEVEL, MMBL/D  
PMMCAPI(MNUMPR,PUNITSN) ! INITIAL REF UNIT CAPACITY, MMBL/D  
GTL\_FSTYR ! FIRST POSSIBLE START YR FOR GTL BLD, 4-digit

! PUT INTO PMMOUT INCLUDE

AKNG\_GTLCONS(MNUMYR) ! CONSUMP OF NG IN AK FOR GTL PROD, Bcf  
AKGTLPRD(MNUMYR) ! GTL PRODUCTION IN AK, Bbl/d  
AKGTLEXP(MNUMYR) ! AK GTL EXPORTS, Bbl/d

! PUT INTO OGSMOUT INCLUDE

AKNG\_SUPCRV(3,2,mnumyr) ! ALASKA NG SUPPLY CURVE, 1987 dollars/mcf, bcf  
! 3 - number of points, 2 - price(1),quantity(2)

## F.18 CTL Representation in PMM

The coal-to-liquids (CTL) process has been incorporated into the PMM. It was developed based on the methodology described in a Mitretek Technical Report: *Coproduction: A Green Coal Technology*, by David Gray and Glen Tomlinson, March 2001. Specifically, the large-scale coproduction with no carbon sequestration (Figure 7 in the report) is adopted as the generic facility for the CTL module. This CTL facility is capable of processing 16,400 TPD bituminous coal (e.g., Illinois Basin) with an energy content of 23 mmBtu/ton, and generating 33,200 BPD fuels and 465.5 MW net cogen for sale to the grid (based on combined heat and power efficiency of 45%). The capacity factor (or utilization rate) for the CTL facility is assumed to be 0.9.

A spreadsheet was developed to translate the economic assumptions for this CTL facility into data that could be incorporated in the PMM. The CTL plant life is assumed to be 25 years, with the capital 1/3 from equity at 15 percent and 2/3 from debt with 8 percent of return on investment. Together, this translates into a capital recovery factor of 0.136.

The cogenerated (cogen) electricity is partially consumed in the facility (292 MW); while the net cogen (465.5 MW) is assumed to be sold to the grid at wholesale industrial prices. The revenue from cogen sales is treated as a credit by the model to offset the costs (feedstock, fixed, and operation costs) of producing CTL “liquids.”

The generic CTL facilities are assumed to be built near the existing refineries. For PADD I, the CTL facilities are assumed to be built near the Delaware River basin; for PADD II, near the Illinois River basin; for PADD III, on the Gulf Coast; for PADD IV, near Billings of Montana; and for PADD V, in the vicinity of Puget Sound in Washington State. In addition, for PADD I, the coal would be 100 percent Northern Appalachian coal; for PADD II, 100 percent Eastern Interior coal; for PADD III, 100 percent Powder River coal; for PADD IV, 100 percent Dakota Lignite; and for PADD V, 100 percent Powder River coal.

The CTL yield distribution is assumed to be similar to that from a Gas-to-Liquids (GTL) facility because both involve the Fischer-Tropsch process to convert syngas ( $\text{CO} + \text{H}_2$ ) to hydrocarbons.

The CTL module allows for a “policy” lever to specify when and how many CTL facilities to be built with government incentives even when it is still economically disadvantaged. Once the CTL becomes economically feasible, its growth rate would be governed by a growth rate based on the Mansfield-Blackman model for market penetration.

## Mathematical Representation of CTL in the PMM

The CTL facility is assumed to be located at a site near the representative refinery in each PMM refining region. Thus, coal feed is delivered to this site and processed into synthetic liquids (with cogenerated electricity that is both consumed on site and sent to the grid). The liquids are then transported (at a small cost) to the refinery for blending or further processing.

A single (representative) coal type is modeled within each region. The quantity, delivered price, and average heat content (LCVTONQ, LCVTONP, and LCVBTU) of each coal available for processing, as well as a price elasticity (LCVELAS), are provided by the CMM. The quantity of coal consumed to produce 33,200 bbl/cd liquids at each CTL facility is a function of the average heat content of the coal provided by the CMM and the base energy content and consumption level of the coal defined for the representative CTL processing unit ( $BASCLRAT * CTL\_BASHHV / LCVBTU$ ). The PMM uses the price, quantity, and elasticity to build a 3-step coal supply curve. The final quantity of coal consumed (Q\_CTLCOAL) is sent back to the CMM for response.

The CTL processing mode is based on a representative GTL processing mode from the PMM technology database provided by Ensys. The input rate (tons coal per bbl liq produced) has been adjusted to reflect the corresponding coal to liquids ratio presented in the Mitretek paper. Special links have been established to ensure the “liquids” will be processed or blended properly downstream. Cogeneration is accounted for at the CTL facility as a function of the liquids produced. A credit (a function of end-use electricity prices, PELIN) is provided to account for sales to the grid.

Capital costs for the CTL facility are based on the cost information provided by Mitretek, including both fixed charges and other operating costs. Also, in accordance with direction from Mitretek, these costs are increased depending on the coal type consumed in the region. In addition, two decline-rate variables (CTL\_DCLCAPCST, CTL\_DCLOPRCST) have been included to allow for costs to improve over time.

The "policy" lever included with the CTL to reflect government incentives consists of a minimum build forecast series. This is tracked as a separate CTL processing unit (CTZ vs CTX) in order to distinguish between incentives builds (CTZ) and economic builds (CTX). Also, the Mansfield-Blackman model for market penetration has been incorporated to limit excessive growth of CTLs once they become economically feasible.<sup>31</sup> The indexes associated with this modeling algorithm are user inputs that define the characteristic of the CTL process. They include an innovation index of the industry (IINDX), the relative profitability of the investment within the industry (PINDX), the relative size of the investment (per

---

<sup>31</sup> E. Mansfield, “Technical Change and the Rate of Imitation,” *Econometrica*, Vol. 29, No. 4 (1961), pp. 741-765.

A.W. Blackman, “The Market Dynamics of Technological Substitution,” *Technological Forecasting and Social Change*, Vol. 6 (1974), pp. 41-63.

plant) as a percentage of total company value (SINVST), and a maximum penetration level (number of units,CTLBLDX). These have been defined in a memorandum from Andy Kydes to Han-Lin Lee, entitled "Development of a model for optimistic growth rates for the coal-to-liquids (CTL) technology in NEMS," dated March 23, 2002.

Carbon dioxide emissions will be handled by the NEMS integrating model by applying a CO<sub>2</sub> emissions coefficient to the coal consumed by the CTL unit.

## **Updates to the LP matrix**

The following LP variables are directly related to CTL production, transport, and accounting:

rows:

C(r)CTLTOT	Total CTL liquids produced for refinery (1000 bbl/cd)
L(r)CTXCAP	CTL capacity balance net of incentive builds (1000 bbl/cd)
L(r)CTZCAP	CTL capacity balance from incentive builds (1000 bbl/cd)
H(r)(liq), B(r)(liq)	CTL liquids balance (1000 bbl/cd)
H(r)(coal)	Coal (into CTL unit) balance (1000 tons/cd)

columns:

B(r)(gaso)(liq)	CTL liquids blended into gasolines (M bbl/cd)
F(r)(dist)(liq)	CTL liquids blended into distillates (M bbl/cd) [DSL, DSU, JTA, N2H, N6I]
K(r)CTXCAP	Existing CTL processing unit capacity, =0 (M bbl/cd)
E(r)CTXINV	CTL processing unit additions (M bbl/cd)
L(r)CTXBLD	Cumulative CTL unit additions (M bbl/cd)
H(r)CTX(mod)	Operating level for CTL (M bbl/cd)
K(r)CTZCAP	Existing planned CTL processing unit capacity, =0 (M bbl/cd)
E(r)CTZINV	planned CTL processing unit additions (M bbl/cd)
L(r)CTZBLD	Cumulative planned CTL unit additions (M bbl/cd)
H(r)CTZ(mod)	Operating level for planned CTL (M bbl/cd)
R(r)(unt)(mod)	New mode to process liquids from CTL units (M bbl/cd)
H(r)MPRF(liq)	Vol of CTL liquids transferred to refinery (M bbl/cd)
N(r)(coal)N(step)	Coal supply curve for CTL processing (1000 tons coal/cd, 87\$/ton)

The following new and modified equations define the relationship between the variables defined above as related to CTL production.

## Equation 1

Coal supply mass balance: The coal supply (represented as a 3-step coal supply curve) must equal the coal consumed at the CTL units (including planned units) to produce liquids (by region/coal type).

$$\mathbf{H(r)(coal):} \quad \Sigma_s \mathbf{N(r)(coal)N(s)} = \Sigma_{\text{mod}} \mathbf{c_1 * H(r)CTX(mod)} + \Sigma_{\text{mod}} \mathbf{c_1 * H(r)CTZ(mod)}$$

[1000tons/cd]

## Equations 2 & 3

Liquids production mass balance: Liquids produced at the CTL unit must equal the liquids transferred to the refinery (by region and liquid type). CTL liquids transferred to the refinery are either consumed by other processing units, blended into mogas, or blended into distillates (by region and liquid type).

$$\mathbf{H(r)(liq):} \quad \Sigma_{\text{mod}} \mathbf{c_2 * H(r)CTX(mod)} + \Sigma_{\text{mod}} \mathbf{c_2 * H(r)CTZ(mod)} = \mathbf{H(r)MPRF(liq)}$$

[1000bbl/cd]

$$\mathbf{B(r)(liq):} \quad \mathbf{H(r)MPRF(liq)} = \Sigma_{\text{dist}} \mathbf{F(r)(dist)(liq)} \quad \text{< distillates >}$$

[1000bbl/cd]

-- or --

$$\mathbf{H(r)MPRF(liq)} = \Sigma_{\text{mgas}} \mathbf{B(r)(mgas)(liq)} + \Sigma_{\text{unt}} \Sigma_{\text{mod}} \mathbf{R(r)(unt)(mod)} \quad \text{<mogas>}$$

## Equation 4

CTL operating/capacity balance: Total operating level of CTL must equal the operating level of existing CTL capacity, newly added capacity, and cumulative added capacity. Total operating level cannot exceed upper bounds on existing, newly added, and cumulative added capacity (by region).

$$\mathbf{L(r)CTXCAP:} \quad \Sigma_{\text{mod}} \mathbf{H(r)CTX(mod)} = \mathbf{K(r)CTXCAP} + \mathbf{cf * E(r)CTXINV} + \mathbf{cf * L(r)CTXBLD}$$

[1000bbl/cd]

$$\mathbf{L(r)CTZCAP:} \quad \Sigma_{\text{mod}} \mathbf{H(r)CTZ(mod)} = \mathbf{K(r)CTZCAP} + \mathbf{cf * E(r)CTZINV} + \mathbf{cf * L(r)CTZBLD}$$

[1000bbl/cd]

## Equation 5

Total CTL liquids produced: This unconstraining row totals CTL liquids produced (by region), for reporting.

$$\mathbf{C(r)CTLTOT:} \quad \Sigma_{liq} \mathbf{H(r)MPRF(liq)}$$

(1000 bbl/cd)

## Equation 6

Objective function: A credit is put in the objective function, attached to the CTL operating variable, to account for cogen produced at the CTL and sent to the grid. A cost is added to the objective function, attached to the transfer variables H(r)CTX(mod) and H(r)CTZ(mod), to account for the transfer tariffs from CTL facility to refinery. Variable operating costs and capital investment costs are included in the objective function for the E, L, and H variables. The cost of coal on each supply step is included in the objective function

$$\begin{aligned} \mathbf{OBJ:} \quad & \Sigma_{mod} \Sigma_r \mathbf{CgnCredit} * \mathbf{H(r)CTX(mod)} + \Sigma_{mod} \Sigma_r \mathbf{CgnCredit} * \mathbf{H(r)CTZ(mod)} \\ \mathbf{[1000\$/cd]} \quad & + \Sigma_{liq} \mathbf{tariff\_liq} * \mathbf{H(r)MPRF(liq)} \\ & + \mathbf{inv\_cst} * \mathbf{E(r)CTXINV} + \mathbf{inv\_cst} * \mathbf{L(r)CTXBLD} \\ [ \quad & + \mathbf{inv\_cst} * \mathbf{E(r)CTZINV} + \mathbf{inv\_cst} * \mathbf{L(r)CTZBLD} \\ & + \Sigma_s \Sigma_r \Sigma_{coal} \mathbf{coal\_cst}_{s,r,coal} * \mathbf{N(r)(coal)N(s)} \end{aligned}$$

where,

$$\mathbf{CgnCredit} = \mathbf{PELIN()} * \mathbf{CFELBK} * \mathbf{CTL\_CGGFAC}$$

(87\$/bbl liq)

$$\mathbf{coal\_cst} = P_o * [ Q / Q_o ]^{elas}$$

(87\$/ton coal)

$$\mathbf{tariff\_liq} = \text{from CMM}$$

(87\$/bbl liq)

$$\mathbf{inv\_cst} = \text{calculated in refine.f from investment data}$$

(87\$/bbl liq)

## Updates to the PMM refine.f code

Three new subroutines (CHGCTLCOEF, PMMCTL\_BLDLIM, and RPTRFCTL) were added, along with other minor changes in the refine.f code to reflect the new CTL capability. Also, a new set of data were added to the rinvest.txt data file (before the GTL data) to define CTL parameters and control flags. The new CTL data are included in the Attachment at the end of this section.

The PMMCTL\_BLDLIM subroutine sets both minimum and maximum build allowances for the CTL. The minimum build represents builds based on government incentives before it is economic to build. This is defined by a forecast series in the rinvest.txt input file (CTL\_PLNBLD) and is associated with the planned CTL unit (CTZ). The maximum build allowance is determined using the Mansfield-Blackman model for market penetration. It tracks the number of units built once it becomes economical to build. This is associated with the mainstream CTL unit (CTX).

The CHGCTLCOEF subroutine updates the relevant CTL coefficients with data provided by the CMM and the EMM. These include the coal supply curve price and quantity levels (and elasticity used to define the coal supply curve), the credit for cogenerated electricity sent to the grid, the tariff for transferring CTL liquids to the refinery, and the adjustment to the coal consumption ratio based on coal heat content. The coal supply curve equation takes the following form:

$$\text{New delivered price of coal} = \left( \frac{\text{LCVTONQ} + \text{delta}}{\text{LCVTONQ}} \right)^{\text{LCVELAS}} * \left( \text{LCVTONP} \right)$$

where,

delta = change in supply curve quantity

LCVTONQ = Coal supply curve production level (mil tons/yr)

LCVTONP = Coal supply curve delivered pr (87\$/ton)

LCVELAS = elasticity fo coal supply curve

The RPTRFCTL report subroutine retrieves CTL solution results from the LP matrix and stores them into special variables -- some are passed to the CMM or to FTAB for reporting, while others are used in the PMM output tables (pmmrpts.txt). These include:

CLMINEP(mnumpr,mnumyr)	! minemouth CTL coal pr
CTL_CGCGD(mnumpr,mnumyr)	! CG cap from CTL--to grid
CTL_CGGGD(mnumpr,mnumyr)	! CG gen from CTL--to grid
P_CTLCOAL(mnumpr,mnumyr)	! PR coal used for CTL (87\$/ton)
Q_CTLCOAL(mnumpr,mnumyr)	! QTY coal used for CTL (M ton/cd)
Q_CTLPRD(mnumpr,mnumyr)	! QTY liquids produced from CTL
QCLRFPD(mnumpr,mnumyr)	! Quantity of coal for CTL (trillion Btu)

RFCTLPRD(mnumpr,mnumyr) ! Quantity of liquids from coal (thousand barrels per day)

Within the existing RFUPD8\_INV subroutine, an adjustment factor (CSTFAC) was added to the CTL costs to account for the added investment costs associated with using lignite and sub-bituminous coals. This adjustment factor is a user input, defined in the rfinvest.txt input file (CTL\_CSTFAC).

In the sprflrt.txt input file, a new set of look-ahead data have been added. These include the prices, quantities, elasticities, and coal transit costs (XLCVTONP, XLCVTONQ, XLCVELAS, XLTRNTON) and the BTU content of the coal (XLCVBTU), provided by the Coal Marketing Module for all regions and years. Thus, the impcurv.txt output file also includes these variables.

(Note: What used to be the COALCOEF was changed to the OGASCOEF for clarity. A CF correction was made to the PUBASE calculation. The cogen from CTL was put into the "other" category in the variables CGREQ, CGRECAP, CGREGEN, but classified as coal for ftab reporting.)

## CTL Data in the rfinvest.txt input file

=====  
PMM input data related to CTLs-- Coal-to-Liquids  
=====

Data: Parameters related to CTL process  
Variables: CTL\_INCBLD -- incremental CTL output levels for building (Mbbld/d)  
CTL\_FSTYR -- first possible start year for facility to come on-line  
CTL\_DCLCAPCST -- annual decline rate for capital recovery costs  
CTL\_DCLOPRCST -- annual decline rate for fixed operating costs  
CTL\_BASHHV -- coal HHV (mmBTU/ton)-- basis used for CTL yields data  
CTL\_BASSIZ -- CTL base size (1000 bbl/cd liq output)  
CTL\_BASCOL -- CTL base coal consump (1000 tons/cd) -- bituminous  
CTL\_BASCGS -- CTL base cogen to self (MW)  
CTL\_BASCGG -- CTL base cogen to grid (MW)  
CTL\_BASCGF -- CTL base cogen capacity factor  
CTL\_NAM -- coal type ID for CTL  
CTL\_CSELAS -- elasticity for coal supply curve, by coal type  
CTL\_CO2FAC -- lbs CO2 emitted/bbl liq produced  
CTL\_CGNFAC -- Fac to est elec cogen to Grid fr CTL (kWh/bbl liq)  
CTL\_CSTFAC -- Fac to adj CTL cap/op cost based on coal type (10% for  
LIG, SUBBIT vs BIT)  
CTL\_CLHHV -- coal HHV (mmBTU/ton)  
P\_CTLTRN -- Cost to transport CTL liq from facility to refinery  
(\$/bbl)  
CTL\_LIQNAM -- Name of liq streams from CTL process  
CTL\_PLNBLD -- CTL planned build series (cum # of units at base size)  
\*\*\*\*Investment info from "Coproduction: A Green Coal Technology" Mitretek  
CTL\_YRCST -- year \$ for investment costs  
CTL\_NFOPCST -- Non-fuel operating costs (MM\$/yr)  
CTL\_CAPREQ -- Total capital requirement (MM\$)  
CTL\_FXREC -- Fixed cost recovery factor (rate)  
\*\*\*\*Mansfield-Blackman model variables\*\*\*\*  
CTLMB\_SW -- switch to apply M-B model to max bld (1=yes)  
CTLBLDX -- max CTL penetration  
IINDX -- innovation index  
PINDX -- relative profitability ratio  
SINVST -- investment ratio

Source: Analyst's judgement  
Notes:

-----  
DOCUMENTATION UPDATES: DATE--AUTHOR--COMMENT  
-----

NOTES:  
04-02-03 em4 CTL BASCGG chg'd fr 696.0 to 465.5 to represent a 46% CHP  
efficiency (vs 60% eff). This was calc'd as follows:  
[ (292 \*696) \* (46% /60%)] - 292 = 465.5  
-----

@  
33.2 CTL\_INCBLD (Mbbld/cd of liq produced)  
2010 CTL\_FSTYR  
0.000 CTL\_DCLCAPCST (fraction)  
0.000 CTL\_DCLOPRCST (fraction)  
23.00 CTL\_BASHHV (mmBtu/ton coal)

33.20	CTL_BASSIZ	(1000 bbl/cd liq produced)
16.40	CTL_BASCOL	(1000 ton/cd coal)
292.0	CTL_BASCGS	(MW per year)
465.0	CTL_BASCGG	(MW per year)
0.900	CTL_BASCGF	(fraction)

@ CTL\_CO2FAC CTL\_CSTFAC

3

CL1E	0.000	1.000
CL2C	0.000	0.800
CL3G	0.000	1.300
CL4M	0.000	0.800
CL5W	0.000	1.100

Source: "Coproduction: A Green Coal Technology" Mitretek

@

1998	!	CTL_YRCST	-- year \$ for investment costs
117.710	!	CTL_NFOPCST	-- Non-fuel operating costs (MM\$/yr)
2161.	!	CTL_CAPREQ	-- Total capital requirement (MM\$)
0.136	!	CTL_FXREC	-- Fixed cost recovery factor (rate)

Source: Memo from Andy S. Kydes, March 23, 2002

"Development of a model for optimistic growth rates for the coal-to-liquids (CTL) technology in NEMS"

@

Parameters for Mansfield-Blackman model for CTL bld series

1	!	CTLMB_SW:	switch to apply M-B model to max bld (1=yes)
300.	!		max number of CTL unit blds allowed (not capacity)
-0.30	!	I:	innovation index
1.25	!	Pr:	relative profitability ratio
2.00	!	SI:	size of investment ratio

Cumulative planned CTL builds (number of CTL units, not capacity)

@

REG	YEAR	NUM	
2	0000	1	end series with 0000 for year

--TEMP CLT -- until coal model is completed

@

	LTRNTON	LCVELAS	LIQUCARB	LIQUSUL	LIQBTU	
CL1E	0.000	1.000	0.000	0.000	25.00	Appalachian Bit
CL2C	0.000	1.000	0.000	0.000	23.00	Ill Basin Bit
CL3G	0.000	1.000	0.000	0.000	23.00	Texas ??
CL4M	0.000	1.000	0.000	0.000	17.38	Powder Riv SubBit
CL5W	0.000	1.000	0.000	0.000	17.38	Powder Riv SubBit

Liquid stream ID's (CTL\_LIQNAM) and

@

transfer costs (P\_CTLTRN)

4

	CL1E	CL2C	CL3G	CL4M	CL5W
CNL	1.500	1.500	1.500	1.500	1.500
CNP	1.500	1.500	1.500	1.500	1.500
CKE	1.500	1.500	1.500	1.500	1.500
CDX	1.500	1.500	1.500	1.500	1.500

=====

## F.19 Petroleum Coke Gasification Representation in PMM

The coke gasification processing unit represented in the PMM was designed by NETL, as described in their document to EIA, "Refinery Technology Profiles: Gasification and Supporting Technologies," June 2003.<sup>32</sup> NETL carried out extensive research on the gasification process and the PMM model design to generate data tables that realistically represented the coke gasification process (with a combined heat/power (CHP) option) that fit into the PMM process data structure. The data tables were reviewed and modified slightly by EIA to better integrate it into the PMM LP structure. The original design allowed either petroleum coke feed or asphalt feed; however, only the coke feed design was adapted into the PMM due to competition issues between the coke and asphalt feeds.

The new coke gasification unit is designed to gasify high sulfur petroleum coke to produce either synthetic gas (SGS) or hydrogen (and synthetic gas). In order to properly represent the difference in investment costs between hydrogen and syngas production, separate gasification units are modeled in the LP (identified as GSH and GSF, respectively). The product hydrogen is put into a pool stream to be used by other processing units at the refinery. The product synthetic gas (with natural gas backup) is routed through a combined heat and power (CHP) unit to produce both steam and electricity, or electricity only. Based on NETL research, the CHP unit assumes a syngas to natural gas consumption ratio of 90:10 during a typical year. Also, a grid/self split was defined in the PMM input files to track the destination of cogen electricity produced by the CHP. The byproduct H<sub>2</sub>S is also produced for all options and sent to an H<sub>2</sub>S pool.

The design size of the coke gasification unit was set to 2000 short tons coke feed per calendar day (s-tons/cd), at an ISBL cost of \$160MM (syngas) and \$194MM (hydrogen), in 1993\$. The ISBL cost for the CHP was set to \$134.9MM (1993\$), for a standard 8.11 bbl FOE/cd (2044 MM BTU/cd) syngas/natural gas throughput. NETL also provided regional starting capacity for the coke gasification units (see below). These levels were used to establish initial capacity for the CHP units, where applicable. The capacity factor (or utilization rate) was assumed to be 0.85 for the gasification units, and 0.96 for the CHP unit.

### *Starting CTL Unit Capacities by PADD*

	I	II	III*	IV	V	
GSF	2.10	0.17	5.05	0.00	0.00	(M s-tons/cd)
GSH	0.00	1.10	0.00	0.00	0.00	(M s-tons/cd)
CHP	8.03	1.06	10.0	0.00	0.00	(M bblFOE/cd)

\* minimally defined capacity to prevent infeasibility

<sup>32</sup> Hohn, Marano, Ph.D., "Refinery Technology Profiles: Gasification and Supporting Technologies," National Energy

## Mathematical Representation of Coke Gasification Process in the PMM

The coke gasification process added to the PMM consumes high sulfur petroleum coke (CKH-- typically from the delayed or fluid coker at the refinery) and produces hydrogen (HH2) and/or syngas (SGS) [and some hydrogen sulfide (H2S)]. The HH2 and H2S are consumed or processed at the refinery, while the SGS (with natural gas as the backup fuel 10% of the year) is sent to the combined heat/power (CHP) unit to generate steam (STM) and/or electricity (KWH). Some of the electricity is sold to the grid, with the remaining consumed at the refinery. The LP variables and constraints created or modified to represent this entire process are presented below:

Definitions (**bold** means new):

<b>GSF</b>	= coke gasifier unit producing synthetic gas
<b>GSH</b>	= coke gasifier unit producing hydrogen
<b>CHP</b>	= combined heat and power unit
<b>CK1, CK2</b>	= operating modes for coke gasifier units
<b>CKH</b>	= high sulfur petroleum coke
<b>SGS</b>	= synthetic gas
NGS	= natural gas
HH2	= hydrogen
H2S	= hydrogen sulfide
FUL	= combined fuel pool
KWH	= electricity
STM	= steam
OVC	= variable operating costs
FXOC	= fixed operating costs
INVST	= capital investment costs
OBJ	= objective function row
R-var	= LP column variable for unit operating level
X-var	= LP column variable representing coke sent to meet demand
K-var	= LP column variable for unit operating level of initial capacity
E-var,L-var	= LP column variable for unit operating level of new capacity
m, mod	= operating mode
c	= coefficient (all unique values)
r	= PMM refinery regions (Padd)
d	= Census demand regions

---

Technology Center, for DOE/EIA, June 2003.

*Stream/Utility Balance Rows:*

These constraints require the supply levels for a stream to equal the demand levels for that stream, within each refinery region (r). This applies to coke (CKH), syngas (SGS), natural gas (NGS), hydrogen (HH2), hydrogen sulfide (H2S), fuel (FUL), electricity (KWH), and steam (STM). The only entirely new stream balance row is for syngas.

$$\begin{aligned}
 \text{B(r)CKH:} & \quad \Sigma_m c^*R(r)KRD(mod) - R(r)GSFCK1 \\
 \text{[M s-ton/cd]} & \quad +\Sigma_m c^*R(r)KRF(mod) - R(r)GSHCK2 \\
 & \quad - c^* X(r)CKHCOK = 0
 \end{aligned}$$

$$\begin{aligned}
 \text{B(r)SGS:} & \quad c^* R(r)GSFCK1 - \Sigma_m c^*R(r)CHP(mod) \\
 \text{[M bbl FOE/cd]} & \quad +c^* R(r)GSHCK2 = 0
 \end{aligned}$$

$$\begin{aligned}
 \text{B(r)NGS:} & \quad \dots - \Sigma_m c^*R(r)CHP(mod) = 0 \\
 \text{[M bbl FOE/cd]} &
 \end{aligned}$$

$$\begin{aligned}
 \text{B(r)HH2:} & \quad \dots + c^* R(r)GSHCK2 = 0 \\
 \text{[M bbl FOE/cd]} &
 \end{aligned}$$

$$\begin{aligned}
 \text{B(r)H2S:} & \quad \dots + c^* R(r)GSFCK1 + c^* R(r)GSHCK2 = 0 \\
 \text{[M bbl FOE/cd]} &
 \end{aligned}$$

$$\begin{aligned}
 \text{B(r)FUL:} & \quad \dots - c^* R(r)GSHCK2 = 0 \\
 \text{[M bbl/cd]} &
 \end{aligned}$$

$$\begin{aligned}
 \text{U(r)KWH:} & \quad \dots - c^* R(r)GSFCK1 - c^* R(r)GSHCK2 \\
 \text{[M kWh/cd]} & \quad + \Sigma_m c^*R(r)CHP(mod) = 0
 \end{aligned}$$

$$\begin{aligned}
 \text{U(r)STM:} & \quad \dots - c^* R(r)GSFCK1 - c^* R(r)GSHCK2 \\
 \text{[M lb/cd]} & \quad + c^*R(r)CHPCO1 = 0
 \end{aligned}$$

*capacity expansion/investment rows:*

New capacity constraints are defined for the GSF, GSH, and CHP units. These constraints require the total operating level of each unit to be less than or equal to the total available capacity (existing + new). The accounting row (A(r)CHPCGN) keeps track of total electricity generated by the CHP unit in each refinery region. The P(r)OVC row accumulates the OVC for each processing unit (defined in 2000 year dollars) and uses the variable T(r)OVCOBJ to convert to 87\$ and put into the objective function. The FXOC and

INVST rows are accounting rows for PMM reports. The objective function row (OBJ) includes the investment costs for the new processing units.

$$\begin{aligned}
 L(r)GSFCAP: & \quad c^* R(r)GSFCK1 - K(r)GSFCAP \\
 [M \text{ s-tons/cd}] & \quad - c^* E(r)GSFINV - c^* L(r)GSFBLD \leq 0
 \end{aligned}$$

$$\begin{aligned}
 L(r)GSHCAP: & \quad c^* R(r)GSHCK2 - K(r)GSHCAP \\
 [M \text{ s-tons/cd}] & \quad - c^* E(r)GSHINV - c^* L(r)GSHBLD \leq 0
 \end{aligned}$$

$$\begin{aligned}
 L(r)CHPCAP: & \quad \sum_m c^* R(r)CHP(mod) - K(r)CHPCAP \\
 [M \text{ bbl FOE/cd}] & \quad - c^* E(r)CHPINV - c^* L(r)CHPBLD \leq 0
 \end{aligned}$$

$$\begin{aligned}
 A(r)CHPCGN: & \quad \sum_m c^* R(r)CHP(mod) && \text{(accounting row)} \\
 [M \text{ kWh/cd}] & &&
 \end{aligned}$$

$$\begin{aligned}
 P(r)OVC: & \quad \dots - c^* R(r)GSFCK1 - c^* R(r)GSHCK2 \\
 [M \$2000/cd] & \quad - \sum_m c^* R(r)CHP(mod) + c^* T(r)OVCOBJ = 0
 \end{aligned}$$

$$\begin{aligned}
 A(r)FXOC: & \quad \dots + c^* E(r)CHPINV + c^* L(r)CHPBLD && \text{(accounting row)} \\
 (A@FXOC, \Sigma_r) & \quad + c^* E(r)GSFINV + c^* L(r)GSFBLD \\
 [M \$87/cd] & \quad + c^* E(r)GSHINV + c^* L(r)GSHBLD
 \end{aligned}$$

$$\begin{aligned}
 A(r)INVST: & \quad \dots + c^* E(r)CHPINV + c^* E(r)GSFINV && \text{(accounting row)} \\
 (A@INVST, \Sigma_r) & \quad + c^* E(r)GSHINV \\
 [M \$87/cd] & &&
 \end{aligned}$$

$$\begin{aligned}
 OBJ: & \quad \dots \Sigma_r [ - c^* E(r)CHPINV - c^* L(r)CHPBLD \\
 [M \$87/cd] & \quad - c^* E(r)GSFINV - c^* L(r)GSFBLD \\
 & \quad - c^* E(r)GSHINV - c^* L(r)GSHBLD \\
 & \quad + \sum_m c^* R(r)CHP(mod) ]
 \end{aligned}$$

*Bounds put on the following variables:*

The initial capacity for each of the new processing units are defined as upper limits on the K-variables. Added capacity for the new units are set as bounds on the E-variables (capacity added this year) and on the L-variables (accumulated capacity added in previous years).

$$[M \text{ s-ton/cd}] \quad K(r)GSFCAP \quad E(r)GSFINV \quad L(r)GSFBLD$$

[M s-ton/cd]	<i>K(r)GSHCAP</i>	<i>E(r)GSHINV</i>	<i>L(r)GSHBLD</i>
[M bbl FOE/cd]	<i>K(r)CHPCAP</i>	<i>E(r)CHPINV</i>	<i>L(r)CHPBLD</i>

### Updates to the PMM Fortran code

In addition to updating the LP matrix structure, various PMM code changes were needed for proper accounting and reporting, as well as for model consistency and stability. First, for FTAB reporting, the resulting cogen electricity production levels were categorized as grid vs self, and put into fuel type accounting totals. The variable used to define the regional grid vs self split is the same one used for other cogen accounting in the PMM: CGPCGRDPD(r). In addition, the following new inputs were added to the rfinvest.txt file to help with the cogen accounting.

<b>CHPCC1</b>	<b>= 992</b>	kWh/bbl FOE processed for mode CC1
<b>CHPCO1</b>	<b>= 722</b>	kWh/bbl FOE processed for mode CO1
<b>NGSCHP</b>	<b>= 0.10</b>	natural gas fraction fed to CHP

These values *must* be consistent with the KWH and the natural gas coefficients defined in the refproc.dat file in the T:CHP data table.

In addition, a new subroutine (PMM\_COKGSF) was created in the refine.f code to transfer model results to report variables. Coke and natural gas consumption, syngas and hydrogen production, and electricity and steam production levels were processed into a PMM report table (48a). The report variables include:

QCOKPRD(3,r,yr)	M s-ton/cd
QASTPRD(3,r,yr)	M bbl FOE/cd
QSGSPRD(r,yr)	M bbl FOE/cd
QHH2PRD(r,yr)	M bbl FOE/cd
QKWHPRD(2,r,yr)	M kWh/cd
QSTMPRD(r,yr)	M lb/cd
QNGSPRD(2,r,yr)	M bbl FOE/cd

Finally, a special algorithm was defined to establish a pet coke export price that better matches historical levels of 45\$/ton in 2001 dollars (~6\$/bbl FOE in 1987 dollars) and to model an expected 5-10% decline rate. This is currently hard-coded in refine.f, subroutine CHGCKSU. Ultimately, the coke export price should be keyed off of coal prices. This will be designed and incorporated at a later date.

## **APPENDIX G**

### **Matrix Generator Documentation**

# APPENDIX G. Matrix Generator Documentation

## G.1 Introduction

The purpose of this appendix is to describe the program which runs the Multi-Refining Model (MRM) (5-regions); and to provide detail on how it works. The program allows the user to simulate a 5-region (MRM) representation of the entire refining industry in the United States.

The MRM models multiple refinery regions within the entire United States. The MRM is a collection of five single refinery regions linked by a transportation network. The regions are defined by the five U.S. Petroleum Administration for Defense Districts (PADDs). The MRM simulates the operation of petroleum refineries in the United States, including the supply and transportation of crude oil to refineries, the regional processing of these raw materials into petroleum products, and the distribution of petroleum product to meet regional demands. The model identifies sources of supply for domestic and imported crude oils, alcohols, biofuels, ethers and natural gas. In addition to these quantities, the MRM projects petroleum product prices, refinery fuel consumption, and capacity expansion in each PADD. The 5-region MRM models the five U.S. PADDs, labeled as follows: E = PADD I, C = PADD II, G = PADD III, M = PADD IV, W = PADD V.

The program generates the matrix for the linear programming model representation of the MRM, solves it, writes the solution, and packs the matrix for use by the analyst using the ANALYZE software.

## G.2 Code

The program is written in Fortran and makes use of the OML (Optimization and Modeling Libraries) to read in the data files, to generate the matrix representation of the model, to solve the problem, to store the solution, and to pack the matrix for use with ANALYZE. In addition to the above, the program produces a report.

The program is data driven and the user provides key information, such as, the model chosen to be run, the location of the input data files, and some other options.

### G.2.a Variables and Constraints

The model consists of variables or activities (columns), constraints (rows), and bounds on activities. A unique name has been assigned to each variable and constraint. In the naming of the variables and rows, indices are used. The following table displays the index set name and the number of elements in the set, gives a brief description of the set, and provides a partial listing of the set members.

<b>Index</b>	<b>No. of Values</b>	<b>Description</b>	<b>Members</b>
@	1	represents all regions	@
c	2	Constraint type	X: for max N: for min
d	9	Census divisions	1: New England 2: Mid Atlantic 3: East North Central 4: West North Central 5: South Atlantic 6: Est South Central 7: West South Central 8: Mountain 9: Pacific
e	2	Emission source	C: Emission from fuel combustion N: Emission from process unit (non-combustion)
m	16	Transportation mode, function of material and means of movement	4: U.S. flag residual oil (dirty tanker) W: crude pipeline from supply reg 3 to PADD III B: Barge light products (clean barge) I: West Texas to PADD II J: U.S. flag light products (clean tanker) M: Aggregate/avg rail, truck, vessel, barg for ETH O: U.S. flag LPG R: PADD III loop to PADD II S: PADD III capeline to PADD II T: Light product pipeline U: LPG, C4, CC5 pipeline V: Barge residual oil (dirty barge) X: Local transportation Y: Pipeline PADD II to demand region 6 Z: Pseudo link A: LOOP to PADD II
o	7	OGSM regions	1: OGSM 1 North East + OGSM 7 Atlantic 2: OGSM 2 Gulf Coast + OGSM 8 Gulf Offshore 3: OGSM 3 Midcontinent 4: OGSM 4 Permian Basin 5: OGSM 5 Rocky Mountain 6: OGSM 6 West Coast + OGSM 9 Pacific A: OGSM A Alaska North
r	5	Refining regions	E: PADD I C: PADD II G: PADD III M: PADD IV W: PADD V
t	2	Type of transportation	V: Vessel P: Pipeline

<b>Index</b>	<b>No. of Values</b>	<b>Description</b>	<b>Members</b>
x	5	Exporting regions	2: Export cd for PADD I (region E, cd 2) 3: Export cd for PADD II (region C, cd 3) 7: Export cd for PADD III (region G, cd 7) 8: Export cd for PADD IV (region M, cd 8) 9: Export cd for PADD V (region W, cd 9)
Nn	3	Negative shift in demand	N1, N2, N3
On	8	Natural Gas refinery supply steps	N1, N2, N3, N4, P5, P6, P7, P8
Pn	3	Positive shift in demand	P1, P2, P3
qm	11	Quality code for gasoline blending	AR: Aromatics BZ: Benzene E2: E 200 E3: E 300 M0: Motor octane PO: Percent oxygen OL: Olefine R0: Research octane RV: Reid vapor pressure SL: Sulfur RE: renewables component (due to required minimum contribution to oxygenates)
qd	7	Quality code for distillate	AR: Aromatics FL: Flash point FZ: Freezing point GR: Gravity LM: Luminometer number SL: Sulfur VB: Viscosity
Qs	3	Step label for crude oil imports	Q1, Q2, Q3
Rs	9	Step label for product imports	R1, ..., R9
S1	1	Step label for product demands	S1
SX	1	Product exports	SX
Z9	1	Distress imports and exports	Z9
col	5	Coal type used for CTL processing	CL1: 100% N. Appalachian CL2: 100% Eastern Interior CL3: 100% Powder and Green River Basin CL4: 50% Dakota Lignite 50% Powder and Green River Basin CL5: 100% Powder and Green River Basin

<b>Index</b>	<b>No. of Values</b>	<b>Description</b>	<b>Members</b>
crt	12	Crude groups by quality and origin	ALL: Alaskan, API 25-66, S<0.5, B<15 AMH: Alaskan, API 21-32, S<1.1, B>15 DLL: Domestic, API 25-66, S<0.5, B<15 DMH: Domestic, API 21-32, S<1.1, B>15 DHL: Domestic, API 29-56, S<1.99, B<15 DHH: Domestic, API 23-35, S<3.0, B>15 DHV: Domestic, API<23, S>0.7, B>15 FLL: Foreign, API 25-66, S<0.5, B<15 FMH: Foreign, API 21-32, S<1.1, B>15 FHL: Foreign API 29-56, S<1.99, B<15 FHH: Foreign, API 23-35, S<3.0, B>15 FHV: Foreign, API<23, S>0.7, B>15
dfo	6	Distillate fuel oil blends	JTA: Jet fuel N2H: Number 2 oil DSL: Low sulfur diesel DSU: Ultra low sulfur diesel N6I: Low sulfur resid N6B: High sulfur resid
emu	6	Emission type	CAR: Total carbon CO1: Carbon monoxide CO2: Carbon dioxide NOX: Nitrous oxides SOX: Sulfur oxides VOC: Volatile organic compounds
ist	834	Refinery intermediate streams	LNI: Light naphtha, (175-250) intermediate LNN: Light naphtha, (175-250) naphthenic LNP: Light naphtha, (175-250) paraffinic
mgb	2	Gasoline blends	TRG: Conventional gasoline RFG: Reformulated gasoline
gbt	12	Gasoline blending component type	G01: Butanes (NC4-I4E) G02: Naphthas ( NAT-LNN) G03: Reformates (R80-V10) G04: FCC Gasolines (LF6-85H) G05: Other (C5E-R6E,ISO-HRA) G06: HCR Gasolines (LHG-MHV) G07: Alkylates (ALN-HAL) G08: Ethanol (ETH) G09: Ethanol Ethers (TAE,THEE) G10: Ethylbenzene (ETBE) G11: MTBE (MTB) G12: Methanol Ethers (TAM,THM)
mod	many	Operating mode	C2A: Ethyl alkylate C3A: Propyl alkylate C4A: Butyl alkylate

<b>Index</b>	<b>No. of Values</b>	<b>Description</b>	<b>Members</b>
ncr	12	Non crude purchase	ARB: Atmospheric resid of type B (unf oils) BIM: Biomas diesel (virgin oil, renewable) BIN: Biomas diesel (non virgin oil, renewable) CC3: Propane (gas plant) ETH: Ethanol (renewable) HGM: Heavy gas oil medium sulfur (unf oils) IC4: Isobutane (gas plant) MET: Methanol (methanol plant) MTB: M.T.B.E. (oxygenate) NAT: Natural gasoline (gas plant) NC4: Normal butane (gas plant) NPP: Paraffinic naphtha (unf oils)
pol	34	Policy type	LOS: Lost OVC: Other variable cost MSD: Maximum distillation feed, cat cracker MSR: Maximum low sulfur resid, cat cracker SVR: Maximum severity, cat cracker H00: Maximum 100 severity, HP reformer H05: Maximum 105 severity, HP reformer
prd	20	Products	AST: Asphalt COK: Coke DSL: Low sulfur diesel DSU: Ultra low sulfur diesel E85: 85% Ethanol and 15% TRG JTA: Jet fuel KER: Kerosene LPG: Liquefied petroleum gas M85: 85% Methanol and 15% TRG N2H: Number 2 oil N67: Low sulfur resid to utilities N68: High sulfur resid to utilities N6B: High sulfur resid N6I: Low sulfur resid OTH: Other PCF: Petrochemical feed stock RFG: Reformulated gasoline RFH: Reformulated high oxygen gasoline TRG: Conventional gasoline TRH: Conventional high oxygen gasoline
pri	14	Product imports	DSL, DSU, JTA, LPG, MET, MTB, N2H, N6B, N6I, OTH, PCF, RFG, TRG, SSR
prx	11	Product exports	COK, DSL, DSU, JTA, LPG, N2H, N6B, N6I, OTH, PCF, TRG
px9	17	Distress exports	AST, COK, DSL, DSU, JTA, LPG, N2H, N67, N68, N6B, N6I, OTH, PCF, RFG, RFH, TRG, TRH
pi9	19	Distress imports	AST, COK, DSL, DSU, E85, JTA, LPG, M85, N2H, N67, N68, N6B, N6I, OTH, PCF, RFG, RFH, TRG, TRH

<b>Index</b>	<b>No. of Values</b>	<b>Description</b>	<b>Members</b>
ss	3	Sub-Spec Products	SSR: Sub-spec Reformulated gasoline (RBOB) SST: Sub-spec High Oxygenate gasoline BOB SSE: Sub-spec Conventional gasoline TBOB
unf	3	Unfinished oil	ARB: Atmospheric residual bottom type B HGM: Heavy gas oil medium sulfur NPP: Medium naphtha paraffin
uns	86 (mrm)	Process unit	ACU: Atmospheric crude distillation See Appendix A.3.9 for complete list of processes
uuu	3	Utility	KWH: Kilo-watt hour NGF: Natural gas liquids STM: Steam

In the naming of the columns and rows, the limit is a maximum of eight characters per name. The following two tables give the name of the variable (activity) and the row (constraint) represented.

The general name structure for columns is (v)(r)(abc)(def), where v is key code, r is region code, abc and def are 3 character names.

<b>Name</b>	<b>Activity Represented</b>
B(r)(mgb)(ist)	Blend stream (ist) to gasoline grade (mgb) in (r)
C(d)ETCR(s)	Ethanol from cellulose supply step (s) in (d)
C(d)ETHR(s)	Ethanol from corn supply step (s) in (d)
C(d)BIMR(s)	Virgin oil biomas diesel supply step (s) in (d)
C(d)BINR(s)	NonVirgin oil biomas diesel supply step (s) in (d)
D@METS1	Total US chemical methanol demand
D(d)(prd)S1	Product (prd) demand in (d)
D(d)(prx)SX	Product (prx) exports from (d)
D(d)(px9)Z9	Distress product (px9) export from (d)
E(r)(uns)INV	Investment in new capacity for process (uns) in (r)
F(r)(dfo)(ist)	Blend stream (ist) to distillate fuel oil (dfo) in (r)
G(r)(ist)(prd)	Gas plant output transfer of stream (ist) to product (prd) in (r)
G(r)DGR	Dry gas exiting gas plant in (r)
G(r)GPL01	Gas plant operations in (r)
G(r)(ist)RFN	Transfer of gas plant stream (ist) to refinery in (r)

Name	Activity Represented
G(r)RFNMET	Transfer of methanol from refinery to meet export demands in refinery in (r)
G(r)SC2CC1	Shift of ethane to natural gas in gas plant in (r)
G(r)SC3CC1	Shift of propane to natural gas in gas plant in (r)
G(r)MOH01	Methanol plant operations in (r)
G(r)METDEM	Methanol production from methanol plant in (r) to chemical industry
G(r)METRFN	Methanol production from methanol plant in (r) to refinery
H(r)(uns)(mod)	Production from process (uns) in operating mode (mod) at merchant, CTL, or GTL plant in (r)
H(r)(aa)(bb)(ist)*	Transfer from (aa) to (bb) of stream (ist) in (r)
I(d)(pi9)Z9	Distress product (pi9) imports to (d)
I(r)(pri)R(s)	Imported product (pri) step (s) to region (r)
K(r)(uns)CAP	Existing capacity for process (uns) in (r)
L(r)(uns)BLD	Cumulative addition to capacity for process (uns) in (r)
N(r)DGP	Dry gas supply in (r)
N(r)(col)N(s)	Coal (col) supply curve step (s) for CTL processing for region (r)
N(r)NGKN(s)	Alaska NG supply curve step (s) for GTL processing for region (r)
N(r)NGRF(On)	Natural gas to refinery supply step (On) in (r)
NZAMH(On)	Export supply step (On) for Alaskan crude
O@CRDEXP	Alaskan crude exports
O@CRDSPR	SPR fill in US
P(o)DCRQ1	Domestic crude in (o)
P(r)(crt)(Qs)	Supply step (Qs) of imported crude (crt) to (r)
PANGLQ1	Supply of natural gas liquids from Alaska North slope
Q(r)(mgb)	Spec vector, total volume of (mgb) produced in (r)
Q(r)(dfo)	Spec vector, total volume of (dfo) produced in (r)
R(r)ACU(crt)	Volume of crude (crt) processed by the ACU unit in (r)
R(r)(uns)(mod)	Refinery process (uns) operation for mode (mod) in (r)
R(r)CGNCGN R(r)CGXCGN	Refinery (CGN) and Merchant (CGX) cogeneration plant operation in region (r)
T(r)(ist)(ist)	transfer of stream (ist) to stream (ist) in (r) ;
T(r)(ist)(prd)	transfer of stream (ist) to product (prd) in (r)

Name	Activity Represented
T@UNFTOT T(r)UNF(ist)	Total unfinished oils in US Unfinished oils from stream (ist) in region (r) [regions E,B only]
TAALLTOT	Total Volume of ALL crude produced in Alaska
TAAMHTOT	Total Volume of AMH crude produced in Alaska
TAAMHXZ	Volume of AMH crude transported from Alaska to Valdez
TAGTLTOT	Total volume of GTL's transported from Alaska N. Slope to Valdez along TAPS
TANSOTOT	Total volume of crude transported from Alaska N. Slope to Valdez along TAPS
T(r)CBNTAX	Carbon tax in (r)
T(r)OVCOBJ	Refinery plant operating variable costs in region (r)
T(r)GPLOVC	Gas plant operating variable costs in region (r)
T(r)MCHOVC	Merchant plant operating variable costs in region (r)
U(r)(uuu)	Utility (uuu) purchased in (r)
VTPC(r)(m)(d)	Crude pipeline transportation capacity from (r) to (d) using mode (m)
VTPL(r)(m)(d)	LPG pipeline transportation capacity from (r) to (d) using mode (m)
VTPP(r)(m)(d) VTPP(d)(m)(r)	Product pipeline transportation capacity from (r) to (d) using mode (m) or from (d) to (r)
VTVC(m)CP	Crude vessel transportation capacity for mode (m)
VTVP(m)CP	Product vessel transportation capacity for mode (m)
WAGTLJ(r)	GTL transportation from Alaska (A) to region (r) using mode J
W(r)(prd)(m)(d) W(d')(prd)(m)(d)	Product (prd) transportation from (r) to (d) or from (d') to (d), using mode (m)
W(d)(ncr)(m)(r)	Ethanol or Biomass diesel (ncr) transportation from (d) to (r) using mode (m)
X(d)(prd)SPG	Recipe blends of product (prd) for oxygenated fuels and electric utility residual oils in (d)
X(r)(ist)(prd)	Recipe blends of product (prd) from stream (ist) in region (r)
X(d)(ncr)(prd)	Splash blending of (prd) from (ncr) in (d)
X(r)(yyyy)**	Recipe blends (yyyy) in region (r)
Y(o)(crt)(m)(r) Y(r')(crt)(m)(r)	Crude (crt) transportation from (o) to (r) or from (r') to (r), using mode (m)
Z(d)ETCTAX	Total supply of ethanol from cellulose in (d) for adding tax credit to objective function
Z(d)ETHTAX	Total supply of ethanol from corn in (d) for adding tax credit to objective function
Z(r)FLO(uns)	Total flow through processing unit (uns) in region (r)

Name	Activity Represented
Z(r)RFGOXY	Total OXY in RFG in region (r)
Z@TOTCRD	Total foreign crude imports
ZZAMHTOT	Total export volume of Alaskan crude oil

\* : (aa), (bb) = MP, GP, RF, where MP = Merchant plant, GP = Gas plant, RF = Refinery. For (ist), first and last character of (ist).

\*\* : (yyyy) = recipe blends for categories of products such as AST, PCF, OTH.

The general name structure for rows is: (v)(r)(abc)(def), where v is key code, r is region code, abc and def are 3 character names.

Name	Constraint Represented
A(d)(prd)	Product demand accounting row in (d) for (prd)
A@1YRBLD	New ACU capacity added in a look-ahead year
A(r)(prd)	Refined product (prd) accounting row in (r)
A@AKAEXP	Accounting row for Alaskan crude oil exports from US
A(d)BIMPRD	Biomass diesel virgin oil accounting row in (d)
A@BIMPRD	and total US (@)
A(d)BINPRD	Biomass diesel non-virgin oil accounting row in (d)
A@BINPRD	and total US (@)
A(r)CHPCGN	Accounting row for combined heat/power from pet coke gasification in (r)
A@COKEXP	Accounting row for petroleum coke exports from US
A@CRDAKA	Alaskan crude oil accounting row in US
A@CRDDCR	Domestic crude oil accounting row in US
A@CRDEXP	Crude oil export accounting row in US
A(r)CRDFCR	Foreign crude oil accounting row in (r)
A@CRDFCR	and US
A(r)CRDIMP	Total crude imported into region (r) in US
A@CRDIMP	Total crude imported into US
A@CRDL48	Lower 48 crude oil accounting row in US
A@CRDSPR	SPR crude oil accounting row in US
A@CRDTOT	Total crude oil accounting row in US
A(r)CRX(crt)	Crude oil (crt) accounting row in (r)

<b>Name</b>	<b>Constraint Represented</b>
A(r)DSLCTI	Average cetane in DSL (low sulfur diesel), in region (r)
A(r)DSUCTI	Average cetane in DSU (ultra-low sulfur diesel), in region (r)
A@ETCPRD	Accounting row for total ethanol from cellulose in US
A@ETHPRD	Accounting row for total ethanol from both corn and cellulose in US
A(d)ETHTAX	Ethanol tax credit accounting row in (d)
A(d)ETCTAX	
A(d)ETH	Accounting row for ethanol supply from (d) from both corn and cellulose
A@ETHE85	Total E85 produced by refineries in US
A@ETHRFG	Accounting of total ethanol blended into RBOB for RFG in US
A@ETHRFH	Accounting of total ethanol blended into RBOB for RFH in US
A@ETHTRG	Accounting of total ethanol blended into TRG (for SSE) in US
A@ETHTRH	Accounting of total ethanol blended into TBOB for TRH in US
A(r)ETHRFN	Ethanol to refinery accounting row in (r)
A(r)FUEL	Refinery fuel use accounting row in (r)
A@FUEL	and US
A(r)FUM(xx)	FUM accounting row in (r) for fuel type (xx)
A@FUM(xx)	and US
A(r)FXOC	Fixed cost accounting row in (r)
A@FXOC	and US
A(d)GO8(yyy)	Gasoline blending accounting row in (d) for mogas (yyy)
A(r)G(gbt)(xxx)	Gasoline blend component type (gbt) accounting row in (r) for mogas (xxx);
A@G(gbt)(xxx)	US total
A(r)GAIN	Process gain accounting row in (r)
A@GAIN	and US
A(r)GPLLPG	Accounting of LPG from gas plant in (r)
A(r)GPLOTH	Accounting of Natural Gasoline from gas plant in (r) to products OTH, PCF
A(r)GPLPCF	
A(r)INVST	Investment accounting row in (r)
A@INVST	and US
A@KWHRFN	Accounting of refinery KWH usage in US
A@(xx)FU	Limit on fuel type xx consumed as refinery fuel in US (xx=LPG,OTH,RES,STG)
A@METDEM	Methanol demand accounting row in US
A(r)METIMP	Methanol imports accounting row in (r);
A@METIMP	US total
A@METM85	Accounting of methanol used for M85 splash blending in US

<b>Name</b>	<b>Constraint Represented</b>
A@METPRD	Methanol production accounting row in US
A(r)METRFN	Accounting of methanol consumption by ETH refinery unit in (r)
A(r)MTBIMP A(@)MTBIMP	MTB refinery imports accounting row in (r) and US
A(r)MTBRFN	MTB refinery imports accounting row in (r)
A@MTBPRD	MTB production accounting row in US
A(r)NGFTOT A@NGFTOT	Natural gas purchase accounting row in (r); US total
A(r)NGLRFN A@NGLRFN	Accounting of NGL transfer from gas plant to refinery in (r); US total
A(r)NGLPRD A@NGLPRD	NGL accounting in (r); US total
A(r)NGSH2P A@NGSH2P	Accounting of NGS consumption by H2P refinery unit in (r); US total
A(r)NGSMER A@NGSMER	Accounting of methanol transfer from methanol plant to refinery in (r); US total
A(r)NGSMET A@NGSMET	Methanol plant production accounting row in (r); US total
A(r)NGSRFN	Accounting of purchased NG to refinery NGS stream in (r)
A(r)PETCOK A@PETCOK	Accounting of high & low sulfur coke production at refinery in (r) and US total
A(x)PRDEXP A@PRDEXP	Product export accounting row in (x) and US total
A@PRDDEM	Accounting of total product demand in US
A(r)PRDIMP A@PRDIMP	Product import accounting row in (r)
A@PRDRFN	Accounting of total product produced at refinery
A(d)RFG(yyy) A(d)TRG(yyy)	Gasoline blending accounting row in (d) for mogas (yyy)
A(r)RFGM00 A(r)RFGR00	Total motor (and research) octane in the reformulated (RFG) mogas stream in refining region (r), based on contribution from each component blend stream.
A(r)TRGM00 A(r)TRGR00	Total motor (and research) octane in the conventional (TRG) mogas stream in refining region (r), based on contribution from each component blend stream.
A(r)SULSAL A@SULSAL	Accounting of sulfur production in (r) and US total
A(r)UNFIMP A@UNFIMP	Unfinished oil imports into (r) and US total

<b>Name</b>	<b>Constraint Represented</b>
A@ZZEXP	Total distress exports
A@ZZIMP	Total distress imports
B(r)(ist)	Balance for intermediate stream (ist) in (r)
C(o)(crt)	Crude balance for crude type (crt) in (o)
C(r)(crt)	Crude balance for crude type (crt) in (r)
CAALLTOT CAAMHTOT	Balance for Alaska crude type ALL and AMH
C@ETHBIO	Minimum renewables requirement in gasoline (national)
C(r)CTLTOT	Balance for CTL's produced in region (r)
CAGLTOT	Balance for GTL's produced in Alaska
CANSOTOT	Balance for Alaska N. Slope crude
C(r)GTL	Balance for GTL's transported from Alaska to region (r)
CZAMH	Alaskan crude exports
D(d)(prd)	Final demand for product (prd) in (d)
D(d)ETH D(d)BIM D(d)BIN	Final supply of renewables ETH, BIM, BIN in (d)
D@MET	Total demand for methanol
E(r)(emu)(e)	Emission of (emu) from source (e) in (r)
F@TOTCRD	Total crude balance for unfinished oil constraint in US
F(r)UNF(unf)	Unfinished oil balance for (unf) in (r)
G(r)(ist)	Gas plant balance for stream (ist) in (r)
G(r)(pol)	Gas plant policy (pol) accounting row in (r)
G(r)PGSLGX	Limit on transfer of PGS to LPG at Gas Plant in (r)
G(r)SC2C1X	Limit on transfer of CC2 to CC1 at Gas Plant in (r)
H(r)(ist)	Merchant oxygenate plant balance row for (ist) in (r) and off-site GTL and CTL balance row for (ist) in (r)
H(r)FUMCAP	Merchant oxygenate fuel balance row in (r)
H(r)(pol) H(r)(uuu)	Merchant oxygenate plant policy (pol) or utility (uuu) accounting row in (r) (pol) = stm, kwh, los, ovc
L(r)(uns)CAP	Process (uns) capacity in (r)
M(r)(prd)	Final product (prd) demand balance at refinery (r)

<b>Name</b>	<b>Constraint Represented</b>
M(d)(prd)	or CD (d)
M(r)MTBRFG	MTBE (and other ethers) limit in RFG motor gasolines in (r)
M(r)MTBTRG	MTBE (and other ethers) limit in TRG motor gasolines in (r)
O(o)(crt)	Domestic crude oil (crt) accounting in (o)
OBJ	Objective function
P(r)(pol)	Policy (pol) constraint in (r)
P(r)CBNTAX	Carbon tax accounting row in (r)
Q(r)(prd)(qd)(c)	Product (prd) specification for quality (qd) constraint type (c) in (r)
Q(r)(prd)(qm)(c)	Product (prd) specification for quality (qm) constraint type (c) in (r)
S(r)(mgb)E	Balance row for blending gasolines (mgb) in (r)
S(r)(dfo)E	Balance row for blending fuel oils (dfo) in (r)
S(r)RFGOXY	Constraint on renewable OXY limits in (r)
TANGKGTX	Maximum NG production in Alaska for GTL use
TAOILGTN	Minimum flow requirement on TAPS in Alaska
TAOILGTX	Maximum flow requirement on TAPS in Alaska
TPC(r)(m)(d)	Crude pipeline transportation capacity balance row from (r) to (d) mode type (m)
TPL(r)(m)(d)	LPG pipeline transportation capacity balance row (r) to (d) mode type (m)
TPP(r)(m)(d)	Product pipeline transportation capacity balance row (r) to (d) mode type (m)
TVC(m)CP	Crude oil vessel transportation capacity limits for mode (m)
TVP(m)CP	Product vessel transportation capacity limits for mode (m)
U(r)(uuu)	Utilities (uuu) in region (r)
Z(r)CAP(uns)	Balance row for total capacity of (uns) in (r)
Z(r)NGFSUM	Sum row for natural gas to refineries in (r)
ZZAMHSUM	Sum row for Alaskan crude export
Z@WOP	Current world oil price in value of RHS
Z@CRDTOT	Sum row for total crude in US
Z@YRITER	Iteration year
Z@IRACX	Sum row to force average refinery crude cost within specified range
Z@IRACN	Sum row to force average refinery crude cost within specified range
ZD(mmddyy)	Month, day, year of matrix generation

(I) = 00, 01, 02, ... , 12

(xx) = LPG, N2H, N6B, N6I, NGS, OTH, STG

(xxx) = TRG and RFG

(yyy) = TRG, TRH, and/or RFG, RFH

The following Table gives the dimensions of the MRM model:

Model	Columns			Rows		
	Total	Fixed	Bound	Total	Fixed	RHS
MRM (5 regions)	18843	763	1611	6762	5451	24

## G.2.b Subroutines

The program consists of several subroutines and a main program. The subroutines can be grouped as those that setup the OML environment, read in the data tables, form parts of the matrix representation of the model, solve the model, retrieve needed information for report writing, and write the reports. All the subroutines that generate part of the matrix representation of the model use input from data files in an OML format. These files have a .dat extension. Some subroutines use ASCII files as input and some others dont use any. The following table shows the subroutine names, the input data file names, and the purpose of the subroutines.

Source Code	Data file	Purpose
accunit.f	accunit.dat	Represents ACU unit
akaexp.f	akaexp.dat	Represents Alaskan exports
avoids.f	avoids.dat	Represents the avoids
cogener.f	cogener.dat	Represents the cogeneration
crdimprt.f	crdimprt.dat	Represents crude imports
demand.f	demand.dat	Represents demands
distblnd.f	distblnd.dat	Represents distillate blending
distress.f	distress.dat	Represents the distress imports and exports
domcrude.f	domcrude.dat	Represents crude inputs
emish.f	emish.dat	Represents emissions
ethanol.f	ethanol.dat	Represents ethanol supply and prices
fixcol.f	fixcol.dat	Fixes some columns
fuelmix.f	fuelmix.dat	Simulates fuel mixing
gasoblnd.f	gasoblnd.dat	Simulates gasoline blending
limpol.f	limpol.dat	Puts limits on policy rows
lplookup.f		Retrieves solution
mrm.f	mrmparam, mrmpath refmain.dat	Program MPS2ANAL: Sets up the OML environment, reads in some main data, controls the program, calls subroutines to form matrix, solves problem, stores solution, writes reports, basis and packs matrix.
mchproc.f	mchproc.dat	Simulates the merchant plant
ngprod.f	ngprod.dat	Provides gas supply steps to refinery
nrfplant.f	nrfplant.dat	Simulates the non refinery plant activities
output.f		Prints a report
prdexp.f	prdexp.dat	Simulates the product exports
prdimprt.f	prdimprt.dat	Simulates the product imports

Source Code	Data file	Purpose
recipes.f	recipes.dat	Specifies product recipe blends
refproc.f	refproc.dat	Simulates the refinery
setrows.f	setrows.dat	Sets some rows
splash.f	splash.dat	Simulates splash blending
stream.f	stream.dat	Simulates stream transfers
tabread.f		Reads data tables
transit5.f	transit.dat	Simulates the product and crude oil transportation for the 3-region representation of MRM
unfinished.f	unfinish.dat	Provide for unfinished oil imports
utility.f	utility.dat	Simulates utility purchased

Most of the subroutines that constitute the program generate part of the matrix representation of the model. The following gives a representation of the submatrix generated by each subroutine in table form. Columns of the tables correspond to activities (variables), and rows of the tables to constraints. The symbols x, -x or +-x represent matrix coefficients.

**accunit.f:** This subroutine simulates the ACU unit. It creates the following submatrix:

	R(r)ACU(crt)
A(r)CRDFCR*	x
A(r)STM	-x
A@CRDFCR*	x
A(r)CRX(crt)	x
A@CRDTOT	x
B(r)(ist)	+-x
C(r)(crt)	-x
F@TOTCRD	x
L(r)ACUCAP	x
P(r)(pol)**	+-x
U(r)(uuu)	-x
Z@CRDTOT*	x

\* for (crt) = FLL, FMH, FHL, FHH, and FHV

\*\* for (pol) = OVC, FRL

Bounds: None

**akaexp.f:** This subroutine simulates the Alaskan exports. It creates the following submatrix:

	NZAMH(i)	ZZAMHTOT	TAAMHXZ	PANGLQ1
OBJ	+x*	x	-x	-x
CAAMH			-x	
CZAMH		-x	x	
BW(ist)				x
ZZAMHSUM	x	-x		
A@AKAEXP		x		
A@CRDEXP		x		
AANGLPRD				x
A@NGLPRD				x
AWNGLRFN				x

(i) = N1, N2, N3, P4, P5, P6

\* : -x if i = N1, N2, N3; x if i = P4, P5, P6

Bounds: PANGLQ1, NZAMH(i)

**avoids.f:** This subroutine simulates the avoids. It is turned off. It creates the following submatrix:

	D(d)(prd)N(i)	D(d)(prd)P(i)
D(d)(prd)	x	-x
A(d)(prd)	-x	x
A@PRDDEM	-x	x
A@AVDNEG	x	
A@AVDPOS		x

(i) = 1, ..., 3

Bounds: D(d)(prd)N(i) and D(d)(prd)P(i)

**cogener.f:** This subroutine simulates the cogeneration unit. It creates the following submatrix

	E(r)CGNINV	K(r)CGNCAP	L(r)CGNBLD	R(r)CGNCGN
B(r)FUL				-X
L(r)CGNCAP	-X	-X	-X	X
OBJ	-X		-X	X
P(r)OVC				-X
U(r)(uuu)				X
A@FXOC	X		X	
A(r)FXOC	X		X	
A@INVST	X			
A(r)INVST	X			
A@KWHRFN				X

	E(r)CGXINV	K(r)CGXCAP	L(r)CGXBLD	R(r)CGXCGN	R(r)CHP(mod)
B(r)FUL				-X	
L(r)CGXCAP	-X	-X	-X	X	
OBJ	-X		-X	X	X
P(r)OVC				-X	
U(r)(uuu)				X	X
A@FXOC	X		X		
A(r)FXOC	X		X		
A@INVST	X				
A(r)INVST	X				
A@KWHRFN				X	X
A(r)CHPCGN					X

Bounds: E(r)CGNINV, K(r)CGNCAP, L(r)CGNBLD, E(r)CGXINV, K(r)CGXCAP, L(r)CGXBLD

**crdimprt.f:** This subroutine simulates the crude imports into the United States. It creates the following matrix:

	P(r)(crt)(Qs)
C(r)(crt)	x
OBJ	-x
Z@IRACN	x
Z@IRACX	x
A(r)CRDIMP*	x
A@CRDIMP	x

(Qs) = supply step Q1,Q2,Q3

\* (r)= PADDs II and IV only.

RHS: A(r)CRDIMP A@CRDIMP

Bounds: P(r)(crt)Q(s)

**demand.f:** This subroutine simulates product demands. It creates the following submatrix:

	D(d)(prd)S1	D@METS1
D(d)(prd)	-x	
OBJ	x	
A(d)(prd)*	x	
A@METDEM		x
A@PRDDEM	x	
D@MET		-x

\* for (prd) not equal to E85 or M85

Bounds: D@METS1 and D(r)(prd)S1

**distblnd.f:** This subroutine simulates the distillate blending. It creates the following matrix:

	F(r)(dfo)(ist)	Q(r)(prd)*
A(r)(prd)*		x
A(r)STM		-x
A@PRDRFN		x
B(r)(ist)	+x	
M(r)(prd)*		x

	F(r)(dfo)(ist)	Q(r)(prd)*
Q(r)(prd)*(qd)(c)	+x	-x
S(r)(dfo)E	x	-x
U(r)STM		-x
A(r)(dfo)CTI**	x	

\* (prd) = (dfo) only

\*\* (dfo) = DSL, DSU only

Bounds: None

**distress.f:** This subroutine simulates product distresses. It creates the following submatrix:

	I(d)(pi9)Z9	D(d)(px9)Z9
OBJ	-x	+x
D(d)(pi9)	x	
A@ZZIMP	x	
D(d)(px9)		-x
A@ZZEXP		x

Bounds: None

**domcrude.f:** This subroutine simulates domestic crudes. It creates the following submatrix:

	P(o)DCRQ1	PADCRQ1	TAALLTOT	TAAMHTOT	O@CRDEXP	O@CRDSPR
OBJ	-x	-x				
C(o)(crt)	x					
CAALLTOT		x	-x			
CAAMHTOT		x		-x		
CAALL			x			
CAAMH				x		
CBFHL						-x
A@CRDDCR	x	x				
A@CRDAKA		x				
A@CRDL48	x					
A@CRDEXP					x	
A@CRDSPR						x

	P(o)DCRQ1	PADCRQ1	TAALLTOT	TAAMHTOT	O@CRDEXP	O@CRDSPR
A@CRDFCR						x
O(o)(crt)	x	x				

(o) : except A

Bounds: P(o)DCRQ1, PADCRQ1, O@CRDEXP, O@CRDSPR

**emish.f:** This subroutine simulates emissions. It creates the following submatrix:

	K(r)(uns)CAP	R(r)FUM(ist)
E(r)(emu)N	x	
E(r)(emu)C		x

where, uns = FCC, VBR, VCU, KRF

Bounds: None

**ethanol.f:** This subroutine represents ethanol supply and prices. It creates the following submatrix:

	C(d)ETCR(i)	Z(d)ETCTAX	C(d)ETHR(i)	Z(d)ETHTAX	X(d)ETHE85
D(d)ETH	x		x		
OBJ	-x	x	-x	x	-x
A(d)ETH	x		x		
A(d)ETHTAX			x	-x	
A@ETHPRD	x		x		
A(d)ETCTAX	x	-x			
A@ETCPRD	x				
D(d)BIM					
C@ETHBIO	x		x		
A(d)BIMPRD					

**ethanol.f (Continued)**

	C(d)BIMR(i)	C(d)BINR(i)
OBJ	-x	-x
A(d)BINPRD		x
A@BINPRD		x
D(d)BIN		x

	C(d)BIMR(i)	C(d)BINR(i)
D(d)BIM	x	
C@ETHBIO	x	
A(d)BIMPRD	x	
A@BIMPRD	x	

$i = 1, \dots, 4$

Bounds: C(d)ETHR(i), C(d)ETCR(i), C(d)BIMR(i), C(d)BINR(I)

RHS: row C@ETHBIO

**fixcols.f:** This subroutine fixes some variables or activity. No submatrix is generated

Bounds: R(r)FCC(ist)

**fuelmix.f:** This subroutine simulates fuel mixing. It creates the following submatrix:

	R(r)FUM(mod)	T(r)CBNTAX	K(r)FUMCAP
OBJ		-x	
P(r)CBNTAX		x	
A(r)FUM(xxx)	x		
A@FUM(xxx)	x		
A(r)FUEL			x
A@FUEL			x

(xxx) = fuel type, LPG, OTH, N2H, NGS, STG, N6I, N6B

Bounds: None

**gasoblnd.f:** This subroutine simulates gasoline blending. It creates the following submatrix:

	B(r)(mgb)(ist)	Q(r)(mgb)	Z(r)RFGOXY
A(r)(xxx)(mgb)	x		
A@(xxx)(mgb)	x		
A(r)(prd)*		x	
A@PRDRFN		x	
A(r)(mgb)M00	x		
A(r)(mgb)R00	x		
B(r)(ist)	-x		
M(r)(prd)		x	
M(r)MTB(mgb)	x **		
Q(r)RFGREN			-x

	B(r)(mgb)(ist)	Q(r)(mgb)	Z(r)RFGOXY
Q(r)(mgb)(qq)(c)	x	-x	
S(r)(mgb)E	x	-x	
S(r)RFGOXY			-x
U(r)KWH		-x	

\* (prd) = (mgb) only; \*\*ist=MTB,ETB,TAE,TAM,THE,THM only; (xxx) = GO1, ..., G12

Bounds: B(r)RFG(ist) and B(r)TRG(ist) where ist= ETB, MTB, TAE, TAM, THE, THM

**limpol.f:** This subroutine defines policy conditions. It creates the following submatrix:

	K(r)(uns)CAP	E(r)(uns)INV	L(r)(uns)BLD	Z(r)FLO(uns)
Z(r)CAP(uns)	x	x	x	-x
P(r)(pol)				-x

(uns) = specific units underpolicy controls (FCC, KRF, RFH, RFL, DDS, ETH, ETM, FUM)

Bounds: None

**lplookup.f:** Retrieves solution values and stores them in arrays.

**mrm.f:** (main) This subroutine reads in the mrmparam file that has the information relative to the model to run; initializes the OML subroutine library environment; opens the database; specifies a problem in the database for processing; initializes the matrix processing; reads in the path file, the main.dat file that contains some global variables such as the refinery, the exporting, and demand regions code; calls the subroutines that generate the matrix; ends the matrix processing; writes out the MPS file; inserts the advanced basis; solves the matrix; puts the solution in output; writes the optimal basis; prints reports; packs the matrix; and closes the database.

**mchproc.f:** This subroutine represents the merchant plant. It creates the following submatrix

	K(r)(uns)CAP	E(r)(uns)INV	L(r)(uns)BLD	T(r)MCHOVC
L(r)(uns)CAP	-x	-x	-x	
OBJ		-x	-x	-x
H(r)OVC				x
A@FXOC		x	x	
A(r)FXOC		x	x	
A@INVST		x		
A(r)INVST		x		

**mchproc.f (Continued)**

	H(r)(uns)(mod)	H(r)FUX(mod)	K(r)FUXCAP	H(r)KWHMCH	H(r)(aa)(bb)(ist)*
H(r)(ist)	+-x	-x			+-x
H(r)(uuu)	+-x	+x			
H(r)(pol)	+-x	+x			
G(r)(ist)					+-x
B(r)(ist)					+-x
H(r)KWH				x	
H(r)OVC	-x				
H(r)STM	+-x				
A@NGLPRD					x
OBJ	x			-x	-x
H(r)FUMCAP		x	-x		
L(r)(uns)CAP	x				

**mchproc.f (Continued)**

	TANSOTOT	TAGTLTOT	N(r)NGKN(s)	N(r)(col)N(s)	H(r)(aa)(bb)(ist)*
OBJ			-x	-x	
H(r)(ist)			x		
H(r)(col)				x	
TANGKGTX			x		
TAOILGTN	x	x			
TAOILGTX	x	x			
CAAMH		x			
CAGTLTOT		-x			x
CANSOTOT		-x			
C(r)CTLTOT					x
C(r)GTL					-x

\*: first and last character of (ist); (aa) and (bb) = MP, GP, RF  
 where MP = Merchant plant, GP = Gas plant, and RF = Refinery

Bounds: K(r)(uns)CAP, E(r)(uns)INV, L(r)(uns)BLD, H(r)GPMP(ist) and H(r)RFMP(ist) = 0;  
 N(r)NGKN(s), N(r)(col)N(s)

RHS: rows TANGKGTX, TAOILGTN, TAOILGTX

**ngprod.f:** This subroutine represents the gas supply steps to refinery. It creates the following submatrix

	N(r)NGRF(ij)*
OBJ	+x**
Z(r)NGFSUM	x

\* (ij) = N1, N2, N3, N4, P5, P6, P7, P8

\*\* +x for N1, N2, N3, N4 and -x for P5, P6, P7, P8

Bounds: N(r)NGRF(ij)

**nrfplant.f:** This subroutine simulates the non refinery plant. It creates the following submatrix:

	G(r)DGR	G(r)GPL0 1	T(r)GPLOVC	N(r)DGP	G(r)SC2CC1	G(r)PGSLPG
G(r)OVC	-x		x			
G(r)DGP	x	-x				
G(r)LOS	-x	-x				
G(r)(xxx)		x				
G(r)CC1	-x			x		
OBJ			-x			
G(r)SC2C1X		-x			x	
G(r)PGSLGX		-x				x

**nrfplant.f (Continued)**

	G(r)NATOTH	G(r)(ist)PCF****	G(r)(xxx)*LPG	G(r)(xxx)**RFN
G(r)(xxx)	-x	-x	-x	-x
OBJ	-x	-x	-x	-x
A(r)GPL(xxx)***	x	x	x	
A(r)NGLRFN				x
A@NGLRFN				x
B(r)(xxx)**				x
M(r)(prd)***	x	x	x	
A(r)NGLPRD	x	x	x	x
A@NGLPRD	x	x	x	x

**nrfplant.f (Continued)**

	G(r)SC2CC1	G(r)SC3CC1	G(r)METRFN	G(r)METDEM	G(r)RFNMET
G(r)CC1	x	x			
G(r)CC3		-x			
G(r)LOS	x	x			
G(r)PGS	-x				
OBJ	x	x	-x	-x	
A(r)NGSMER			x		
A@NGSMER			x		
B(r)MET			x		-x
G(r)MET			-x	-x	x
D@MET				x	

**nrfplant.f (Continued)**

	E(r)MOHINV	L(r)MOHBLD	K(r)MOHCAP	G(r)MOH01
L(r)MOHCAP	-x	-x	-x	x
G(r)MET				x
G(r)OVC				-x
U(r)NGF				-x
U(r)KWH				-x
A(r)NGSMET				x
A@NGSMET				x
A@METPRD				x
OBJ	-x	-x		
A(r)INVST	x			
A@INVST	x			
A(r)FXOC	x	x		
A@FXOC	x	x		

(xxx) : PGS, CC3, IC4, NC4, NAT

\* : (xxx) except NAT ; \*\*: (xxx) except PGS, CC3;

\*\*\* LPG, OTH, PCF; \*\*\*\* ist = NAT, PGS

Bounds: G(r)SC3CC1, N(r)DGP, E(r)MOHINV, K(r)MOHCAP, L(r)MOHBLD

**output.f:** This subroutine prints reports.

**prdexpf:** Simulates product exports. It creates the following submatrix:

	D(z)(prx)*SX	D(z)COKSX	D(z)ASTSX
D(z)(prx)	-x	-x	-x**
OBJ	x	x	
A@COKEXP		x	
A(d)PRDEXP	x		x**
A@PRDEXP	x		x**

\*: All (prx) except COK and AST; (z) = export demand regions (d) 2,3,7,8,9

\*\* : d = z = CD 9 only

Bounds: D(z)(prx)SX, except for (prx) = COK

RHS: A@COKEXP

**prdimprt.f :** This subroutine simulates product imports. It creates the following submatrix:

	I(r)(pri)*R(s)	I(r)(pri)**R(s)	I(r)SSRR(s)
A@(pri)*IMP	x		
A(r)(pri)*IMP	x		
B(r)(pri)*	x		
A(r)(pri)RFN	x***		
A(r)PRDIMP		x	
A@PRDIMP		x	
M(r)(pri)**		x	
OBJ	-x	-x	
A(r)SSRIMP			x****

\* : for (pri) = MET and MTB; \*\*: for all (pri) except MET and MTB;

\*\*\* for (pri) = MTB only; \*\*\*\* (r) = PADD I only (E)

(s) = product import steps 1-9

RHS: A@PRDIMP, A(r)PRDIMP [(r) = PADD's II, IV only], A(r)SSRIMP [(r) = PADD I only]

Bounds: I(r)(pri)R(s)

**recipes.f:** This subroutine simulates product recipe blending. It creates the following submatrix:

	X(r)(xxx)(yyy)	X(r)(yyyy)
B(r)(ist)	-x	-x
M(r)(yyy)	x***	x
OBJ	x	-x*
U(r)STM		-x**
A(r)STM		-x**
A(r)(yyy)	x***	x
A(r)SULSAL	x****	
A@SULSAL	x****	
A(r)PETCOK	x***	
A@PETCOK	x***	
A@PRDRFN	x***	x

(xxx) = AST, AVG, CKH, CKL, GOP, SUL ; (yyy) = AST, OTH, COK, PCF, SAL

(yyyy) = AST0, AST1, AVG0, GOP0;

\*: for (yyyy) = AVG\*; \*\*: for (yyyy) = AST0; \*\*\*: for (yyy) = COK; \*\*\*\* for (yyy) = SAL

**refproc.f:** This subroutine simulates the refinery processes. It creates the following submatrix:

	E(r)(uns)INV	K(r)(uns)CAP	L(r)(uns)BLD	T(r)OVCOBJ	R(r)(uns)(mod)
OBJ	-x		-x	-x	
A@1YRBLD	x*****				
A(r)INVST	x				
A@INVST	x				
A(r)FXOC	x		x		
A@FXOC	x		x		
A(r)GAIN					+x
A@GAIN					+x
A(r)METRFN					x**
A(r)NGSH2P					x***
A@NGSH2P					x***
A@MTBPRD					x****
A(r)STM					-x

	E(r)(uns)INV	K(r)(uns)CAP	L(r)(uns)BLD	T(r)OVCOBJ	R(r)(uns)(mod)
A@(fff)FU					X*****
B(r)(ist)					+X
L(r)(uns)CAP	-X	-X	-X		X
M(r)(prd)*****					-X
P(r)(pol)				X*	+X
P(r)CBNTAX*****					-X*****
U(r)(uuu)					+X

\*: (pol)=OVC; \*\*: (uns)=ETH; \*\*\*: (uns)=H2P; \*\*\*\*: (uns)=ETH and (mod) = MTB;  
 \*\*\*\*\*: (uns)=FUM only; \*\*\*\*\*: (prd)=N6I, N6B only; (fff)=LPG, STG, RES, OTH;  
 \*\*\*\*\*: (uns) = ACU only

Bounds: K(r)(uns)CAP, E(r)(uns)INV, L(r)(uns)BLD,  
 R(r)FUM(mod) where (r)=PADD V only, (mod)=NPI,NPN,NPP,SRC,SRH,SRI,SRL,  
 R(r)FCC(mod) where mod = 70H,70M,70U,H70,M70,U70  
 RHS: rows A@STGFU, A@LPGFU, A@RESFU, A@OTHFU, A@1YRBLD

**setrows.f:** This subroutine sets the row types (G, L, E, N) for rows P(r)(pol).

**splash.f:** This subroutine simulates splash blending. It creates the following submatrix:

	X(d)ETH(xxx)	X(d)METM85	X(d)(www)SPG	Q(r)(mgb)	B(r)RFG(sss)	B(r)RFG(rrr)
D(d)(xxx)	x	-X*****				
D(d)ETH	-x					
D(d)(yyy)	-x					
D(d)M85		x				
D(d)MET		-x				
A(d)G08(xxx)	x*					
A@ETH(xxx)	x					
A@METM85		x				
A(d)RFG(xxx)** not linked to col						
A(d)TRG(xxx)	x***					
D(d)(www)			x			
D(d)(ttt)			-x			
Q(r)RFGREN	x**				x	
S(r)RFGOXY	x**					x

	X(d)ETH(xxx)	X(d)METM85	X(d)(www)SPG	Q(r)(mgb)	B(r)RFG(sss)	B(r)RFG(rrr)
M(r)MTB(mgb)				-x		x

(rrr) = ETB, MTB, TAE, TAM, THE, THM; (sss) = ETB, TAE, THE;  
 (ttt) = N6B, N6I; (www) = N67, N68; (xxx) = E85, RFG, RFH, TRH, TRG;  
 (yyy)=SSR when (xxx)=RFG, RFH and (yyy)=SST when (xxx)=TRH and  
 (yyy)=SSE when (xxx)=TRG;  
 \*: (xxx) not E85; \*\*: (xxx)=RFG, RFH only;  
 \*\*\*:(xxx)=TRG, TRH only; \*\*\*\*:(xxx)=TRG only  
 Bounds: none.

**stream.f:** This subroutine simulates stream transfers. It creates the following submatrix:

	T(r)(ist)(ist)	T(r)(ist)(prd)
B(r)(ist)	+x	-x
M(r)(prd)		x
A(r)(prd)		x
A@PRDRFN		x

**tabread.f:** This subroutine prints the data file names, the number of tables and lists the tables names that are read.

**transit5.f:** This subroutine simulates the transportation network for MRM 3-region

	Y(o)*(crt)(m)(r)	W(d)ETH(m)(r)	W(r)MET(m)(d)	W(s)(prd)(m)(d)	V(xxxxxx)
C(o)(crt)	-x				
C(r)(crt)	x				
OBJ	-x	-x	-x	+x****	
TPC(o)*(m)(r)	x				-x
TVC(m)CP	x				-x
TVP(m)CP				x	-x
TPP(s)(m)(d)				x***	-x
TPL(s)(m)(d)				x****	-x
B(r)ETH		x			
D(d)ETH		-x			
D(r)ETH		x**			
A(r)ETHRFN		x			
B(r)MET			-x		

	Y(o)*(crt)(m)(r)	W(d)ETH(m)(r)	W(r)MET(m)(d)	W(s)(prd)(m)(d)	V(xxxxxx)
D(d)MET			x		
D(d)(prd)				x	
M(r)(prd)				-x	
M(d)(prd)				x	
(xxxxxx)					-x

**transit5.f:** (continued)

	Y(o)*(crt)(m)(r)	TANSOTOT	TAAMHXZ	TAGTLTOT	W(d)(nrc)(m)(s)	WAGTLJ(r)
C(r)GTL						x
CANSOTOT	x	-x	x			
OBJ		-x		-x	-x	-x
B(r)(nrc) *****					x	
D(d)(nrc) *****					-x	
TVPJCP						x

\* OGSM supply (o) and refinery (r) regions; \*\* for (r)=Census Division  
 \*\*\* for (prd) different than MET, ETH; \*\*\*\* for (prd) = LPG and PCF;  
 \*\*\*\*\* for (nrc) = BIM, BIN only; (s) = refinery (r) and demand (d) regions;  
 (xxxxxx) = TVC5CP, TVPJCP, .....

Bounds: V(xxxxxx), W(d)ETH(m)(r)

**unfinished.f:** This subroutine simulates the unfinished oil process. It creates the following submatrix:

	T(r)UNF(ist)	T@UNFTOT	RHS
B(r)(ist)	x		
F(r)UNF(ist)	-x	x	
OBJ	-x		
A(r)UNF	x		
A@UNFIMP	x		
A(r)UNFIMP	x		
F@TOTCRD		-x	x

**utility.f:** This subroutine represents the utility. It creates the following submatrix:

	U(r)(uuu)	R(r)KWGPGN	T(r)NGFNGS
U(r)(uuu)	x		-x***
OBJ	-x		
A@KWHRFN	x*	x	
B(r)NGS			x
A(r)NGSRFN			x
A@NGFTOT	x***		
A(r)NGFTOT	x***		
Z(r)NGFSUM	-x***		

\*: for (uuu) = KWH ;\*\*\*: for (uuu) = NGF

All the FORTRAN files are located in the directory n:/default/source/ on the EIA NT server.

### G.2.c Common Blocks

Variables shared by several subroutines are set up in common. There are four files that contain the common blocks used by the program. Some of the files consist of several common blocks.

The following table lists the common block names, gives a brief description and the location of the block.

Common	Description	Location
IPMMREAL	Common for real variables shared by subroutines that generate submatrices	/default/includes/ipmmtest
IPMMINT	Common for integer variables shared by subroutines that generate submatrices	/default/includes/ipmmtest
IPMMCHAR	Common for character variables shared by subroutines that generate submatrices	/default/includes/ipmmtest
LPTAB	Common used for solution retrieval and report writing	/refine/pmm_lp_gen/includes/lpout
OMLREAL	Common for real variables used to set LP mrmory size	/default/includes/omlspace
OMLINT	Common for integer variables used to set LP mrmory size	/default/includes/omlspace
DFINC2	Common for OML database functions	/default/includes/dfinc2
WCR	Common for the WHIZ optimizer	/default/includes/wfinc2

A list of the common blocks and the variables that constitute them is given in Appendix G-D.

## G.3 Data

Most of the data that the program uses is provided in files with a .dat extension. There is a one to one correspondence between the FORTRAN files that form part of the matrix and the .dat data files (eg, accunit.f gets its input from accunit.dat). In each of the .dat files, the data is arranged in an OML format that consists of data tables. Each table consists of a table name; row (or stub) and column (or head) names; and values at the intersection of rows and columns. In addition there are ASCII files. These ASCII files are for control of the program. The following is the description of each input file.

### G.3.a Data Sets

.dat files

#### accunit.dat

Table Name	Columns	Rows	Description
ACUCUTS	(crt)	(ist); FUL	Crude distillation yield
ACUPOL	OVC, LOS	(crt)	ACU policy table
ACUUTI	STM, KWH	(crt)	ACU utility consumption
INVLIM	MAX	(r) , @	Maximum investment

#### akaexp.dat

Table name	Columns	Rows	Description
EXPAKA	P, Q	N1, N2, N3, P4, P5, P6	Price and quantity of Alaskan crude exports.
NGLAKA	PER	PGS, CC3, NC4, IC4, and NAT	Yield of NGL
PRQAKA	VOL, TRP, EXPPRC	A	Volume, and transportation and expected cost for Alaskan crude exports

#### avoids.dat (no longer used)

Table	Columns	Rows	Description
SADELPX	FACTORS	N1, N2, N3, P1, P2, P3	Price differentiate
PRDAVOID	DUMMY	(prd)	Product list
SADELQ	N1, N2, N3, P1, P2, P3	(prd)	Demand shift quality fraction

**cogener.dat**

Table	Columns	Rows	Description
CGNCAP	CAP, PUL, BLD	(r)	Refinery cogeneration capacity, %utilization and build
CGNINV	INV, FXOC, CAPREC	(r)	Refinery cogeneration investment, fixed cost and capital recovery
CGNPOL	OVC	CGN	Refinery cogeneration policy
CGNREP	CGN	FUL	Refinery cogeneration yields
CGNUTI	(uuu)*	(r)	Refinery cogeneration utility usage
SELCGN	SOLD	(r)	% cogeneration sold to grid from Refinery
VPELAS	(r)	(year)	Electric utility prices for Refinery cogen (87\$/kwh)
CGXCAP	CAP, PUL, BLD	(r)	Merchant plant cogeneration capacity, %utilization and build
CGXINV	INV, FXOC, CAPREC	(r)	Merchant plant cogeneration investment, fixed cost and capital recovery
CGXPOL	OVC	CGN	Merchant plant cogeneration policy
CGXREP	CGX	FUL	Merchant plant cogeneration yields
CGXUTI	(uuu)*	(r)	Merchant plant cogeneration utility usage
SELCGX	SOLD	(r)	% cogeneration sold to grid from Merchant plant
VPELWS	(r)	(year)	Electric utility prices for Merchant cogen (87\$/kwh)

\* except NGF

**crdimprt.dat**

Table	Columns	Rows	Description
CRUDETYP	DUMMY	(crt)*	Foreign crude types
ICR(crt)*(r)	C1, Q1, C2, Q2, C3, Q3	(year)	Price and quantity available for crude imports.

\*: for (crt) = FLL, FMH, FHL, FHH, FHV (i.e. foreign crude only)

**demand.dat**

Table	Columns	Rows	Description
CKSMIX	CKL, CKH	OBJ, CKL, CKH, COK	Coke price and conversion factor
PRODLIST	DUMMY	(prd)	List of products

Table	Columns	Rows	Description
(prd)*	(d)	(year)	Product (prd) demand
DEMMET	CHEM	(year)	MET demand by Chemical Industry

\* RFH mapping and corresponding table renamed to RFHA due to duplicate table name elsewhere.

#### distblnd.dat

Table	Columns	Rows	Description
Q(r)DFO	(dfo)	(spec)	Distillate fuel oil blend specs
DFOUTI	STM	(dfo)	Distillate blend steam use.
DCC	(dfo)*	(ist)	Distillate recipe blend.
DCB	spec categories **	(ist)	Distillate blend intermediate stream quality specification.

\* from Z:MAPDFOPD

\*\* from Z:MAPDFOSP

#### distress.dat

Table	Columns	Rows	Description
ZPX	VALUE	(prd)	Distress code for pricing

#### domcrude.dat

Table	Columns	Rows	Description
DCRSUP	(o)	Y96	Historical crude supplies by OGSM region
DCRSHR	(o)	(crt)*	Domestic crude share by OGSM region
CREXP	CRDEXP, CRDSPR	VOL	Crude exports and SPR

\*: (crt) except FLL, FMH, FHL, FHH, FHV

#### emish.dat

Table	Columns	Rows	Description
EMUNS	(emu)*	Process unit	Emission by process unit
EMFUM	(emu)	Fuel stream burned	Emission by fuel burned

\* except CO2

## ethanol.dat

Table	Columns	Rows	Description
SUPETH(d)*	C1, R1, C2, R2, C3, R3, C4, R4	(year)	Ethanol supply curves
ETHTAX	TAXETH, TAXE85	(year)	Ethanol taxes; tax subsidy
MINRENEW	USMIN	(year)	Min renewables required in gasoline (US total)
SUPBIM	C1, R1, C2, R2, C3, R3, C4, R4	(d)	Biomass diesel supply curves (virgin oil)
SUPBIN	C1, R1, C2, R2, C3, R3, C4, R4	(d)	Biomass diesel supply curves (non-virgin oil)

\* (d) from Z:CDMAP

## fixcols.dat (no longer used)

Table	Columns	Rows	Description
FIXCOL	R	Dummy	First letter of column to fix
(r)RCOL	FCC	(mod)	Column to fix to zero

## fuelmix.dat

Table	Columns	Rows	Description
GROUP	DUMMY	Fuel stream	List of fuel stream

## gasoblnd.dat

Table	Columns	Rows	Description
Z:MAPGSLPD	ENSYS CODE	TRG, RFG	Map Ensyst mogas ID to EIA mogas ID
Z:MAPGSLSP	ENSYS CODE	EIA codes	Map Ensyst spec ID to EIA spec ID
Q(r)GSL	TRG, RFG	(spec)	TRG, RFG specs
(r)SSR	Y1, Y2, Y3, Y4, Y5	RFG(spec); YEAR	Gasoline specs for subspec SSR ; year of data
(r)SST	Y1, Y2, Y3, Y4, Y5	TRG(spec); YEAR	Gasoline specs for subspec SST; year of data
(r)SSE	Y1, Y2, Y3, Y4, Y5	TRG(spec); YEAR	Gasoline specs for subspec SSE; year of data
(r)RFH	Y1, Y2, Y3, Y4, Y5	RFG(spec); YEAR	Gasoline spec for RFH; year of data
(r)TRH	Y1, Y2, Y3, Y4, Y5	TRG(spec); YEAR	Gasoline spec for TRH; year of data
Z:GASGROUP	TEXT(1)	(ist)	List of blending streams specially grouped

Table	Columns	Rows	Description
GCB	Quality codes	(ist)	Gasoline blend intermediate stream quality spec.
GCC	Gasoline type	(ist)	Gasoline recipe blend.
MCO	Motor octane codes*	(ist)	Gasoline component base octane ratings
(xxx)BV	Motor octane codes**	(ist)	Gasoline component blending values
GSLUTI	KWH	(prd), SSE, SST, SSR	Gasoline utility use.
GSPETH	RE	RFGN	Gasoline specs for ETH

(spec) = 2 character quality code followed by X (maximum) or N (minimum).

(xxx) = many exist, however, PMM uses UNC and RFM defined by Z:MAPGSLPD (representing TRG and RFG, respectively).

\* R00, R05, R15, R30, M00, M05, M15, M30, of which only R00 and M00 are used by the PMM.

\*\* same as \*, except column TEL added (but not used by the PMM).

### limpol.dat

Table	Columns	Rows	Description
UNITPOL	DUMMY	(uns)	List of processes that have a limit on POL
LIM(uns)(r)	(ist)	DUM	Limit on (ist)

### refmain.dat

Table	Columns	Rows	Description
EXPROD	DUMMY	(prx)	List of product exports
INVFACT	LOC, ENV	(r)	Location and environment factors
TRSOVC	OVC	(r)	Year \$ conversion factor for operating cost
FORCRD	DUMMY	(crt)*	List of foreign crude
YRDOLLAR	2000	1987	Year \$ conversion factor
ZIRACFAC	DELTA	ZIRAC	Range of price differential for IRAC
WOP	WOP	(year)	World oil price (87\$)
RFNREG	PAD	(r)	List of refinery regions vs PADD
RFNEXP	RFID	Linked list of refinery and export regions	List of exporting regions
DEMNDREG	REGION	Linked list of refinery and demand regions	List of demand region
USERYEAR	YEAR	Y96	Year to run model

\* FFL, FMH, FHL, FHH, FHV

## mchproc.dat

Table	Columns	Rows	Description
MCHINV	INV, FXOC, CAPREC	(uns)	Merchant plant investment, fixed cost and capital recovering
(r)CAPMCH	CAP, PUL, BLD	(uns)	Merchant plant processes capacity, % utilization and build.
(uns)POL*	(pol)	(ist)	Merchant plant processes policy
(uns)CAP*	(uns)CAP	(ist)	Merchant plant process capacity
(uns)REP*	(mod)	(ist)	Merchant plant process yields
(uns)UTI*	(uuu)	(ist)	Merchant plant process utility usage
TRANSFER	Dummy	GP, MP, RF	Transfer allowed
RFTRANS	MP	(ist)	Refinery transfer to merchant plant
GPTRANS	MP	(ist)	Gas plant transfer to merchant plant
MPTRANS	GP, RF	(ist)	Merchant plant transfer to gas plant and refinery
MPTRANS1	GTLRF, CTLRF	(ist)**	Merchant plant transfer to refinery
(r)UAP	CST	(uuu)	Utility purchases

\* uns defined by T:MCHINV

\*\* (ist) related to GTL and CTL liquid streams

## ngprod.dat

Table	Columns	Rows	Description
SPNGF	ALLREG	N1, ..., N4, P5, ..., P8	Price steps for gas supply
SQNGF	MAX, MIN	N1, ..., N4, P5, ..., P8	Quantity steps for gas supply
SCVAL	(r)	VOL	Volume limits on each step

## nrfplant.dat

Table	Columns	Rows	Description
INVMOH	INV, CAPREC, FXOC	MOH	Non refinery plant process investment, capital recovery, and fixed cost.
MOHPLT	(r)01	CC1, MET, OVC, KWH	Production of methanol
MOHCAP	(r)01	CAP	Methanol capacity
GASPLT	(r)01	(ist), (pol)	Yield from gas plant
GASSHFT	SC2, SC3	CC1, LOS, OBJ	Shift of ethane and propane to methane

Table	Columns	Rows	Description
GASCAP	(r)01	FAC, CAP, LIM, PCU	Gas plant capacity limits
CC1CAP	(r)01	(year)	Dry gas production capacity

### prdexp.dat

Table	Columns	Rows	Description
(x)PRDEXP	MINY1, MAXY1, MINY2, MAXY2, ... MINY5, MAXY5	(prx), YEAR	Limit on volume to export; year of data
EXPLIM	YRPC, FIX	1995	Limit on volume and yearly increase
MULTEXPR	MULT	PRICE	Price for exports as function of imports

(x) = export regions (CDs 2,3,7,8,9).

### prdimprt.dat

Table	Columns	Rows	Description
PRODTYP	DUMMY	(pri)	List of product import
IMPLIM	MAX	@	Maximum imports into USA
IPR(pri)(r)	C1, R1, ..., C9, R9	(year)	Product import supply curve
NEMSRSD	R1B, R1PR	R1, ..., R9	Resid import supply curve

### recipes.dat

Table	Columns	Rows	Description
RCPEIA	A, CST, JTA, N2H, SLP, CKH, CKL	KERSPG, SULSAL, CKHCOK, CKLCOK	Cost of sulfur and coke; kerosene split; unit conversions.
RCP	A, CST, component stream, STM	Recipe blended products	Recipe blends (fractions)

### refproc.dat

Table	Columns	Rows	Description
(r)CAP	CAP, PUL, BLD	(uns)	CAP, PUL and BLD values
(uns)	(mod)	(ist), (uuu), CAP, (pol)	Refinery process yields, utility usage, capacity factor, policy
MATBAL	A, B	(ist)	Streams requiring material balance
INV	INV, FXOC, CAPREC	(uns)	Refinery processes investment, fixed cost and capital recovery

Table	Columns	Rows	Description
SCL	selected processing units	selected streams/utilities	selected factors applied to selected coeff in T: (uns)

### setrows.dat

Table	Columns	Rows	Description
(r)POL	TYPE	(pol)	Row type

### splash.dat

Table	Columns	Rows	Description
HOXETH	TRH, RFH, RFG, TRG	Gasoline stream	Ethanol recipe for splash blending
BLNSP(d)	KER, N67, N68	JTA, N2H, KER, N6I, N6B, N67, N68	Blend composition recipe
BLOX(d)YXX	E85, M85, TRH, RFH, RFG, TRG	Gasoline stream	Recipe blend composition
XETH	PO	XETH	Oxygen content of ethanol
SCB	PO	Oxygenate stream	Oxygen content of oxygenates

### stream.dat

Table	Columns	Rows	Description
XSALE	DUMMY	(ist)(prd)	Linked list of stream transfer to products
TRS	MIN, MAX, CST	(ist)(ist)	Linked list of stream to stream transfers

### transit.dat

Table	Columns	Rows	Description
MVCCAP	MAX	TVC(m)CP, TVP(m)CP	Marine vessel capacity for crude & product
BVPCAP	MAX	TVP(m)CP	Marine barge capacity for product
PLCCAP	MAX	TPC(o)(m)(r) TPP(r)**(m)(d) TPL(r)**(m)(d)	Pipeline capacity for (C) crude (P) product (L) LPG
TPCRLIST	DUMMY	(o)	Domestic crude supply regions for transportation
TPCR(o)	(crt); GTL	(m)(r); TAPS	Crude oil transportation cost from domestic supply region (o) to refinery region (r)
PLCRLIST	DUMMY	(o)	List of domestic crude oil supply regions for pipeline
PLCR(o)	(crt)	(m)(r)	Crude pipeline transportation cost from (o) to (r)

Table	Columns	Rows	Description
BVPR(r)	(prd)	(m)(d)	Product barge/truck transportation cost from (r) to (d)
TPPR(r)	(prd)	(m)(d)	Product marine transportation cost from (r) to (d)
TPME(r)	MET	(m)(d)	Methanol transportation cost from (r) to (d)
TPETLIST	DUMMY	(d)	List of Census Divisions for ethanol transportation source
TPET(d)	ETH	(m)(r)**	Ethanol transportation cost from (d) to (r)
PLPRLIST	DUMMY	(d)	List linked census divisions for product pipeline from region B to East Coast
PLPR(r)**	(prd), SSE, SST, SSR	(m)(d)	Product pipeline transportation cost from (r)** to (d)
PLLG(r)	LPG, PCF	(m)(d)	LPG transportation cost from (r) to (d)
PLNKLIST	DUMMY	(r)**	List of product pipeline originations.
PLNK(r)**	(prd), SSE, SST, SSR	(m)(r)**	Product pipeline transport connections and costs from (r)** to (r)**
TPBDLIST	DUMMY	(d)	List of Census Divisions for biomass diesel transportation source
TPBD(d)	BIM	(m)(r)	Biomass diesel transportation cost from (r)

\*\* refinery (r) and/or demand (d) regions

#### unfinish.dat

Table	Columns	Rows	Description
UNFOIL	E, G, W, PD	streams: NPP, HGM, ARB	Types (3) of unfinished oil imports into the U.S.
UNFEQT	SLOPE, CONST	XYZ	eq. parameters that correlate unfinished oil imports to crude input

#### utility.dat

Table	Columns	Rows	Description
UTITRS	COEF	NGFNGS	BFOE natural gas.
(r)UAP	CST	(uuu)	Utility costs.
VALPNG	(r)	(year)	Industrial price of natural gas.
VPELIN	(r)	(year)	Industrial elec utility prices (87\$/kwh)

## G.3.b Other input files

### 1. **mrmparam** file

The mrmparam file is a control file read by mrm.f to map input and output file names and instructions. In the mrmparam, the user chooses the model that he wants to run; the names for the problem, solution, path file, basis, mps file, and packed matrix; the model title; and the location and name of the starting basis and optimal basis. The following table lists the information that is to be supplied in the mrmparam file.

Variable name	Variable length	Variable purpose	Restrictions
MODELN	8	Model to be run	MRM5
ACTPROB	8	Act problem	
SOLNAME	8	Solution name	
PATHNF	7	Name of file where data files paths are stored.	
TITLE	40	Problem title	
INBASISN*	40	Location and name of advanced basis	
OUTBASIS	8	Name of optimal basis	
BASISN	8	Basis name	Must be name in INBASISN file
MPSOUTN**	8	MPS file name	
PAKCN**	8	Packed matrix file name	.PCK extension
TRACE	3	Toggle Trace Utility	

\*: If no name or a file does not exist, the program will operate without an advanced basis.

\*\* : if "NULL" or "null" is provided, the program will skip the part of the program that generates the file.

The above variables have to be provided in the order they are listed in the above Table and should start at column 18. Appendix G-A provides an example of an mrmparam file. The mrmparam file has to be in the subdirectory where the model is executed.

### 2. **mrmpath** file:

In this file the user provides the program with the location and name of the data files. The order in which the names appear is important. See Appendix G-B for an example of a path file. The path file has to be in the directory from which the model is executed. This file format is that of an OML table.

### 3. **Advanced basis** file:

In this file the user provides an advanced basis to the model. If the user does not provide one or provides one whose name does not coincide with the basis name provided in the mrmparam, the program will not use it.

## G.4 Submission of a Run

In order to run the model, one has to first compile and link the different FORTRAN source files to form an executable. Once the executable is created, the user submits a run in conjunction with a mrmparam and a mrmrpath file. The execution of the program will solve the problem and create:

- An ACTFILE file
- An MPS file
- A SYSPRINT file (solution)
- An out basis file
- A packed matrix file
- Reports (only for MRM5)

The following are the files created by a run:

	MRM
ACTFILE	ACTFILE.act
MPS file	Name provided by user in the mrmparam file
Solution file	SYSPRINT
Out basis	Name provided by user in the mrmparam file
Packed matrix	Name provided by user in the mrmparam file
Report	reports5, fort.75

All the files used for the MRM matrix generation reside within the NEMS default directories on EIA's NEMS NT servers, as defined next. The source files that encompass the program are on n:/default/source/. The user must create and link the object files to form the mrm executable (mrm.exe) to be located in the user's directory. The *Developer's Studio* (a debugging package for the PC) is used by the user to compile, link, execute, debug, and manage files. Instructions on how to use this package, in connection with the mrm is defined below.

The mrmparam file and the mrmrpath file used for the MRM model are located in the n:/default/scripts/ directory. To run the model, the param and path files must be copied to the user's Debug directory. The path files point to the default data files (\*.dat) that are stored in n:/default/input/ directory.

### Runs

First, connect to the NEMS-F8 via a terminal server client, and open a korn shell. You are now operating within a unix environment. All runs will be made using the *Developer's Studio*.

1. Set up and run the default (no changes):

- a. Create a scenario directory in your user directory, then create the following directories within the scenario directory: Source, Data, Debug
- b. In the Debug directory, *nemsco* the default **mrmparam** and **mrmrpath** files.
- c. In the scenario directory, *nemsco* mrmmps.dsp (a *Developer's Studio* project file).
- d. Double-click the *Developer's Studio* icon on your NEMS-F8 terminal server desktop.
  - from the FILE, OPEN menu, set file type to \*.dsp, and select the mrmmps.dsp file. (This creates two more files in the scenario directory: mrmmps.dsw and mrmmps.opt.)
  - from the PROJECT, SETTINGS menu, click on the Debug tab. Highlight the path defined in the "Executable for debug session" display, and copy it to the "Working directory" display just below. HOWEVER, go to the "Working directory" display and delete "\\mrmmps.exe" portion of the path just created. Click OK.
- e. To compile and link all default mrm code and DLLs, go to the BUILD menu, and select "Rebuild All." A message will appear in the lower window that the executable has been created. (Note: Lately, a single warning appears, which can be ignored.)
- f. To execute the default, go the the BUILD menu, and select "Execute." A pop-up window will show the progress of the mrm run. When finished, the pop-up window will instruct the user to press any key to continue.
- g. The resulting mps file will be called mrm5mps (as defined in the mrmparam) and will be located in the Debug directory.

## 2. Make changes to a mrm data file and rerun mrm:

- a. In the Data directory, *nemsco* the data file the user wants to change.
- b. Edit, change, and resave.
- c. In the Debug directory, edit the **mrmrpath** file.
  - modify the path of the updated data file to point to the new location in the Data directory, and resave
  - delete (remove) the following two files that were created from a previous mrm run: ACTFILE.act and SYSPRINT
- d. Double-click the *Developer's Studio* icon on your NEMS-F8 terminal server desktop.
  - from the FILE, OPEN menu, set file type to \*.dsw, and select the mrmmps.dsw file from the scenario directory (created in step 1.4 above)
- e. To execute [assuming source code has already been compiled], go the the BUILD menu, and select "Execute." A pop-up window will show the progress of the mrm run. When finished, the pop-up window will instruct the user to press any key to continue.
- f. The resulting mps file will be called mrm5mps (as defined in the mrmparam) and will be located in the Debug directory.
- g. REMEMBER: After a new data file is defaulted, the corresponding data file name in the **mrmrpath** file must be updated to map the proper default version. Then, the **mrmrpath** file must be defaulted.

## 3. Make changes to a mrm source code and rerun mrm:

- a. In the Source directory, *nemsco* the source code one wants to change.
- b. Edit, change, and resave.
- c. In the Debug directory, delete (remove) the following two files that were created from a previous mrm run: ACTFILE.act and SYSPRINT
- d. Double-click the *Developer's Studio* icon on the NEMS-F8 terminal server desktop.

- from the FILE, OPEN menu, set file type to \*.dsw, and select the mrmmps.dsw file from the scenario directory (created in step 1.4 above)
- e. [Need to do only once.] In the workspace window, double-click on the **mrmmps files** listing, and then on the **Source Files** listing.
  - find the source code filename, right-click on the filename, and select **Properties** from this sub-menu: a pop-up window entitled "Source File Properties" appears
  - within the pop-up window, modify the path of the source code (in the "Persist as" line) to point to the new location in the source directory
  - close the pop-up window by clicking on the 'x' in this window
- f. To recompile updated code and link to other code, go to the BUILD menu, and select "Rebuild All." A message will appear in the lower window that the executable has been created.
- g. To execute, go to the BUILD menu, and select "Execute." A pop-up window will show the progress of the mrm run. When finished, the pop-up window will instruct the user to press any key to continue.
- h. The resulting mps file will be called mrm5mps (as defined in the mrmparam) and will be located in the Debug directory.

## Appendix G-A: Example of An mrmparam File

mrmparam:

```
MODELN      'MRM5      '           !8
ACTPROB     'OMLMRM5  '           !8
SOLNAM      'MRM5SOL  '           !8
PATHNF      'mrmpath'           !7
TITLE       'MRM5 MULTI REGION REFINERY ' !48
INBASISN    'inbasis5 '           !48
OUTBASISN   'outbasis5'          !9
BASISN      'MRM5      '           !9
MPSOUTN     'mrm5mps  '           !9
PACKN       'MRMPACK  '           !9
TRACE       'ON      '           !3
```

The mrmparam file will run the 5-region MRM model; the act problem will be “OMLMRM5;” the solution name will be “MRM5SOL;” the data files path will be read from the file “mrmpath;” the title of the MRM model will be “MRM5, MULTIPLE REGIONS REFINERY;” the advanced basis will be read from “inbasis5;” the optimal basis will be stored in the file “outbasis5;” both the advanced and optimal basis will be named “MRM5;” the mps file will be stored in “mrm5mps;” and the packed matrix will be created and called “MRMPACK.” The last line toggles the Ketron debugging utility TRACE.

## Appendix G-B: Example of A Path File

mrrmpath:

```
NAME          PATHDATA
DATA          Z:PATHNAME
**           TEXT(6)
accunit       n:/default/input/accunit.dat.v1.6
avoids        n:/default/input/avoids.dat.v1.1
cogener       n:/default/input/cogener.dat.v1.7
crdimprt      n:/default/input/crdimprt.dat.v1.4
demand        n:/default/input/demand.dat.v1.4
distblnd     n:/default/input/distblnd.dat.v1.3
distress      n:/default/input/distress.dat.v1.2
domcrude      n:/default/input/domcrude.dat.v1.2
emish         n:/default/input/emish.dat.v1.1
ethanol       n:/default/input/ethanol.dat.v1.4
fixcols       n:/default/input/fixcols.dat.v1.3
fuelmix       n:/default/input/fuelmix.dat.v1.2
gasoblnd     n:/default/input/gasoblnd.dat.v1.7
main          n:/default/input/main.dat.v1.4
ngprod        n:/default/input/ngprod.dat.v1.2
nrfplant      n:/default/input/nrfplant.dat.v1.7
prdimprt      n:/default/input/prdimprt.dat.v1.3
recipes       n:/default/input/recipes.dat.v1.2
refproc       n:/default/input/refproc.dat.v1.18
setrows       n:/default/input/setrows.dat.v1.4
splash        n:/default/input/splash.dat.v1.4
stream        n:/default/input/stream.dat.v1.3
transit       n:/default/input/transit.dat.v1.6
utility       n:/default/input/utility.dat.v1.5
mchproc       n:/default/input/mchproc.dat.v1.5
limpol        n:/default/input/limpol.dat.v1.3
unfinished    n:/default/input/unfinish.dat.v1.2
prdexp        n:/default/input/prdexp.dat.v1.2
akaexp        n:/default/input/akaexp.dat.v1.1
foreign1
foreign2
fsu
intsetup
epsetup
bldhead
bldstub
ENDATA
```

## Appendix G-C: Makefile

(not part of the Developer's Studio Methodology)

```
FLAGS= -c -g -C -qcharlen=16384 -qmaxmem=-1 -qnoprint \  
-qfltrap=zerodivide -qsave  
INC= -I/refine/pmm_lp_gen/includes/ -I/default/includes  
LIBS= -lwhiz -ldb -lutil -L/usr/lpp/MPS/oml/lib  
DIR= /default/objects/  
SIR= /default/source/  
LIR= /default/objects/  
OMLSPA = /refine/pmm_lp_gen/includes/omlspace \  
/refine/pmm_lp_gen/includes/ipmmtest  
OBJS= $(LIR)mrm.v1.2.o \  
$(LIR)extpnt.v1.2.o \  
$(LIR)epadjust.v1.2.o \  
$(LIR)bldhead.v1.2.o \  
$(LIR)bldstub.v1.2.o \  
$(LIR)intsetup.v1.2.o \  
$(LIR)foreign.v1.2.o \  
$(LIR)fsu.v1.2.o \  
$(LIR)akaexp.v1.2.o \  
$(LIR)prdexp.v1.4.o \  
$(LIR)unfinished.v1.2.o \  
$(LIR)lplookup.v1.2.o \  
$(LIR)output.v1.2.o \  
$(LIR)ermcrude.v1.2.o \  
$(LIR)ermother.v1.2.o \  
$(LIR)ermprod.v1.2.o \  
$(LIR)tabread.v1.2.o \  
$(LIR)limpol.v1.2.o \  
$(LIR)mchproc.v1.4.o \  
$(LIR)crdimprt.v1.2.o \  
$(LIR)accunit.v1.6.o \  
$(LIR)refproc.v1.6.o \  
$(LIR)nrflant.v1.5.o \  
$(LIR)stream.v1.2.o \  
$(LIR)distbld.v1.3.o \  
$(LIR)gasobld.v1.4.o \  
$(LIR)domcrude.v1.3.o \  
$(LIR)demand.v1.3.o \  
$(LIR)utility.v1.3.o \  
$(LIR)utilitye.v1.2.o \  
$(LIR)cogener.v1.4.o \  
$(LIR)fuelmix.v1.2.o \  
$(LIR)recipes.v1.2.o \  
$(LIR)ethanol.v1.9.o \  
$(LIR)ngprod.v1.2.o \  
$(LIR)setrows.v1.2.o \  
$(LIR)fixcols.v1.2.o \  
$(LIR)transit3.v1.4.o \  
$(LIR)transit5.v1.2.o \  
$(LIR)prdimprt.v1.2.o \  
$(LIR)splash.v1.3.o \  
$(LIR)distress.v1.2.o \  
$(LIR)avoids.v1.2.o \  
$(DIR)omlanal.v1.6.o \  
$(LIR)emish.v1.2.o
```

```
mrm: $(OBJS)  
xlf -o mrm -g -C $(OBJS) $(LIBS) -bloadmap:loadmap
```

\$(LIR)mrm.v1.3.o: \$(SIR)mrm.f \$(OMLSPA)  
xlf \$(FLAGS) -o \$(LIR)mrm.v1.3.o \$(INC) \$(SIR)mrm.f  
\$(LIR)extpnt.v1.2.o: \$(SIR)extpnt.f  
xlf \$(FLAGS) -o \$(LIR)extpnt.v1.2.o \$(INC) \$(SIR)extpnt.f  
\$(LIR)epadjust.v1.2.o: \$(SIR)epadjust.f  
xlf \$(FLAGS) -o \$(LIR)epadjust.v1.2.o \$(INC) \$(SIR)epadjust.f  
\$(LIR)bldhead.v1.2.o: \$(SIR)bldhead.f  
xlf \$(FLAGS) -o \$(LIR)bldhead.v1.2.o \$(INC) \$(SIR)bldhead.f  
\$(LIR)bldstub.v1.2.o: \$(SIR)bldstub.f  
xlf \$(FLAGS) -o \$(LIR)bldstub.v1.2.o \$(INC) \$(SIR)bldstub.f  
\$(LIR)intsetup.v1.2.o: \$(SIR)intsetup.f  
xlf \$(FLAGS) -o \$(LIR)intsetup.v1.2.o \$(INC) \$(SIR)intsetup.f  
\$(LIR)foreign.v1.2.o: \$(SIR)foreign.f  
xlf \$(FLAGS) -o \$(LIR)foreign.v1.2.o \$(INC) \$(SIR)foreign.f  
\$(LIR)fsu.v1.2.o: \$(SIR)fsu.f  
xlf \$(FLAGS) -o \$(LIR)fsu.v1.2.o \$(INC) \$(SIR)fsu.f  
\$(LIR)akaexp.v1.2.o: \$(SIR)akaexp.f  
xlf \$(FLAGS) -o \$(LIR)akaexp.v1.2.o \$(INC) \$(SIR)akaexp.f  
\$(LIR)prdexp.v1.4.o: \$(SIR)prdexp.f  
xlf \$(FLAGS) -o \$(LIR)prdexp.v1.4.o \$(INC) \$(SIR)prdexp.f  
\$(LIR)unfinished.v1.2.o: \$(SIR)unfinished.f  
xlf \$(FLAGS) -o \$(LIR)unfinished.v1.2.o \$(INC) \$(SIR)unfinished.f  
\$(LIR)lplookup.v1.2.o: \$(SIR)lplookup.f  
xlf \$(FLAGS) -o \$(LIR)lplookup.v1.2.o \$(INC) \$(SIR)lplookup.f  
\$(LIR)output.v1.2.o: \$(SIR)output.f  
xlf \$(FLAGS) -o \$(LIR)output.v1.2.o \$(INC) \$(SIR)output.f  
\$(LIR)limpol.v1.2.o: \$(SIR)limpol.f  
xlf \$(FLAGS) -o \$(LIR)limpol.v1.2.o \$(INC) \$(SIR)limpol.f  
\$(LIR)tabread.v1.2.o: \$(SIR)tabread.f  
xlf \$(FLAGS) -o \$(LIR)tabread.v1.2.o \$(INC) \$(SIR)tabread.f  
\$(LIR)mchproc.v1.4.o: \$(SIR)mchproc.f  
xlf \$(FLAGS) -o \$(LIR)mchproc.v1.4.o \$(INC) \$(SIR)mchproc.f  
\$(LIR)ermcrude.v1.2.o: \$(SIR)ermcrude.f  
xlf \$(FLAGS) -o \$(LIR)ermcrude.v1.2.o \$(INC) \$(SIR)ermcrude.f  
\$(LIR)ermother.v1.2.o: \$(SIR)ermother.f  
xlf \$(FLAGS) -o \$(LIR)ermother.v1.2.o \$(INC) \$(SIR)ermother.f  
\$(LIR)ermprod.v1.2.o: \$(SIR)ermprod.f  
xlf \$(FLAGS) -o \$(LIR)ermprod.v1.2.o \$(INC) \$(SIR)ermprod.f  
\$(LIR)crdimprt.v1.2.o: \$(SIR)crdimprt.f  
xlf \$(FLAGS) -o \$(LIR)crdimprt.v1.2.o \$(INC) \$(SIR)crdimprt.f  
\$(LIR)accunit.v1.6.o: \$(SIR)accunit.f  
xlf \$(FLAGS) -o \$(LIR)accunit.v1.6.o \$(INC) \$(SIR)accunit.f  
\$(LIR)refproc.v1.6.o: \$(SIR)refproc.f  
xlf \$(FLAGS) -o \$(LIR)refproc.v1.6.o \$(INC) \$(SIR)refproc.f  
\$(LIR)nrfplant.v1.5.o: \$(SIR)nrfplant.f  
xlf \$(FLAGS) -o \$(LIR)nrfplant.v1.5.o \$(INC) \$(SIR)nrfplant.f  
\$(LIR)stream.v1.2.o: \$(SIR)stream.f  
xlf \$(FLAGS) -o \$(LIR)stream.v1.2.o \$(INC) \$(SIR)stream.f  
\$(LIR)distblnd.v1.3.o: \$(SIR)distblnd.f  
xlf \$(FLAGS) -o \$(LIR)distblnd.v1.3.o \$(INC) \$(SIR)distblnd.f  
\$(LIR)gasoblnd.v1.4.o: \$(SIR)gasoblnd.f  
xlf \$(FLAGS) -o \$(LIR)gasoblnd.v1.4.o \$(INC) \$(SIR)gasoblnd.f  
\$(LIR)domcrude.v1.3.o: \$(SIR)domcrude.f  
xlf \$(FLAGS) -o \$(LIR)domcrude.v1.3.o \$(INC) \$(SIR)domcrude.f  
\$(LIR)demand.v1.3.o: \$(SIR)demand.f  
xlf \$(FLAGS) -o \$(LIR)demand.v1.3.o \$(INC) \$(SIR)demand.f  
\$(LIR)utility.v1.3.o: \$(SIR)utility.f  
xlf \$(FLAGS) -o \$(LIR)utility.v1.3.o \$(INC) \$(SIR)utility.f  
\$(LIR)utilitye.v1.2.o: \$(SIR)utilitye.f  
xlf \$(FLAGS) -o \$(LIR)utilitye.v1.2.o \$(INC) \$(SIR)utilitye.f  
\$(LIR)cogener.v1.4.o: \$(SIR)cogener.f  
xlf \$(FLAGS) -o \$(LIR)cogener.v1.4.o \$(INC) \$(SIR)cogener.f  
\$(LIR)fuelmix.v1.2.o: \$(SIR)fuelmix.f

```

xIf $(FLAGS) -o $(LIR)fuelmix.v1.2.o $(INC) $(SIR)fuelmix.f
$(LIR)recipes.v1.2.o: $(SIR)recipes.f
xIf $(FLAGS) -o $(LIR)recipes.v1.2.o $(INC) $(SIR)recipes.f
$(LIR)ethanol.v1.9.o: $(SIR)ethanol.f
xIf $(FLAGS) -o $(LIR)ethanol.v1.9.o $(INC) $(SIR)ethanol.f
$(LIR)ngprod.v1.2.o: $(SIR)ngprod.f
xIf $(FLAGS) -o $(LIR)ngprod.v1.2.o $(INC) $(SIR)ngprod.f
$(LIR)setrows.v1.2.o: $(SIR)setrows.f
xIf $(FLAGS) -o $(LIR)setrows.v1.2.o $(INC) $(SIR)setrows.f
$(LIR)fixcols.v1.2.o: $(SIR)fixcols.f
xIf $(FLAGS) -o $(LIR)fixcols.v1.2.o $(INC) $(SIR)fixcols.f
$(LIR)transit3.v1.4.o: $(SIR)transit3.f
xIf $(FLAGS) -o $(LIR)transit3.v1.4.o $(INC) $(SIR)transit3.f
$(LIR)transit5.v1.2.o: $(SIR)transit5.f
xIf $(FLAGS) -o $(LIR)transit5.v1.2.o $(INC) $(SIR)transit5.f
$(LIR)prdimprt.v1.2.o: $(SIR)prdimprt.f
xIf $(FLAGS) -o $(LIR)prdimprt.v1.2.o $(INC) $(SIR)prdimprt.f
$(LIR)splash.v1.3.o: $(SIR)splash.f
xIf $(FLAGS) -o $(LIR)splash.v1.3.o $(INC) $(SIR)splash.f
$(LIR)distress.v1.2.o: $(SIR)distress.f
xIf $(FLAGS) -o $(LIR)distress.v1.2.o $(INC) $(SIR)distress.f
$(LIR)avoids.v1.2.o: $(SIR)avoids.f
xIf $(FLAGS) -o $(LIR)avoids.v1.2.o $(INC) $(SIR)avoids.f
$(LIR)emish.v1.2.o : $(SIR)emish.f
xIf $(FLAGS) -o $(LIR)emish.v1.2.o $(INC) $(SIR)emish.f

```

## Appendix G-D: Common Blocks

### File: ipmmtest

```
! $Header: N:/default/includes/RCS/ipmmtest,v 1.3 1999/12/21 14:13:29 DSA Exp $
COMMON /IPMMREAL/MAX, MIN, VALUE, INFINITY,          &
    WOP,                                             &
    REALURYR, YRDOLLAR, ENV, LOC, OVCOST
REAL*8    MAX(1000)
REAL*8    MIN(1000)
REAL*8    VALUE(1000)
REAL*8    INFINITY
REAL*8    WOP(26)
REAL*8    REALURYR
REAL*8    YRDOLLAR
REAL*8    ENV(5)
REAL*8    LOC(5)
REAL*8    OVCOST(5)
COMMON /IPMMINT/COUNT, DUMMY,                      &
    I, IRET, IROWS, J, JCOLS, K, KROWS, NUMREG, EXPREGSS, &
    USERYEAR, DMDREG, NUMYRS, DBPROBG, COMTAB1, COMTAB2
INTEGER*4  COUNT
INTEGER*4  DUMMY
INTEGER*4  I
INTEGER*4  IRET
INTEGER*4  IROWS
INTEGER*4  J
INTEGER*4  JCOLS
INTEGER*4  K
INTEGER*4  KROWS
INTEGER*4  NUMREG
INTEGER*4  EXPREGSS
INTEGER*4  USERYEAR
INTEGER*4  DMDREG
INTEGER*4  NUMYRS
INTEGER*4  DBPROBG(22)
INTEGER*4  COMTAB1(13)
INTEGER*4  COMTAB2(13)
COMMON /IPMMCHAR/HEAD, STUB, PROCESS, BND, CNAME,   &
    DECKNAME, LRNAME, OBJ, RHS, RNAME, RCHAR5, REGION, &
    EXPREG, DEMNDREG, DEMNDPAD, PATH, FRCRD, EXPRD
CHARACTER*8    HEAD(1000)
CHARACTER*8    STUB(1000)
CHARACTER*8    PROCESS(1000)
CHARACTER*8    BND
CHARACTER*8    CNAME
CHARACTER*8    DECKNAME
CHARACTER*8    LRNAME
CHARACTER*8    OBJ
CHARACTER*8    RHS
CHARACTER*8    RNAME
CHARACTER*5    RCHAR5
CHARACTER*1    REGION(5)
CHARACTER*2    EXPREG(5)
CHARACTER*1    DEMNDREG(9)
CHARACTER*1    DEMNDPAD(9)
CHARACTER*48    PATH(40)
CHARACTER*8    FRCRD(5)
CHARACTER*8    EXPRD(11)
```

**File: lpout**

Common block used for report writing

C LPOUT COMMON BLOCK FOR USE IN OML MATRIX SOLUTION

```

!
REAL    PRDPRC(9,18)
REAL    BASECAP(5,27)
REAL    BASEUTL(5,27)
REAL    INVCAP(5,27)
REAL    INVUTL(5,27)
REAL    TOTCAP(5,27)
REAL    TOTUTL(5,27)
REAL    TOTSUP(6)
REAL    PUTL(5,27)
REAL    RFCRDCR(6)
REAL    RFCRDAKA(6)
REAL    RFCRDL48(6)
REAL    RFQICRD(6)
REAL    RFIMCR(6)
REAL    RFQISPR(6)
REAL    RFIMTP(6)
REAL    RFQEXCRD(6)
REAL    RFPQNGL(6)
REAL    RFQNGLRF(6)
REAL    NGLRF(6)
REAL    NGLMK(6)
REAL    RFQPRCG(6)
REAL    RFPQIPRDT(6)
REAL    RFPQUFC(6)
REAL    RFQEXPRDT(6)
REAL    RFQPRDDM(11)
REAL    QCDUPD(6)
REAL    RFQDINPOT(6)
REAL    RFETHD(6)
REAL    RFMTBI(6)
REAL    RFMETI(6)
REAL    RFMETD(6)
REAL    RFMETCHM(6)
REAL    RFMETM85(6)
REAL    RFMETTETH(6)
REAL    RFETHE85(6)
REAL    RFETHETB(6)
REAL    RFETHMGS(6)
REAL    RFCRDOTH(6)
REAL    OTHOXY(6)
REAL    QPRDIMD(11,23)
REAL    QPRDEXD(6,23)
COMMON/LPTAB/PRDPRC,BASECAP,BASEUTL,INVCAP,INVUTL,TOTCAP,
TOTUTL,PUTL,RFCRDCR,RFCrAKA,RFCrL48,RFQICRD,RFIMCR,
RFQEXCRD,RFPQNGL,RFQNGLRF,NGLRF,NGLMK,RFQPRCG,RFPQIPRDT,
RFPQUFC,RFQEXPRDT,RFQPRDDM,QCDUPD,RFQDINPOT,RFETHD,RFMTBI,
RFMETI,RFMETD,RFMETCHM,RFMETM85,RFMETTETH,RFETHE85,TOTSUP,
RFQISPR,RFIMTP,RFETHETB,RFETHMGS,OTHOXY,QPRDIMD,QPRDEXD,
RFCRDOTH
```

## File: DFINC2

Common block used for OML database functions

```
! $Header: N:/default/includes/RCS/dfinc2,v 1.5 2000/05/18 15:12:11 DSA Exp $
INTERFACE
INTEGER*4 FUNCTION DFINIT (TITLE,TBUF,LEN)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFINIT
!DEC$ATTRIBUTES REFERENCE :: TITLE,TBUF,LEN
CHARACTER*8 TITLE
CHARACTER*1 TBUF(2)
INTEGER*4 LEN
END FUNCTION

INTEGER*4 FUNCTION SetConsolePrintMode(IVAL)
!DEC$ATTRIBUTES STDCALL, ALIAS: '_SetConsolePrintMode@4' :: SetConsolePrintMode
!DEC$ATTRIBUTES VALUE :: IVAL
INTEGER*4 IVAL
END FUNCTION

INTEGER*4 FUNCTION DFOPEN (DBFILE,ACTFILE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFOPEN
!DEC$ATTRIBUTES REFERENCE :: DBFILE,ACTFILE
INTEGER*4 DBFILE(2)
CHARACTER*8 ACTFILE
END FUNCTION

INTEGER*4 FUNCTION DFCLOSE (DBFILE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFCLOSE
!DEC$ATTRIBUTES REFERENCE :: DBFILE
INTEGER*4 DBFILE(2)
END FUNCTION

INTEGER*4 FUNCTION DFDEL (DBFILE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFDEL
!DEC$ATTRIBUTES REFERENCE :: DBFILE
INTEGER*4 DBFILE(2)
END FUNCTION

INTEGER*4 FUNCTION DFLIST (DBFILE,MASK,PNAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFLIST
!DEC$ATTRIBUTES REFERENCE :: DBFILE,MASK,PNAME
INTEGER*4 DBFILE(2)
CHARACTER*8 MASK
CHARACTER*8 PNAME
END FUNCTION

INTEGER*4 FUNCTION DFPINIT (DB,DBFILE,ACTPROB)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFPINIT
!DEC$ATTRIBUTES REFERENCE :: DB,DBFILE,ACTPROB
INTEGER*4 DB(2)
INTEGER*4 DBFILE(2)
CHARACTER*8 ACTPROB
END FUNCTION

INTEGER*4 FUNCTION DFPDEL (DB)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFPDEL
!DEC$ATTRIBUTES REFERENCE :: DB
INTEGER*4 DB(2)
END FUNCTION

INTEGER*4 FUNCTION DFPCPY (TO,FROM)
```

```
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFPCPY
!DEC$ATTRIBUTES REFERENCE :: TO,FROM
INTEGER*4 TO
INTEGER*4 FROM
END FUNCTION
```

```
INTEGER*4 FUNCTION DFPLIST (DB,MASK,TNAME,TYPE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFPLIST
!DEC$ATTRIBUTES REFERENCE :: DB,MASK,TNAME,TYPE
INTEGER*4 DB(2)
CHARACTER*8 MASK
CHARACTER*8 TNAME
INTEGER*4 TYPE
END FUNCTION
```

```
INTEGER*4 FUNCTION DFPTDEL (DB)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFPTDEL
!DEC$ATTRIBUTES REFERENCE :: DB
INTEGER*4 DB(2)
END FUNCTION
```

```
INTEGER*4 FUNCTION DFPTCPY (TO,FROM)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFPTCPY
!DEC$ATTRIBUTES REFERENCE :: TO,FROM
INTEGER*4 TO
INTEGER*4 FROM
END FUNCTION
```

```
INTEGER*4 FUNCTION DFPMDL (DB)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFPMDL
!DEC$ATTRIBUTES REFERENCE :: DB
INTEGER*4 DB(2)
END FUNCTION
```

```
INTEGER*4 FUNCTION DFPMCPY (TO,FROM)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFPMCPY
!DEC$ATTRIBUTES REFERENCE :: TO,FROM
INTEGER*4 TO
INTEGER*4 FROM
END FUNCTION
```

```
INTEGER*4 FUNCTION DFPSDEL (DB)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFPSDEL
!DEC$ATTRIBUTES REFERENCE :: DB
INTEGER*4 DB(2)
END FUNCTION
```

```
INTEGER*4 FUNCTION DFPSCPY (TO,FROM)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFPSCPY
!DEC$ATTRIBUTES REFERENCE :: TO,FROM
INTEGER*4 TO
INTEGER*4 FROM
END FUNCTION
```

```
INTEGER*4 FUNCTION DFPRTBI (DB,FILENAME,DECKNAME,PRNTSW,TABLIST)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFPRTBI
!DEC$ATTRIBUTES REFERENCE :: DB,FILENAME,DECKNAME,PRNTSW,TABLIST
INTEGER*4 DB(2)
CHARACTER*8 FILENAME
CHARACTER*8 DECKNAME
INTEGER*4 PRNTSW
CHARACTER*8 TABLIST
END FUNCTION
```

```

INTEGER*4 FUNCTION DFTINIT (TABLE,DB,TABNAME,TYPE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFTINIT
!DEC$ATTRIBUTES REFERENCE :: TABLE,DB,TABNAME,TYPE
INTEGER*4 TABLE(2)
INTEGER*4 DB(2)
CHARACTER*8 TABNAME
INTEGER*4 TYPE
END FUNCTION

```

```

INTEGER*4 FUNCTION DFTNEW (TABLE,DB,TABNAME,TYPE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFTNEW
!DEC$ATTRIBUTES REFERENCE :: TABLE,DB,TABNAME,TYPE
INTEGER*4 TABLE(2)
INTEGER*4 DB(2)
CHARACTER*8 TABNAME
INTEGER*4 TYPE
END FUNCTION

```

```

INTEGER*4 FUNCTION DFTDIM (TABLE,NROWS,NCOLS)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFTDIM
!DEC$ATTRIBUTES REFERENCE :: TABLE,NROWS,NCOLS
INTEGER*4 TABLE(2)
INTEGER*4 NROWS
INTEGER*4 NCOLS
END FUNCTION

```

```

INTEGER*4 FUNCTION DFTDEL (TABLE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFTDEL
!DEC$ATTRIBUTES REFERENCE :: TABLE
INTEGER*4 TABLE(2)
END FUNCTION

```

```

INTEGER*4 FUNCTION DFTCPY (TO,FROM)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFTCPY
!DEC$ATTRIBUTES REFERENCE :: TO,FROM
INTEGER*4 TO
INTEGER*4 FROM
END FUNCTION

```

```

INTEGER*4 FUNCTION DFTSNDX (TABLE,STUB)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFTSNDX
!DEC$ATTRIBUTES REFERENCE :: TABLE,STUB
INTEGER*4 TABLE(2)
CHARACTER*8 STUB
END FUNCTION

```

```

INTEGER*4 FUNCTION DFTHNDX (TABLE,HEAD)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFTHNDX
!DEC$ATTRIBUTES REFERENCE :: TABLE,HEAD
INTEGER*4 TABLE(2)
CHARACTER*8 HEAD
END FUNCTION

```

```

INTEGER*4 FUNCTION DFTSMSK (TABLE,START,MASK)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFTSMSK
!DEC$ATTRIBUTES REFERENCE :: TABLE,START,MASK
INTEGER*4 TABLE(2)
INTEGER*4 START
CHARACTER*8 MASK
END FUNCTION

```

```

INTEGER*4 FUNCTION DFTHMSK (TABLE,START,MASK)

```

```

!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFTHMSK
!DEC$ATTRIBUTES REFERENCE :: TABLE,START,MASK
INTEGER*4 TABLE(2)
INTEGER*4 START
CHARACTER*8 MASK
END FUNCTION

INTEGER*4 FUNCTION DFTNDX (TABLE,RNAME,CNAME,VALUE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFTNDX
!DEC$ATTRIBUTES REFERENCE :: TABLE,RNAME,CNAME,VALUE
INTEGER*4 TABLE(2)
INTEGER*4 RNAME
INTEGER*4 CNAME
INTEGER*4 VALUE(1)
END FUNCTION

INTEGER*4 FUNCTION DFTGETVC (TABLE,RNAME,CNAME,VALUE,COUNT)
!DEC$ATTRIBUTES STDCALL,REFERENCE,ALIAS: '_dftget@20' :: DFTGETVC
!DEC$ATTRIBUTES REFERENCE :: TABLE,RNAME,CNAME,VALUE,COUNT
INTEGER*4 TABLE(2)
INTEGER*4 RNAME
CHARACTER*8 CNAME(1)
REAL*8 VALUE(1)
INTEGER*4 COUNT
END FUNCTION

INTEGER*4 FUNCTION DFTGETV (TABLE,RNAME,CNAME,VALUE,COUNT)
!DEC$ATTRIBUTES STDCALL,REFERENCE,ALIAS: '_dftget@20' :: DFTGETV
!DEC$ATTRIBUTES REFERENCE :: TABLE,RNAME,CNAME,VALUE,COUNT
INTEGER*4 TABLE(2)
INTEGER*4 RNAME
INTEGER*4 CNAME
REAL*8 VALUE(1)
INTEGER*4 COUNT
END FUNCTION

INTEGER*4 FUNCTION DFTGETN (TABLE,RNAME,CNAME,VALUE,COUNT)
!DEC$ATTRIBUTES STDCALL,REFERENCE,ALIAS: '_dftget@20' :: DFTGETN
!DEC$ATTRIBUTES REFERENCE :: TABLE,RNAME,CNAME,VALUE,COUNT
INTEGER*4 TABLE(2)
INTEGER*4 RNAME
INTEGER*4 CNAME
CHARACTER*8 VALUE(1)
INTEGER*4 COUNT
END FUNCTION

INTEGER*4 FUNCTION DFTPUT (TABLE,RNAME,CNAME,VALUE,COUNT)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFTPUT
!DEC$ATTRIBUTES REFERENCE :: TABLE,RNAME,CNAME,VALUE,COUNT
INTEGER*4 TABLE(2)
INTEGER*4 RNAME
INTEGER*4 CNAME
INTEGER*4 VALUE
INTEGER*4 COUNT
END FUNCTION

INTEGER*4 FUNCTION DFTSADD (TABLE,INDEX,STUB)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFTSADD
!DEC$ATTRIBUTES REFERENCE :: TABLE,INDEX,STUB
INTEGER*4 TABLE(2)
INTEGER*4 INDEX
CHARACTER*8 STUB
END FUNCTION

```

```

INTEGER*4 FUNCTION DFTHADD (TABLE,INDEX,HEAD)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFTHADD
!DEC$ATTRIBUTES REFERENCE :: TABLE,INDEX,HEAD
INTEGER*4 TABLE(2)
INTEGER*4 INDEX
CHARACTER*8 HEAD
END FUNCTION

```

```

INTEGER*4 FUNCTION DFTSDEL (TABLE,STUB)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFTSDEL
!DEC$ATTRIBUTES REFERENCE :: TABLE,STUB
INTEGER*4 TABLE(2)
INTEGER*4 STUB
END FUNCTION

```

```

INTEGER*4 FUNCTION DFTHDEL (TABLE,HEAD)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFTHDEL
!DEC$ATTRIBUTES REFERENCE :: TABLE,HEAD
INTEGER*4 TABLE(2)
INTEGER*4 HEAD
END FUNCTION

```

```

INTEGER*4 FUNCTION DFTDISP (TABLE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFTDISP
!DEC$ATTRIBUTES REFERENCE :: TABLE
INTEGER*4 TABLE(2)
END FUNCTION

```

```

INTEGER*4 FUNCTION DFMINIT (DB,MODE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMINIT
!DEC$ATTRIBUTES REFERENCE :: DB,MODE
INTEGER*4 DB(2)
INTEGER*4 MODE
END FUNCTION

```

```

INTEGER*4 FUNCTION DFMEND ()
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMEND
END FUNCTION

```

```

INTEGER*4 FUNCTION DFMSTAT (STAT)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMSTAT
!DEC$ATTRIBUTES REFERENCE :: STAT
INTEGER*4 STAT(9)
END FUNCTION

```

```

INTEGER*4 FUNCTION DFMCRTP (RNAME,TYPE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMCRTP
!DEC$ATTRIBUTES REFERENCE :: RNAME,TYPE
CHARACTER*8 RNAME
CHARACTER*8 TYPE
END FUNCTION

```

```

INTEGER*4 FUNCTION DFMCRSC (RNAME,SCALE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMCRSC
!DEC$ATTRIBUTES REFERENCE :: RNAME,SCALE
CHARACTER*8 RNAME
REAL*8 SCALE
END FUNCTION

```

```

INTEGER*4 FUNCTION DFMCCSC (CNAME,SCALE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMCCSC
!DEC$ATTRIBUTES REFERENCE :: CNAME,SCALE

```

```
CHARACTER*8 CNAME
REAL*8 SCALE
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMCVAL (CNAME,RNAME,VALUE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMCVAL
!DEC$ATTRIBUTES REFERENCE :: CNAME,RNAME,VALUE
CHARACTER*8 CNAME
CHARACTER*8 RNAME
REAL*8 VALUE
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMMVAL (CNAME,RNAME,VALUE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMMVAL
!DEC$ATTRIBUTES REFERENCE :: CNAME,RNAME,VALUE
CHARACTER*8 CNAME
CHARACTER*8 RNAME
REAL*8 VALUE
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMCLR (CNAME,FLAG)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMCLR
!DEC$ATTRIBUTES REFERENCE :: CNAME,FLAG
CHARACTER*8 CNAME
INTEGER*4 FLAG
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMCRRHS (CNAME,RNAME,VALUE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMCRRHS
!DEC$ATTRIBUTES REFERENCE :: CNAME,RNAME,VALUE
CHARACTER*8 CNAME
CHARACTER*8 RNAME
REAL*8 VALUE
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMCRRNG (RNGNAME,RNAME,VALUE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMCRRNG
!DEC$ATTRIBUTES REFERENCE :: RNGNAME,RNAME,VALUE
CHARACTER*8 RNGNAME
CHARACTER*8 RNAME
REAL*8 VALUE
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMCBND (BNDNAME,CNAME,LVALUE,UVALUE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMCBND
!DEC$ATTRIBUTES REFERENCE :: BNDNAME,CNAME,LVALUE,UVALUE
CHARACTER*8 BNDNAME
CHARACTER*8 CNAME
REAL*8 LVALUE
REAL*8 UVALUE
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMRRTTP (RNAME,TYPE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMRRTTP
!DEC$ATTRIBUTES REFERENCE :: RNAME,TYPE
CHARACTER*8 RNAME
CHARACTER*8 TYPE
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMRRTC (RNAME,SCALE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMRRTC
!DEC$ATTRIBUTES REFERENCE :: RNAME,SCALE
CHARACTER*8 RNAME
```

```
REAL*8 SCALE
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMRCSC (CNAME,SCALE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMRCSC
!DEC$ATTRIBUTES REFERENCE :: CNAME,SCALE
CHARACTER*8 CNAME
REAL*8 SCALE
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMRVAL (CNAME,RNAME,VALUE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMRVAL
!DEC$ATTRIBUTES REFERENCE :: CNAME,RNAME,VALUE
CHARACTER*8 CNAME
CHARACTER*8 RNAME
REAL*8 VALUE
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMRRHS (CNAME,RNAME,VALUE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMRRHS
!DEC$ATTRIBUTES REFERENCE :: CNAME,RNAME,VALUE
CHARACTER*8 CNAME
CHARACTER*8 RNAME
REAL*8 VALUE
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMRRNG (RNGNAME,RNAME,VALUE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMRRNG
!DEC$ATTRIBUTES REFERENCE :: RNGNAME,RNAME,VALUE
CHARACTER*8 RNGNAME
CHARACTER*8 RNAME
REAL*8 VALUE
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMRBNB (BNDNAME,CNAME,LVALUE,UVALUE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMRBNB
!DEC$ATTRIBUTES REFERENCE :: BNDNAME,CNAME,LVALUE,UVALUE
CHARACTER*8 BNDNAME
CHARACTER*8 CNAME
REAL*8 LVALUE
REAL*8 UVALUE
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMIROW (NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMIROW
!DEC$ATTRIBUTES REFERENCE :: NAME
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMICOL (NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMICOL
!DEC$ATTRIBUTES REFERENCE :: NAME
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMIRHS (NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMIRHS
!DEC$ATTRIBUTES REFERENCE :: NAME
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMIRNG (NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMIRNG
```

```
!DEC$ATTRIBUTES REFERENCE :: NAME
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMIBND (NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMIBND
!DEC$ATTRIBUTES REFERENCE :: NAME
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMNROW (INDEX,NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMNROW
!DEC$ATTRIBUTES REFERENCE :: INDEX,NAME
INTEGER*4 INDEX
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMNCOL (INDEX,NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMNCOL
!DEC$ATTRIBUTES REFERENCE :: INDEX,NAME
INTEGER*4 INDEX
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMNRHS (INDEX,NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMNRHS
!DEC$ATTRIBUTES REFERENCE :: INDEX,NAME
INTEGER*4 INDEX
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMNRNG (INDEX,NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMNRNG
!DEC$ATTRIBUTES REFERENCE :: INDEX,NAME
INTEGER*4 INDEX
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMNBND (INDEX,NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMNBND
!DEC$ATTRIBUTES REFERENCE :: INDEX,NAME
INTEGER*4 INDEX
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMLROW (MASK,NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMLROW
!DEC$ATTRIBUTES REFERENCE :: MASK,NAME
CHARACTER*8 MASK
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMLCOL (MASK,NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMLCOL
!DEC$ATTRIBUTES REFERENCE :: MASK,NAME
CHARACTER*8 MASK
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMLRHS (MASK,NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMLRHS
!DEC$ATTRIBUTES REFERENCE :: MASK,NAME
CHARACTER*8 MASK
```

```
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMLRNG (MASK,NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMLRNG
!DEC$ATTRIBUTES REFERENCE :: MASK,NAME
CHARACTER*8 MASK
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMLBND (MASK,NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMLBND
!DEC$ATTRIBUTES REFERENCE :: MASK,NAME
CHARACTER*8 MASK
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMLVAL (CNAME,START,INDEX,VALUE,COUNT)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMLVAL
!DEC$ATTRIBUTES REFERENCE :: CNAME,START,INDEX,VALUE,COUNT
CHARACTER*8 CNAME
INTEGER*4 START
INTEGER*4 INDEX(*)
REAL*8 VALUE(*)
INTEGER*4 COUNT
END FUNCTION
```

```
INTEGER*4 FUNCTION DFMTAB (TABLE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFMTAB
!DEC$ATTRIBUTES REFERENCE :: TABLE
INTEGER*4 TABLE
END FUNCTION
```

```
INTEGER*4 FUNCTION DFSINIT (DB,CNAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFSINIT
!DEC$ATTRIBUTES REFERENCE :: DB,CNAME
INTEGER*4 DB(2)
CHARACTER*8 CNAME
END FUNCTION
```

```
INTEGER*4 FUNCTION DFSROW (NAME,SELECT,STAT,VALUE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFSROW
!DEC$ATTRIBUTES REFERENCE :: NAME,SELECT,STAT,VALUE
CHARACTER*8 NAME
CHARACTER*8 SELECT
character*2 stat
REAL*8 VALUE(5)
END FUNCTION
```

```
INTEGER*4 FUNCTION DFSCOL (NAME,SELECT,STAT,VALUE)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFSCOL
!DEC$ATTRIBUTES REFERENCE :: NAME,SELECT,STAT,VALUE
CHARACTER*8 NAME
CHARACTER*8 SELECT
character*2 STAT
REAL*8 VALUE(5)
END FUNCTION
```

```
INTEGER*4 FUNCTION DFSSEND ()
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFSSEND
END FUNCTION
```

```
SUBROUTINE DFNCOPY (TO,FROM)
```

```
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFNCPY
!DEC$ATTRIBUTES REFERENCE :: TO,FROM
INTEGER*4 TO
INTEGER*4 FROM
END SUBROUTINE
```

```
SUBROUTINE DFNCAT (NAME1,NAME2)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFNCAT
!DEC$ATTRIBUTES REFERENCE :: NAME1,NAME2
CHARACTER*8 NAME1
CHARACTER*8 NAME2
END SUBROUTINE
```

```
SUBROUTINE DFNFILL (NAME1,NAME2)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFNFILL
!DEC$ATTRIBUTES REFERENCE :: NAME1,NAME2
CHARACTER*8 NAME1
CHARACTER*8 NAME2
END SUBROUTINE
```

```
SUBROUTINE DFNINCR (NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFNINCR
!DEC$ATTRIBUTES REFERENCE :: NAME
CHARACTER*8 NAME
END SUBROUTINE
```

```
SUBROUTINE DFNMASK (NAME1,NAME2)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFNMASK
!DEC$ATTRIBUTES REFERENCE :: NAME1,NAME2
CHARACTER*8 NAME1
CHARACTER*8 NAME2
END SUBROUTINE
```

```
SUBROUTINE DFNSQOZ (NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFNSQOZ
!DEC$ATTRIBUTES REFERENCE :: NAME
CHARACTER*8 NAME
END SUBROUTINE
```

```
SUBROUTINE DFNSHFT (NAME,N)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFNSHFT
!DEC$ATTRIBUTES REFERENCE :: NAME,N
CHARACTER*8 NAME
INTEGER*4 N
END SUBROUTINE
```

```
INTEGER*4 FUNCTION DFNCMP (NAME1,NAME2)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFNCMP
!DEC$ATTRIBUTES REFERENCE :: NAME1,NAME2
CHARACTER*8 NAME1
CHARACTER*8 NAME2
END FUNCTION
```

```
INTEGER*4 FUNCTION DFNMCMP (MASK,NAME)
!DEC$ATTRIBUTES STDCALL,REFERENCE :: DFNMCMP
!DEC$ATTRIBUTES REFERENCE :: MASK,NAME
CHARACTER*8 MASK
CHARACTER*8 NAME
END FUNCTION
```

```
END INTERFACE
```

## File: WFINC2

Common block used for the WHIZ optimizer

```
! $Header: N:/default/includes/RCS/wfinc2,v 1.4 2003/04/21 14:57:12 DSA Exp $
  TYPE CR
  SEQUENCE
!
  CHARACTER*8 XNAME
  INTEGER   XCORE
  INTEGER   XCORELEN
!
  CHARACTER*8 XACTCASE
  CHARACTER*8 XACTFILE
  CHARACTER*8 XACTPROB
  CHARACTER*8 XBOUND
  CHARACTER*8 XCHOBJ
  CHARACTER*8 XCHRHS
  CHARACTER*8 XCMASK
  CHARACTER*8 XDATA
  CHARACTER*8 XINSERT
  CHARACTER*8 XLOADB
  CHARACTER*8 XMINMAX
  CHARACTER*8 XOBJ
  CHARACTER*8 XPUNCH
  CHARACTER*8 XRANGE
  CHARACTER*8 XRHS
  CHARACTER*8 XRMASK
  CHARACTER*8 XRNGFILE
  CHARACTER*8 XRNGPRNT
  CHARACTER*8 XSAVEB
  CHARACTER*8 XSOLFILE
  CHARACTER*8 XSOLPRNT
  CHARACTER*8 XSOLSTAT
  CHARACTER*8 XTABCASE
!
  REAL*8   XEPS
  REAL*8   XFUNCT
  REAL*8   XINTGOAL
  REAL*8   XMAXVAR
  REAL*8   XPARAM
  REAL*8   XPENCOST
  REAL*8   XPHI
  REAL*8   XRSTOP
  REAL*8   XSIF
  REAL*8   XSSCALE
  REAL*8   XTHETA
  REAL*8   XTOLCHK
  REAL*8   XTOLCHZR
  REAL*8   XTOLCKRW
  REAL*8   XTOLCLRT
  REAL*8   XTOLDJ
  REAL*8   XTOLERR
  REAL*8   XTOLFSTM
  REAL*8   XTOLINV
  REAL*8   XTOLLMAX
  REAL*8   XTOLPERT
  REAL*8   XTOLPIV
  REAL*8   XTOLREL
  REAL*8   XTOLRMAX
  REAL*8   XTOLRWRT
  REAL*8   XTOLUREL
```

```

REAL*8 XTOLV
REAL*8 XTOLZE
REAL*8 XZERO
!
INTEGER XCHECKSW
INTEGER XCLOCKSW
INTEGER XCOMPERR
INTEGER XCOMPSW
INTEGER XCRASHSW
INTEGER XCYCLESW
INTEGER XDEGEND
INTEGER XDEGMAX
INTEGER XDEMAND
INTEGER XDETAIL
INTEGER XDOATTN
INTEGER XDODELTM
INTEGER XDOFEAS
INTEGER XDOLFREQ1
INTEGER XDONFS
INTEGER XDOUNB
INTEGER XDUAL
INTEGER XEQUIL
INTEGER XFEAS
INTEGER XFREQINV
INTEGER XFREQLOG
INTEGER XFREQSAV
INTEGER XFREQSUM
INTEGER XINVERT
INTEGER XITERNO
INTEGER XJ
INTEGER XLUDENSE
INTEGER XLUFILL
INTEGER XLUINV
INTEGER XM
INTEGER XMAJERR
INTEGER XMAXITER
INTEGER XMAXPASS
INTEGER XMAXTIME
INTEGER XMINERR
INTEGER XNEGDJ
INTEGER XNET
INTEGER XNIF
INTEGER XNOWT
INTEGER XRUNMODE
INTEGER XRYANOSB
INTEGER XSCALESW
INTEGER XSCRNSW
INTEGER XSLPNZ
INTEGER XTIMESAV
INTEGER XTRACE
INTEGER XTRAN
INTEGER XUNIQUES
INTEGER XUNBDNDX
INTEGER XUSEFREE
END TYPE CR
!
INTERFACE
!
subroutine getwcr ( icrloc )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: getwcr
!DEC$ATTRIBUTES REFERENCE :: icrloc
integer*4 icrloc
end subroutine

```

```

SUBROUTINE DALPHA (MESSAGE, POS, LENG)
!DEC$ATTRIBUTES STDCALL, REFERENCE :: DALPHA
!DEC$ATTRIBUTES REFERENCE :: MESSAGE, POS, LENG
CHARACTER(*) MESSAGE
INTEGER*4 POS
INTEGER*4 LENG
END SUBROUTINE

```

```

INTEGER*4 FUNCTION WFINIT ( TITLE, TBUF, LEN )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFINIT
!DEC$ATTRIBUTES REFERENCE :: TITLE, TBUF, LEN
CHARACTER*8 TITLE
real*8 TBUF(*)
INTEGER*4 LEN
END FUNCTION

```

```

INTEGER*4 FUNCTION WFDEF ( MODEL, LEN, MODLNAME )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFDEF
!DEC$ATTRIBUTES REFERENCE :: MODEL, LEN, MODLNAME
REAL*8 MODEL(*)
INTEGER*4 LEN
CHARACTER*8 MODLNAME
END FUNCTION

```

```

INTEGER*4 FUNCTION WFSET ( MODEL )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFSET
!DEC$ATTRIBUTES REFERENCE :: MODEL
REAL*8 MODEL(*)
END FUNCTION

```

```

INTEGER*4 FUNCTION WFMP SIN ( ACTFILE, ACTPROB, FILENAME, &
    DECKANME, PRNTSW, REVISE )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFMP SIN
!DEC$ATTRIBUTES REFERENCE :: ACTFILE, ACTPROB, FILENAME
!DEC$ATTRIBUTES REFERENCE :: DECKANME, PRNTSW, REVISE
CHARACTER*8 ACTFILE
CHARACTER*8 ACTPROB
CHARACTER*8 FILENAME
CHARACTER*8 DECKANME
INTEGER*4 PRNTSW
INTEGER*4 REVISE
END FUNCTION

```

```

INTEGER*4 FUNCTION WFMP SOU ( ACTFILE, ACTPROB, FILENAME, &
    DECKANME, ONECOEF )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFMP SOU
!DEC$ATTRIBUTES REFERENCE :: ACTFILE, ACTPROB, FILENAME
!DEC$ATTRIBUTES REFERENCE :: DECKANME, ONECOEF
CHARACTER*8 ACTFILE
CHARACTER*8 ACTPROB
CHARACTER*8 FILENAME
CHARACTER*8 DECKANME
INTEGER*4 ONECOEF
END FUNCTION

```

```

INTEGER*4 FUNCTION WFLOAD ( ACTFILE, ACTPROB )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFLOAD
!DEC$ATTRIBUTES REFERENCE :: ACTFILE, ACTPROB
CHARACTER*8 ACTFILE
CHARACTER*8 ACTPROB
END FUNCTION

```

```
INTEGER*4 FUNCTION WFOPT ( )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFOPT
END FUNCTION
```

```
INTEGER*4 FUNCTION WFEND ( )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFEND
END FUNCTION
```

```
INTEGER*4 FUNCTION WFCVAL ( COLNAME, ROWNAME, VALUE )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFCVAL
!DEC$ATTRIBUTES REFERENCE :: COLNAME, ROWNAME, VALUE
character*8 COLNAME
character*8 ROWNAME
REAL*8 VALUE
END FUNCTION
```

```
INTEGER*4 FUNCTION WFCRHS ( ROWNAME, VALUE )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFCRHS
!DEC$ATTRIBUTES REFERENCE :: ROWNAME, VALUE
character*8 ROWNAME
REAL*8 VALUE
END FUNCTION
```

```
INTEGER*4 FUNCTION WFCRNG ( ROWNAME, VALUE )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFCRNG
!DEC$ATTRIBUTES REFERENCE :: ROWNAME, VALUE
CHARACTER*8 ROWNAME
REAL*8 VALUE
END FUNCTION
```

```
INTEGER*4 FUNCTION WFCBND ( COLNAME, LOBOUND, UPBOUND )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFCBND
!DEC$ATTRIBUTES REFERENCE :: COLNAME, LOBOUND, UPBOUND
character*8 COLNAME
REAL*8 LOBOUND
REAL*8 UPBOUND
END FUNCTION
```

```
INTEGER*4 FUNCTION WFRVAL ( COLNAME, ROWNAME, VALUE )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFRVAL
!DEC$ATTRIBUTES REFERENCE :: COLNAME, ROWNAME, VALUE
character*8 COLNAME
character*8 ROWNAME
REAL*8 VALUE
END FUNCTION
```

```
INTEGER*4 FUNCTION WFRRHS ( ROWNAME, VALUE )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFRRHS
!DEC$ATTRIBUTES REFERENCE :: ROWNAME, VALUE
character*8 ROWNAME
REAL*8 VALUE
END FUNCTION
```

```
INTEGER*4 FUNCTION WFRRNG ( ROWNAME, VALUE )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFRRNG
!DEC$ATTRIBUTES REFERENCE :: ROWNAME, VALUE
CHARACTER*8 ROWNAME
REAL*8 VALUE
END FUNCTION
```

```
INTEGER*4 FUNCTION WFRBND ( COLNAME, LOBOUND, UPBOUND )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFRBND
!DEC$ATTRIBUTES REFERENCE :: COLNAME, LOBOUND, UPBOUND
```

```
character*8 COLNAME
REAL*8 LOBOUND
REAL*8 UPBOUND
END FUNCTION
```

```
INTEGER*4 FUNCTION WFRLVAL ( COLNAME, START, INDEX, VALUE, COUNT)
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFRLVAL
!DEC$ATTRIBUTES REFERENCE :: COLNAME, START, INDEX, VALUE, COUNT
INTEGER*4 COLNAME
INTEGER*4 START
INTEGER*4 INDEX(*)
REAL*8 VALUE(*)
INTEGER*4 COUNT
END FUNCTION
```

```
INTEGER*4 FUNCTION WFRNAME ( INDEX, NAME )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFRNAME
!DEC$ATTRIBUTES REFERENCE :: INDEX, NAME
INTEGER*4 INDEX
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION WFCNAME ( INDEX, NAME )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFCNAME
!DEC$ATTRIBUTES REFERENCE :: INDEX, NAME
INTEGER*4 INDEX
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION WFRMASK ( MASK, NAME )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFRMASK
!DEC$ATTRIBUTES REFERENCE :: MASK, NAME
CHARACTER*8 MASK
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION WFCMASK ( MASK, NAME )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFCMASK
!DEC$ATTRIBUTES REFERENCE :: MASK, NAME
CHARACTER*8 MASK
CHARACTER*8 NAME
END FUNCTION
```

```
INTEGER*4 FUNCTION WFSROW ( NAME, SELECT, STAT, SOLVAL )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFSROW
!DEC$ATTRIBUTES REFERENCE :: NAME, SELECT, STAT, SOLVAL
CHARACTER*8 NAME
CHARACTER*8 SELECT
character*2 STAT
REAL*8 SOLVAL(2)
END FUNCTION
```

```
INTEGER*4 FUNCTION WFSCOL ( NAME, SELECT, STAT, SOLVAL )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFSCOL
!DEC$ATTRIBUTES REFERENCE :: NAME, SELECT, STAT, SOLVAL
CHARACTER*8 NAME
CHARACTER*8 SELECT
character*2 STAT
REAL*8 SOLVAL(2)
END FUNCTION
```

```
INTEGER*4 FUNCTION WFRROW ( NAME, SELECT, STAT, SOLVAL )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFRROW
```

```
!DEC$ATTRIBUTES REFERENCE :: NAME, SELECT, STAT, SOLVAL
INTEGER*4 NAME
CHARACTER*8 SELECT
character*2 STAT
REAL*8 SOLVAL
END FUNCTION
```

```
INTEGER*4 FUNCTION WFCOL ( NAME, SELECT, STAT, SOLVAL )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFCOL
!DEC$ATTRIBUTES REFERENCE :: NAME, SELECT, STAT, SOLVAL
INTEGER*4 NAME
CHARACTER*8 SELECT
character*2 STAT
REAL*8 SOLVAL
END FUNCTION
```

```
INTEGER*4 FUNCTION WFRLIST ( LIST, COUNT )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFRLIST
!DEC$ATTRIBUTES REFERENCE :: LIST, COUNT
CHARACTER*8 LIST
INTEGER*4 COUNT
END FUNCTION
```

```
INTEGER*4 FUNCTION WFCLIST ( LIST, COUNT )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFCLIST
!DEC$ATTRIBUTES REFERENCE :: LIST, COUNT
CHARACTER*8 LIST
INTEGER*4 COUNT
END FUNCTION
```

```
INTEGER*4 FUNCTION WFSVRT ( ACTIVE )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFSVRT
!DEC$ATTRIBUTES REFERENCE :: ACTIVE
INTEGER*4 ACTIVE
END FUNCTION
```

```
INTEGER*4 FUNCTION WFSFILE ( FILENAME, ACTIVE )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFSFILE
!DEC$ATTRIBUTES REFERENCE :: FILENAME, ACTIVE
CHARACTER*8 FILENAME
INTEGER*4 ACTIVE
END FUNCTION
```

```
INTEGER*4 FUNCTION WFCORD ( ACTFILE, ACTPROB, CASENAME, ACTIVE )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFCORD
!DEC$ATTRIBUTES REFERENCE :: ACTFILE, ACTPROB, CASENAME, ACTIVE
CHARACTER*8 ACTFILE
CHARACTER*8 ACTPROB
CHARACTER*8 CASENAME
INTEGER*4 ACTIVE
END FUNCTION
```

```
INTEGER*4 FUNCTION WFRPRT ( )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFRPRT
END FUNCTION
```

```
INTEGER*4 FUNCTION WFRFILE ( FILENAME )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFRFILE
!DEC$ATTRIBUTES REFERENCE :: FILENAME
CHARACTER*8 FILENAME(*)
END FUNCTION
```

```
INTEGER*4 FUNCTION WFSAVEB ( FILENAME )
```

```

!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFSAVEB
!DEC$ATTRIBUTES REFERENCE :: FILENAME
CHARACTER*8 FILENAME(*)
END FUNCTION

INTEGER*4 FUNCTION WFLOADB ( FILENAME )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFLOADB
!DEC$ATTRIBUTES REFERENCE :: FILENAME
CHARACTER*8 FILENAME(*)
END FUNCTION

INTEGER*4 FUNCTION WFPUNCH ( FILENAME, DECKANME )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFPUNCH
!DEC$ATTRIBUTES REFERENCE :: FILENAME, DECKANME
CHARACTER*8 FILENAME
CHARACTER*8 DECKANME
END FUNCTION

INTEGER*4 FUNCTION WFINSRT ( FILENAME, DECKANME )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFINSRT
!DEC$ATTRIBUTES REFERENCE :: FILENAME, DECKANME
CHARACTER*8 FILENAME
CHARACTER*8 DECKANME
END FUNCTION

INTEGER*4 FUNCTION WFMGDMP ( MODEL, WMGNAME, KEEPFC )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFMGDMP
!DEC$ATTRIBUTES REFERENCE :: MODEL, WMGNAME, KEEPFC
REAL*8 MODEL(*)
CHARACTER*8 WMGNAME
INTEGER*4 KEEPFC
END FUNCTION

INTEGER*4 FUNCTION WFMGLOD ( MODEL, WMGNAME, MODLNAME )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFMGLOD
!DEC$ATTRIBUTES REFERENCE :: MODEL, WMGNAME, MODLNAME
REAL*8 MODEL(*)
CHARACTER*8 WMGNAME
CHARACTER*8 MODLNAME
END FUNCTION

INTEGER*4 FUNCTION WFCRGET ( NAME, VALUE, VLEN, ALEN )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFCRGET
!DEC$ATTRIBUTES REFERENCE :: NAME, VALUE, VLEN, ALEN
CHARACTER*8 NAME
INTEGER*4 VALUE
INTEGER*4 VLEN
INTEGER*4 ALEN
END FUNCTION

INTEGER*4 FUNCTION WFCRPUT ( COMMAND, NAME, VALUE, STRING, VERBOSE )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFCRPUT
!DEC$ATTRIBUTES REFERENCE :: COMMAND, NAME, VALUE, STRING, VERBOSE
CHARACTER*8 COMMAND
CHARACTER*8 NAME
INTEGER*4 VALUE
INTEGER*4 STRING
INTEGER*4 VERBOSE
END FUNCTION

INTEGER*4 FUNCTION WFALLOC ( MODEL, LEN )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFALLOC
!DEC$ATTRIBUTES REFERENCE :: MODEL, LEN

```

```
REAL*8 MODEL(*)
INTEGER*4 LEN
END FUNCTION
```

```
SUBROUTINE WFFREE ( MODEL, LEN )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFFREE
!DEC$ATTRIBUTES REFERENCE :: MODEL, LEN
REAL*8 MODEL(*)
INTEGER*4 LEN
END SUBROUTINE
```

```
INTEGER*4 FUNCTION WFRDCR ( CRFILE )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFRDCR
!DEC$ATTRIBUTES REFERENCE :: CRFILE
CHARACTER*8 CRFILE
END FUNCTION
```

```
INTEGER*4 FUNCTION WFWRCR ( CRFILE )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFWRCR
!DEC$ATTRIBUTES REFERENCE :: CRFILE
CHARACTER*8 CRFILE
END FUNCTION
```

```
SUBROUTINE WFSYSR ( FMT )
!DEC$ATTRIBUTES STDCALL, REFERENCE :: WFSYSR
!DEC$ATTRIBUTES REFERENCE :: FMT
CHARACTER*8 FMT
END SUBROUTINE
```

!

```
subroutine PICK (CASEKEY, PICKRG, PICRTN, I)
!DEC$ATTRIBUTES STDCALL, REFERENCE :: pick
integer*2 casekey(*)
integer*4 pickrg(*)
integer*4 picrtn(*)
integer*4 i
END SUBROUTINE
```

```
subroutine FIND (CASEKEY, Ival, SL, Jval, I)
!DEC$ATTRIBUTES STDCALL, REFERENCE :: find
integer*2 casekey(*)
integer*4 sl(*)
integer*4 i,ival,jval
END SUBROUTINE
```

```
END INTERFACE
integer icrloc
TYPE (CR) :: OML
POINTER (icrloc,OML)
common/wcr/icrloc
```

## Appendix G-E: MRM Data Conversion

The current data used in the MRM were last updated using the Jun2003 data (referred to as ENSYS03Jun) provided by EnSys Company. (No updates were made for *AEO2005*.) Due to the differences in data format (OMNI vs OML) and naming conventions, the ENSYS03Jun data had to undergo conversion; and, new mapping data tables had to be added to the MRM files prior to being used by the MRM.

The updated OMNI data files provided by ENSYS and used to update the mrm data tables are located in the directory `m:/ogs/pmm_prj/ensys/ensys03_Jun/data/`, and include:

R-GCB.DAT  
R-MPROC.DAT  
R-NPROC1.DAT  
R-NPROC2.DAT  
R-PROC1.DAT  
R-PROC2.DAT  
Table INUNIT Revised 0703.xls

The following provides a summary of the effort it took to convert the ENSYS03Jun OMNI data tables (\*.DAT) into OML RTB tables (to be read by the matrix generation code). A shareware c-compiler called LCC-win32 was used. The `omni2rtb.c` program is located in the directory `m:/ogs/pmm_prj/ensys/ensys03_Jun/source/`. The c-compiler may be installed on a local PC by executing the installation program `M:\ogs\pmm_prj\C-Compiler\LCC-Win32.exe`.

To compile on the PC:

1. Put the `omni2rtb.c` file in the directory you want to run from:  
`c:\Documents and Settings\EM4\mydocs\c-test\`
2. From the START menu, click on Programs, `lcc-win32`, `lcc-win32.exe`
3. From within the LCC program window, OPEN the `omni2rtb.c` file located in the `c-test` directory.
4. If no changes are needed, click on the COMPILER menu and select REBUILD ALL. This will create an `omni2rtb.exe` file in a new `lcc` directory within the `c-test` directory.

To execute on the PC:

1. Go to the newly created `lcc` directory, put the Ensys \*.DAT files into this directory, and open a DOS window (Command Prompt). In this window, move to the `...c-test/lcc/` directory and type

```
omni2rtb <input file path/name> <output file path/name>
```

```
ie., omni2rtb R-GCB.DAT gcb.out
```

**Note: prior to the AEO2003 effort, the following methodology was used from the RS6000 using a c-compiler on that platform.**

1. The code to convert the OMNI tables to RTB tables is called *omni2rtb.c* and can be found in directory *m:/ogs/pmm\_prj/ensys/ensys01-feb/source01/* (on the EIA NT server).
2. To compile and execute the *omni2rtb* type:  
compile: *cc -o <exec filename> <source code filename>*  
execute: *<exec filename> <input data path/filename> <output filename>*

For example, if all files are in the same directory:

```
cc -o omniexec omni2rtb.c  
omniexec v0.ensrymeq.gdb omniout
```

3. Technology database development since 1994, according to Ensys:
  - C Implementation of weight balancing on every process vector
  - C Implementation of rigorous sulfur balancing on every process vector (down to the ppm level)
  - C Conversion of the technology database to spreadsheet basis (Excel)
  - C Implementation of model compositing system. This current task is directed to RYM-type regional/prototypical refinery fuels/regulatory studies and takes advantage of the fact that, in any one case, crude slate is essentially fixed. This enables a much smaller matrix to be generated, with yields and qualities crude slate dependent, from the un-composited model tables. Resulting model matrix has far fewer prototypical streams, less susceptibility to over-optimization (and attendant criticism), more manageable when ratio controls are used. (The task to develop this system is proving to be a rigorous diagnostic on model structure, non-composited and composited, and as such is helping eliminate any errors.)

The following list of \*.dat and tables were updated using the new ensys03Jun data:

DISTBLND.DAT

T:DCC

T:DCB

GASOBLND.DAT

T:GCB

T:GCC

T:MCO

T:REGBV

T:LOGBV

T:PRMBV

T:PRCBV

T:UNLBV

T:UNCBV

T:RFMBV

T:RBBV

T:RGCBV

MCHPROC.DAT

T:C4XREP,T:C4XCAP,T:C4XPOL,T:C4XUTI

T:ETXREP,T:ETXCAP,T:ETXPOL,T:ETXUTI

T:FUXREP,T:FUXCAP,T:FUXPOL,T:FUXUTI

T:IOXREP,T:IOXCAP,T:IOXPOL,T:IOXUTI

T:OLXREP,T:OLXCAP,T:OLXPOL,T:OLXUTI

T:SMDREP,T:SMDCAP,T:SMDPOL,T:SMDUTI  
T:SODREP,T:SODCAP,T:SODPOL,T:SODUTI  
RECIPES.DAT  
T:RCP  
REFPROC.DAT  
T:MATBAL  
T:SCL  
T:(uns)  
T:INVGEN  
T:INVUNT  
STREAM.DAT  
T:TRS

## Appendix G-F: Refinery Processes

Refinery Process	Abbreviation
Atmospheric crude distillation	ACU
Alkylation	ALK
Atmospheric Residuum Desulfurization	ARD****
Aromatic recovery	ARP
C2E to C4E dimerization	C24*
Butane isomerization	C4I
Butane splitter	C4S**
Alkylation feed butene isomerizer	C4T*
Butane isomerization	C4X***
Catalytic Distillation Technology	CDT
Cogeneration unit	CGN**
Cogeneration unit, merchant	CGX**
Combined Heat/Power burning syngas fr Pet Coke	CHP**
Polymerization	CPL
Coal to Liquids process	CTX, CTZ
Cyclar	CYC
Distillate desulfurizer	DDS
Gas oil dewaxer	DEW
Dimersol	DIM
Etherol	ETH, ETM
Cryogenic C2 fractionation	ETS*
Etherol unit	ETX***
Fluid cat cracker	FCC
FCC feed hydrofiner	FDS
Mid-distillate furfural treating	FEX
FCC gasoline fractionation units	FGS
Fuel plant	FUM**
Fuel plant	FUX***
Petroleum Coke gasification (produces syngas)	GSF
Petroleum Coke gasification (produces hydrogen)	GSH

<b>Refinery Process</b>	<b>Abbreviation</b>
Hydrogeneration normal pentenes/hexenes	H56*
H2-stream reformer	H2P
H2-partial oxidizer	H2X
Low Conversion Hydrocracking	HCL****
Hydrocracker (partial)	HCM (old MAK)
Naphta hydrocracker	HCN
Gas oil hydrocraker	HCR
Hydrocracker (GasOil)- advanced technology	HCU
Residum hydrocracker	HCV
Hydrodesulfurizer 1	HD1****
Hydrodesulfurizer 2	HD2, HS2****
High density jet fuel hydrotreating	HDN
Hydogen/fuel gas reformer hydrogen	HLO**
Hydogen Purification	HPM
Iso-octane unit converted from MTBE	IOT
Iso-octane unit converted from MTBE, merchant	IOX
High density jet fuel prefractionation	JFP
Recut for JTA	JPS**
Delayed-coker	KRD
Fluid/flexi-coker	KRF
Power generation	KWG**
Lub and wax	LUB
Olefin Saturation Process (MOH fr Ensys)	MDH****
Catalytic Fluidized Bed	MOD****
Naphta hydrotreater	NDS
OCTGAIN Catalytic Hydroprocessor	OCT
C2-C5 dehydrogenation	OLE*
C2-C5 dehydrogenation	OLX***
Produced Fuel Adjustment	PFA**
Pentane/hexane isomerization	PHI
Phillips S zorb	PHS

<b>Refinery Process</b>	<b>Abbreviation</b>
Prism Pressure Swing Absorption- H <sub>2</sub> Purification	PSA
Hydrodesulfurization (S-Zorb) for diesel	PSZ
Residuum desulfurizer	RDS
Refinery Loss	REL**
LP continuous reformer	RFC
HP semi-regenerative reformer	RFH
LP cyclic reformer	RFL
Solvent deasphalting	SDA
Shell Middle Distillate	SMD
Syntroleum GTL Process	SOD
Caustic SO <sub>x</sub> Scrubber	SOX****
Naphta splitter	SPL
Steam generation, lbs/hr	STG**
Sulfur, short tons/day	SUL
Sulphco Selective Oxydation	SUP
Mid-distillate deep hydrotreater	SYD
Thermal cracker C2-C4 feed	TCG*
Thermal cracker naphta feed	TCN*
Thermal cracker gas oil feed	TCV*
Total recycle isomerization	TRI*
Visbreaker/thermal craker	VBR
Vaccum distillation	VCU

\* : Processes involved in reformulated gasoline manufacturing

\*\* : Utilities and pseudo-units

\*\*\* : Processes represented in OXY-Refineries

\*\*\*\* : Not made available for AEO2005-- new, not ready for production

## **APPENDIX H**


### **Historical Data Processing**

# APPENDIX H. Historical Data Processing

## H.1 Processing Data for PMM History File

The PMM uses historical data from a variety of sources. The Microsoft Access database “Build Elcgpur.mdb” collects and aggregates this data to prepare the PMM input file Elcgpur.txt. The three principle databases it collects from (see Figure H.1 ) are the Oil and Gas Information Reporting System (OGIRS) which contains most historical wholesale price and volume information, the Non-Utility Generators (NUGs) database which contains refinery co-generation information, and the Short-Term Integrated Forecasting System (STIFS) database which contains data from the end of the historical period until the PMM forecast is available. Additional individual data elements are added as tables to the Elcgpur.mdb database as described below.

Figure H.1 Database Linkages



### Accessing Data:

The file “Build Elcgpur.mdb” currently resides in the PMM Project folder on nems-f8 (“M” drive) in the folder M:\ogs\pmm\_prj\Database\History (History folder). The following explains how to connect to the component databases that are used in processing the historical input file.

- 1) OGIRS: The OGIRS database is called via a short Visual Basic Application (VBA) script called “modOgirsFunction.” This script searches the table “tblParkList” for the OGIRS keys and frequency of the data required to form a request to the main OGIRS server. Executing this function creates the local table “dbo\_Ogidata” (**Ogidata**) with all data for the requested keys and

frequency. For example, to pull annual data for kerosene-based jet fuel production for all the U.S. PAD Districts enter the OGIRS Sourcekeys for the data series in the Sourcekey column and an “A” (for annual) in the “FrqncName” column as shown in Table H.1 . While it is unnecessary to complete the “SERIES” field, having a local reference to the Sourcekey definition is advisable. A partial list of Sourcekeys available can be found in the database “OGIRS keys.mdb” in the History folder.

**Table H.1 Park List Sample**

<b>SOURCEKEY</b>	<b>SERIES</b>	<b>FrqncName</b>
MKJRPP12	PADD I Jet Fuel Kero Refinery Production (Mbbbl/d)	A
MKJRPP22	PADD II Jet Fuel Kero Refinery Production (Mbbbl/d)	A
MKJRPP32	PADD III Jet Fuel Kero Refinery Production (Mbbbl/d)	A
MKJRPP42	PADD IV Jet Fuel Kero Refinery Production (Mbbbl/d)	A
MKJRPP52	PADD V Jet Fuel Kero Refinery Production (Mbbbl/d)	A
MKJRPUS2	US Jet Fuel Kero Refinery Production (Mbbbl/d)	A

Most of data used by PMM is pulled from OGIRS as an annual number. The only time monthly data are used is for the computation of Refinery Operable Capacity. For this value the January data are used to record the previous year’s capacity.

The OGIRS database is mostly complete; however, there are a few missing fields in the database. To prevent errors from occurring when the queries are executed, the short list of missing values can be appended to **Ogidata** by running the query “Add Missing Keys to data.” This query pulls known missing data<sup>1</sup> from the table “Missing Keys.” An even rarer occurrence is when data are incorrect in OGIRS. Should this be discovered, the correct values can be placed in the table “Data Errors” which will update **Ogidata** when the query “Update data” is executed. All new missing or incorrect data should be reported to the OGIRS database administrator (currently Jaime Chan 202-586-1515). It is also worthwhile to check that keys are, in fact, still missing. The query “Check still missing” will display any duplicate keys in **Ogidata**.

Assuming correct entries in the tables “Missing Keys” and “Data Errors,” the entire download process can accomplished automatically by running the “Update From OGIRS and add missing Keys” Macro.

- 2) STIFS: The Current Month’s Stifs database is located on the EIA LAN at: \\fs-f1\L6489\PRJ\STEO Web Query Database\stifs.mdb. Assistance in obtaining access to this file can be arranged with Tancred Lidderdale (202-586-7321). After obtaining a local copy (typically stored in the History directory), open “Build Elcgpur.mdb” and from the “Tools” menu select “Data base Utilities” and then Linked table manager. Check the tables “Dates” and “Table\_PA” and the box “prompt for new location.” Click OK and Browse to the location of Stifs.mdb. This enables the database to extract the latest STEO database.

---

<sup>1</sup> The last version of OGIRS is missing some of the elements of refinery production: nfrpp1-p5(naphtha feedstocks), otrpp1-p5 (other oils for feedstock), msrpp1-us(miscellaneous products for non-fuel use), and pfrp-us(total petrochemical feedstocks).

- 3) NUGs: Al Beamon (202-586-2025) produces the file “AEO200xNonUtilityData.mdb” each year which contains annual updates to co-generation capacity, generation, and fuel use. This file is “linked” in the manner described above to the file “Nugs.mdb” which manipulates this data to extract refinery specific data. Each of the flowing tables then becomes a linked table to “Build Elcgpur.mdb.”

- 1- Gen Grid
- 2- Gen Own
- 3- Grid Gen Cap
- 4- Own Gen Cap
- 5- Data Grid Fuel Use
- 6- Data Own Fuel Use
- 7- Tbl Grid Gen Percent

- 4) Other Data: Additional sources are used for creation of the PMM history data file.

a) Crude oil wellhead production and prices are provided by the OGSM modeling team (Generally Ted McCallister at 202-586-4820) and are added to the history file as table “Imported OGSM.”

b) Manually update fuel consumption data in Table 47 of the *Petroleum Supply Annual* to table “PSA Table 47.”

c) Global Database Variables: STEOYEAR, HISOYEAR, and STEOYEARS must be reset each year the History file generator is used. Running the Macro “STEO-HISTO” will prompt the user to enter the last Historical information year and the remaining keys will be updated automatically.

d) Index for GDP Price deflators for the forecast period are stored in table “GDP87.” These are generally updated each year by the Macro team and can be found in Table 101 of the Ftab report.

e) Ethanol plant energy costs are derived by Tony Radich (202-586-0504) and stored in Table “Ethanol Energy Costs.”

f) Historical Petroleum Product Prices are from the [State Energy Data 2000: Prices \(SEDP\)](#) and stored in the “Product price data” Table. For *AEO2005*, aggregated CD level data from the previous year was used through 2001. For years 2002 through 2005 these prices were scaled by the change in the equivalent national numbers reported in the September 2004 *Short Term Energy Outlook*.

## Data Processing Queries:

After all the data from the different sources have been input (or linked) to the database several queries (see examples in Figure H.2) are executed to manipulate the data into PMM variables. The numbers correspond with the position of the variable being generated in the Elcgpur.txt file.  code should not need to be changed absent a change in the definition of PMM variable it represents. Should this occur the individual variable query can be examined and edited.

**Figure H.2 Sample Database Queries**

 Create query in Design view	 6b - Calc Refinery Utilization for STEO Years	 a1_15-16a- Create Series for High and Low Sulfur	 a1_29a- Product Stock Withdrawal - STEO years
 Create query by using wizard	 6b - Refinery Utilization for STEO Years	 a1_17a- Ref Prod - OTH Last Year	 a1_30- Ethanol for ETBE All
 1- Collect crude export data	 7-8- Collect Product Import/Export data	 a1_17a- STEO Refined Products OTH	 a1_31- Ethanol for E85 production All
 1- Crude exports -RFQEXCRD	 7-8- Product Import/Export	 a1_18a- Ref Prod - PCF Last Year	 a1_32a- Acquire STEO Year FUEL ETH data
 1- Grab last year of exports	 7-8- Product Import/Export Last Year	 a1_18a- STEO Refined Products PCF	 a1_32a- Fuel ethanol: demand All
 1- Last year as STEOYEARS	 8a- Acquire STEO Year Product imports	 a1_19a- Ref Prod - STG Last Year	 a1_33- Methanol for MTBE production All
 2- Collect crude import data	 8a- Calc Product Import splits in Histo year	 a1_19a- STEO Refined Products STG	 a1_34- Imported MTBE
 2- Crude imports- RFQICRD	 8a- Pivot Histo year split	 a1_20a- Calc TRG Prod in STEO Years	 a1_34a- Imported MTBE STEO
 2a -complete	 8a- STEO Year Gross Product Imports	 a1_20a- Collect STEO TRG Production	 a1_35- US Unfinished Oils Imports
 2a- Acquire STEO Year Import data	 8a- STEO Year Net Product Imports	 a1_21-23- Collect Other Crude Inputs	 a1_35a- Acquire STEO Year UO Import data
 2a- Calc Import Splits in Histo year	 9-20- Collect Refinery Production data	 a1_21-23- Other Crude Inputs	 a1_35a- SETO Years UO Imports
 2a- Pivot STEO Data	 9-20- Refinery Production	 a1_21-23- Other Crude Inputs (Pmm Var on left)	 a1_36- SPR fill rate
 2a- STEO Year Imports Complete	 9-20a- Pivot Histo year split	 a1_21a- Acquire Unaccounted crude - STEO Years	 a1_36a- Acquire STEO Year SPR Fill Rate
 2a- STEO Years	 9-20a- Pivot Ref Prod in STEO Years	 a1_21a- STEO Year UC data	 a1_36a- Acquire STEO Year SPR Wdrl data
 2a- STEO Years2	 9-20a- Ref Prod - Ave Growth	 a1_22 Calc Delta COSXPUSa	 a1_36a- SPR Withdrawal Rate STEO
 2a- Test STEOYEARS	 9-20a- Ref Prod splits in Histo year	 a1_22a- Acquire SPR Withdraw - STEO Years	 a1_37-49 Collect Product Supplied data
 3- Add historical year splits	 9-20a- Ref Prod trends	 a1_22a- Acquire STEO Year crude stocks	 a1_37-49 Product Supplied
 3- Collect NGL data	 9-20a- Refinery Production - Last Years	 a1_22a- Crude Stock Withdrawal - STEO years	 a1_37-49- Product Supplied -STEO trend 1
 3- NGL data- RFPQNGL	 9-20a- Refinery Production -STEO trend 1	 a1_23 Crude product supply- ALL	 a1_37-49a- Collect SETO Product Demands (Supplied)
 3a- Acquire STEO Year NGL data	 9a- Collect STEO Asphalt	 a1_24 Refinery Processing Gain	 a1_37-49a- Product Supplied - Ave Growth
 3a- Calc NLG splits in Histo year	 9a- Ref Prod - Clac AST based on last 10 Year growth	 a1_24a- Acquire RPG- SETO years	 a1_37-49a- Product Supplied in STEO Years
 3a- Pivot Histo year split	 9a- STEO Year Refined Products AST	 a1_24a- RPG SETO	 a1_37a STEO Year Product Supplied-AST
 3a- STEO Year NGL complete	 a1_10a- Ref Prod - COK Last Year	 a1_25-28 Blending Components	 a1_38a- Calc COK Supplied in STEO Years
 4- Collect BASE DISTILLATION CAPACITY MBCD	 a1_10a- STEO Year Refined Products COK	 a1_25a- Gas Blend Comps Imp - STEO	 a1_39a- Calc Jet Fuel Supplied in SETO Years
 4- Last year as STEOYEARS	 a1_11a- Calc Jet Fuel Prod in STEO Years	 a1_25a- Pull Blend Comp Imp- SETO years	 a1_40a- Calc Kerosene Supplied in STEO Years
 4- Refine Cap- RFB DSTCAP	 a1_11a- Collect SETO Jet Fuel	 a1_26a- Blendstock Production- SETO years	 a1_41a- Calc LPG Supplied in SETO Years
 4- Refine Cap- RFB DSTCAP 1	 a1_12a- Ref Prod - KER Last Year	 a1_26a- Pull Blendstock Production- SETO	 a1_42a- Calc Distillate Supplied in SETO Years
 4- Refine Cap- RFB DSTCAP last year	 a1_12a- SETO Year Refined Products KER	 a1_27a- NGL Production- SETO years	 a1_43 High Resid Supplied Splits
 5- Refine Expansion- RFD SCUM	 a1_13a- Calc LPG Prod in STEO years	 a1_27a- Pull NGL from refinery- STEO Years	 a1_43-44 Resid Split
 5- Refine Expansion- STEO year	 a1_13a- Collect SETO LPG Production	 a1_28a- Other Oxygenates- SETO Years	 a1_43-44 Resid Supplied Splits
 6- Collect Utilization data	 a1_14a- Calc SETO N2H Production	 a1_28a- Pull Other Oxygenates- SETO	 a1_43-44- Calc Resid Sulfur split by PADD
 6- Refinery Utilization- RFDSTLTL	 a1_14a- Collect SETO N2H Production	 a1_29 Calc Delta PASXPUSa	 a1_43-44a Resid Split in Histo year
 6-b STEO US Utilization	 a1_15-16a- Calc Resid Sulfur split	 a1_29- Product stock withdraws	 a1_43a- Calc High Sulfur Residual Supplied in SETO Years
 6a- BASE DISTILLATION CAPACITY in histo year MBCD	 a1_15-16a- Calc Resid Sulfur split2	 a1_29- Product stock withdraws 1	 a1_44 Low Resid Supplied Splits
 6a- Calc Refine Utilization in Histo Year	 a1_15-16a- Calc SETO Residual Fuel Production	 a1_29- Pull Crude Stock Change	 a1_44a- Calc Low Sulfur Residual Supplied in SETO Years
 6a- Collect STEO year Total inputs to refineries	 a1_15-16a- Collect SETO Resid Production	 a1_29a- Acquire STEO Year all Pet stocks	 a1_45a- Calc Other Pet Prods Supplied in SETO Years

PMM variables are linked to variables in input databases (primarily OGIRS and STIFS) by table “Map PMM to OGIRS.” A complete list of mappings for both historical and STEO years is available in Table H1. Multiple entries for a PMM variable indicate that more than one OGIRS or STEO variable is needed to calculate the value for these variables. The multiple entries are summed to obtain the PMM variable. For example the OGIRS keys for RFPDOTH are the sum of the keys in that row (Aviation Fuel, Lubes, Naphtha, and Waxes). In the case where a (-) appears before a variable, the key is multiplied by -1 before summation. A “Δ” before a key refers to the difference between the current and previous years value for that key.

**Table H.2 Components of PMM Variables**

PMM Variable Definition	Historical Years	Description	STEO Years	
RFQEXCRD	CRUDE EXPORTS IN MBD	OGIRS- MCREXPx2 (Where x is PADD#)	PADD x Averages/Totals Crude Oil Exports (Mbb/d)	Assume last historical year
RFQICRD	CRUDE IMPORTS IN MMBD	OGIRS- MCRIMPx2 (Where x is PADD#)	PADD x Averages/Totals Crude Oil Imports (Mbb/d)	CONXPUS use last historical year % to parse to PADDs
RFPQNGL	NGL PRODUCTION IN MMBD	OGIRS- MLPSNPx1 (Where x is PADD#)	PADD x Averages/Totals Natural Gas Liquids and LRGs Totals Field Production (Mbb/d)	NLPRPUS use last historical year % to parse to PADDs
RFBdstCAP	BASE DISTILLATION CAPACITY MBCD	OGIRS- MOCLEPx1 (Where x is PADD#)	PADD x Averages/Totals Refinery Operable Capacity (Mbb/d) - January Value	Not available use most recent historical year -proxy: CODIPUS
RFDSTUTL	DIST UTILIZATION RATE IN MBD	OGIRS- MOPUEPx2 (Where x is PADD#)	PADD x Averages/Totals Other Petroleum Products % Utilization Ref	CODIPUS/Last historical years Capacity
RFQEXPRDT	PRODUCT EXPORTS IN MMBD	OGIRS- MTTEXPx2 (Where x is PADD#)	PADD x Averages/Totals Total Crude Oil and Petroleum Products Exports (Mbb/d)	Last years exports of Petroleum Products
		(-)OGIRS-MCREXPx2 (Where x is PADD#)	PADD x Averages/Totals Crude Oil Exports (Mbb/d)	
RFPQIPRDT	PRODUCT IMPORTS IN MMBD	OGIRS- MTPIMPx2 (Where x is PADD#)	PADD x Finished Petroleum Products Imports (Mbb/d)	PANIPUS
		OGIRS- MNGIMPx2 (Where x is PADD#)	PADD x Averages/Totals Natural Gas Liquids and LRGs Totals Imports (Mbb/d)	Last years exports of Petroleum Products
RFDPRDAST (AST)	Asphalt Refinery Production (Mbb/d)	OGIRS- MAPRPPx2 (Where x is PADD#)	PADD x Asphalt Refinery Production (Mbb/d)	Use 10 year average growth
RFDPRDCOK (COK)	Pet Coke Refinery Production (Mbb/d)	OGIRS- MCKRPPx2 (Where x is PADD#)	PADD x Petroleum Coke Refinery Production (Mbb/d)	Use 10 year average growth
RFDPRDJTA (JTA)	Jet Fuel Kero Refinery Production (Mbb/d)	OGIRS- MKJRPPx2 (Where x is PADD#)	PADD x Jet Fuel Kero Refinery Production (Mbb/d)	JFROPUS* Last Histo Year PADD Splits
RFDPRDKER (KER)	Kerosene Refinery Production (Mbb/d)	OGIRS- MKERPx2 (Where x is PADD#)	PADD x Kerosene Refinery Production (Mbb/d)	Use 10 year average growth
RFDPRDLPG (LPG)	Refinery production; LPG	OGIRS- MLPRPPx2 (Where x is PADD#)	PADD x Liquefied Petroleum Gases Refinery Production (Mbb/d)	LGROPUS* Last Histo Year PADD Splits
RFDPRDN2H (N2H)	Refinery prd; no. 2 distillate	OGIRS- MDIRPPx2 (Where x is PADD#)	PADD x Total Distillate Refinery Production (Mbb/d)	DFROPUS* Last Histo Year PADD Splits
RFDPRDN6B (N6B)	Refinery prd; high sulfur oil	OGIRS- MRGNPPx2 (Where x is PADD#)	PADD x Averages/Totals Residual Fuel Oil Sulfur > 1.0 Net Production (Mbb)	RFROPUS*Histo year Sulfur Split and PADD
RFDPRDN6I (N6I)	Refinery prd; low sulfur resid oil	OGIRS- MRLNPPx2 (Where x is PADD#)	PADD x Averages/Totals Residual Fuel Oil Sulfur 0-0.3 Net Production (Mbb/d)	RFROPUS*Histo year Sulfur Split and PADD
		OGIRS- MRMNPPx2 (Where x is PADD#)	PADD x Averages/Totals Residual Fuel Oil Sulfur .31-100 Net Production (Mbb/d)	
RFDPRDOTH (OTH)	Refinery prd; other petroleum	OGIRS- MGARPPx2 (Where x is PADD#)	PADD x Averages/Totals Aviation Gasoline Refinery Production (Mbb/d)	Use 10 year average growth
		OGIRS- MLURPPx2 (Where x is PADD#)	PADD x Averages/Totals Lubes Refinery Production (Mbb/d)	
		OGIRS- MNSRPPx2 (Where x is PADD#)	PADD x Averages/Totals Naphtha Special Refinery Production (Mbb/d)	
		OGIRS- MWXRPPx2 (Where x is PADD#)	PADD x Averages/Totals Waxes Refinery Production (Mbb/d)	
RFDPRDPCF (PCF)	Refinery prd; petrochemical feeds	OGIRS- MPFRPPx2 (Where x is PADD#)	PADD x Averages/Totals Petroleum Products Refinery Production (Mbb/d)	Use 10 year average growth
RFDPRDSTG (STG)	Refinery prd; still gas	OGIRS- MSGRPPx2 (Where x is PADD#)	PADD x Still Gas Refinery Production (Mbb/d)	Use 10 year average growth
RFDPRDTRG (TRG)	Refinery prd; motor gasoline	OGIRS- MGFRRPPx2 (Where x is PADD#)	PADD x Finished Gasoline Refinery Production (Mbb/d)	MGROPUS* Last Histo Year PADD Splits
RFQDCRD	Unaccounted crude	OGIRS- MCRAUPx2 (Where x is PADD#)	PADD x Averages/Totals Crude Oil Unaccounted for (Mbb/d)	CONXPUS
CRDSTWDR	Crude stock withdrawals	OGIRS- MCRSCPx2 (Where x is PADD#)	PADD x Averages/Totals Crude Oil Stock Change (Mbb/d)	CONQUPUS
				ACOSXPUS/365
CRDPRDSUP	Crude product withdrawals	OGIRS- MCRUPPx2	PADD x Averages/Totals Crude Oil Product Supplied (Mbb/d)	0
RFQPRCG1	PROCESSING GAIN IN MMBD	OGIRS- MPGNPUS1/365	US Processing Gain Net Production (Mbb)	PAGLPUS
BLDIMP	Blending component imports	OGIRS- MBCIMUS2	US Blending Components Gasoline Imports (Mbb/d)	MBNIPUS
BLDPRD	Product blending component	OGIRS- MBCFPUS2	US Blending Components Gasoline Field Production (Mbb/d)	MBFPPUS
NGLRF	NGL from refinery	OGIRS- MNGRIUS2	US Natural Gas Liquids and LRGs Totals Input into Refineries (Mbb/d)	LGRIPIUS
				PPRIPIUS
OTHOXY	Other oxygenates	OGIRS- MOHPUS2	US Other Hydrocarbons/Oxygenates Field Production (Mbb/d)	OHRIPUS
PRDSTKWDR	Product stocks withdrawals	OGIRS- MTTSCUS2	United States Total Crude Oil and Petroleum Products Stock Change (Mbb/d)	Assume Zero
		(-)OGIRS-MCRSCPx2 (Where x is PADD#)	PADD x Averages/Totals Crude Oil Stock Change (Mbb/d)	
RFETHE85	Ethanol for E85 production	Hart	Oxy Fuel News Data	Oxy Fuel News Data
RFETHMGS	Ethanol for motor gasoline	OGIRS- OFETPUS2	US Oxygenates Fuel Ethanol Production (Mbb/d)	EOPPPUS
RFMETETH	Methanol for ether	Historical Quantities not tracked	Zeros	Assume Zero
RFMTBI	Imported MTBE	OGIRS- MMTIMUS2	US Oxygenates MTBE Imports (Mbb/d)	Assume Zero
RFPQUFC	Total imports of unfinished crude	OGIRS- MUOIMUS2	US Unfinished Oils Imports (Mbb/d)	UORIPUS
RFSPFRF	SPR fill rate	OGIRS- MCSSCUS1/365	US Crude Oil Stock Change SPR (Mbb)	CONQUPUS
AST	Asphalt Product Supplied (Mbb/d)	OGIRS- MAPUPPx2 (Where x is PADD#)	PADD x Averages/Totals Asphalt Product Supplied (Mbb/d)	ARTCPUS
COK	Petroleum Coke Product Supplied (Mbb/d)	OGIRS- MCKUPPx2 (Where x is PADD#)	PADD x Averages/Totals Petroleum Coke Product Supplied (Mbb/d)	PCTCPUS
JTA	Jet Fuel Kero Product Supplied (Mbb/d)	OGIRS- MKJUPPx2 (Where x is PADD#)	PADD x Averages/Totals Jet Fuel Kero Product Supplied (Mbb/d)	JFTCPUS
KER	Kerosene Product Supplied (Mbb/d)	OGIRS- MKEUPPx2 (Where x is PADD#)	PADD x Averages/Totals Kerosene Product Supplied (Mbb/d)	KSTCPUS
LPG	Product Supplied; LPG	OGIRS- MLPUPPx2 (Where x is PADD#)	PADD x Averages/Totals Liquefied Petroleum Gases Product Supplied (Mbb/d)	LGTCUPUS
N2H	Product Supplied; no. 2 distillate	OGIRS- MDIUPPx2 (Where x is PADD#)	PADD x Averages/Totals Total Distillate Product Supplied (Mbb/d)	DFTCPUS
N6B	Product Supplied; high sulfur oil	Computed- MRSUPHx2 (Where x is PAD#)	PADD x Averages/Totals Residual Fuel Oil Sulfur > 1.0 Product Supplied (Mbb/d)	RFTCPUS * High%
N6I	Product Supplied; low sulfur residual oil	Computed- MRSUPLx2 (Where x is PAD#)	PADD x Averages/Totals Residual Fuel Oil Sulfur < 1.0 Product Supplied (Mbb/d)	RFTCPUS* Low%
OTH	Product Supplied; other petroleum	OGIRS- MGAUPPx2 (Where x is PADD#)	PADD x Averages/Totals Aviation Gasoline Product Supplied (Mbb/d)	AVTCPUS
		OGIRS- MLUUPPx2 (Where x is PADD#)	PADD x Averages/Totals Lubes Product Supplied (Mbb/d)	LUTCPUS
		OGIRS- MNSUPPx2 (Where x is PADD#)	PADD x Averages/Totals Naphtha Special Product Supplied (Mbb/d)	SNTCPUS
		OGIRS- MWXUPPx2 (Where x is PADD#)	PADD x Averages/Totals Waxes Product Supplied (Mbb/d)	WXTCPUS
PCF	Product Supplied; petrochemical feeds	OGIRS- MPFUPPx2 (Where x is PADD#)	PADD x Averages/Totals Petroleum Products Product Supplied (Mbb/d)	FETCPUS
STG	Product Supplied; still gas	OGIRS- MSGUPPx2 (Where x is PADD#)	PADD x Averages/Totals Still Gas Product Supplied (Mbb/d)	SGTCPUS
RFQPRDT	Total product supplied	OGIRS- MTTUPPx2 (Where x is PADD#)	PADD x Averages/Totals Total Crude Oil and Pet Products Supplied (Mbb/d)	Sum STEO Product Quantities
		(-)OGIRS-MCRUPPx2 (Where x is PADD#)	PADD x Averages/Totals Crude Oil Product Supplied (Mbb/d)	
TRG	Product Supplied; motor gasoline	OGIRS- MGFUPPx2 (Where x is PADD#)	PADD x Averages/Totals Finished Gasoline Product Supplied (Mbb/d)	MGTCUPUS
QELETH	Historical Electricity use at Ethanol plants -			Multiply EOFPUS ethanol production by Tony Radich's formulas for energy consumption

**Table H.2 Components of PMM Variables**

PMM Variable Definition		Historical Years	Description	STEO Years
QNGETH	Historical Nat Gas use at Ethanol plants			
QCLETH	Historical Coal use at Ethanol plants			
QCLRF	Refinery Fuel –Coal	Paste in from table 47 of PSA	Use In MMBTU	Assume last Historical Year ratio of fuel to production Average refiner price of residual fuel oil
QDSRF	Refinery Fuel -Distillate Fuel Oil	Paste in from table 47 of PSA	Use In MMBTU	
QELRF	Refinery Fuel -Purchased Elec.	Paste in from table 47 of PSA	Use In MMBTU	
QLGRF	Refinery Fuel –LPG	Paste in from table 47 of PSA	Use In MMBTU	
QNGRF	Refinery Fuel -Nat Gas	Paste in from table 47 of PSA	Use In MMBTU	
QOTRF	Refinery Fuel –Other	Paste in from table 47 of PSA	Use In MMBTU	
QPCRF	Refinery Fuel -Pet Coke	Paste in from table 47 of PSA	Use In MMBTU	
QRSRF	Refinery Fuel -Residual Fuel	Paste in from table 47 of PSA	Use In MMBTU	
QSGRF	Refinery Fuel -Still Gas	Paste in from table 47 of PSA	Use In MMBTU	
PASIN	Asphalt, Road Oil, Industrial		PRODUCT PRICES IN 87\$ PER MMBTU	RFTCUUS
PDSCM	Distillate, Commercial		PRODUCT PRICES IN 87\$ PER MMBTU	DSTCUUS
PDSEL	Distillate, Electricity (+petroleum coke)		PRODUCT PRICES IN 87\$ PER MMBTU	PRODUCT PRICES IN 87\$ PER MMBTU
PDSIN	Distillate, Industrial		PRODUCT PRICES IN 87\$ PER MMBTU	DSTCUUS
PDSRS	Distillate, Residential		PRODUCT PRICES IN 87\$ PER MMBTU	DSTCUUS
PDSTR	Distillate, Transportation		PRODUCT PRICES IN 87\$ PER MMBTU	DSTCUUS
PJFTR	Jet Fuel, Transportation		PRODUCT PRICES IN 87\$ PER MMBTU	JKTCUUS
PKSCM	Kerosene, Commercial		PRODUCT PRICES IN 87\$ PER MMBTU	JKTCUUS
PKSIN	Kerosene, Industrial		PRODUCT PRICES IN 87\$ PER MMBTU	JKTCUUS
PKSRS	Kerosene, Residential		PRODUCT PRICES IN 87\$ PER MMBTU	JKTCUUS
PLGCM	Liquid Petroleum Gases, Commercial		PRODUCT PRICES IN 87\$ PER MMBTU	PRTCUIUS
PLGIN	Liquid Petroleum Gases, Industrial		PRODUCT PRICES IN 87\$ PER MMBTU	PRTCUIUS
PLGRS	Liquid Petroleum Gases, Residential		PRODUCT PRICES IN 87\$ PER MMBTU	PRTCUIUS
PLGTR	Liquid Petroleum Gases, Transportation		PRODUCT PRICES IN 87\$ PER MMBTU	PRTCUIUS
PMGCM	Motor Gasoline, Commercial		PRODUCT PRICES IN 87\$ PER MMBTU	MGEIRUS
PMGIN	Motor Gasoline, Industrial		PRODUCT PRICES IN 87\$ PER MMBTU	MGEIRUS
PMGTR	Motor Gasoline, Transportation		PRODUCT PRICES IN 87\$ PER MMBTU	MGEIRUS
PPFIN	Petrochemical Feedstocks, Industrial		PRODUCT PRICES IN 87\$ PER MMBTU	PRTCUIUS
PRHEL	Residual Fuel, High Sulfur, Electricity		PRODUCT PRICES IN 87\$ PER MMBTU	RFTCUUS
PRHTR	Residual Fuel, High Sulfur, Transp.		PRODUCT PRICES IN 87\$ PER MMBTU	RFTCUUS
PRLCM	Residual Fuel, Low Sulfur, Commercial		PRODUCT PRICES IN 87\$ PER MMBTU	RFTCUUS
PRLEL	Residual Fuel, Low Sulfur, Electricity		PRODUCT PRICES IN 87\$ PER MMBTU	RFTCUUS
PRLIN	Residual Fuel, Low Sulfur, Industrial		PRODUCT PRICES IN 87\$ PER MMBTU	RFTCUUS
		<b>SEDP</b>		
OG GEN GRID90	COGENERATION IN MMBTU	<b>NUGs Database (AI Beamon)</b>	<b>Aggregates plant data to CD regions</b>	<b>Use Last Historical Year for STEO Years 1 &amp; 2</b>
PT GEN GRID90	COGENERATION IN MMBTU			
NG GEN GRID90	COGENERATION IN MMBTU			
OT GEN GRID90	COGENERATION IN MMBTU			
OG GEN OWN 90	COGENERATION IN MMBTU			
PT GEN OWN 90	COGENERATION IN MMBTU			
NG GEN OWN 90	COGENERATION IN MMBTU			
OT GEN OWN 90	COGENERATION IN MMBTU			
OG CAP GRID90	Capacity MW			
PT CAP GRID90	Capacity MW			
NG CAP GRID90	Capacity MW			
OT CAP GRID90	Capacity MW			
OG CAP OWN 90	Capacity MW			
PT CAP OWN 90	Capacity MW			
NG CAP OWN 90	Capacity MW			
OT CAP OWN 90	Capacity MW			
OG FUL GRID90	Cogen Fuel consumption			
PT FUL GRID90	Cogen Fuel consumption			
NG FUL GRID90	Cogen Fuel consumption			
OT FUL GRID90	Cogen Fuel consumption			
OG FUL OWN 90	Cogen Fuel consumption			
PT FUL OWN 90	Cogen Fuel consumption			
NG FUL OWN 90	Cogen Fuel consumption			
OT FUL OWN 90	Cogen Fuel consumption			
DCRDWHP	WELLHEAD CRUDE OIL PRICES	From Ted McCallister's Calculations.	IN \$/BBL	Assume Region's price changes as Δ of WOP
RFQDCRD	CONVENTIONAL CRUDE PRODUCTION		IN MBD	Assume Region's Production changes as Δ of COPRPUS
RFQDTCRD	TOTAL CRUDE PRODUCTION		IN MMBD	Assume Region's Production changes as Δ of COPRPUS

### **Creating PMM Flat-file:**

To create the final elcgpur.txt, file query results are called by the access report writer. For each variable or collection of variables a report formats the results of the data queries into the exact FORTRAN fixed format position necessary to be read into the PMM. The most often employed method for this is to have a report with the historical data include a sub-report which appends the STEO year data to it. These individual reports are all then included in the master report “zz- Generate Elcgpur” in the appropriate sequence. This file is then exported from the database as a text file.

Because Access formats reports to a specific printer (page size), additional lines appear where there are breaks in pages. To remove them a Short VBA script was written (eat space) that removes all of the blank lines from the file. All of the report generation and subsequent post-processing can be done automatically by running the macro “Make Elcgpur.” The resulting file will be placed in the local c:\ directory of the desktop computer running the macro. Formatting inconsistencies occur when using Access 2002. To avoid the inconsistencies, run the report in Access 2000.

## **H.2 Processing Other Historical Data**

In addition to developing an input history file (described in Appendix H-1), the PMM utilizes other historical data to develop some inputs and to support analysis of the model results. This section describes the updating of these data, which is usually done on an annual basis.

### **Petroleum Product Price Data**

Data on petroleum product prices is obtained from the EIA-782 surveys. The EIA-782A survey contains only refiner data, the EIA-782B survey includes petroleum marketers. Prices and volumes are produced monthly for the *Petroleum Marketing Monthly* and updated for annual publication in the *Petroleum Marketing Annual* available in the summer of each year. This information is also available as series of OGIRS keys from which the state level data by product can be retrieved. By matching equivalent product volume and price information for each state a weighted average for each Census District can be determined.

### **Historical Prices and Margins**

Historical wholesale and end-use prices from the EIA-782 are aggregated and presented in tabular form by product type and Census Division. The end-use transportation prices include State and Federal taxes but for jet fuel and LPGs the State taxes are not included prior to 1995.

Differentials with the world oil price (the refiner acquisition cost of imported oil from the EIA-14) are also calculated by product type and Census Division and presented in tabular form for analyzing similar margin calculations from the PMM. The margins include the 1 percent local tax that is currently being added to gasoline price projections.

## **APPENDIX I**

### **Ethanol Supply Model**

# **Appendix I. Ethanol Supply Model**

## **I.1 Model Purpose**

The objective of the ethanol supply model is to provide the NEMS Petroleum Market Model (PMM) with supply curves for corn and cellulose based ethanol, thus allowing the PMM to forecast transportation ethanol demand throughout the NEMS forecast period. To be consistent with the market clearing mechanism adopted for NEMS, the model provides ethanol prices in the form of annual price-quantity curves. The curves, derived from an ethanol production cost function, represent the prices of ethanol at which associated quantities of transportation ethanol are expected to be available for production of E85 and ETBE, and for blending with gasoline.

The delivered ethanol prices are provided to the PMM linear program in the form of a separate supply curve for each of the nine U.S. Census Divisions. The majority of ethanol currently produced in the United States is made from corn and is produced in the East North Central Census Division (NEMS region 3), and the West North Central Census Division (NEMS region 4). Smaller amounts are available in the East South Atlantic (NEMS region 6), the Mountain (NEMS region 8), and the Pacific (NEMS region 9) Census Divisions. The PMM also models planned cellulose-based ethanol production beginning in 2010 in the Pacific Census Division (NEMS region 9), where wood waste and rice straw are the most likely feedstocks. Cellulose ethanol supply is available in 2012 in the Middle Atlantic (NEMS region 2), East North Central (NEMS region 3), West North Central (NEMS region 4), and West South Central (NEMS region 7) Census Divisions. Large quantities of corn stover are available in the East North Central and West North Central Census Divisions, and large quantities of wood waste are available in the Middle Atlantic and West South Central Census Divisions.

## **I.2 Corn-Based Ethanol**

### **Fundamental Assumptions**

The cost of corn ethanol is subdivided into capital cost, feedstock cost, operating cost, energy cost, and a credit for marketable coproducts of ethanol production. Energy cost includes the energy needed to grow and transport corn to market and the energy needed to run the ethanol plant. Each of the above factors contributes a part of the total price of ethanol.

Conversion of corn to ethanol is accomplished by either a wet milling or dry milling process. The coproducts produced from the wet milling process are corn gluten feed (CGF), corn gluten meal (CGM), and corn oil, while the dry milling process produces distillers dried grains (DDGS). Coproduct credits for wet mills and dry mills are estimated from ethanol industry financial data.

The price of corn is projected from *Effects on the Farm Economy of a Renewable Fuels Standard for Motor Vehicle Fuel*, Office of Energy Policy and New Uses, Department of Agriculture, August 2002. This paper estimates the effect on agricultural markets of a renewable fuels requirement for gasoline and diesel fuel. The Department of Agriculture constructed two agricultural market forecasts, one with lower levels of ethanol production from corn and another with higher levels of ethanol production from corn. The forecasts include corn prices and quantity of corn input to ethanol production for each forecast year. The quotient of the difference between corn prices and the difference between quantities of corn used for ethanol production gives the rate of change of corn prices with respect to quantity of corn input to ethanol production. The most current baseline corn prices and corn ethanol production were obtained from *USDA Agricultural Baseline Projections to 2013* (<http://www.usda.gov/agency/oce/waob/commodity-projections/2013projections.pdf>) The baseline forecast and the estimated rate of change are used to construct a cost curve of corn to ethanol production.

Energy cost of corn production is estimated from *The Energy Balance of Corn Ethanol: An Update*. Fuel and chemical use per acre of land, fuel use in chemical production, acres planted, and average yields per acre were estimated for nine major corn-producing States. The majority of fuel ethanol is produced in Census Division 4, so estimates for this region were assumed for all other regions. The *USDA Agricultural Baseline Projections to 2013* include energy costs in their corn price estimates. Estimates of delivered industrial energy prices from *Annual Energy Outlook 2003*, the most current EIA forecast when the Dept. of Agriculture forecast was being prepared, were deducted in order to estimate the price of corn to ethanol producers excluding the energy needed to grow the corn. The quantities of fuel and current industrial energy prices are used to estimate the energy cost of corn production within NEMS.

Wet milling accounts for about 33 percent of current ethanol production, while new ethanol facilities are projected to be dry milling plants.<sup>1</sup> PMM can choose to produce up to 370 Mbbl/day of corn ethanol in any forecast year. The variability of the market price for the feedstock corn and the conversion by-products and the variable influences of competitive uses for corn (e.g., for producing corn syrup) give rise to broad fluctuations in net corn feedstock prices. As ethanol production from corn increases, land becomes scarcer, causing both land and feedstock costs to increase. These factors are included in the Agriculture model. The Agriculture projections end in 2013, so net feedstock prices for 2014 to 2025 were set equal to the 2013 estimates. The net feedstock costs were then converted to 1987 dollars.

In addition to feedstock prices and quantities, the model requires capital cost, feedstock conversion cost (non-energy operating cost), and energy cost data. The cost data were derived from several sources which are documented in the Inventory of Variables, Data, and Parameters section of this report. Note that with this theoretical approach, only the agricultural, or feedstock production costs are modeled as a function of the total quantity of ethanol produced. The conversion plant process costs, (capital, operating, and process energy) are independent of production quantities.

---

<sup>1</sup> Renewable Fuels Association, *Ethanol Industry Outlook 2003* (<http://www.ethanolrfa.org/outlook2003.html>)

Capital and conversion costs were assumed to be constant across all Census Divisions and for all forecast years. Energy costs vary across Census Divisions as a function of industrial-sector coal, natural gas, and electricity prices. Natural gas prices are obtained from the NEMS Natural Gas Transmission and Distribution Model, coal prices are from the NEMS Coal Market Model, and electricity prices are from the NEMS Electricity Market Model.

There are currently two Federal tax incentives for blending ethanol into gasoline. One is a reduced rate of Federal excise tax on ethanol-blended gasoline, and the other is a business income tax credit for ethanol blended into gasoline. The excise tax reduction and income tax credit are of equal value, 52 cents per gallon of ethanol in 2003 and 2004 and 51 cents per gallon of ethanol thereafter. The value of the Federal incentives for ethanol blending are input to the ethanol model but applied elsewhere in the PMM.

### Key Computations and Equations

Corn ethanol costs net of energy and subsidies are calculated in a separate spreadsheet (NEMScornsupplycurve.xls, maintained by Tony Radich of EIA). These costs are tabulated as a function of ethanol production quantity in the PMM input file WETOHIN. This file also contains natural gas, coal, and electricity use as a function of ethanol production quantity. Once the data are read, the ethanol price is calculated from the following equation:

$$\begin{aligned}
 PETOH_{cd,t,e} = & ( FC_{t,e} + CAPCST_e + OPCST_e ) \\
 & + PEN_{cd,t,e} - STSUB_{cd}
 \end{aligned}
 \tag{1}$$

where:

$PETOH_{cd,t,e}$	=	Delivered price of ethanol produced in Census Division $cd$ in year $t$ for volume step $e$ (\$/gal),
$FC_{t,e}$	=	Feedstock corn production cost, exclusive of energy, in year $t$ for volume step $e$ (\$/gal),
$CAPCST_e$	=	Capital cost for conversion technology for volume step $e$ (\$/gal),
$OPCST_e$	=	Operating costs, exclusive of energy, for volume step $e$ (\$/gal),
$PEN_{cd,t,e}$	=	Cost of energy used in the corn-to-ethanol conversion process in Census Division $cd$ in year $t$ on volume step $e$ (\$/MMBtu),
$STSUB_{cd}$	=	State incentive for ethanol production in Census Division $cd$ (\$/gal).

The price of energy in each case is calculated as follows:

$$PEN_{cd,t,e} = CRNDS * PDSIN_{cd,t} + CRNMG * PMGIN_{cd,t} + CRNLG * PLGIN_{cd,t} + (CRNNG + QNG_{t,e}) * PNGIN_{cd,t} + QCL_{t,e} * PCLIN_{cd,t} + (CRNEL + QEL_{t,e}) * PELIN_{cd,t} \quad (2)$$

where:

<i>CRNDS</i>	=	Distillate needed to grow corn (MMBtu/gal)
<i>CRNMG</i>	=	Motor gasoline needed to grow corn (MMBtu/gal)
<i>CRNLG</i>	=	Liquefied petroleum gas (LPG) needed to grow corn (MMBtu/gal)
<i>CRNEL</i>	=	Electricity needed to grow corn (MMBtu/gal)
<i>CRNNG</i>	=	Natural gas needed to grow corn (MMBtu/gal)
<i>PDSIN<sub>cd,t</sub></i>	=	Industrial price of distillate for Census Division <i>cd</i> in year <i>t</i> (\$/MMBtu)
<i>PMGIN<sub>cd,t</sub></i>	=	Industrial price of motor gasoline for Census Division <i>cd</i> in year <i>t</i> (\$/MMBtu)
<i>PLGIN<sub>cd,t</sub></i>	=	Industrial price of LPG for Census Division <i>cd</i> in year <i>t</i> (\$/MMBtu)
<i>PNGIN<sub>cd,t</sub></i>	=	Industrial price of natural gas for Census Division <i>cd</i> in year <i>t</i> (\$/MMBtu),
<i>PCLIN<sub>cd,t</sub></i>	=	Industrial price of coal for Census Division <i>cd</i> in year <i>t</i> (\$/MMBtu).
<i>PELIN<sub>cd,t</sub></i>	=	Industrial price of electricity for Census Division <i>cd</i> in year <i>t</i> (\$/MMBtu).
<i>QNG<sub>t,e</sub></i>	=	Quantity of natural gas in year <i>t</i> on volume step <i>e</i> , MMBtu/gal
<i>QCL<sub>t,e</sub></i>	=	Quantity of coal in year <i>t</i> on volume step <i>e</i> , MMBtu/gal
<i>QEL<sub>t,e</sub></i>	=	Quantity of electricity in year <i>t</i> on volume step <i>e</i> , MMBtu/gal

## Inventory of Variables, Data, and Parameters

**MODEL INPUT:**      *CAPCST<sub>e</sub>*

**DEFINITION:** Capital cost of corn ethanol plants on volume step *e*.

The current value is zero on steps 1 and 2, \$0.055 on step 3, and \$0.11 per gallon on step 4 (1987 dollars). A corn ethanol plant is assumed to cost \$1 per annual gallon of capacity in all forecast years e.g. a 40 million gallon per year plant would cost \$40 million. The cost is discounted at 15 percent over 20 years. Located in the spreadsheet NEMScornsupplycurve.xls.

**MODEL INPUT:**      *OPCST<sub>e</sub>*

**DEFINITION:** Operating cost, exclusive of energy, for corn ethanol plants on volume step  $e$ .

Value is \$0.261/gallon for wet mills and \$0.215/gallon for dry mills (1987 \$) for 2000 thru 2025. Located in the spreadsheet NEMScornsupplycurve.xls.

**SOURCE:** *USDA's 1998 Ethanol Cost-of-Production Survey*, Agricultural Economic Report Number 808

**MODEL INPUTS:**  $CRNDS$ ,  $CRNMG$ ,  $CRNLG$ ,  $CRNEL$ ,  $CRNNG$

**DEFINITION:** Distillate, motor gasoline, LPG, electricity, and natural gas, respectively, needed to grow corn.

**SOURCE:** Shapouri, Hosein; Duffield, James A.; Wang, Michael. *The Energy Balance of Corn Ethanol: An Update*. Agricultural Economic Report Number 814.

**MODEL INPUT:**  $PDSIN_{cd,t}$ ,  $PMGIN_{cd,t}$ ,  $PLGIN_{cd,t}$

**DEFINITION:** Prices of distillate, motor gasoline, and LPG, respectively, for industrial use in Census Division  $cd$  in year  $t$ .

Located in the Price common block, (MPBLK).

**SOURCE:** Generated by the Petroleum Market Model.

**MODEL INPUT:**  $PCLIN_{cd,t}$

**DEFINITION:** Price of coal for industrial use in Census Division  $cd$  in year  $t$ .

Located in the Price common block, (MPBLK).

**SOURCE:** Generated by the Coal Market Model.

**MODEL INPUT:**  $PNGIN_{cd,t}$

**DEFINITION:** Price of natural gas for industrial use in Census Division  $cd$  in year  $t$ .

Located in the Price common block, (MPBLK).

**SOURCE:** Generated by the Natural Gas Transmission and Distribution Model.

**MODEL INPUT:**  $PELIN_{cd,t}$

**DEFINITION:** Price of electricity for industrial use in Census Division  $cd$  in year  $t$ .

Located in the Price common block, (MPBLK).

**SOURCE:** Generated by the Electricity Market Model.

**MODEL INPUT:**  $QNG_{t,e}, QCL_{t,e}; e=1$

**DEFINITION:** Quantity of natural gas and coal needed to convert corn to ethanol in year  $t$  on volume step 1.

Ethanol production on this step is assumed to come from wet mills, which consume 0.051 million Btu of process energy and electricity per gallon of output. Wet mills generate their own electricity, so their only energy inputs are coal and natural gas. Natural gas is 20% of the energy input per gallon, and coal is 80% of the energy input per gallon.

**SOURCE:** *USDA's 1998 Ethanol Cost-of-Production Survey*, Agricultural Economic Report Number 808

**MODEL INPUT:**  $QNG_{t,e}, QCL_{t,e}; e=2-4$

**DEFINITION:** Quantities of natural gas and coal needed to convert corn to ethanol in year  $t$  on volume steps 2-4.

Ethanol production on these steps is assumed to come from dry mills. Process energy consumption values, in million Btu per gallon, are as follows: 0.050 in 1990, 0.041 in 2000, 0.037 in 2005, 0.035 in 2020 and 2025. This decreasing trend is based on the assumption that energy required decreases linearly over time. Existing dry mills, on step 2, use natural gas for 50% of their process energy and coal for 50% of their process energy. New dry mills, on steps 3 and 4, use natural gas for 100% of their process energy. Located in the spreadsheet NEMScornsupplycurve.xls.

**SOURCE:** Marland, G. and A.F. Turhollow. 1991. "CO<sub>2</sub> Emissions From the Production and Combustion of Fuel Ethanol from Corn." *Energy*, 16(11/12):1307-1316.

**MODEL INPUT:**  $QEL_{t,e}; e=2-4$

**DEFINITION:** Quantity of electricity needed to convert corn to ethanol in year  $t$  on volume steps 2-4.

Ethanol production on these steps is assumed to come from dry mills, which consume 1.1 kwh (0.0037 million Btu) per gallon. Located in the spreadsheet NEMScornsupplycurve.xls.

**SOURCE:** *USDA's 1998 Ethanol Cost-of-Production Survey*, Agricultural Economic Report Number 808

**MODEL INPUT:**  $ETHSUB_t$

**DEFINITION:** Value of Federal tax incentive in year  $t$ , in nominal dollars. The incentive is 52 cents per gallon in 2004 and 51 cents per gallon thereafter.

Located in the WETOHIN data input file.

## **I.3 Cellulose-Based Ethanol**

### **Theoretical Approach**

The cost of cellulose ethanol is subdivided into capital cost, feedstock cost, operating cost, and a credit for excess electricity generated at the ethanol plant. As with the corn model, each of the above factors contributes a part of the total price of ethanol.

Biomass feedstock supply is not modeled in the Petroleum Market Model ethanol model. Biomass price/quantity data are obtained from the Renewable Fuels Model of NEMS and are used as input to the ethanol model. The Model Documentation: Renewable Fuels Module of the National Energy Modeling System”, DOE/EIA-M069(2005) contains a complete description of the approach and assumptions used in generating the biomass feedstock supply functions.

Briefly, the biomass use in NEMS is modeled as two distinct markets, the captive and non-captive biomass markets. The captive market pertains to users with dedicated biomass supplies that obtain energy by burning biomass byproducts resulting from the manufacturing process. The noncaptive market is defined to include the commercial, transportation, and electric utility sectors, as well as the resources marketed in the industrial sector. There is an additional noncaptive market serving residential uses of biomass.

EIA developed a fairly simple model structure consisting of one supply schedule per region. This schedule defines the quantity and cost relationships of biomass resources accessible by all noncaptive, non-residential consumers. It is based on an aggregation of supply/price information from U.S. Forest Service and forest product experts. The wood portion of the cost-supply schedule is static throughout the model period. Energy crop cost-supply schedules are also developed and superimposed onto the wood total.

### **Fundamental Assumptions**

A basic assumption for the biomass feedstock is that the supply price for noncaptive biomass energy is the same across all sectors. Biomass feedstock costs are input from the NEMS Renewable Fuels Model at the Census Division level. Biomass usage by the PMM ethanol model is fed back to the Renewable Fuels Model. At lower prices, the NEMS biomass supply is mostly urban wood waste. Cellulose ethanol technology, however, is being developed for agricultural residue, forestry residue, and purpose-grown energy crops. These sources of supply are assumed to be available only at higher biomass prices. A feedstock cost premium, estimated by region and by ethanol quantity, was applied to cellulose ethanol to reflect this.

An important modeling consideration for cellulose ethanol production is the imposition of a constraint on the amount of ethanol production capacity assumed for the early years of the forecast. Ethanol from cellulose is relatively new technology and ethanol production from cellulose is currently at the demonstration level. By assumption, commercial cellulose ethanol production begins in 2010 in the *AEO2005* reference case. Commercial production is assumed to begin 2 years earlier in the *AEO2005* High Renewables side case. A constraint on cellulose ethanol production prevents unrealistically large increases in production capacity from occurring suddenly in response to favorable market prices. Cellulose ethanol production capacity is allowed to grow by 50 million gallons per year per region after 2010 (2008 in the High Renewables case)...

In addition to feedstock prices and quantities input from the Renewable Fuels Model, the ethanol model requires feedstock conversion and energy cost data, and capital and operating cost data. The conversion and capital cost data were derived from a joint study by the Dept. of Agriculture and the Dept. of Energy, *Determining the Cost of Producing Ethanol from Corn Starch and Lignocellulosic Feedstocks.*,

Ethanol production costs are assumed to be constant across the United States. However, feedstock availability and price varies from Census Division to Census Division. Ethanol production in Census Divisions 2 and 7 is expected to be based on forest residue. Census Divisions 3 and 4 have corn stover in large volume. The feedstocks available in Census Division 9 are forest residue and rice straw. The Federal tax incentives for blending ethanol also apply to ethanol from cellulose.

## Key Computations and Equations

The main computations performed by the cellulose portion of the ethanol model involve the derivation of an ethanol supply-price curve for each Census Division. The computations consist of three major steps:

1. Reading in ethanol component cost data from the PMM input file WETOHIN.
2. Obtaining biomass feedstock prices at the census division level from the Renewable Fuels Model.
3. Derivation of delivered ethanol prices, calculated as a function of the biomass feedstock price and the ethanol conversion costs.

Total Conversion Costs are calculated as follows:

$$TOTCONV_t = CAPSTCL_t + OPCSTCL_t + PWCRDCL_t \quad (3)$$

where:

$TOTCONV_t$  = Total ethanol conversion cost for year  $t$ ,

$CAPSTCL_t$  = Capital cost for year  $t$ ,

$OPCSTCL_t$  = Operating cost for year  $t$ ,

$PWRCDCL_t$  = Power credit for co-products combusted and sold as power for year  $t$

The delivered ethanol price equation is as follows:

$$PETOH_{cd,t} = (PBMET_{cd,t} * 17.2) / CONEFF_t + TOTCONV_t \quad (4)$$

where:

$PETOH_{cd,t}$  = Delivered price of cellulose ethanol in Census Division  $cd$  in year  $t$

$PBMET_{cd,t}$  = Biomass feedstock cost for Census Division  $cd$  in year  $t$

17.2 = Converts MMBtu of biomass to tons of biomass.

$CONEFF_t$  = Feedstock conversion rate, gallons of ethanol per ton of biomass. Yield increases from 79.8 gallons per ton of feedstock in 2010 to 85 gallons per ton in 2014.

## Inventory of Variables, Data, and Parameters

**MODEL INPUT:**  $CAPCSTCL_t$ ,  $OPCSTCL_t$ ,  $PWRCDCL_t$

**DEFINITION:** Capital cost and operating cost for conversion technology and power credit for coproducts combusted and sold as power in year  $t$ , respectively.

$CAPCSTCL_t$  varies by year. Capital cost was estimated to be \$100.8 million (1987 \$) for a 25 million gallon per year plant. We assume that the plant size will be 50 million gallons, so we follow the scaling procedure used in the study. The capital cost is increased by a factor of  $(50/25)^{0.6}$ . The discount rate is assumed to be 20 percent in 2010 but declines linearly to 15 percent in 2020. A 20-year investment life is assumed..

$OPCSTCL_t$  is \$0.428 per gallon, and  $PWRCDCL_t$  is \$-0.0802 per gallon (1987 \$).

Located in the WETOHIN input data file.

**SOURCE:** McAloon, Andrew; Taylor, Frank; Yee, Winnie. *Determining the Cost of Producing Ethanol from Corn Starch and Lignocellulosic Feedstocks*. National Renewable Energy Laboratory, October 2000.

**MODEL INPUT:**  $PBMET_{cd,t}$

**DEFINITION:** Biomass feedstock cost for Census Division *cd* in year *t*.

Input from the Renewable Fuels Model.

**SOURCE:** National Energy Modeling System common block WRENEW.

**MODEL INPUT:**  $ETHSUB_t$

**DEFINITION:** Value of Federal tax incentive in year *t*, in nominal dollars. The incentive is 52 cents per gallon in 2004 and 51 cents per gallon thereafter.

Located in the WETOHIN data input file.

## I.4 Ethanol Transportation Costs

The most comprehensive work regarding ethanol distribution infrastructure and costs is a report by Downstream Alternatives, Inc. (DAI), *Infrastructure Requirements for an Expanded Ethanol Industry*, June 2002, performed for the Department of Energy Office of Energy Efficiency and Renewable Energy. This source was used to develop cost estimates for transporting ethanol between and within Census Divisions (CD's).

The DAI study estimates the infrastructure investment costs and the transportation costs that would likely be incurred if ethanol demand reached 5.0 billion gallons per year (BGY) by 2012. The infrastructure costs are incremental and represent additional expenditures from an established baseline level of 1.5 BGY. Transportation costs are the largest category of costs, far larger than the amortized costs of modifications to petroleum terminals and retail stations for blends of 10 percent ethanol or less. Rail and water are the modes of ethanol transport that are considered, as pipeline shipment is not currently considered a cost-effective method of transport due to special handling requirements of ethanol.

The DAI study examines the costs and ethanol demand by PADD. The links needed for PMM, as shown in Table I1, are based on Census Divisions for demands. There are some discrepancies between the PADD and CD mapping in terms of states; however, for the purpose of ethanol transportation cost estimates between the CD's, the following table is not expected to introduce significant error to the modeling results.

**Table I1. DAI Regions and NEMS Regions**

DAI Regions		NEMS/PMM Regions	
Code	Locations	Code	Locations
1	PADD 1	1, 2, 5	CDs 1, 2, and 5
2	PADD 2	3, 4	CDs 3 and 4
3	PADD 3	6, 7	CDs 6 and 7
4	PADD 4	8	CD 8
5	PADD 5	9	CD 9

Most ethanol is produced in either CD 3 or 4, and transported by rail, barge, ship, or truck. Ethanol produced and consumed in the same CD is assumed to be shipped by truck at a freight cost of 4 cents/gallon. Starting with the baseline of existing ethanol sales from year 2000, the DAI study examines the costs and ethanol demand for the years 2004, 2007, and 2012. The corresponding demands in the PMM model for each mode of transportation and the estimated freight costs are shown for these 3 years in Tables I2, I3, and I4.

The average cents per gallon in Tables I2 through I4 are provided on an amortized, cost per gallon of ethanol basis. Costs for capital improvement are included in the PMM model but are not included in the freight costs shown below. (Amortized capital improvement costs range from 0.52 cents per gallon to 0.87 cents per gallon, with a nationwide average of 0.66 cents per gallon)

**Table I2. 2004 New Ethanol Shipments and Freight Costs by Census Divisions**

From	To	Mode of Transport	Amount of New Ethanol Shipped (mgy)	Freight Costs (cents/gallon)
CD 3	CD 1	Rail	44.8	9.0
CD 3	CD 1	Ship	25.1	11.0
CD 3	CD 2	Rail	160.5	8.0
CD 3	CD 2	Ship	89.9	11.0
CD 3	CD 3	Barge	103.2	4.0
CD 3	CD 5	Rail	44.7	8.0
CD 3	CD 5	Ship	25.0	11.0
CD 4	CD 3	Rail	52.0	4.0
CD 4	CD 3	Truck	52.0	4.0
CD 4	CD 4	Truck	103.3	4.0
CD 4	CD 9	Rail	84.0	13.0
CD 4	CD 9	Ship	70.0	13.0

**Source:** Based on data from Downstream Alternatives Inc., *Transportation and Infrastructure Requirements for a Renewable Fuels Standard*, (June 2002), and personal communication with author (Robert Reynolds, August 2002)

**Note:** Costs shown reflect 2000 dollars.

**Table I3. 2007 New Ethanol Shipments and Freight Costs by Census Divisions**

From	To	Mode of Transport	Amount of New Ethanol Shipped (mgy)	Freight Costs (cents/gallon)
CD 3	CD 1	Rail	34.8	9.0
CD 3	CD 1	Ship	18.8	11.0
CD 3	CD 2	Rail	124.5	9.0
CD 3	CD 2	Ship	67.4	11.0
CD 3	CD 3	Truck	38.6	4.0
CD 3	CD 5	Rail	34.7	9.0
CD 3	CD 5	Ship	18.8	11.0
CD 3	CD 6	Barge	12.2	3.5
CD 3	CD 6	Rail	24.9	7.0
CD 4	CD 3	Truck	38.6	4.0
CD 4	CD 4	Truck	38.6	4.0
CD 4	CD 6	Barge	4.1	3.5
CD 4	CD 6	Rail	8.3	7.0
CD 4	CD 7	Barge	43.7	3.5
CD 4	CD 7	Rail	88.8	7.0
CD 4	CD 9	Rail	195.0	13.0
CD 4	CD 9	Ship	105.0	13.0

**Source:** Based on data from Downstream Alternatives Inc., *Transportation and Infrastructure Requirements for a Renewable Fuels Standard*, (June 2002), and personal communication with author (Robert Reynolds, August 2002)

**Table I4. 2012 New Ethanol Shipments and Freight Costs by Census Divisions**

From	To	Mode of Transport	Amount of New Ethanol Shipped (mgy)	Freight Costs (cents/gallon)
CD 3	CD 1	Rail	71.8	9.0
CD 3	CD 1	Ship	43.1	11.0
CD 3	CD 2	Rail	256.8	9.0
CD 3	CD 2	Ship	154.1	11.0
CD 3	CD 3	Barge	16.8	4.0
CD 3	CD 3	Truck	146.3	4.0
CD 3	CD 3	Rail	10.0	4.0
CD 3	CD 5	Rail	71.5	9.0
CD 3	CD 5	Ship	42.9	11.0
CD 3	CD 6	Barge	20.6	3.5
CD 3	CD 6	Rail	11.4	7.0
CD 3	CD 9	Rail	25.0	14.0
CD 3	CD 9	Ship	15.0	14.0
CD 4	CD 1	Rail	17.9	11.0
CD 4	CD 1	Ship	10.8	12.0
CD 4	CD 2	Rail	64.2	11.0
CD 4	CD 2	Ship	38.5	12.0
CD 4	CD 3	Barge	33.6	4.0
CD 4	CD 3	Rail	20.0	4.0
CD 4	CD 3	Truck	36.6	4.0
CD 4	CD 4	Truck	36.6	4.0
CD 4	CD 5	Rail	17.9	11.0
CD 4	CD 5	Ship	10.7	12.0
CD 4	CD 6	Barge	20.6	3.5
CD 4	CD 6	Rail	11.4	7.0
CD 4	CD 7	Barge	110.1	3.5
CD 4	CD 7	Rail	61.0	7.0
CD 4	CD 8	Rail	35.0	4.5
CD 4	CD 9	Rail	225.0	13.0
CD 4	CD 9	Ship	135.0	13.0

**Source:** Based on data from Downstream Alternatives Inc., *Transportation and Infrastructure Requirements for a Renewable Fuels Standard*, (June 2002), and personal communication with author (Robert Reynolds, August 2002)

## **APPENDIX J**

### **Biodiesel Supply Model**

# Appendix J. Biodiesel Supply Model

## J.1 Model Purpose

The objective of the biodiesel supply model is to provide the NEMS Petroleum Market Model (PMM) with supply curves for biodiesel made from soybean oil and yellow grease. The model provides plant-gate biodiesel prices as a function of quantity for each Census Division and each forecast year. The curves, derived from a biodiesel production cost function, represent the prices at which biodiesel is expected to be available for blending into distillate and highway diesel.

## J. 2 Fundamental Assumptions

PMM can choose up to approximately 200 million gallons of biodiesel from soybean oil and up to approximately 100 million gallons of biodiesel from yellow grease. Soybean oil biodiesel capacity is assumed to be 100 million gallons per year in CD 3 and 100 million gallons per year in CD 4. Yellow grease consists primarily of used cooking oil from restaurants. As such, it is available Nationwide. Yellow grease biodiesel capacity is assumed to be about 11.1 million gallons per CD.

The biodiesel model uses a process costing approach to model the impacts of net feedstock production costs plus capital and operating costs. Biodiesel is produced in a type of chemical reaction called a transesterification. Fats or oils are reacted with an alcohol, usually methanol, to produce esters of the fat or oil and glycerine.

The price of soybean oil is projected from *Effects on the Farm Economy of a Renewable Fuels Standard for Motor Vehicle Fuel*, Office of Energy Policy and New Uses, Department of Agriculture, August 2002. This paper estimates the effect on agricultural markets of a renewable fuels requirement for gasoline and diesel fuel. The Department of Agriculture constructed two agricultural market forecasts, a renewable fuels standard case with and a reference case without biodiesel production from soybean oil. The forecasts include soybean oil prices and quantity of oil input to biodiesel production for each forecast year. The quotient of the increase in soybean oil prices and the quantity of soybean oil used for biodiesel production in the renewable fuels standard case gives the rate of change of soybean oil prices with respect to quantity of soybean oil input to biodiesel production. The most current baseline soybean oil prices, assuming no biodiesel production, were obtained from *USDA Agricultural Baseline Projections to 2013* (<http://www.usda.gov/agency/oce/waob/commodity-projections/2013projections.pdf>) The baseline forecast and the estimated rate of change are used to construct a cost curve of soybean oil to biodiesel production.

The Department of Agriculture does not forecast yellow grease prices. In the past, however, the prices of yellow grease and soybean oil have moved together. Monthly soybean oil price data were obtained from the Department of Agriculture, and monthly yellow grease price data were obtained from the Jacobsen Publishing

Company. Unweighted averages were used to construct annual prices. The Producer Price Index was used to covert all prices to a 2001 basis. A linear regression gives:

$$\text{Yellow grease price} = 0.49 \text{ Soybean oil price} \quad (1)$$

where prices are in 2001 dollars per pound. Baseline yellow grease prices are obtained by substituting baseline soybean oil prices into the above equation. It follows from the regression equation that:

$$\Delta \text{Yellow grease price} = 0.49 \Delta \text{Soybean oil price}, \quad (2)$$

The rate of increase in soybean oil prices with respect to soybean oil input to biodiesel production is substituted into this relation to obtain the rate of increase in yellow grease prices with respect to yellow grease input to biodiesel production. The baseline forecast and the estimated rate of change are used to construct a cost curve of yellow grease to biodiesel production.

The feedstock cost credit for the glycerine coproduct is estimated to be 11 cents per gallon (1987 dollars; E-mail from K. Shaine Tyson of the National Renewable Energy Laboratory, Feb. 12, 2002).

In addition to feedstock prices and quantities, the model requires capital cost and operating cost. The cost data are documented in the Inventory of Variables, Data, and Parameters section of this report. Note that with this theoretical approach, only the agricultural, or feedstock production costs are modeled as a function of the total quantity of ethanol produced. The conversion plant process costs are independent of production quantities.

There are no current Federal tax incentives for biodiesel blending, but such incentives are part of the current energy policy discussion. The biodiesel model has variables for a virgin oil (e.g. soybean oil) biodiesel tax incentive and another for a nonvirgin oil (e.g. yellow grease) biodiesel tax incentive. The values of these incentives would be read into the biodiesel model but applied elsewhere in PMM.

Soybean oil biodiesel is assumed to contain no sulfur and therefore is assumed to be blended into ultra low sulfur highway diesel, which has a sulfur limit of 15 parts per million by mass. Yellow grease biodiesel is very low in sulfur, but may exceed the limit for highway diesel. Therefore, yellow grease biodiesel is assumed to be blended into nonroad diesel, which has higher sulfur limits.

### J. 3 Key Computations and Equations

Biodiesel costs net of subsidies are calculated in a separate spreadsheet (NEMS biodieselsupplycurve.xls, maintained by Tony Radich of EIA). These costs are tabulated as functions of biodiesel production quantity. The price for biodiesel is calculated from the following equation:

$$PBDSL_{i,cd,t,e} = FC_{i,t,e} + CAPBDSL + OPBDSL \quad (3)$$

Where:

$i$ =feedstock index; 1=soybean oil biodiesel, 2=yellow grease biodiesel

$PBDSL_{i,cd,t,e}$  = Delivered price of biodiesel produced from feedstock  $i$  in Census Division  $cd$  in year  $t$  for volume step  $e$  (\$/gal),

$FC_{i,t,e}$  = Net cost of feedstock  $i$  in year  $t$  for volume step  $e$  (\$/gal),

$CAPBDSL$  =Capital cost for conversion technology (\$/gal),

$OPBDSL$ =Operating cost for biodiesel production (\$/gal),

### J. 4. Inventory of Variables, Data, and Parameters

**MODEL INPUT:**  $CAPBDSL$

**DEFINITION:** Capital cost of biodiesel plants.

A new biodiesel plant costs \$0.729 per gallon per year of capacity, discounted at 10 percent over 15 years. Value is \$0.096 per gallon (1987 \$) Located in spreadsheet NEMSbiodieselsupplycurve.xls.

**SOURCE:** National Renewable Energy Laboratory estimate

**MODEL INPUT:**  $OPBDSL$

**DEFINITION:** Operating cost of biodiesel plants, including energy

Value is \$0.308 per gallon (1987 \$). Located in spreadsheet NEMSbiodieselsupplycurve.xls.

**SOURCE:** National Renewable Energy Laboratory estimate

**MODEL INPUT:** *FEDSUBV*

**DEFINITION:** Value of Federal tax incentive for virgin oil (e.g. soybean oil) biodiesel.

Value is zero currently. Located in the WETOHIN data input file.

**MODEL INPUT:** *FEDSUBNV*

**DEFINITION:** Value of Federal tax incentive for nonvirgin oil (e.g. yellow grease) biodiesel.

Value is zero currently. Located in the WETOHIN data input file.